

SKILL 2

2520030225

R.RAGHUVeer

```
#include <stdio.h>
#include <string.h>

int main() {
    char input[100];

    while (1) {
        printf("raghuveer@LAPTOP-SHKTDDI3 :~ $ ");

        fgets(input, sizeof(input), stdin);

        input[strcspn(input, "\n")] = '\0';

        if (strcmp(input, "exit") == 0) {
            printf("Exiting shell ...\n");
            break;
        }

        printf("You entered: %s\n", input);
    }

    return 0;
}
```

```
raghu@Raghu:~/ossp-shell$ nano shell.c
raghu@Raghu:~/ossp-shell$ gcc shell.c -o shell
raghu@Raghu:~/ossp-shell$ ./shell
raghuveer@LAPTOP-SHKTDDI3 :~ $ hello
You entered: hello
raghuveer@LAPTOP-SHKTDDI3 :~ $ test
You entered: test
raghuveer@LAPTOP-SHKTDDI3 :~ $ exit
Exiting shell ...
```

```
#include <stdio.h>
#include <unistd.h>
#include <termios.h>

int main() {
    struct termios oldt, newt;
    char ch;

    tcgetattr(STDIN_FILENO, &oldt);

    newt = oldt;
    newt.c_lflag &= ~(ICANON | ECHO);

    tcsetattr(STDIN_FILENO, TCSANOW, &newt);

    printf("Type something: ");

    while (1) {
        ch = getchar();

        if (ch == '\n') {
            break;
        }

        printf("\nYou pressed: %c", ch);
    }

    tcsetattr(STDIN_FILENO, TCSANOW, &oldt);

    printf("\nExiting...\n");
    return 0;
}
```

```
raghu@Raghu:~/ossp-shell$ nano shell.c
raghu@Raghu:~/ossp-shell$ nano keyboard.c
raghu@Raghu:~/ossp-shell$ gcc keyboard.c -o keyboard
raghu@Raghu:~/ossp-shell$ ./keyboard
Type something:
You pressed: b
You pressed:

You pressed: c
You pressed:

You pressed: d
You pressed:

You pressed: d
You pressed: p
You pressed:
You pressed:
You pressed: d
You pressed: o
Exiting...
raghu@Raghu:~/ossp-shell$
```

```
#include <stdio.h>
#include <unistd.h>
#include <termios.h>

int main() {
    struct termios oldt, newt;
    char buffer[100];
    int index = 0;
    char ch;

    tcgetattr(STDIN_FILENO, &oldt);

    newt = oldt;
    newt.c_lflag &= ~(ICANON | ECHO);

    tcsetattr(STDIN_FILENO, TCSANOW, &newt);

    printf("raghuveer@LAPTOP-SHKTDDI3 :~ $ ");
    fflush(stdout);

    while (1) {
        ch = getchar();

        if (ch == '\n') {
            buffer[index] = '\0';
            printf("\nYou entered: %s\n", buffer);
            break;
        }
        else if (ch == 127) {    // Backspace
            if (index > 0) {
                index--;
                printf("\b \b");
                fflush(stdout);
            }
        }
        else {
            if (index < 99) {
                buffer[index] = ch;
                index++;
            }
        }
    }
}
```

```

        buffer[index] = ch;
        index++;

        printf("%c", ch);
        fflush(stdout);
    }
}

tcsetattr(STDIN_FILENO, TCSANOW, &oldt);

return 0;
}
|

```

```

^G Help
^X Exit

```

```

^O Write Out
^R Read File

```

```

^F Where Is
^_ Replace

```

```

^K Cut
^U Past

```

```

raghu@Raghu:~/ossp-shell$ nano buffer.c
raghu@Raghu:~/ossp-shell$ gcc buffer.c -o buffer
raghu@Raghu:~/ossp-shell$ ./buffer
raghuveer@LAPTOP-SHKTDDI3 :~ $ hello
You entered: hello

```