

주식회사 큐로 경기도 양주시 은현면 화합로 941번길 83 TEL, 031-862-8556 FAX, 031-862-8558 www.quro.co.kr



활선접근경보기 Electric Live Alarm













전압 선택형 😡 🕒 🕦







🔎 🔔 소리 🄆 빛

모 델	전 압	작동거리	모 델	전 압	작동거리
QREI-A	220 V	1 cm	QREI-D	220 V	1 cm
	440 V	30 cm		154 000 V	4 m
	3 300 V	30 cm		345 000 V	6 m
	6 600 V	50 cm		765 000 V	10 m
QREI-F	220 V	1 cm	QREI-E	22 900 V	1 cm
	3 300 V	40 cm		154 000 V	4 m
	6 600 V	80 cm	OBES-C pates after after Common.	345 000 V	6 m
	22 900 V	110 cm	Afficia Maria	765 000 V	10 m

QRE-D5	220 V	10 cm
	30 kV	1 m
0	154 kV	4 m
1111	345 kV	6 m
	765 kV	10 m

^{*} ORF-DS는 소모배드형으로 하정되어 있습니다

- 경고방법: 소리, 빛
- 주파수: (50 / 60) Hz
 - 중량: 25g

● 크기: (39 x 64 x 17) mm

- 사용전원: 리튬전지 CR2032(3V 1개) 사용온도: (-20 ~ +50) ℃
- 1. 전원을 가동한 후 소리, 빛을 확인한다.
- 2. 파란색 버튼을 눌러 전압을 선택 후 사용한다.

전압 자유형 🕝 🕒





QREFV ▲ 소리 ※ 빛 (ᠬ) 진동

모 델	전 압	작동거리	
QREFV—A	220 V ~ 6 600 V	5 cm ~ 50 cm	
QREFV-F	220 V ~ 22 900 V	10 cm ~ 110 cm	

- 경고방법: 소리, 빛 진동
- 크기: (39 x 64 x 17) mm

중량: 25g

- 주파수: (50 / 60) Hz
- 사용온도: (-20 ~ +50) ℃
- 사용전원: 리튬전지 CR2032 3 V

● 작동방법: 전원을 가동한 후 소리, 빛, 진동을 체크하고 사용한다.

스마트 워치형 🍛



QREH 🌲 소리 🔆 빛

모 델	전 압	작동거리
QREH3	220 V	10 cm
	22 kV	1 m
03:00	154 kV	4 m
	345 kV	6 m
	765 kV	10 m





● 작동방법: ❷를 터치 후 화면을 밀어서 전압을 선택하여 사용한다.















● 경고방법: 소리, 빛

중량: 25g

- 크기: (39 x 64 x 17) mm
- - 주파수: (50 / 60) Hz
- 사용온도: (-20 ~ +50) °C ● 사용전원: 마그네틱 USB 케이블 충전



주위 환경 및 전선 피복의 차폐율에 따라 작동 거리가 변동 될 수 있음

제조 | 주식회사 큐로 | ☎ 82-31-862-8556

총판 | 시험기제작소 | ☎ 82-70-7709-3399





