

MySQL RDBMS

Trainer: Mr. Nilesh Ghule



SQL functions

- RDBMS provides many built-in functions to process the data.
- These functions can be classified as:
 - Single row functions
 - One row input produce one row output.
 - e.g. ABS(), CONCAT(), IFNULL(), ...
 - · Multi-row or Group functions or aggregate treactions
 - · Values from multiple rows are aggregated to single value.
 - e.g. SUM(), MIN(), MAX(), ...
- These functions can also be categorized based on data types or usage.
 - Numeric functions
 - String functions
 - Date and Time functions
 - Control flow functions
 - Information functions
 - Miscellaneous functions





Single ROW

Function

GEOUP

Function

fraction work

Numeric & String functions

- ABS()
- POWER()
- ROUND(), FLOOR(), CEIL()
- ASCII(), CHAR()
- CONCAT()
- SUBSTRING()
- LOWER(), UPPER()
- TRIM(), LTRIM(), RTRIM()
- LPAD(), RPAD()
- REGEXP_LIKE()



Date-Time and Information functions

- VERSION()
- USER(), DATABASE()
- MySQL supports multiple date time related data types
 - DATE (3), TIME (3), DATETIME (5), TIMESTAMP (4), YEAR (1)
- SYSDATE(), NOW()
- DATE(), TIME()
- DAYOFMONTH(), MONTH(), YEAR(), HOUR(), MINUTE(), SECOND(), ...
- DATEDIFF(), DATE_ADD(), TIMEDIFF()
- MAKEDATE(), MAKETIME()



Control and NULL and List functions

- NULL is special value in RDBMS that represents absence of value in that column.
- NULL values do not work with relational operators and need to use special operators.
- Most of functions return NULL if NULL value is passed as one of its argument.
- ISNULL()
- IFNULL()
- NULLIF()
- COALESCE()
- GREATEST(), LEAST()
- IF(condition, true-value, false-value)



Group functions

- Work on group of rows of table.
- Input to function is data from multiple rows & then output is single row. Hence these functions are called as "Multi Row Function" or "Group Functions".
- These functions are used to perform aggregate ops like sum, avg, max, min, count or std dev, etc. Hence these fns are also called as "Aggregate Functions".
- Example: SUM(), AVG(), MAX(), MIN(), COUNT().
- NULL values are ignored by group functions.
- Limitations of GROUP functions:
 - Cannot select group function along with a column.
 - Cannot select group function along with a single row fn.
 - Cannot use group function in WHERE clause/condition.
 - Cannot nest a group function in another group fn.





Thank you!

Nilesh Ghule <nilesh@sunbeaminfo.com>

