MEDIKIOSK CLINICAL PLATFORM DOCUMENTATION

WORKFLOW


System Workflow & Execution Architecture

Last Analyzed: 2026-09-16 Commit:`f118085510bdf2fa44785ee3ca5aaf5b4875c209`

1. End-to-End Clinical System Workflow

The MediKiosk clinical platform orchestrates multi-lingual patient intake, automated triage, AYUSH clinical decision support, and doctor verification.


ARCHITECTURE / WORKFLOW DIAGRAM



2. System Sub-Workflows & Stage Details

Phase 1: Data Ingestion & RAG Corpus Pre-seeding

📊 ARCHITECTURE / WORKFLOW DIAGRAM



- **Entry Points**: `backend/src/rag/parse.ts`, `backend/src/rag/chunk.ts`, `backend/src/rag/embed.ts`, `backend/src/rag/preseed.ts`
- **Inputs**: Ancient text corpus in `rag_corpus/raw/`
- **Outputs**: Embedded 768-dimensional vectors seeded in `rag_chunks` table

Execution Command Sequence:

```bash
# 1. Parse raw text into structured JSON format
npx tsx backend/src/rag/parse.ts


# 2. Chunk text into semantic sections with metadata
npx tsx backend/src/rag/chunk.ts

# 3. Generate vector embeddings using Gemini API
npx tsx backend/src/rag/embed.ts

# 4. Seed vector embeddings into Supabase pgvector store
npx tsx backend/src/rag/preseed.ts
```

Phase 2: Kiosk Intake & Emergency Screening Workflow


📊 ARCHITECTURE / WORKFLOW DIAGRAM



1. **Consent & Registration**: Patient completes DPDP Act 2023 compliant consent screen (`/consent`).
2. **Audio/Text Intake**: Speech input processed via Sarvam Saaras v3 ASR (`/api/sarvam/asr`) or touch interface.
3. **Emergency Red-Flag Screening**: Evaluated against 15 deterministic red-flag rules in `backend/src/redflags.ts` .
4. **Document & Record Extraction**: Uploaded medical reports are scanned via Gemini Document OCR (`/api/gemini/extract-entities`).

Phase 3: Doctor Triage & EHR Integration Workflow

📊 **ARCHITECTURE / WORKFLOW DIAGRAM**



1. **OPD Dashboard**: Real-time triage queue displaying patient risk scores and emergency alerts.
2. **Provenance Badging**: Clear demarcation between `patient_reported`, `ocr_extracted`, and `doctor_entered` data points.
3. **Interoperability Standard**: Standardized output as an HL7 FHIR R4 Bundle (`/api/fhir/:sessionId`) and integrated with Ayushman Bharat Digital Mission (ABDM).

---

3. Local & Containerized Setup Workflow

Prerequisites

- **Node.js**: v22 LTS (specified in `package.json`, `.node-version`)
- **npm**: ^10.0.0
- **Docker & Docker Compose** (optional container runtime)

Quickstart Commands

```bash
# 1. Install dependencies across packages
npm install
cd backend && npm install
cd ../frontend && npm install

# 2. Configure Environment Variables
cp backend/.env.example backend/.env
cp frontend/.env.example frontend/.env

# 3. Run Concurrent Local Server (Backend: 3001, Frontend: 5173)
npm run demo
```

4. Cloud Deployment Architecture

- **Backend Service**: Deployed to Railway using Nixpacks configuration (`railway.json`).
- **Frontend App**: Deployed to Vercel with SPA routing rules (`vercel.json`).
- **Database**: Supabase Cloud PostgreSQL with pgvector extension enabled.