

代码

周潇翔

摘要. 这里总结自己学过的代码供查阅。为啥不用英文？英文的参考文献浩如烟海，也不差我一个啊。另外引用的很多网页也都是中文的，我也懒得再花时间解释哪个是中文哪个是英文了。对数学系的同学而言，代码的逻辑并不难，大家不会的只是格式而已。第一节横向介绍我们需要啥，之后纵向对每一种语言给出对应的代码。

在这份文档的编译中第一次学 python 和 Github, 可以说是紧跟潮流
23333

1. 代码需求

大部分的语言都需要：

- 安装 + 初始代码 (Halloworld)
- 基本逻辑
- 调试
- 参考文档
- (想保留的) 例子

以下是具体需求：

1.1. 安装 + 初始代码.

- 简要说明该语言的目的
- 说明自己使用何种编译器
- 解释该语言的结构 (基本框架)
- 使用该语言在屏幕中打出”Halloworld”
- 必要时给出英文注释

1.2. 基本逻辑.

- 数据结构类型 (数字、字符串、其他结构)
- 基本四则运算 + mod (若数据结构中包含矩阵，则需要矩阵的各类运算；)
- 条件语句
- 循环语句

- 函数

对于图形化输出的语言，我们还有很多额外的需求：

- 图形

- 基本几何图形 (尽可能多样化)
- Bézier 曲线 (钢笔工具)
- 参数化曲线
- 直线，箭头等基本图形库，电路，棋盘，乐器等专业库
- 几何变换 (平移，旋转，伸缩)
- 集合运算 (如交并补)
- 几何运算 (如平行，垂直，切线，交点)
- 度量衡转换 (数值，距离单位，向量运算，弧度制与角度制)
- 测量

- 图形进阶

- 光滑化
- 锐化

- 坐标系

- 直角坐标系
- 其他类型坐标系

- 其他细节

- 颜色设置
- 背景与边界设置
- 透明背景设置
- 图片嵌入设置
- 材质设置
- 数学字体嵌入设置
- 动画 + 声音嵌入设置 (可选)

对于主要用于排版的语言，我们还希望能了解页面布局的相关知识，如盒子模型。

1.3. 调试.

- 快捷键 (Keyboard shortcut)

- 运行代码
- 注释方式及快捷键 (单行注释 + 多行注释)
- 自动补全功能
- 自动对齐功能

– 其他快捷键

- 如何获得帮助
- 控制输出 (包含调整至 debug 模式)
- 如何设置断点
- 控制输入

1.4. 参考文档.

- 官方文档
- 民间优秀文档

超出科大 C 语言的知识: 编程范式 (Programming paradigm)、方法 (method)

2. PYTHON

2.1. 安装 + 初始代码. Python 是一门高级的编程语言。他有许多的标准模块 (standard module). 你可以在网上在线的编辑器CoCalc练习 Python.¹

2.2. 基本逻辑. 与 C 语言不同, Python 不需要声明变量。当有赋值时不输出结果。

数据类型在这里看到。²

对于数字, Python 不仅有 int 和 float, 还有 Decimal, Fraction and complex numbers 这些奇葩的变量。Task: 学会 Decimal, Fraction.

```
1 >>> complex('1+2j')*complex('1+3j')
```

四则计算像自然计算一样自然, 不过带余除法用//, 余数用%, 幂次用**.(好符号)³

```
>>> a,b=8,13 # a++ is not allowed in python
>>> a ** (b-1) % b # verify the Fermat's little theorem
```

计算器上的 Ans 记为_, round(0.142857,1)给出 0.1

python 中的逻辑运算符如下: 与 (and &), 或 (or |)

条件语句和循环语句的书写规范详见这里。以下是计算素数的例子。

```
import math    # Compute square root
def isPrime(n):    # return true when n is a prime
    for x in range(2, math.isqrt(n)+1):
        if n % x == 0:
```

¹但是使用图形化用户界面时往往需要下载。

²你需要知道那些类型是可改变的 (mutable);

³请小心使用负数的带余除法。

```

5         return False;
    else:
        # loop fell through without finding a factor
        return True;
isPrime(57)

```

用库可以更加容易地计算素数:

```

1 from sympy.ntheory import isprime
  isprime(10000019)

# find primes by sieve method
from sympy import sieve
3 sieve._reset() # this line for doctest only
  # 10000019 in sieve    #10000019 is a prime
  sieve.extend(100)
  sieve._list

```

2.3. 调试. 运行代码的快捷键为 Shift+Enter. 单行注释使用井号#, 多行注释使用 `'''注释'''` or `"""注释"""`. 快捷键为 Ctrl+/.

在 Cocalc 中输入部分单词可以按 Tab 键补全代码。

控制输入使用函数 `input()`。

2.4. 参考文档. 官方文档 SymPy PKU CS 自学指南 python 教程

2.5. 可能会学习的标准模块.

- Tkinter: GUI 图形界面。可以参考教程.

2.6. (想保留的) 例子. 这个例子计算正整数的各位数之和, 用到了把数转化为字符串的技巧:

```
print(sum([int(d) for d in str(int(input("number:"))])))
```

这个例子计算 gl_n 幂零轨道的维数.

```

# this computes dimension of orbits of nilpotent elements
young_diagram = [2,1,1,1,1] # Here is the input
n=len(young_diagram)
4 a,b=0,0
  for i in range(n):
    a=a+young_diagram[i]
    for j in range(n):
      if young_diagram[i]<young_diagram[j]:
9         b=b+young_diagram[i]
      else:
        b=b+young_diagram[j]

```

```
c=a**2 -b
print("the dimension of this orbit is", str(c)+".") # one small trick for
printing result
```

这个例子想要验证某个猜想。据说是 BSD 猜想的推论。

```
from sympy.ntheory import isprime
2 import math      # Compute square root
def isQuart(k):
    for i in range(k//2):
        if i**4 % k == 3:
            return True
7     return False
def solution(m):
    n=math.isqrt(m)+1
    num=0
    for i in range(n):
12        for j in range(n):
            for k in range(n):
                if 6* i**2+j**2+18* k**2 == m:
                    #print("find the solution", i, j, k)
                    if i*j*k==0:
17                        if k % 2 ==0:
                            num=num+4
                        else:
                            num=num-4
                    else:
22                        if k % 2 ==0:
                            num=num+8
                        else:
                            num=num-8
    return num
27 for l in range(25, 10000, 24):
    if isprime(l) & (isQuart(l)==False):
        #print(l,"find the number")
        if solution(l) % 16 ==8:
            print("the conjecture is true for ", l)
32     else:
        print("the conjecture is not true for ", l)
```

这个例子计算 affine quiver 正根的可能情形 (real positive root + regular simple).

```
# Usage of format
2 # E6 case
```

```

orderedCouple1 = [(a1,a2,a3,a4,a5,a6,a7) for a1 in range(2) for a2 in
    range(3) for a3 in range(4) for a4 in range(3) for a5 in range(2) for
    a6 in range(3) for a7 in range(2)]
k=0 # compute the number of positive real root which is possible regular
    simple
for a1,a2,a3,a4,a5,a6,a7 in orderedCouple1: # do everything in one line*
    if a1**2+a2**2+a3**2+a4**2+a5**2+a6**2+a7**2-a1*a2-a2*a3-a3*a4-a4*a5-
        a3*a6-a6*a7 ==1:
7         k=k+1
        print('                                {0}'.format(a7)) #ugly code
        have better output
        print('                                {0}'.format(a6))
        print('The positive real root is {0}, {1}, {2}, {3}, {4}.'.format(
            a1,a2,a3,a4,a5))
        print("")
12    print('There are {0} results'.format(k))

# E7 case
orderedCouple2 = [(a1,a2,a3,a4,a5,a6,a7,a8) for a1 in range(2) for a2 in
    range(3) for a3 in range(4) for a4 in range(5) for a5 in range(4) for
    a6 in range(3) for a7 in range(2) for a8 in range(3)]
k=0 # compute the number of positive real root which is possible regular
    simple
17 for a1,a2,a3,a4,a5,a6,a7,a8 in orderedCouple2: # do everything in one line
    *
    if a1**2+a2**2+a3**2+a4**2+a5**2+a6**2+a7**2+a8**2-a1*a2-a2*a3-a3*a4-
        a4*a5-a5*a6-a6*a7-a4*a8 ==1:
        k=k+1
        print('                                {0}'.format(a8)) #ugly
        code have better output
        print('The positive real root is {0}, {1}, {2}, {3}, {4}, {5},
            {6}.'.format(a1,a2,a3,a4,a5,a6,a7))
22    print("")
    print('There are {0} results'.format(k))

# E8 case
orderedCouple3 = [(a1,a2,a3,a4,a5,a6,a7,a8,a9) for a1 in range(2) for a2
    in range(3) for a3 in range(4) for a4 in range(5) for a5 in range(6)
    for a6 in range(7) for a7 in range(5) for a8 in range(3) for a9 in
    range(4)]
27 k=0 # compute the number of positive real root which is possible regular
    simple
for a1,a2,a3,a4,a5,a6,a7,a8,a9 in orderedCouple3: # do everything in one
    line*

```

```

if a1**2+a2**2+a3**2+a4**2+a5**2+a6**2+a7**2+a8**2+a9**2-a1*a2-a2*a3-
a3*a4-a4*a5-a5*a6-a6*a7-a7*a8-a8*a9 ==1:
    k=k+1
    print('                                {0}'.format(a9)) #
ugly code have better output
32     print('The positive real root is {0}, {1}, {2}, {3}, {4}, {5},
        {6}, {7}.'.format(a1,a2,a3,a4,a5,a6,a7,a8))
        print("")
print('There are {0} results'.format(k))

# E6 case, subspace case
37 orderedCouple1 = [(a1,a2,a3,a4,a5,a6,a7) for a1 in range(2) for a2 in
    range(3) for a3 in range(4) for a4 in range(3) for a5 in range(2) for
    a6 in range(3) for a7 in range(2)]
k=0 # compute the number of positive real root which is possible regular
    simple
for a1,a2,a3,a4,a5,a6,a7 in orderedCouple1: # do everything in one line*
if a1**2+a2**2+a3**2+a4**2+a5**2+a6**2+a7**2-a1*a2-a2*a3-a3*a4-a4*a5-
a3*a6-a6*a7 == 1 and a1+a2-3*a3+a4+a5+a6+a7==0:
    k=k+1
42     print('                                {0}'.format(a7)) #ugly code
    have better output
        print('                                {0}'.format(a6))
        print('The positive real root is {0}, {1}, {2}, {3}, {4}.'.format(
a1,a2,a3,a4,a5))
        print("")
print('There are {0} results'.format(k))

```

3. SAGE

3.1. 安装 + 初始代码. Sage 是专为数学家设计的程序, 基于 python, 通过集成大量数据库, 使用其中的数学函数来简化编程难度。我使用的是网上的编辑器CoCalc, 在 New 中生成 Sage worksheet. 你可以在每一行前添加sage: 或者不加。在最开始输入需要的宏包, 然后直接进行计算即可。

```
sage: print("Halloworld!233") #The code is the same as
python
```

3.2. 基本逻辑. 本节的基本内容参见[这里](#)。

在矩阵群中的计算可以模仿这个例子。

```
G=SL(2,ZZ)
A = G([0,-1,1,0])
```

```

B = G([1,1,0,1])
4 A*B*A^(-1)

```

在指定代数结构的时候可以同时指定生成元。定义数域须先生成多项式环再使用其中的多项式定义。

```

1 R.<t> = PolynomialRing(QQ) #R= Q[t]
  F.<i>=NumberField(t^2+1) #Define number field
  OF=F.ring_of_integers() #Define ring of integers
  [OF.0,OF.1] #Find the basis of ring of integers
  T.<z>= PolynomialRing(OF)
6 L.<l>=NumberField(z^2+i) #define number field in the same
  way again
  LL.<u> = L.absolute_field() #Change the base field
  Q8.<c>= CyclotomicField(8) #Second way to construct field
  Q8.is_isomorphic(LL)

```

3.3. 调试. 大部分同 python.

3.4. 参考文档. 官方文档

Sage V9.1 中文文档以及专题文档

Sage Quick Reference Cards

Sage for Undergraduates

Sage for Computational Mathematics

基本例子的视频教程

除了 sage 外还有一些数学自动证明软件, 比如Lean theorem prover. 只是我懒不想学自动证明。

3.5. (想保留的) 例子. 这个例子能帮助我计算 Dynkin quiver 的所有不可约表示.

```

1 sage: Q = DiGraph({1:{2:['a1']},2:{3:['a2']},4:{3:['a3']},
  sage: M = Q.I(GF(11),3)
  sage: M
  sage: tauM = M.AR_translate()
  sage: tauM

```

这个例子能帮助我画出 $\Gamma(5)$ 对应的基本区域.

```

G5 = Gamma(5)
A = FareySymbol(G5).fundamental_domain(show_pairing =
    true)
show(A,figsize=10,fontsize=10)

```


这个例子为了实现这里的作业, 练练手感。

```

#This document solves the problems in https://ctnt-summer.
math.uconn.edu/wp-content/uploads/sites/1632/2020/06/
CTNT2020-CompNT-Exercises.pdf
2
# Exercise 5
# https://ask.sagemath.org/question/41952/int-object-has-no
-attribute-is_prime/
def relative_prime(a,N,X):
    primenumber=0
7   for i in range(a,X,N):
        if is_prime(i):
            primenumber=primenumber+1
    return primenumber
relative_prime(1,5,10000)
12 # v = [(x, relative_prime(1,5,x)) for x in [6,11,...,10000]]
# show(points(v, rgbcolor=(0.2,0.6, 0.1), pointsize=2))
def quotient(X):
    return N(relative_prime(1,5,X)/X*ln(X))
# w = [(x, quotient(x)) for x in [6,26,...,10000]]
17 # show(points(w, rgbcolor=(0.2,0.6, 0.1), pointsize=2))

# Exercise 6 & 7
from scipy import integrate
22 def newpi(X):
    sum=0
    for i in range(2,X):
        sum=sum+N(1/ln(i))
    return sum
27 def Li(X):
    def g(t):
        return N(1/ln(t))
    return integrate.quad(g, 2, X)[0]
def compare(X):
32    return N(X/ln(X))
# newpiplot = [(x, newpi(x)) for x in [5,25,...,1000]]
# oldpiplot = [(x, prime_pi(x)) for x in [5,25,...,1000]]
# compareplot = [(x, compare(x)) for x in [5,25,...,1000]]
# Liplot = [(x, Li(x)) for x in [5,25,...,1000]]

```

```

37 # show(points(newpiplot, rgbcolor=(0.2,0.6, 0.1), pointsize
    =2)+points(oldpiplot, rgbcolor=(0.2,0.2, 1), pointsize
    =5)+points(compareplot, rgbcolor=(0.9,0.1, 0.1),
    pointsize=2) +points(Liplot, rgbcolor=(0,0, 0),
    pointsize=2))

    compare1plot = [(x, prime_pi(x)/compare(x)) for x in
        [5,25,...,1000]]
    compare2plot = [(x, prime_pi(x)/newpi(x)) for x in
        [5,25,...,1000]]
    compare3plot = [(x, prime_pi(x)/Li(x)) for x in
        [5,25,...,1000]]
42 show(points(compare1plot, rgbcolor=(1,0, 0), pointsize=5)+
    points(compare2plot, rgbcolor=(0,1,0), pointsize=5)+
    points(compare3plot, rgbcolor=(0,0,1), pointsize=5))

    # Exercise 8
    # https://ask.sagemath.org/question/51114/how-can-i-find-
        number-of-elements-of-n-torsion-points-on-an-elliptic-
        curve-over-finite-field/
    # p = 1233.next_prime()
47 # E = EllipticCurve(GF(p),[3,12])
    p = 100.next_prime()*3
    E = EllipticCurve(GF(p),[1,0])
    E.abelian_group().order().factor()
    E.abelian_group()

52 # Exercise 9
    Qpadic=Qp(53,prec=20) #By changing the number of q, we know
        that \phi_7(x) factors exactly when q \mod 1,2,4,6 mod
        7.
    R.<t> = PolynomialRing(Qpadic)
    g= t^6+t^5+t^4+t^3+t^2+t+1
57 g.factor()

    # Exercise 10
    # https://stackoverflow.com/questions/132988/is-there-a-
        difference-between-and-is
    Q32.<c>= CyclotomicField(32)
62 G = Q32.galois_group()
    # Some standard test of the group
    # G.number_field() is Q32
    # G.order()
    # G.is_galois()
67 # G.is_abelian()

```

```

# G.is_cyclic()
# G.transitive_label()
# G.list()
for K in G.normal_subgroups():
72     if K.order() == 8: # We can't replace "==" with "is"
        print("we've found")
        newfield=K.fixed_field(polred=True)[0]
        print("The number field is a ",newfield,"with
            Galois group of order",newfield.galois_group().
            order())
for K in G.normal_subgroups():
77     if K.order() == 4: # We can't replace "==" with "is"
        newfield=K.fixed_field(polred=True)[0]
        if newfield.galois_group().is_cyclic():
            print("Congrats! The number field is a ",
                newfield)

```

4. MANIM COMMUNITY

4.1. **安装 + 初始代码.** 这是做数学科普视频的软件，同样基于 python, 其对数学公式的支持远远超过了其他软件，而且是开源的。不想安装的懒惰者可以试试在线编译网页 EulerTour。

4.2. 参考文档. 官方文档

中文文档

可以参考hello world 视频教学,常用代码总结/教程

实例:3B1B 的所有动画视频, Dirac's belt trick和自由变形动画。

5. LATEX

5.1. 本文参考文献. listings 的具体设置

fancy 版本的 Mathematica 代码没学会。

L^AT_EX 中如何自动补全代码？ 不容易。

本文 python 代码格式来源

5.2. 参考文档. 刘海洋的书:《L^AT_EX 入门》

如何在 latex 里面使用注释效果、tikz 整体调整、颜色名称设置总结

如何在 amsart 下调整目录

5.3. 非初等但是值得学习的宏包.

- Tikz: 数学系画图专属宏包, 其子宏包 Tikzcd 也是相当实用⁴, 为了简化制图流程大佬们甚至做了两个网站tikzcd-editor和quiver: a modern commutative diagram editor, 都非常实用。另外还可以尝试TikZiT来辅助画图。
- hobby: 画曲线的宏包 (妈妈再也不用担心我画 Tikz 中的曲线)
- tcolorbox: 把文档变得花里胡哨的宏包 (你甚至可以做海报)

5.4. (想保留的) 例子. 这个例子可以画文本宽度的水平直线, 并把公式拉长到文本宽度:

```

\hrule % show text width
\resizebox{\textwidth}{!}{ %show the formula very big
    $\displaystyle \frac{1}{\pi}=\frac{2\sqrt{2}}{99^2}$
    \sum_{k=0}^{\infty} \frac{(4k)!}{k!^4}\frac{
{26390k+1103}{396^{4k}}} $
}
5 \begin{gather*} % or small
3.1415926535897932384626433832795028841971693993751
058209749445923078164062862089986280348253421170679
821480865132823066470938446095505822317253594081284
8111745028410270193852110555964462294895493038196
10 \end{gather*}

```

6. MATHEMATICA

6.1. 安装 + 初始代码. Mathematica 是收费的数学计算软件, 参考文档量多但是不够有结构性, 导致我的代码往往是临时性的, 每次计算都需要重新学习代码。(而且我也没有结构性地保存它们) 不过现在可以在这份文档中储存代码了。

6.2. (想保留的) 例子. 这个例子能帮助我计算 affine quiver 相关的矩阵.

```

Cp = ({
    {1, 1, 1, 0, 0, 0},
    {0, 1, 1, 0, 0, 0},
    {0, 0, 1, 0, 0, 0},
5   {0, 0, 1, 1, 0, 0},
    {0, 0, 1, 1, 1, 0},
    {0, 0, 1, 0, 0, 1}
});

```

⁴tikzcd is in fact only an improvement of matrix in TikZ. Cited from here.

```

Ci = Transpose[Cp];
10 Phi = -Ci.Inverse[Cp]
MatrixPower[Phi, 6]
A = Transpose[Inverse[Ci]] + Inverse[Ci] (*symmetric form*)

```

这个例子计算四元数 \mathbb{H} 上的 non-reduced norm.

```

3 Det[({
    {x, -y, -z, -w},
    {y, x, -w, z},
    {z, w, x, -y},
    {w, -z, y, x}
  )}]
Factor[w^4 + 2 w^2 x^2 + x^4 + 2 w^2 y^2 + 2 x^2 y^2 + y^4
+
8 2 w^2 z^2 + 2 x^2 z^2 + 2 y^2 z^2 + z^4]

```

这个例子画彩色的点.(255 位 RGB)

```

2 ListPlot[{Style[{{1, 1}, {2, 3}, {2, 4}},
    Interpreter["Color"]["RGB 255 0 0"]],
    Style[{{1.5, 1}, {2.3, 3}, {2.4, 4}},
    Interpreter["Color"]["RGB 0 255 0"]}]}

```

7. PUZZLESCRIPT

游戏制作软件:Unity 可以由免费开源游戏引擎Godot替代。简单的 2D 游戏可以先尝试用 PuzzleScript 实现。

请注意, PuzzleScript 只是一个类推箱类游戏制作语言, 比较难制作 3D/扭曲/用鼠标处理的游戏, 而且基本逻辑不完备导致许多功能的实现需要大量技巧。如果不是技术开发狂热者请只把它当成游戏开发初始阶段的调试器使用。

7.1. 基本逻辑. 本节目前主要讨论 RULES. 在 OBJECT 中可以用 transparent 来表示变量 (在正常对象之后), 在 LEGEND 中请将一个字符放在其他变量名之后。

RULES 的基本结构是 keyword1 [keyword2 objectA] -> [objectB] result, 其中

- keyword1 可以取 up/down/left/right, horizontal/vertical, random, +, late, global, orthogonal;
- keyword2 可以取 >/</~v/up/down/left/right, moving/stationary, no, action;

- result可以取 Message, sfx0, win, checkpoint, restart, cancel, again.

否定语句比较困难，目前只知道部分否定，如[Background no Player]->[wall]。⁵

RULES 中的每一句都是循环至不再循环为止，如果不允许循环，在该句之前输入random; 如果需要多行语句合在一起循环，则从第二行起每行前添加+.

循环语句以 startloop 开始，以 endloop 结束，当循环的过程不再改变游戏内容时停止。(这种循环语句是不是智障?)

7.2. 调试. 单行多行注释使用括号(). 快捷键可以参考这里。

Debug 可以在 Prelude 中写上verbose_logging, 或者功能弱一点的debug. 另外游戏中可以用音效来辅助调试.

7.3. 参考文档. 官方文档 和官方例子

一些例子。差不多类推箱游戏都有 PuzzleScript 的版本。

7.4. (想保留的) 例子. PuzzleScript 网上的例子已经非常方便了。这里只是把网上的例子改着玩。

```

title Basic Objects
author Xiaoxiang Zhou
homepage http://home.ustc.edu.cn/~xx352229/
background_color #222323
5 text_color #f0f6f0
(color_palette 3)
zoomscreen 10x10
enable_level_select
noaction
10 (
References
https://www.sokobanonline.com/play
http://www.sneezingtiger.com/sokoban/levels/microbanText.
html
https://www.sohu.com/a/274843792_627888
15 )
=====
OBJECTS
=====
20
```

⁵通过部分否定以及一些额外的变量即可达到全局的否定，就是代码丑陋一点罢了。

```
Background
green lightgreen darkgreen
00000
10000
25 00010
00000
01000
```

```
Target
30 DarkBlue
.....
.000.
.0.0.
.000.
35 .....
```

```
Wall
BROWN DARKBROWN
40 00010
11111
01000
11111
00010
45
```

```
Player
darkblue red BLACK
.000.
.000.
50 11111
.111.
.2.2.
```

```
Crate
55 orange
00000
0...0
0...0
0...0
60 00000
```

```
Spike
black gray white
.....
65 ..0..
```

```
.010.  
02110  
02210  
  
70 Stone  
black white  
.000.  
00110  
00010  
75 00000  
.000.  
  
Angle  
BROWN red  
80 00000  
0111.  
011..  
01...  
0....  
85 0  
black  
.000.  
.0.0.  
90 .0.0.  
.0.0.  
.000.  
  
1  
95 black  
..0..  
.00..  
..0..  
..0..  
100 .000.  
  
2  
black  
.000.  
105 ...0.  
.000.  
.0...  
.000.  
  
110 3
```



```
black
.000.
...0.
.000.
115 ...0.
.000.

4
black
120 .0.0.
.0.0.
.000.
...0.
...0.

125 5
black
.000.
.0...
130 .000.
...0.
.000.

6
135 black
.000.
.0...
.000.
.0.0.
140 .000.

7
black
.000.
145 ...0.
...0.
...0.
...0.

150 8
black
.000.
.0.0.
.000.
155 .0.0.
```

```
.000.

9
black
160 .000.
    .0.0.
    .000.
    ...0.
    .000.
165 =====
    LEGEND
    =====

    . = Background
170 # = Wall
    P = Player
    * = Crate
    @ = Crate and Target
    O = Target
175 ! = Spike
    S = Stone
    A = Angle

    =====
180 SOUNDS
    =====
    player Move 33184907
    Crate Move 412312
    EndLevel 123413
185 Player CantMove 4123412
    =====
    COLLISIONLAYERS
    =====

190 Background
    Target
    Player, Wall, Crate
    Spike
    0,1,2,3,4,5,6,7,8,9
195 Stone, Angle

    =====
    RULES
    =====
200
```

```

[ > Player | Crate ] -> [ > Player | > Crate ]
late [ Player Spike ] -> [ Spike ]
=====
WINCONDITIONS
=====
205

All Target on Crate

=====
210 LEVELS
=====

level_select_point
MESSAGE I make no claim for the original.
215
MESSAGE Just some test.

.p*0@!SA..
.#####.
220 .#..p*.o...
.#####.
01234567890

level_select_point
225 MESSAGE Er. I copied something to check.

#####
#.*00..#
230 #P*...*.#
#..00*.*#
#####

level_select_point
235 message If you don't know how to solve this, you can try
      the SokobanAutomaticSolver: http://m.wodown.com/soft/14821.html#downAddress

.....####.
#####.p#.
#.....*...#.
240 #...*##.*#.
###*ooo#.#.
#.*ooo..#.
#.#o.o#.#.#

```

```

245  .#...#.#*.#
    .#*...*....#
    .#..#####
    .####.....
    level_select_point

250  #####
    ###...###
    ##.....#
    ##@#@#@.#
    ##.#p*##
255  ##.#.#o##
    #.....##
    #...#...##
    #####

260  level_select_point

    #####
    #####...##
265  #.*...*...##
    #.#...o#.#
    #..o.#op.#
    ###.#@...#
    ##...#####
270  #####

MESSAGE Thank you for playing the game.

```

想要做自己的游戏，先得学会复刻已有的小游戏。做了点尝试。

小技巧：制造边缘砖块的方式（堆叠）以及关卡编辑器中可以使用特殊符号来形象表达，比如LUMirror 。

```

title Demake of ORBOX B
author Xiaoxiang Zhou
homepage http://home.ustc.edu.cn/~xx352229/
background_color #222323
5 text_color #f0f6f0
  (color_palette 3)
  verbose_logging (for better debug)
  youtube CKAc3nYEatw
  enable_level_select
10 (realtime_interval 0.15 (automove)

```

```

again_interval 1 (The amount of time it takes an 'again'
    event to trigger. We won't use it.)
key_repeat_interval 0.10 (hold one key))
noaction
=====
15 OBJECTS
=====

Background
green lightgreen  darkgreen
20 00000
    10000
    00010
    00000
    01000
25
Target
DarkBlue
    .....
    .000.
30 .0.0.
    .000.
    .....

BombObstacle
35 gray
    00000
    00000
    00000
    00000
40 00000

Wall
BROWN DARKBROWN
45 11111
    01000
    11111
    00010
    11111
50
WallL
Black
    0....
    0....

```

```
55 0....
    0....
    0....

    WallR
60 Black
    ....0
    ....0
    ....0
    ....0
65 ....0

    WallU
    Black
    00000
70 .....
    .....
    .....
    .....

75 WallD
    Black
    .....
    .....
    .....
80 .....
    00000

    Wall2
    red
85 0...0
    .0.0.
    ..0..
    .0.0.
    0...0
90

    Player
    darkblue red BLACK
    .000.
    .000.
95 11111
    .111.
    .2.2.

    Crate
```

```
100 orange
    00000
    0...0
    0...0
    0...0
105 00000

    LUMirror
    BROWN LightBlue
110 ....0
    ...10
    ..110
    .1110
    00000
115

    URMirror
    BROWN LightBlue
    0....
    01...
120 011..
    0111.
    00000

    RDMirror
125 BROWN LightBlue
    00000
    0111.
    011..
    01...
130 0....

    DLMirror
    BROWN LightBlue
    00000
135 .1110
    ..110
    ...10
    ....0

140 Bomb
    blue white
    00000
    01110
    01110
```

```

145 01110
    00000

    Teleport
    blue purple black
150 00000
    01110
    01210
    01110
    00000

155 Initial
    transparent

    Shiftbomb
160 transparent

    =====
    LEGEND
    =====

165

    WallOutline = WallU or WallD or WallL or WallR
    Obstacle = Wall or Wall2 or BombObstacle or Bomb
    Mirror = LUMirror or URMirror or RDMirror or DLMirror
170 Solid = Obstacle or Mirror

    . = Background
    # = Wall
    P = Player and Initial
175 * = Crate
    O = Target
    g = BombObstacle and Target
    d = Wall2
    B = Bomb
180 t = Teleport

    =====
    SOUNDS
    =====

185 Sfx0 73682502 (die)
    sfx1 74413905 (mirror)
    sfx2 89661502 (explosion)
    sfx3 63441708 (walk)
    sfx4 29985308 (teleport)

```



```

190 Sfx10 77515308 (test)
    EndLevel 123413
    =====
    COLLISIONLAYERS
    =====
195
    Background
    Mirror, Target, Teleport
    Player, Crate, Obstacle
    (for beauty)
200 WallL
    WallR
    WallU
    WallD
    Initial
205 Shiftbomb

    =====
    RULES
    =====
210 (Initial setting)
    (Editing convenience: Automatically add outlines to walls)
    [Initial][ WallOutline ] -> [Initial][ ]
    up   [Initial][ Wall | No Wall ] -> [Initial][ Wall WallU |
        ]
    down [Initial][ Wall | No Wall ] -> [Initial][ Wall WallD |
        ]
215 left [Initial][ Wall | No Wall ] -> [Initial][ Wall WallL |
        ]
    right [Initial][ Wall | No Wall ] -> [Initial][ Wall WallR |
        ]
    [Initial] ->[]

    (begin every step)
220 (Test if player touches the Bomb)
    [ > Player | Bomb ] -> [ Player| ] sfx2

    (Go directly, for a loop)
225 (Here stationary is important. Without it the LUMirror can
    also move. And the Mirrors must be near the wall.
    Otherwise the player would go across the mirror. And be
    careful that never make a loop with mirrors and
    teleports!)

```

```

right [ > Player | LUMirror] -> [ |up Player stationary
    LUMirror ] sfx1
+down [ > Player | LUMirror] -> [ |left Player stationary
    LUMirror ] sfx1
+left [ > Player | URMirror] -> [ |up Player stationary
    URMirror ] sfx1
+down [ > Player | URMirror] -> [ |right Player stationary
    URMirror ] sfx1
230 +left [ > Player | RDMirror] -> [ |down Player stationary
    RDMirror ] sfx1
+up [ > Player | RDMirror] -> [ |right Player stationary
    RDMirror ] sfx1
+right [ > Player | DLMirror] -> [ |down Player stationary
    DLMirror ] sfx1
+up [ > Player | DLMirror] -> [ |left Player stationary
    DLMirror ] sfx1
(now move on)
235 + [ > Player| no Obstacle no Mirror] -> [ |> Player ] (
    better if one can wait for some time)
(Teleport)
+ [> Player Teleport][Teleport no Player] ->[Teleport][
    Teleport > Player] sfx4
(stop)
+ [ > Player| Obstacle] -> [ Player|Obstacle] sfx3
240 (win condition)
+ [Player Target] -> [stationary Player Target]win

random [Bomb][BombObstacle] -> [Bomb][BombObstacle
    Shiftbomb]
245 [BombObstacle no Shiftbomb] -> []
[Shiftbomb] -> []
late [ Player | Wall2 ] -> restart sfx0
(Here I want to wait several seconds to restart)
=====
250 WINCONDITIONS
=====

=====
LEVELS
255 =====

MESSAGE I make no claim for the original.

LEVEL_SELECT_POINT Level 1

```

```
260 MESSAGE Level 1
    dddddddddddd
    d.....d
265 d....#.....d
    d.....#..d
    d..#.....d
    d.....#.d
    d....p#....d
270 d.0.....d
    d.#.....d
    d.....#...d
    d...#.....d
    d.....d
275 dddddddddddd

LEVEL_SELECT_POINT Level 2
MESSAGE Level 2
    dddddddddddddddd
280 d.....d
    d.....#.....d
    d.....#...d
    d...##.....d
    d.#..#.....o.d
285 d.....p#....d
    d.....#.....#..d
    d.....#.....d
    d..#.....#...d
    d.....#.....d
290 d.....d
    dddddddddddddddd

LEVEL_SELECT_POINT Level 3
MESSAGE Level 3
295 ddddddddddddddddd
    d.....d
    d.....###.....d
    d.....#...#.....d
    d.....#...d
300 d..####...#b....d
    d.p.bbb..bb#b.o#.d
    d..####...#b....d
    d.....#...d
    d.....#...#.....d
```

```

305 d.....###.....d
    d.....d
    dddddddddddddddddd

    LEVEL_SELECT_POINT Level 4
310 MESSAGE Level 4
    dddddddddddddddddd
    d.....d
    d..#.....d
    d.....#.....d
315 d.....#.....d
    d.....#.....d
    d.#.....d
    d..#.....#p.....d
    d.....#.....d
320 d....#.....d
    d.....#.#.....d
    d.....#..d
    d.....#.....d
    d...#.....d
325 d....o...#.....d
    d.....#.#..d
    d.....#.....d
    d...#.....d
    d.....#.....d
330 d.....d
    dddddddddddddddddd

    LEVEL_SELECT_POINT Level 5
    MESSAGE Level 5
335 dddddddddddddddddd
    d.....d
    d.....###.d
    d....#.....##.##.d
    d.bb....b...#..#.d
340 d.bb..p..b....g....d
    d.....#..#.d
    d.....###.d
    d...#...#.....d
    d...#####.....d
345 d.....d
    dddddddddddddddddd

    LEVEL_SELECT_POINT Level 6
    MESSAGE Level 6

```

```

350 ddddddddddddddd
    d.....d
    d.....#...d
    d.....#...d
    d..#.....d
355 d....bbb.#o..d
    d....bpb.#...d
    d....bbb...#.d
    d.#.....d
    d.....#.#...d
360 d.....#...d
    d....#.....d
    d.....d
    ddddddddddddddd

365 LEVEL_SELECT_POINT Level 7
    MESSAGE Level 7
    ddddddddddddddddddd
    d.....d
    d.#####...d
370 d.###...#.....d
    d.#.....#.....d
    d.#.....#...d
    d.##...#.....o.....d
    d.###.##.... ##### .d
375 d..... #####. # .d
    d.##..... #p.#...#.d
    d.#..t...###...t...#.d
    d.....#.#...#...#.d
    d.#.....#. #####...#.d
380 d.##...##.... ##### .d
    d.....d
    ddddddddddddddddddd

    LEVEL_SELECT_POINT What?
385 MESSAGE That's just a test, not a game!
    ... ##... #
    ...g ## .t.
    ...####...
    ##..####... #
390 .# . ## ###
    .###... ####
    .# .bbb#####
    .#.bbbbbb...
    .# .bbb.....

```

```
395 .#####.
    .## ...p.t..
    .## .....

400

MESSAGE Thank you for playing the game.
```

以下是黎曼面版本的 2048.

```
title ramified 2048
author Xiaoxiang Zhou
homepage http://home.ustc.edu.cn/~xx352229/
youtube CKAc3nYEatw
5 verbose_logging (for better debug)
noaction
flickscreen 13x6
(
ref:
10 https://dario-zubovic.github.io/PuzzleScript/play.html?p=
    e6e4b858fb96486f5d91f390b640345b
    https://gist.github.com/tinjoonatan/
    ada1f82d7a51bad137083c4133ad4fc2
)
=====
OBJECTS
15 =====

Background
lightblue

20 wall
green red
1.0.1
.1.1.
0.1.0
25 .1.1.
1.0.1

1
white lightgrey
30 00000
00000
```

```
00100
00000
00000
35
2
white grey
00000
00100
40 00000
00100
00000

3
45 white darkgray
00000
01000
00100
00010
50 00000

4
white black
00000
55 01010
00000
01010
00000

60 5
white darkblue
00000
01010
00100
65 01010
00000

6
white blue
70 00000
01010
01010
01010
00000
75

7
```

```
white lightblue
00000
01010
80 01110
01010
00000

8
85 white lightred
00000
01110
01010
01110
90 00000

256
white red
00000
95 01110
01110
01110
00000

100 512
white darkred
00000
01110
01110
105 01110
00000

1024
white orange
110 00000
01110
01110
01110
00000

115 2048
white yellow
00000
01110
120 01110
01110
```



```
00000
glow
125 yellow
00000
0...0
0...0
0...0
130 00000

glow2
orange
00000
135 0...0
0...0
0...0
00000

140 overabove
blue
00000
.....
.....
145 .....
.....

reach256
transparent
150

reach512
transparent

reach1024
155 transparent

copy1
transparent

160 copy2
transparent

vert
transparent
165

didmove
```

[illegible]

```

210 Player, wall
    c,d
    vert
    glow, glow2
    overabove
215 didmove
    specialcase
    reach256
    reach512
    reach1024
220 =====
    RULES
    =====
    (indication)
    random[up Player]->[up Player vert]
225 random[down Player]->[down Player vert]
    (If one put the vertical arrow, than switsch copy1 and
        copy2)
    random [vert][copy1][copy2] -> [vert][copy2][copy1]

230 [ > player | no Player no wall] -> [ | > player didmove]

    [ > 1 | 1 ] -> [ | 2 didmove ]
    [ > 2 | 2 ] -> [ | 3 didmove ]
235 [ > 3 | 3 ] -> [ | 4 didmove ]
    [ > 4 | 4 ] -> [ | 5 didmove ]
    [ > 5 | 5 ] -> [ | 6 didmove ]
    [ > 6 | 6 ] -> [ | 7 didmove ]
    [ > 7 | 7 ] -> [ | 8 didmove ]
240 [ > 8 | 8 ] -> [ | 512 didmove ]
    [ > 512 | 512 ] -> [ | 1024 didmove ]
    [ > 1024 | 1024 ] -> [ | 2048 didmove ]

245
    (horizontal move --- copy1 to copy2)

    [copy1 Player][copy2] -> [copy1 Player][copy2 Player]
    + [copy1 no Player][copy2] -> [copy1 no Player][copy2 no
        Player]
250 + right[copy1]->[|copy1]
    + right[copy2]->[|copy2]

```

```

random down [copy1|] ->[|copy1]
random down [copy2|] ->[|copy2]
255
[copy1 Player][copy2] -> [copy1 Player][copy2 Player]
+ [copy1 no Player][copy2] -> [copy1 no Player][copy2 no
  Player]
+ left[copy1|]->[|copy1]
+ left[copy2|]->[|copy2]
260
random down [copy1|] ->[|copy1]
random down [copy2|] ->[|copy2]

[copy1 Player][copy2] -> [copy1 Player][copy2 Player]
265 + [copy1 no Player][copy2] -> [copy1 no Player][copy2 no
  Player]
+ right[copy1|]->[|copy1]
+ right[copy2|]->[|copy2]

random down [copy1|] ->[|copy1]
270 random down [copy2|] ->[|copy2]

[copy1 Player][copy2] -> [copy1 Player][copy2 Player]
+ [copy1 no Player][copy2] -> [copy1 no Player][copy2 no
  Player]
+ left[copy1|]->[|copy1]
275 + left[copy2|]->[|copy2]

(twist)
random right [copy1|] ->[|copy1]
random right [copy2|] ->[|copy2]
280 random [copy1 Player][copy2] -> [copy1 Player][copy2 Player
  ]
random [copy1 no Player][copy2] -> [copy1 no Player][copy2
  no Player]
random right [copy1|] ->[|copy1]
random right [copy2|] ->[|copy2]
random [copy1 Player][copy2] -> [copy1 Player][copy2 Player
  ]
285 random [copy1 no Player][copy2] -> [copy1 no Player][copy2
  no Player]
random up [copy1|] ->[|copy1]
random up [copy2|] ->[|copy2]
random [copy1 Player][copy2] -> [copy1 Player][copy2 Player
  ]

```

```

random [copy1 no Player][copy2] -> [copy1 no Player][copy2
no Player]
290 random left [copy1|] ->[|copy1]
random left [copy2|] ->[|copy2]
random [copy1 Player][copy2] -> [copy1 Player][copy2 Player
]
random [copy1 no Player][copy2] -> [copy1 no Player][copy2
no Player]

295 (second twist)
random right [copy1|||||] ->[|||||copy1]
random right [|||||copy2] ->[copy2|||||]
random [copy1 Player][copy2] -> [copy1 Player][copy2 Player
]
random [copy1 no Player][copy2] -> [copy1 no Player][copy2
no Player]
300 random right [copy1|] ->[|copy1]
random right [copy2|] ->[|copy2]
random [copy1 Player][copy2] -> [copy1 Player][copy2 Player
]
random [copy1 no Player][copy2] -> [copy1 no Player][copy2
no Player]
random down [copy1|] ->[|copy1]
305 random down [copy2|] ->[|copy2]
random [copy1 Player][copy2] -> [copy1 Player][copy2 Player
]
random [copy1 no Player][copy2] -> [copy1 no Player][copy2
no Player]
random left [copy1|] ->[|copy1]
random left [copy2|] ->[|copy2]
310 random [copy1 Player][copy2] -> [copy1 Player][copy2 Player
]
random [copy1 no Player][copy2] -> [copy1 no Player][copy2
no Player]

(return)
315 left[copy1|]->[|copy1]
+ left[copy2|]->[|copy2]
random up [copy1|||] ->[|||copy1]
random up [copy2|||] ->[|||copy2]

320 (If one put the vertical arrow, than switsch back copy1 and
copy2)
random [vert][copy1][copy2] -> [vert][copy2][copy1]

```

```

      (destroy indicator)
      [vert]-> []

325  [glow] -> []
      random [ no Player no wall ][Player didmove] -> [glow][
        Player] sfx0
      [didmove]->[]
      [reach256][256]->[] [256]sfx1
      [reach512][512]->[] [512]sfx2
330  [reach1024][1024]->[] [1024]sfx3

      up [glow specialcase|||||]->[glow specialcase|||||glow2]
      down [glow specialcase|||||]->[glow specialcase|||||glow2]
      left [glow2 specialcase|||||]->[glow2 specialcase|||||
        glow]
335  right [glow2 specialcase|||||]->[glow2 specialcase|||||
        glow]
      [glow2]->[]

      up [glow no specialcase|||||]->[glow|||||glow]
      down [glow no specialcase|||||]->[glow|||||glow]
340  [glow] -> [glow 1]

      =====
      WINCONDITIONS
      =====

345  some 2048

      =====
      LEVELS
350  =====

      Message Welcome to the twisted world!

      Message The original version of 2048 is here: https://gist.
        github.com/tinjoonatan/ada1f82d7a51bad137083c4133ad4fc2
355  Message Here you would have a brand new experience of the
        game 2048. It's simpler since there are more spaces for
        you to move.

      Message Now enjoy it!

360  ?#####

```

```

# c8...###...#
#...###...#
#..oo###..oo#
#..ss###..ss#
365 #####
# d8...###...#
#...###...#
#..ss###..ss#
#..ss###..ss#
370 #####

Message Congratulations!
375 Message You can make more games on this special twisted
      world! It's a special Riemann surface with constant zero
      curvature.
Message If you think that is easy, then try this one!

?#####
380 # c8#...###...#
#...###...#
#..oo###..oo#
#.#ss###.#ss#
#####
385 # d8#...###...#
#...###...#
#..ss###..ss#
#.#ss###.#ss#
#####
390

Message Congratulations! You finally figure it out!

```

8. POV-RAY

8.1. 安装 + 初始代码. POV-Ray 是一款依赖代码的 3D 建模软件, 免费开源, 目前个人感觉是“3D 版本的 Tikz”. 一款能够在短时间内持续追踪光线视觉, 产生高质量计算机图像的工具。” from here.

程序对大小写敏感。

一些特殊符号:

```

o=<0,0,0>, x=<1,0,0>, y=<0,1,0>, z=<0,0,1>, u=<1,0>, v
    =<0,1>.

```

```
sqrt(a), pi, pow(a,n) sin(radians(90)), degrees(atan2(1,1))
```

8.2. **基本逻辑.** 基本几何体请参考[这里](#)。

透明背景设置

superellipsoid 可以画圆角圆柱和方体。

8.3. **调试.** 单行注释使用两斜杠//, 多行注释使用/*注释*/。对于.ini 文档, 单行注释使用分号;

关于输出请参考此文档。

8.4. **参考文档.** 官方文档、视频教程、本地 demo、动画效果

POV-Ray 的经典实例是维度: 数学漫步。另外也可以参考Mathematical Imagery.

关于 3D 建模还有很多优秀的软件, 比如:

- solidwork: 曾经尝试过, 后来删了
- 3DMax: 实例可以参考GM 的建模基地。但是收费。
- blender: 免费开源, 似乎是 3DMax 的高级替代品, 依赖快捷键。

如果我有一台优质的电脑、时间 (没书读时) 和精力那我也会尝试下。现在就算了。

8.5. **(想保留的) 例子.** 这个例子实现了杯子的旋转动画, 并制作了一个好的坐标轴。

```
// POV-Ray Scene File "begin.pov"
// by Friedrich A. Lohmueller, Jan-2013, now Xiaoxiang Zhou
//-----
global_settings{assumed_gamma 1.0}
5 // #default{ finish{ ambient 0.1 diffuse 0.9 }}
//-----

#include "colors.inc"
#include "textures.inc"
10 #include "woods.inc"
//-----
// camera -----
camera{
  location <25,25,25> //best: <25,25,25> <10,-25,25>
15 right -x*image_width/image_height
sky <0,0,1> //see the sky
look_at <0,0,0>
angle 22
}
```



```
20 // sun -----
light_source{
    <25,25,25>,
    White
    shadowless
25 }
// sky -----
sky_sphere{
    pigment{
        gradient z-3
30     color_map {
        [0 color White]
        [0.95 color Blue]
        [1 color White]
    }
35
    scale 2
    translate <0,0,1>
    }
}
40 // axis arrows -----
cone {
    6*x, .1, 6.5*x, 0
}
cone {
45     6*y, .1, 6.5*y, 0
}
cone {
    6*z, .1, 6.5*z, 0
}
50
// axis -----
cylinder {
    -6*x, 6*x, .021
    pigment{ Black}
55     finish {ambient .3}
}
cylinder {
    -6*y, 6*y, .021
    pigment{ Black}
60     finish {ambient .3}
}
cylinder {
    -6*z, 6*z, .021
    pigment{ Black}
```

```

65     finish {ambient .3}
    }
    // grid -----
    #for (i,-5,5,1)
    cylinder {
70         <i,-5,0>, <i,5,0>, .02
        pigment{ Grey}
        finish {ambient .3}
    }
    cylinder {
75         <-5,i,0>, <5,i,0>, .02
        pigment{ Grey}
        finish {ambient .3}
    }
    #end
80
    text {
        ttf "timrom.ttf" "x" 0.05, 0
        pigment { Black }
85        translate -0.25*x
        rotate<90,0,180>
        translate 6*x-0.8*z
    }
    text {
90        ttf "timrom.ttf" "y" 0.05, 0
        pigment { Black }
        translate -0.25*x
        rotate<90,0,90>
        translate 6*y-0.8*z
95    }
    text {
        ttf "timrom.ttf" "z" 0.05, 0
        pigment { Black }
        translate -0.25*x
100       rotate<90,0,135>
        translate 6*z-0.8/sqrt(2)*x+0.8/sqrt(2)*y
    }

    difference{
105 union {
        sphere_sweep {
            b_spline
            7,
            <.7,2.2,0>, .8

```

```

110     <1.5,.5,0>,.3
        <3.1,.5,0>,.3
        <3.8,2.4,0>,.3
        <3.1,4.1,0>,.3
        <1.5,4.1,0>,.3
115     <.7,2.6,0>,.8
        texture{
pigment{ Grey}
finish { phong 1}
    }
120     finish {ambient .3}
        scale <1,1,2.5>
    } //cup
cylinder{
    <0,0,0>, <0,4.75,0>,2
125
        scale 1/4.75

        texture{
pigment{ Grey}
130     finish { phong 1}
    }
        scale 4.75
        finish {ambient .4}
        rotate<0,-60,0>
135     }
    } //end of union

cylinder {
    <0,.2,0>, <0,4.9,0>, 1.8
140     texture{
pigment{ Grey}
finish { phong 1}
    }
        finish {ambient .3}
145
    }
    rotate<90,0,360*clock>
    } //end of difference

```

我们还需要.ini 文档才能够生成动画。

```

; Persistence Of Vision raytracer version 3.7 example file.
2 Antialias=On

Antialias_Threshold=0.1

```

```

Antialias_Depth=2
Input_File_Name=begin.pov
7
Initial_Frame=1
Final_Frame=30
Initial_Clock=0
Final_Clock=1
12
Cyclic_Animation=on
Pause_when_Done=off

```

8.6. **Tasks.** 制造一个基本对象集，以及基本操作。

9. 前端, SUBLIME

9.1. **安装 + 初始代码.** 前端没有啥好说的, 我所理解的就是 html+css+javascript. 初学者用记事本就可以了, 我目前用的是 sublime, 原因请参考这个教程. 代码技术主要参考的是 W3(英文版)、Web 技术教程.

9.2. **非初等但是值得学习的库.**

- Apache ECharts: 一个基于 JavaScript 的开源可视化图表库，不过这里的图表限定范围较窄。

10. 电脑快捷键 (中级)

部分参见 Chrome 快捷键。

- ctrl+win+left: 切换桌面
- alt+(shift)+tab: 切换任务栏上的程序
- ctrl+(shift)+tab: 切换标签页
- win+D: 显示桌面
- win+left: 页面占左半边
- win+R: 调出运行窗口

11. 正则表达式

正则表达式可以大幅提升搜索和修改代码的效率。

```
1 .{0,100}(?=\d{0,3};\d{0,3}m\n);\d{0,3});(\d{0,3})m\n
```

11.1. **参考文档.** 推荐 B 站视频。与之配套的练习。

你可以在 regexr 中测试。

12. 热键设置 (AutoHotkey)

这是一款开源软件。为了 Hackergame 的脚本，同时我猜会大幅度提高打代码的速度。我想可以实现快速打笔记的功能？

12.1. 调试. 注释使用分号；。

12.2. 参考文档. 官方文档. ；

12.3. (想保留的) 例子. 这个例子模拟鼠标和键盘，使用了条件和循环语句。

```

^j::
Sleep,300
loop, 1
{
5   Random, rand, 1, 999
      CoordMode, ToolTip
      Click, 1743 81 1
      Sleep, 100
      Click, 36 64 2
10   Sleep, 100
      Send, {rand}.0.0.0
      Sleep, 100
      Click, 433 323 2
      Sleep, 100
15   Send, 0.0.0.0
      Sleep, 100
      Click, 452 321 1
      Sleep, 100
      if GetKeyState("F10")
20   {
      break
      }
      Sleep,1000
}
25 Return

```

这是第二版本，能够 95% 成功提交。

```

#MaxThreadsPerHotkey 3
^j:: ; 热键(可根据您的喜好改变此热键).
#MaxThreadsPerHotkey 1
if KeepWinZRunning ; 这说明一个潜在的线程正在下面的循环中
   运行.
5 {
      KeepWinZRunning := false ; 向那个线程的循环发出停止的
      信号.

```

```

    return ; 结束此线程，这样才可以让下面的线程恢复并得知
        上一行所做的更改。
}
; 否则:
10 KeepWinZRunning := true
    rand := 0
    Loop
    {
        ; 以下四行是您要重复的动作(可根据您的需要修改它们):
15     MyNumber := rand . ".233.233.233"
        Click, 1743 81 1
        Sleep, 70
        Click, 74 74 2
        Sleep, 70
20     Send, %MyNumber%
        Sleep, 70
        Click, 429 346 2
        Sleep, 80
        Send, %MyNumber%
25     Sleep, 90
        Click, 1073 31 1
        Send ^{Click 432 360 1}
        Sleep, 190
        rand += 1
30     ; 但请不要修改下面剩下的内容.
        if not KeepWinZRunning ; 用户再次按下 Win-Z 来向循环发
            出停止的信号.
            break ; 跳出此循环.
    }
    KeepWinZRunning := false ; 复位，为下一次使用热键做准备.
35 return

```

第三个版本可以提交 254 个，还剩 2 个。。。

```

#MaxThreadsPerHotkey 3
^j::
#MaxThreadsPerHotkey 1
if KeepWinZRunning
5 {
    KeepWinZRunning := false
    return
}
KeepWinZRunning := true
10 rand := 0
    Loop
    {

```

```

    MyNumber := rand . ".233.233.233"
    Click, 1751 91 1
15    Sleep, 120
    Click, 74 74 2
    Sleep, 50
    Send, %MyNumber%
    Sleep, 70
20    Click, 429 346 2
    Sleep, 80
    Send, %MyNumber%
    Sleep, 50
    Click, 587 747 1
25    ;Click, 1073 31 1
    Send ^{Click 387 437 1}
    Sleep, 60
    rand += 1
    if not KeepWinZRunning
30        break
}
KeepWinZRunning := false
return

```

最后成功的版本:

```

#MaxThreadsPerHotkey 3
2 ^j::
#MaxThreadsPerHotkey 1
if KeepWinZRunning
{
    KeepWinZRunning := false
7    return
}
KeepWinZRunning := true
rand := 0
Loop
12 {
    MyNumber := rand . ".233.233.233"
    Click, 1751 91 1
    Sleep, 120
    Click, 74 74 2
17    Sleep, 50
    Send, %MyNumber%
    Sleep, 70
    Click, 429 346 2
    Sleep, 80
22    Send, %MyNumber%

```

```

        Sleep, 40
        Click, 587 747 1
        ;Click, 1073 31 1
        Send ^{Click 387 437 1}
27     Sleep, 60
        rand += 1
        if not KeepWinZRunning
            break
    }
32 KeepWinZRunning := false
    return

```

12.4. **Tasks.** 通过该软件创建一个 L^AT_EX 的脚本，要求：

- 自动翻译 iff, SES, LES, mfl, rep...
- 长段代码如 equ+aligned
- 只在打开 TeXstudio 时生效 (使用 IfWinActive+Window Spy)

通过该软件创建一个脚本，要求：

- 自动打开日常软件
- 将其放入开机启动项

已完成，代码如下：

```

#IfWinActive, ahk_class Qt5QWindowIcon
2  ::SES::short exact sequence

    ::LES::long exact sequence

    ::TFAE::the following are equivalent:
7  ::iff::if and only if

    ::st::such that

12  ::eg::for example

    ::wrt::with respect to

    ::geo::geometry
17  ::cont::continuous

    ::diff::differential

```



```
22 ::sm::smooth
    ::mfld::manifold
    ::lb::line bundle
27 ::mlb::metrized line bundle
    ::vb::vector bundle
32 ::cplx::complex
    ::RS::Riemann surface
    ::AG::algebraic geometry
37 ::agc::algebraic geometric
    ::AV::abelian variety
42 ::ell::elliptic curve
    ::proj::projective ;be careful for projection
    ::inj::injective
47 ::fct::function
    ::fctor::functor
52 ::iso::isomorphism
    ::irr::irreducible
    ::ind::indecomposable
57 ::adm::admissible
    ::rep::representation
62 ::repe::representable
    ::Archi::Archimedean field
    ::sign::Best wishes,`n`nXiaoxiang Zhou
```

```

67  ::sym::symmetric

    ::corrg::corresponding ;be careful for correspondence

72  ::corre::correspondence

    ::sset::simplicial set

    ::LLC::local langlands correspondence

77  ::align:: ;超长变换,我的Texstudio还是有些问题
    (
    \begin{equation*}
    \begin{aligned}
82    =\;&\& \\\
    )

    ::draw:: ;Texstudio如何原样打出?
    (
87  \begin{figure}[ht]
        \vspace{0cm}
        \centering
        \includegraphics[width=12cm]{}
        \label{fig:}
92    \caption{}
    \end{figure}
    )

    ::minipage::
97  (
    \begin{figure}[th]
        \begin{minipage}[t]{.48\textwidth}
            \centering
            \includegraphics[width=\textwidth]{}
102        \label{fig1}
        \end{minipage}
        \begin{minipage}[t]{.48\textwidth}
            \centering
            \includegraphics[width=1\textwidth]{}
107        \label{fig2}
        \end{minipage}
        \caption{}
        \end{figure}
    )

```

```

112 ^+c:: ;注释
    send ^c
    sleep, 200
    clipboard=%clipboard%
117 tooltip, %clipboard%
    sleep, 500
    tooltip,
    return

122 ::||:: ;临时符号
    (
    \norm{\cdot}
    )

127 ::CLm::Chambert-Loir measure

    ::dps::\displaystyle

    ::comm diag::commutative diagram

132 ::reso::resolution

    ::pfv::partial flag variety

137 ::qgr::quiver Grassmannian

    ::dv::dimension vector

    #IfWinActive
142 ^j::
    Run, "F:\hide\Snipaste\Snipaste.exe"
    Run, "F:\hide\WiFi 共享大师\WiFiMaster.exe"
    return

```

13. 其他

这里收集乱七八糟的材料，以后说不定可以单独搞个文件。

13.1. 数学的可视化. 这里以四维空间为例。

可以参考Andrew J. Hanson 的主页，也可以参考Github 中的项目(这里有很多可以了解到的就不引用了)。

脑洞：参考四维截面游戏，我们是否可以做个四维版本的小球进洞？

13.2. 数学与游戏. 脑洞: 搞个 Riemann surface 的世界, 在介绍这个世界的时候以神的旨意来介绍相关概念

1. 安装 Unity
2. 用 sublime 配置 unity
3. 制作横版跳跃游戏, 包含:
场景/人物/交互/动作(左右动, 跳跃, 蹲)/人物动画
4. 制作贪吃蛇游戏, 熟悉代码(无边框, 不蠢, 带格子)
5. 制作扭结+贪吃蛇游戏
6. 制作黎曼面游戏(两点)
- 8 方程
游戏类型: 找不同? 横版跳跃? 迷宫? 五子棋(4/3子棋, 粘附5/4/3子棋)? 围棋(扭羊头游戏)? 跳棋? 空间爬行? 扭结+贪吃蛇? 塔防? 数独? 数回? 华容道? ORBOX B?(这玩意可以做成三维版本! 4维就有点难了)(mini metro? 连连看? 泡泡龙? 消砖块? 2048? 推箱子? 其他的Nikoli Puzzles?)
- 简易示意图
可能引入的概念: Laurent 展开/同调群、基本群的概念(在数回中, 请使得最后画出的曲线表示基本群不平凡但是同调群不平凡)/覆盖, 万有覆盖, deck transformation(华容道简化难度: 允许 deck transformation 将区块变换至另一个基本区域中相同的位置; 或者, 我们允许上下粘接)/曲率/曲率驱动游戏/descent(数独解何时能成为更小的黎曼面的解)
- 视角: 收敛区域视角(遮罩圆形)、星形区域视角、基本区域视角、万有覆盖视角、第一人称视角、二维3D视角(视角需要通过"培训+考试"解锁)
- 13 虚拟对话
- 宇宙到底是啥?(永远都到达不了的点是否真的存在? -black hole 宇宙是几维的? 2+3(颜色)+1(时间) 如何测量时间, or 时间的流逝是否是均匀的?)
- 自由意志(我可以自由地说我想说的东西, 而你的输入却受到限制)
- 表达自己想做却做不到的事
- 18 - 对数学的热爱

脑洞: 利用扭结来制作游戏, 例如“贪吃蛇”。需要的时候考虑离散化, 也可以考虑离散版本的 Reidemeister moves。游戏制作的难点在于如何判定成功(好的 Goal 是啥。很难去说明一个扭结和另一个扭结等价) 扭结的相关知识可参考这个视频。Ballance 如果能添加磁场和电场, 考虑带电小球(不考虑电磁感应)的话就是高中物理的必玩游戏了。

13.3. 数学相关句子模板. 这里收集“啊我之前不知道咋表达, 这就是我当时卡住的时候可以用的句子!”的外文句子。绝对是原创的。

```

notations:
Beginning with..., only ... are considered.
shorthand
By an aesthetically desirable abuse of notation,
6 One word about the notation: for simplicity we often omit
    ...
For notational reasons we usually extend the ... to (
    negative indices) by defining ...
The term ... is a convenient, but temporary, expedient.
To save adjectives, if ... is described as ..., it is
    implicitly assumed to be ...
Finally, a word about terminology.
11 However on many occasions it is natural or customary to
    stay in ... mode when nonetheless one has ... in mind.
While for the most part this convention seems to work well,
    it occasionally leads us to make extraneous ...
    hypotheses in order to invoke ...
We try to flag this artifice when it occurs.
The following abuse of notation will prove handy:...

16 refer to:
The main references for the material covered in this
    section are ...
A more detailed overview of this chapter may be obtained by
    reading the introductions to the various sections.
More detailed treatments appear in ..., to which we will
    refer for proofs.
mimic the arguments for ...
21 We refrain from giving a more detailed introduction here
    and instead refer the reader to the table of contents as
    well as to the short introductions of the individual
    sections.
References for ... include the monograph ... and the more
    introductory account ...

example and generalization:
prototypical example
26 By the same argument as the special case above, ...
The arguments in ... carry over mutatis mutandis.
provide a navigable route into the area with a complete and
    self-contained account of the case ...
eschew all generality
exploit special features to abbreviate/simplify the
    arguments
31 tinker with the examples

```

Disclaimer:

minor errors **and** obscurities, a couple of significant lapses

I am by far **not** a person with serious knowledge/ understanding of ..., thus **in** the ... I may oversimplify /overcomplicate things, be inaccurate, **or** even wrong, **and** miss subtelties.

36 I have actually been meaning to correct some typos **for** a **while and** so I will hopefully do **all** these corrections **in** the **next** few weeks.

technical problem:

achieve some technical control

Ceci nous contraint à prouver ... par une voie détournée

41 It should be noted that even **if** one **is** interested only **in** ..., the proofs often involve more general ...

ask **for** details:

I find there are a lot of cool ideas **in** your answers, but I would be grateful **if** you could be a bit more precise.

46 digression:

We now want to describe the ... This can be done **in** a more straightforward way, but we prefer to include a short digression **in** ... theory as this allows us to mention a general fact which **is in** the background of a later construction anyhow.

Nevertheless, the reader can skip this digression without loss of continuity **and continue** with ... instead.

excitement/beauty:

51 The literature on ... **is** vast **and** often technical, but the underlying ideas are possessing of an undeniable beauty. The excitement provoked by ... stimulated a period of intense **and** widespread activity.

convey the breadth **and** excitement of the ideas

At first sight, ... does **not** seem

very natural **from** a ... perspective. However, at least **for** ..., ... **is** important **from**

56 ... perspective, since...

connect different areas:

unveils intricate links between

reveals connections between

```

61 is akin to the phenomenon of ...
   is deeply intertwined with
   give a bird's eye view on

   waiting for classification:
66 equivalently(replace i.e.)
   encyclopaedic knowledge of ...
   In fact, the arguments used in the final part of this proof
     , give the following result.
   Let us unravel this definition a little.(after complicated
     definition)
   ... is pivotal in this matter./ ... play a pivotal rôle.
71 The arithmetic/information/structure of ... is encapsulated
     in ...
   encapsulate a significant amount of information concerning
     ...
   We point out the similarities and the differences whenever
     appropriate.
   There is also some degree of novelty in our treatment of
     ...
   ... contiennent les outils requis pour surmonter ces
     difficultés.
76 give a sense of the directions in which the area is going.
   there is nothing to be gained from specialization at this
     stage
   take it as a little rebus
   whirlwind tour of ...
   be enamored with
81 brackets:
   {}:curly set brackets
   ():round brackets
   []:square brackets
   <>:angle brackets
86 beginning words: Goals, Pros and Cons

```

另外关于英语语法，可以参考天文物理类英文科技论文写作的常见问题。

13.4. 德语日常句子。临时存储这里。

```

Ich bin pappsatt.
Der Fisch war nicht üppig.
3 Es war ein großer Reinfall!
Wir müssen feststellen, inwiefern sich die Situation geä
  ndert hat.

```

ums Leben kommen
Jeder ist seines Glückes Schmied.

REFERENCES

SCHOOL OF MATHEMATICAL SCIENCES, UNIVERSITY OF SCIENCE AND TECHNOLOGY
OF CHINA, HEFEI, 230026, P.R. CHINA,
Email address: `xx352229@mail.ustc.edu.cn`