

代码

周潇翔

摘要. 这里总结自己学过的代码供查阅。为啥不用英文？英文的参考文献浩如烟海，也不差我一个啊。另外引用的很多网页也都是中文的，我也懒得再花时间解释哪个是中文哪个是英文了。对数学系的同学而言，代码的逻辑并不难，大家不会的只是格式而已。第一节横向介绍我们需要啥，之后纵向对每一种语言给出对应的代码。

在这份文档的编译中第一次学 python 和 Github, 可以说是紧跟潮流
23333

1. 代码需求

大部分的语言都需要：

- 安装 + 初始代码 (Halloworld)
- 基本逻辑
- 调试
- 参考文档
- (想保留的) 例子

以下是具体需求：

1.1. 安装 + 初始代码.

- 简要说明该语言的目的
- 说明自己使用何种编译器
- 解释该语言的结构 (基本框架)
- 使用该语言在屏幕中打出”Halloworld”
- 必要时给出英文注释

1.2. 基本逻辑.

- 数据结构类型 (数字、字符串、其他结构)
- 基本四则运算 + mod (若数据结构中包含矩阵，则需要矩阵的各类运算；)
- 条件语句
- 循环语句

- 函数

对于图形化输出的语言，我们还有很多额外的需求：

- 图形

- 基本几何图形 (尽可能多样化)
- Bézier 曲线 (钢笔工具)
- 参数化曲线
- 直线，箭头等基本图形库，电路，棋盘，乐器等专业库
- 几何变换 (平移，旋转，伸缩)
- 集合运算 (如交并补)
- 几何运算 (如平行，垂直，切线，交点)
- 度量衡转换 (数值，距离单位，向量运算，弧度制与角度制)
- 测量

- 图形进阶

- 光滑化
- 锐化

- 坐标系

- 直角坐标系
- 其他类型坐标系

- 其他细节

- 颜色设置
- 背景与边界设置
- 透明背景设置
- 图片嵌入设置
- 材质设置
- 数学字体嵌入设置
- 动画 + 声音嵌入设置 (可选)

对于主要用于排版的语言，我们还希望能了解页面布局的相关知识，如盒子模型。

1.3. 调试.

- 快捷键 (Keyboard shortcut)

- 运行代码
- 注释方式及快捷键 (单行注释 + 多行注释)
- 自动补全功能
- 自动对齐功能

– 其他快捷键

- 如何获得帮助
- 控制输出 (包含调整至 debug 模式)
- 如何设置断点
- 控制输入

1.4. 参考文档.

- 官方文档
- 民间优秀文档

超出科大 C 语言的知识: 编程范式 (Programming paradigm)、方法 (method)

2. PYTHON

2.1. 安装 + 初始代码. Python 是一门高级的编程语言。他有许多的标准模块 (standard module). 你可以在网上在线的编辑器CoCalc练习 Python.¹

2.2. 基本逻辑. 与 C 语言不同, Python 不需要声明变量。当有赋值时不输出结果。

数据类型在这里看到。²

对于数字, Python 不仅有 int 和 float, 还有 Decimal, Fraction and complex numbers 这些奇葩的变量。Task: 学会 Decimal, Fraction.

```
1 >>> complex('1+2j')*complex('1+3j')
```

四则计算像自然计算一样自然, 不过带余除法用//, 余数用%, 幂次用**.(好符号)³

```
>>> a,b=8,13 # a++ is not allowed in python
>>> a ** (b-1) % b # verify the Fermat's little theorem
```

计算器上的 Ans 记为_, round(0.142857,1)给出 0.1

python 中的逻辑运算符如下: 与 (and &), 或 (or |)

条件语句和循环语句的书写规范详见这里。以下是计算素数的例子。

```
import math    # Compute square root
def isPrime(n):    # return true when n is a prime
    for x in range(2, math.isqrt(n)+1):
        if n % x == 0:
```

¹但是使用图形化用户界面时往往需要下载。

²你需要知道那些类型是可改变的 (mutable);

³请小心使用负数的带余除法。

```

5         return False;
    else:
        # loop fell through without finding a factor
        return True;
isPrime(57)

```

用库可以更加容易地计算素数:

```

1 from sympy.ntheory import isprime
  isprime(10000019)

# find primes by sieve method
from sympy import sieve
3 sieve._reset() # this line for doctest only
  # 10000019 in sieve    #10000019 is a prime
  sieve.extend(100)
  sieve._list

```

2.3. 调试. 单行注释使用井号#, 多行注释使用'''注释'''or """注释""". 快捷键为 Ctrl+./.

控制输入使用函数input()。

2.4. 参考文档. 官方文档 SymPy PKU CS 自学指南 python 教程

2.5. 可能会学习的标准模块.

- Tkinter: GUI 图形界面。可以参考教程.

2.6. (想保留的) 例子. 这个例子计算正整数的各位数之和, 用到了把数转化为字符串的技巧:

```
print(sum([int(d) for d in str(int(input("number:"))])))
```

这个例子计算 gl_n 幂零轨道的维数.

```

# this computes dimension of orbits of nilpotent elements
young_diagram = [2,1,1,1,1] # Here is the input
n=len(young_diagram)
4 a,b=0,0
  for i in range(n):
    a=a+young_diagram[i]
    for j in range(n):
      if young_diagram[i]<young_diagram[j]:
9         b=b+young_diagram[i]
      else:
        b=b+young_diagram[j]
c=a**2 -b

```

```
print("the dimension of this orbit is", str(c)+".") # one small trick for
printing result
```

这个例子想要验证某个猜想。据说是 BSD 猜想的推论。

```
from sympy.ntheory import isprime
2 import math      # Compute square root
def isQuart(k):
    for i in range(k//2):
        if i**4 % k == 3:
            return True
7     return False
def solution(m):
    n=math.isqrt(m)+1
    num=0
    for i in range(n):
12         for j in range(n):
            for k in range(n):
                if 6* i**2+j**2+18* k**2 == m:
                    #print("find the solution", i, j, k)
                    if i*j*k==0:
17                         if k % 2 ==0:
                            num=num+4
                        else:
                            num=num-4
                    else:
22                         if k % 2 ==0:
                            num=num+8
                        else:
                            num=num-8
    return num
27 for l in range(25, 10000, 24):
    if isprime(l) & (isQuart(l)==False):
        #print(l,"find the number")
        if solution(l) % 16 ==8:
            print("the conjecture is true for ", l)
32     else:
        print("the conjecture is not true for ", l)
```

这个例子计算 affine quiver 正根的可能情形 (real positive root + regular simple).

```
# Usage of format
2 # E6 case
```

```

orderedCouple1 = [(a1,a2,a3,a4,a5,a6,a7) for a1 in range(2) for a2 in
    range(3) for a3 in range(4) for a4 in range(3) for a5 in range(2) for
    a6 in range(3) for a7 in range(2)]
k=0 # compute the number of positive real root which is possible regular
    simple
for a1,a2,a3,a4,a5,a6,a7 in orderedCouple1: # do everything in one line*
    if a1**2+a2**2+a3**2+a4**2+a5**2+a6**2+a7**2-a1*a2-a2*a3-a3*a4-a4*a5-
        a3*a6-a6*a7 ==1:
7         k=k+1
        print('                                {0}'.format(a7)) #ugly code
        have better output
        print('                                {0}'.format(a6))
        print('The positive real root is {0}, {1}, {2}, {3}, {4}.'.format(
            a1,a2,a3,a4,a5))
        print("")
12    print('There are {0} results'.format(k))

# E7 case
orderedCouple2 = [(a1,a2,a3,a4,a5,a6,a7,a8) for a1 in range(2) for a2 in
    range(3) for a3 in range(4) for a4 in range(5) for a5 in range(4) for
    a6 in range(3) for a7 in range(2) for a8 in range(3)]
k=0 # compute the number of positive real root which is possible regular
    simple
17 for a1,a2,a3,a4,a5,a6,a7,a8 in orderedCouple2: # do everything in one line
    *
    if a1**2+a2**2+a3**2+a4**2+a5**2+a6**2+a7**2+a8**2-a1*a2-a2*a3-a3*a4-
        a4*a5-a5*a6-a6*a7-a4*a8 ==1:
        k=k+1
        print('                                {0}'.format(a8)) #ugly
        code have better output
        print('The positive real root is {0}, {1}, {2}, {3}, {4}, {5},
            {6}.'.format(a1,a2,a3,a4,a5,a6,a7))
22    print("")
    print('There are {0} results'.format(k))

# E8 case
orderedCouple3 = [(a1,a2,a3,a4,a5,a6,a7,a8,a9) for a1 in range(2) for a2
    in range(3) for a3 in range(4) for a4 in range(5) for a5 in range(6)
    for a6 in range(7) for a7 in range(5) for a8 in range(3) for a9 in
    range(4)]
27 k=0 # compute the number of positive real root which is possible regular
    simple
for a1,a2,a3,a4,a5,a6,a7,a8,a9 in orderedCouple3: # do everything in one
    line*

```

```

if a1**2+a2**2+a3**2+a4**2+a5**2+a6**2+a7**2+a8**2+a9**2-a1*a2-a2*a3-
a3*a4-a4*a5-a5*a6-a6*a7-a7*a8-a8*a9 ==1:
    k=k+1
    print('                                {0}'.format(a9)) #
ugly code have better output
32     print('The positive real root is {0}, {1}, {2}, {3}, {4}, {5},
        {6}, {7}'.format(a1,a2,a3,a4,a5,a6,a7,a8))
        print("")
print('There are {0} results'.format(k))

# E6 case, subspace case
37 orderedCouple1 = [(a1,a2,a3,a4,a5,a6,a7) for a1 in range(2) for a2 in
    range(3) for a3 in range(4) for a4 in range(3) for a5 in range(2) for
    a6 in range(3) for a7 in range(2)]
k=0 # compute the number of positive real root which is possible regular
    simple
for a1,a2,a3,a4,a5,a6,a7 in orderedCouple1: # do everything in one line*
    if a1**2+a2**2+a3**2+a4**2+a5**2+a6**2+a7**2-a1*a2-a2*a3-a3*a4-a4*a5-
        a3*a6-a6*a7 == 1 and a1+a2-3*a3+a4+a5+a6+a7==0:
        k=k+1
42     print('                                {0}'.format(a7)) #ugly code
        have better output
        print('                                {0}'.format(a6))
        print('The positive real root is {0}, {1}, {2}, {3}, {4}'.format(
            a1,a2,a3,a4,a5))
        print("")
print('There are {0} results'.format(k))

```

3. SAGE

3.1. 安装 + 初始代码. Sage 是专为数学家设计的程序, 基于 python, 通过集成大量数据库, 使用其中的数学函数来简化编程难度。我使用的是网上在线的编辑器CoCalc, 在 New 中生成 Sage worksheet. 你可以在每一行前添加sage: 或者不加。在最开始输入需要的宏包, 然后直接进行计算即可。

```
sage: print("Halloworld!233") #The code is the same as
python
```

3.2. 基本逻辑. 本节的基本内容参见[这里](#)。

3.3. 调试. 大部分同 python.

3.4. 参考文档. 官方文档

Sage V9.1 中文文档以及专题文档

Sage Quick Reference Cards

Sage for Undergraduates

基本例子的视频教程

除了 sage 外还有一些数学自动证明软件, 比如Lean theorem prover. 只是我懒不想学自动证明。

3.5. (想保留的) 例子. 这个例子能帮助我计算 Dynkin quiver 的所有不可约表示.

```
sage: Q = DiGraph({1:{2:['a1']},2:{3:['a2']},4:{3:['a3']},5:{4:['a4']},6:{3:['a5']}}).path_semigroup()
sage: M = Q.I(GF(11),3)
sage: M
4 sage: tauM = M.AR_translate()
sage: tauM
```

这个例子能帮助我画出 $\Gamma(5)$ 对应的基本区域.

```
G5 = Gamma(5)
A = FareySymbol(G5).fundamental_domain(show_pairing = true)
show(A, figsize=10, fontsize=10)
```

4. MANIM COMMUNITY

4.1. 安装 + 初始代码. 这是做数学科普视频的软件, 同样基于 python, 其对数学公式的支持远远超过了其他软件, 而且是开源的。不想安装的懒惰者可以试试在线编译网页 EulerTour。

4.2. 参考文档. 官方文档

中文文档

可以参考hello world 视频教学,常用代码总结/教程

实例:3B1B 的所有动画视频, Dirac's belt trick和自由变形动画。

5. LATEX

5.1. 本文参考文献. listings 的具体设置

fancy 版本的 Mathematica 代码没学会。

L^AT_EX 中如何自动补全代码? 不容易。

本文 python 代码格式来源

5.2. 参考文档. 刘海洋的书: 《L^AT_EX 入门》

如何在 latex 里面使用注释效果、tikz 整体调整、颜色名称设置总结

如何在 amsart 下调整目录

5.3. 非初等但是值得学习的宏包.

- Tikz: 数学系画图专属宏包, 其子宏包 Tikzcd 也是相当实用⁴, 为了简化制图流程大佬们甚至做了两个网站tikzcd-editor和quiver: a modern commutative diagram editor, 都非常实用。另外还可以尝试TikZiT来辅助画图。
- hobby: 画曲线的宏包 (妈妈再也不用担心我画 Tikz 中的曲线)
- tcolorbox: 把文档变得花里胡哨的宏包 (你甚至可以做海报)

5.4. (想保留的) 例子. 这个例子可以画文本宽度的水平直线, 并把公式拉长到文本宽度:

```

\hrule % show text width
2 \resizebox{\textwidth}{!}{ %show the formula very big
    $\displaystyle \frac{1}{\pi}=\frac{2\sqrt{2}}{99^2}
    \sum_{k=0}^{\infty} \frac{(4k)!}{k!^4}\frac{
    {26390k+1103}{396^{4k}}$
}
\begin{gather*} % or small
3.1415926535897932384626433832795028841971693993751
7 058209749445923078164062862089986280348253421170679
821480865132823066470938446095505822317253594081284
8111745028410270193852110555964462294895493038196
\end{gather*}

```

6. MATHEMATICA

6.1. 安装 + 初始代码. Mathematica 是收费的数学计算软件, 参考文档量多但是不够有结构性, 导致我的代码往往是临时性的, 每次计算都需要重新学习代码。(而且我也没有结构性地保存它们) 不过现在可以在这份文档中储存代码了。

6.2. (想保留的) 例子. 这个例子能帮我计算 affine quiver 相关的矩阵.

```

Cp = ({
    {1, 1, 1, 0, 0, 0},
    {0, 1, 1, 0, 0, 0},
    {0, 0, 1, 0, 0, 0},

```

⁴tikzcd is in fact only an improvement of matrix in TikZ. Cited from here.

```

5      {0, 0, 1, 1, 0, 0},
      {0, 0, 1, 1, 1, 0},
      {0, 0, 1, 0, 0, 1}
    });
    Ci = Transpose[Cp];
10  Phi = -Ci.Inverse[Cp]
    MatrixPower[Phi, 6]
    A = Transpose[Inverse[Ci]] + Inverse[Ci] (*symmetric form*)

```

这个例子计算四元数 \mathbb{H} 上的 non-reduced norm.

```

Det[({
  {x, -y, -z, -w},
3  {y, x, -w, z},
  {z, w, x, -y},
  {w, -z, y, x}
})]
Factor[w^4 + 2 w^2 x^2 + x^4 + 2 w^2 y^2 + 2 x^2 y^2 + y^4
+
8  2 w^2 z^2 + 2 x^2 z^2 + 2 y^2 z^2 + z^4]

```

这个例子画彩色的点.(255 位 RGB)

```

ListPlot[{Style[{1, 1}, {2, 3}, {2, 4}],
2  Interpreter["Color"]["RGB 255 0 0"]],
  Style[{1.5, 1}, {2.3, 3}, {2.4, 4}],
  Interpreter["Color"]["RGB 0 255 0"]]}]

```

7. PUZZLESCRIPT

游戏制作软件:Unity 可以由免费开源游戏引擎Godot替代。简单的 2D 游戏可以先尝试用 PuzzleScript 实现。

请注意, PuzzleScript 只是一个类推箱类游戏制作语言, 比较难制作 3D/扭曲/用鼠标处理的游戏, 而且基本逻辑不完备导致许多功能的实现需要大量技巧。如果不是技术开发狂热者请只把它当成游戏开发初始阶段的调试器使用。

7.1. 基本逻辑. 本节目前主要讨论 RULES. 在 OBJECT 中可以用 transparent 来表示变量 (在正常对象之后), 在 LEGEND 中请将一个字符放在其他变量名之后。

RULES 的基本结构是keyword1 [keyword2 objectA] -> [objectB] result, 其中

- keyword1可以取 up/down/left/right, horizontal/vertical, random, +, late, **global**, orthogonal;
- keyword2可以取 >/</~/v/up/down/left/right, moving/stationary, no, action;
- result可以取 Message, sfx0, win, checkpoint, restart, cancel, again.

否定语句比较困难, 目前只知道部分否定, 如[Background no Player]->[wall]。⁵

RULES 中的每一句都是循环至不再循环为止, 如果不允许循环, 在该句之前输入random; 如果需要多行语句合在一起循环, 则从第二行起每行前添加+.

循环语句以 startloop 开始, 以 endloop 结束, 当循环的过程不再改变游戏内容时停止。(这种循环语句是不是智障?)

7.2. 调试. 单行多行注释使用括号(). 快捷键可以参考这里。

Debug 可以在 Prelude 中写上verbose_logging, 或者功能弱一点的debug. 另外游戏中可以用音效来辅助调试.

7.3. 参考文档. 官方文档 和官方例子

一些例子。差不多类推箱游戏都有 PuzzleScript 的版本。

7.4. (想保留的) 例子. PuzzleScript 网上的例子已经非常方便了。这里只是把网上的例子改着玩。

```

title Basic Objects
author Xiaoxiang Zhou
homepage http://home.ustc.edu.cn/~xx352229/
background_color #222323
5 text_color #f0f6f0
  (color_palette 3)
  zoomscreen 10x10
  enable_level_select
  (
10 References
  https://www.sokobanonline.com/play
  http://www.sneezingtiger.com/sokoban/levels/microbanText.
    html
  https://www.sohu.com/a/274843792_627888

```

⁵通过部分否定以及一些额外的变量即可达到全局的否定, 就是代码丑陋一点罢了。

```
15  )
    =====
    OBJECTS
    =====

20  Background
    green lightgreen  darkgreen
    00000
    10000
    00010

25  00000
    01000

    Target
    DarkBlue

30  .....
    .000.
    .0.0.
    .000.
    .....

35

    Wall
    BROWN DARKBROWN
    00010

40  11111
    01000
    11111
    00010

45  Player
    darkblue red BLACK
    .000.
    .000.
    11111

50  .111.
    .2.2.

    Crate
    orange

55  00000
    0...0
    0...0
    0...0
    00000
```

```
60 Spike
   black gray white
   .....
   ..0..
65 .010.
   02110
   02210

   Stone
70 black white
   .000.
   00110
   00010
   00000
75 .000.

   Angle
   BROWN red
   00000
80 0111.
   011..
   01...
   0....

85 0
   black
   .000.
   .0.0.
   .0.0.
90 .0.0.
   .000.

   1
   black
95 ..0..
   .00..
   ..0..
   ..0..
   .000.

100 2
   black
   .000.
   ...0.
```

105 .000.
.0...
.000.

3

110 black
.000.
...0.
.000.
...0.
115 .000.

4

black
.0.0.
120 .0.0.
.000.
...0.
...0.

5

black
.000.
.0...
.000.
130 ...0.
.000.

6

black
.000.
135 .0...
.000.
.0.0.
.000.

140

7

black
.000.
...0.
145 ...0.
...0.
...0.

8

```
150 black
    .000.
    .0.0.
    .000.
    .0.0.
155 .000.

    9
    black
    .000.
160 .0.0.
    .000.
    ...0.
    .000.
    =====
165 LEGEND
    =====

    . = Background
    # = Wall
170 P = Player
    * = Crate
    @ = Crate and Target
    O = Target
    ! = Spike
175 S = Stone
    A = Angle

    =====
    SOUNDS
180 =====
    player Move 33184907
    Crate Move 412312
    EndLevel 123413
    Player CantMove 4123412
185 =====
    COLLISIONLAYERS
    =====

    Background
190 Target
    Player, Wall, Crate
    Spike
    0,1,2,3,4,5,6,7,8,9
    Stone, Angle
```

```

195  =====
    RULES
    =====

200  [ > Player | Crate ] -> [ > Player | > Crate ]
    late [ Player Spike ] -> [ Spike ]
    =====
    WINCONDITIONS
    =====

205  All Target on Crate

    =====
    LEVELS
    =====

210  level_select_point
    MESSAGE I make no claim for the original.

215  MESSAGE Just some test.

    .#p*0@!SA..
    .#####.
    .#..p*.o...
220  .#####.
    01234567890

    level_select_point
    MESSAGE Er. I copied something to check.

225  #####
    #.*00..#
    #P*...*.#
230  #..00*.*#
    #####

    level_select_point
    message If you don't know how to solve this, you can try
        the SokobanAutomaticSolver: http://m.wodown.com/soft/14821.html#downAddress

235  .....####.
    #####.p#.

```



```

#.....*...#.
#...*##.*#.
240 ###*#ooo#.#.
    .#.*ooo...#.
    .#.#o.o#.#.
    .#...#.#*.#
    .#*...*...#.
245 .#..#####
    .####.....
    level_select_point

#####
250 ###...###
    ##.....#
    ##@#@#@.#
    ##.#p*..##
    ##.#.#o##
255 #.....##
    #...#...##
    #####

260 level_select_point

#####
#####...##
#.*...*...##
265 #.#...o#.#.
    #..o.#op.#
    ##*#.@...#
    ##...#####
    #####

270 MESSAGE Thank you for playing the game.

```

想要做自己的游戏，先得学会复刻已有的小游戏。做了点尝试。

小技巧：制造边缘砖块的方式（堆叠）以及关卡编辑器中可以使用特殊符号来形象表达，比如LUMirror 。

```

title Demake of ORBOX B
author Xiaoxiang Zhou
homepage http://home.ustc.edu.cn/~xx352229/
background_color #222323
5 text_color #f0f6f0
(color_palette 3)

```

```

verbose_logging (for better debug)
youtube CKAc3nYEatw
enable_level_select
10 (realtime_interval 0.15 (automove)
    again_interval 1 (The amount of time it takes an 'again'
        event to trigger. We won't use it.)
    key_repeat_interval 0.10 (hold one key))
=====
OBJECTS
15 =====

Background
green lightgreen darkgreen
00000
20 10000
    00010
    00000
    01000

25 Target
    DarkBlue
    .....
    .000.
    .0.0.
30 .000.
    .....

BombObstacle
gray
35 00000
    00000
    00000
    00000
    00000
40

Wall
BROWN DARKBROWN
11111
45 01000
    11111
    00010
    11111

50 WallL

```

```
Black
0....
0....
0....
55 0....
0....

WallR
Black
60 ....0
....0
....0
....0
....0
65 ....0

WallU
Black
00000
.....
70 .....
.....
.....

WallD
75 Black
.....
.....
.....
.....
80 00000

Wall2
red
0...0
85 .0.0.
..0..
.0.0.
0...0

90 Player
darkblue red BLACK
.000.
.000.
11111
95 .111.
```

```
.2.2.

Crate
orange
100 00000
    0...0
    0...0
    0...0
    00000
105
    LUMirror
    BROWN LightBlue
    ....0
110    ...10
    ..110
    .1110
    00000
115    URMirror
    BROWN LightBlue
    0....
    01...
    011..
120    0111.
    00000

    RDMirror
    BROWN LightBlue
125    00000
    0111.
    011..
    01...
    0....
130
    DLMirror
    BROWN LightBlue
    00000
    .1110
135    ..110
    ...10
    ....0

    Bomb
140    blue white
```

```
00000
01110
01110
01110
145 00000

Teleport
blue purple black
00000
150 01110
01210
01110
00000

155 Initial
transparent

Shiftbomb
transparent
160

=====
LEGEND
=====

165 WallOutline = WallU or WallD or WallL or WallR
Obstacle = Wall or Wall2 or BombObstacle or Bomb
Mirror = LUMirror or URMirror or RDMirror or DLMirror
Solid = Obstacle or Mirror

170 . = Background
# = Wall
P = Player and Initial
* = Crate
175 0 = Target
g = BombObstacle and Target
d = Wall2
B = Bomb
t = Teleport

180

=====
SOUNDS
=====

185 sfx0 73682502 (die)
sfx1 74413905 (mirror)
```

```

sfx2 89661502 (explosion)
sfx3 63441708 (walk)
sfx4 29985308 (teleport)
Sfx10 77515308 (test)
190 EndLevel 123413
=====
COLLISIONLAYERS
=====

195 Background
Mirror, Target, Teleport
Player, Crate, Obstacle
(for beauty)
WallL
200 WallR
WallU
WallD
Initial
Shiftbomb

205
=====
RULES
=====
(Initial setting)
210 (Editing convenience: Automatically add outlines to walls)
[Initial][ WallOutline ] -> [Initial][ ]
up [Initial][ Wall | No Wall ] -> [Initial][ Wall WallU |
]
down [Initial][ Wall | No Wall ] -> [Initial][ Wall WallD |
]
left [Initial][ Wall | No Wall ] -> [Initial][ Wall WallL |
]
215 right [Initial][ Wall | No Wall ] -> [Initial][ Wall WallR |
]
[Initial] ->[]

(begin every step)
(Test if player touches the Bomb)
220 [ > Player | Bomb ] -> [ Player| ] sfx2

(Go directly, for a loop)

```

```

(Here stationary is important. Without it the LUMirror can
also move. And the Mirrors must be near the wall.
Otherwise the player would go across the mirror. And be
careful that never make a loop with mirrors and
teleports!)
225 right [ > Player | LUMirror] -> [ |up Player stationary
    LUMirror ] sfx1
+down [ > Player | LUMirror] -> [ |left Player stationary
    LUMirror ] sfx1
+left [ > Player | URMirror] -> [ |up Player stationary
    URMirror ] sfx1
+down [ > Player | URMirror] -> [ |right Player stationary
    URMirror ] sfx1
+left [ > Player | RDMirror] -> [ |down Player stationary
    RDMirror ] sfx1
230 +up [ > Player | RDMirror] -> [ |right Player stationary
    RDMirror ] sfx1
+right [ > Player | DLMirror] -> [ |down Player stationary
    DLMirror ] sfx1
+up [ > Player | DLMirror] -> [ |left Player stationary
    DLMirror ] sfx1
(now move on)
+ [ > Player| no Obstacle no Mirror] -> [ |> Player ] (
    better if one can wait for some time)
235 (Teleport)
+ [> Player Teleport][Teleport no Player] ->[Teleport][
    Teleport > Player] sfx4
(stop)
+ [ > Player| Obstacle] -> [ Player|Obstacle] sfx3
(win condition)
240 + [Player Target] -> [stationary Player Target]win

random [Bomb][BombObstacle] -> [Bomb][BombObstacle
    Shiftbomb]
[BombObstacle no Shiftbomb] -> []
245 [Shiftbomb] -> []
late [ Player | Wall2 ] -> restart sfx0
(Here I want to wait several seconds to restart)
=====
WINCONDITIONS
250 =====

=====
LEVELS

```

```

=====
255 MESSAGE I make no claim for the original.

LEVEL_SELECT_POINT Level 1
260 MESSAGE Level 1

dddddddddddd
d.....d
d....#....d
265 d.....#..d
d..#.....d
d.....#.d
d....p#....d
d.O.....d
270 d.#.....d
d.....#...d
d..#.....d
d.....d
dddddddddddd

275 LEVEL_SELECT_POINT Level 2
MESSAGE Level 2
dddddddddddddddd
d.....d
280 d.....#.....d
d.....#...d
d...##.....d
d.#..#.....o.d
d.....p#....d
285 d.....#.....#..d
d.....#.....d
d..#.....#...d
d.....#.....d
d.....d
290 ddddddddddddddddd

LEVEL_SELECT_POINT Level 3
MESSAGE Level 3
dddddddddddddddd
295 d.....d
d.....###....d
d.....#...#...d
d.....#...d

```



```

300 d...####...#b...d
    d.p.bbb..bb#b.o#.d
    d...####...#b...d
    d.....#...d
    d.....#...#...d
    d.....###...d
305 d.....d
    dddddddddddddddd

    LEVEL_SELECT_POINT Level 4
    MESSAGE Level 4
310 dddddddddddddddd
    d.....d
    d..#.....d
    d.....#...d
    d.....#...d
315 d.....#...d
    d.#.....d
    d..#.....#p...d
    d.....#...d
    d...#.....d
320 d.....#.#...d
    d.....#..d
    d.....#...d
    d...#.....d
    d...o...#...d
325 d.....#.#..d
    d.....#...d
    d...#.....d
    d.....#...d
    d.....d
330 dddddddddddddddd

    LEVEL_SELECT_POINT Level 5
    MESSAGE Level 5
    dddddddddddddddd
335 d.....d
    d.....###.d
    d...#.....##.##.d
    d.bb....b...# . #.d
    d.bb..p..b....g...d
340 d.....# . #..d
    d.....###.d
    d...# . #.....d
    d...#####...d

```

```

d.....d
345 ddddddddddddddddddd

LEVEL_SELECT_POINT Level 6
MESSAGE Level 6
dddddddddddddd
350 d.....d
d.....#....d
d.....#....d
d..#.....d
d....bbb.#o..d
355 d....bpb.#...d
d....bbb...#.d
d.#.....d
d.....#.#....d
d.....#....d
360 d....#.....d
d.....d
dddddddddddddd

LEVEL_SELECT_POINT Level 7
365 MESSAGE Level 7
dddddddddddddddddd
d.....d
d.#####.....d
d.###...#.....d
370 d.#.....#.....d
d.#.....#....d
d.##...#.....o.....d
d.###.##.... ##### .d
d..... ###...# .d
375 d.##..... #p.#....#.d
d.#..t...###...t...#.d
d.....#.#....#.d
d.#.....#. #####.###.d
d.##...##..... ##### .d
380 d.....d
dddddddddddddddddd

LEVEL_SELECT_POINT What?
MESSAGE That's just a test, not a game!
385 ... ##... #
...g ## .t.
...####...
##.####... #

```

```

390 .# . ## ###
    .###... ####
    .# .bbb#####
    .#.bbbbbb...
    .# .bbb.....
    .#####.
395 .## ...p.t..
    .## .....

```

400

```
MESSAGE Thank you for playing the game.
```

8. POV-RAY

8.1. **安装 + 初始代码.** POV-Ray 是一款依赖代码的 3D 建模软件，免费开源，目前个人感觉是“3D 版本的 Tikz”。“一款能够在短时间内持续追踪光线视觉，产生高质量计算机图像的工具。” from here.

程序对大小写敏感。

一些特殊符号：

```

1 o=<0,0,0>, x=<1,0,0>, y=<0,1,0>, z=<0,0,1>, u=<1,0>, v
  =<0,1>.
  sqrt(a), pi, pow(a,n) sin(radians(90)), degrees(atan2(1,1))

```

8.2. **基本逻辑.** 基本几何体请参考[这里](#)。

透明背景设置

superellipsoid 可以画圆角圆柱和方体。

8.3. **调试.** 单行注释使用两斜杠//，多行注释使用/*注释*/。对于.ini 文档，单行注释使用分号；。

关于输出请参考此文档。

8.4. **参考文档.** 官方文档、视频教程、本地 demo、动画效果

POV-Ray 的经典实例是维度：数学漫步。另外也可以参考Mathematical Imagery.

关于 3D 建模还有很多优秀的软件，比如：

- solidwork: 曾经尝试过，后来删了

- 3DMax: 实例可以参考GM 的建模基地。但是收费。
- blender: 免费开源，似乎是 3DMax 的高级替代品，依赖快捷键。

如果我有一台优质的电脑、时间 (没书读时) 和精力那我也会尝试下。现在就算了。

8.5. (想保留的) 例子. 这个例子实现了杯子的旋转动画，并制作了一个好的坐标轴。

```

// POV-Ray Scene File "begin.pov"
// by Friedrich A. Lohmueller, Jan-2013, now Xiaoxiang Zhou
//-----
global_settings{assumed_gamma 1.0}
5 // #default{ finish{ ambient 0.1 diffuse 0.9 }}
//-----

#include "colors.inc"
#include "textures.inc"
10 #include "woods.inc"
//-----
// camera -----
camera{
  location <25,25,25>    //best: <25,25,25> <10,-25,25>
15 right -x*image_width/image_height
  sky    <0,0,1>    //see the sky
  look_at <0,0,0>
  angle 22
}
20 // sun -----
light_source{
  <25,25,25>,
  White
  shadowless
25 }
// sky -----
sky_sphere{
  pigment{
    gradient z-3
30 color_map {
      [0 color White]
      [0.95 color Blue]
      [1 color White]
    }
  }
35
  scale 2

```

```
        translate <0,0,1>
    }
}
40 // axis arrows -----
    cone {
        6*x, .1, 6.5*x, 0
    }
    cone {
45     6*y, .1, 6.5*y, 0
    }
    cone {
        6*z, .1, 6.5*z, 0
    }
50 // axis -----
    cylinder {
        -6*x, 6*x, .021
        pigment{ Black}
55     finish {ambient .3}
    }
    cylinder {
        -6*y, 6*y, .021
        pigment{ Black}
60     finish {ambient .3}
    }
    cylinder {
        -6*z, 6*z, .021
        pigment{ Black}
65     finish {ambient .3}
    }
    // grid -----
    #for (i,-5,5,1)
    cylinder {
70     <i,-5,0>, <i,5,0>, .02
        pigment{ Grey}
        finish {ambient .3}
    }
    cylinder {
75     <-5,i,0>, <5,i,0>, .02
        pigment{ Grey}
        finish {ambient .3}
    }
    #end
80
```

```

text {
    ttf "timrom.ttf" "x" 0.05, 0
    pigment { Black }
85    translate -0.25*x
    rotate<90,0,180>
    translate 6*x-0.8*z
}
text {
90    ttf "timrom.ttf" "y" 0.05, 0
    pigment { Black }
    translate -0.25*x
    rotate<90,0,90>
    translate 6*y-0.8*z
95 }
text {
    ttf "timrom.ttf" "z" 0.05, 0
    pigment { Black }
    translate -0.25*x
100    rotate<90,0,135>
    translate 6*z-0.8/sqrt(2)*x+0.8/sqrt(2)*y
}

difference{
105 union {
    sphere_sweep {
        b_spline
        7,
        <.7,2.2,0>, .8
110    <1.5,.5,0>,.3
        <3.1,.5,0>,.3
        <3.8,2.4,0>,.3
        <3.1,4.1,0>,.3
        <1.5,4.1,0>,.3
115    <.7,2.6,0>,.8
        texture{
            pigment{ Grey}
            finish { phong 1}
        }
120    finish {ambient .3}
        scale <1,1,2.5>
    } //cup
    cylinder{
125    <0,0,0>, <0,4.75,0>,2

        scale 1/4.75
    }
}

```

```
        texture{
    pigment{ Grey}
130    finish { phong 1}
    }
    scale 4.75
    finish {ambient .4}
    rotate<0,-60,0>
135    }
} //end of union

cylinder {
    <0,.2,0>, <0,4.9,0>, 1.8
140    texture{
    pigment{ Grey}
    finish { phong 1}
    }
    finish {ambient .3}
145    }
rotate<90,0,360*clock>
} //end of difference
```

我们还需要.ini 文档才能够生成动画。

```
; Persistence Of Vision raytracer version 3.7 example file.
2 Antialias=On

Antialias_Threshold=0.1
Antialias_Depth=2
Input_File_Name=begin.pov
7

Initial_Frame=1
Final_Frame=30
Initial_Clock=0
Final_Clock=1
12

Cyclic_Animation=on
Pause_when_Done=off
```

8.6. **Tasks.** 制造一个基本对象集，以及基本操作。

9. 前端, SUBLIME

9.1. **安装 + 初始代码.** 前端没有啥好说的, 我所理解的就是 html+css+javascript. 初学者用记事本就可以了, 我目前用的是 sublime, 原因请参考这个教程。代码技术主要参考的是 W3(英文版)、Web 技术教程。

9.2. 非初等但是值得学习的库.

- Apache ECharts: 一个基于 JavaScript 的开源可视化图表库, 不过这里的图表限定范围较窄。

10. 电脑快捷键 (中级)

部分参见 Chrome 快捷键。

- ctrl+win+left: 切换桌面
- alt+(shift)+tab: 切换任务栏上的程序
- ctrl+(shift)+tab: 切换标签页
- win+D: 显示桌面
- win+left: 页面占左半边
- win+R: 调出运行窗口

11. 正则表达式

正则表达式可以大幅提升搜索和修改代码的效率。

```
1 .{0,100}(?=\d{0,3};\d{0,3}m\n);\d{0,3});(\d{0,3})m\n
```

11.1. 参考文档. 推荐 B 站视频。与之配套的练习。

你可以在 regexr 中测试。

12. 热键设置 (AUTOHOTKEY)

这是一款开源软件。为了 Hackergame 的脚本, 同时我猜会大幅度提高打代码的速度。我想可以实现快速打笔记的功能?

12.1. 调试. 注释使用分号;。

12.2. 参考文档. 官方文档. ;

12.3. (想保留的) 例子. 这个例子模拟鼠标和键盘, 使用了条件和循环语句。

```

^j::
Sleep,300
loop, 1
{
5   Random, rand, 1, 999
      CoordMode, ToolTip
      Click, 1743 81 1
      Sleep, 100
      Click, 36 64 2
10   Sleep, 100
      Send, {rand}.0.0.0
      Sleep, 100
      Click, 433 323 2
      Sleep, 100
15   Send, 0.0.0.0
      Sleep, 100
      Click, 452 321 1
      Sleep, 100
      if GetKeyState("F10")
20   {
      break
      }
      Sleep,1000
}
25 Return

```

这是第二版本, 能够 95% 成功提交。

```

#MaxThreadsPerHotkey 3
^j:: ; 热键(可根据您的喜好改变此热键).
#MaxThreadsPerHotkey 1
if KeepWinZRunning ; 这说明一个潜在的线程正在下面的循环中
运行.
5 {
      KeepWinZRunning := false ; 向那个线程的循环发出停止的
      信号.
      return ; 结束此线程, 这样才可以让下面的线程恢复并得知
      上一行所做的更改.
}
; 否则:
10 KeepWinZRunning := true
rand := 0
Loop
{

```

```

; 以下四行是您要重复的动作(可根据您的需要修改它们):
15  MyNumber := rand . ".233.233.233"
    Click, 1743 81 1
    Sleep, 70
    Click, 74 74 2
    Sleep, 70
20  Send, %MyNumber%
    Sleep, 70
    Click, 429 346 2
    Sleep, 80
    Send, %MyNumber%
25  Sleep, 90
    Click, 1073 31 1
    Send ^{Click 432 360 1}
    Sleep, 190
    rand += 1
30  ; 但请不要修改下面剩下的内容.
    if not KeepWinZRunning ; 用户再次按下 Win-Z 来向循环发
        出停止的信号.
        break ; 跳出此循环.
}
KeepWinZRunning := false ; 复位, 为下一次使用热键做准备.
35  return

```

第三个版本可以提交 254 个, 还剩 2 个。。。

```

#MaxThreadsPerHotkey 3
^j::
#MaxThreadsPerHotkey 1
if KeepWinZRunning
5  {
    KeepWinZRunning := false
    return
}
KeepWinZRunning := true
10 rand := 0
Loop
{
    MyNumber := rand . ".233.233.233"
    Click, 1751 91 1
15  Sleep, 120
    Click, 74 74 2
    Sleep, 50
    Send, %MyNumber%
    Sleep, 70
20  Click, 429 346 2

```

```
        Sleep, 80
        Send, %MyNumber%
        Sleep, 50
        Click, 587 747 1
25      ;Click, 1073 31 1
        Send ^{Click 387 437 1}
        Sleep, 60
        rand += 1
        if not KeepWinZRunning
30      break
    }
    KeepWinZRunning := false
    return
```

最后成功的版本:

```
#MaxThreadsPerHotkey 3
2 ^j::
#MaxThreadsPerHotkey 1
if KeepWinZRunning
{
    KeepWinZRunning := false
7    return
}
KeepWinZRunning := true
rand := 0
Loop
12 {
    MyNumber := rand . ".233.233.233"
        Click, 1751 91 1
        Sleep, 120
        Click, 74 74 2
17    Sleep, 50
        Send, %MyNumber%
        Sleep, 70
        Click, 429 346 2
        Sleep, 80
22    Send, %MyNumber%
        Sleep, 40
        Click, 587 747 1
        ;Click, 1073 31 1
        Send ^{Click 387 437 1}
27    Sleep, 60
        rand += 1
        if not KeepWinZRunning
            break
```

```

}
32 KeepWinZRunning := false
return

```

12.4. **Tasks.** 通过该软件创建一个 L^AT_EX 的脚本，要求：

- 自动翻译 iff, SES, LES, mfld, rep...
- 长段代码如 equ+aligned
- 只在打开 TeXstudio 时生效 (使用 IfWinActive+Window Spy)

通过该软件创建一个脚本，要求：

- 自动打开日常软件
- 将其放入开机启动项

已完成，代码如下：

```

#IfWinActive, ahk_class Qt5QWindowIcon
2 ::SES::short exact sequence

::LES::long exact sequence

::TFAE::the following are equivalent:
7 ::iff::if and only if

::st::such that

12 ::eg::for example

::wrt::with respect to

::geo::geometry
17 ::cont::continuous

::diff::differential

22 ::sm::smooth

::mfld::manifold

::lb::line bundle
27 ::mlb::metrized line bundle

```

```
::vb::vector bundle
32 ::cplx::complex
::RS::Riemann surface
::AG::algebraic geometry
37 ::agc::algebraic geometric
::AV::abelian variety
42 ::ell::elliptic curve
::proj::projective ;be careful for projection
::inj::injective
47 ::fct::function
::fctor::functor
52 ::iso::isomorphism
::irr::irreducible
::ind::indecomposable
57 ::adm::admissible
::rep::representation
62 ::repe::representable
::Archi::Archimedean field
::sign::Best wishes,`n`nXiaoxiang Zhou
67 ::sym::symmetric
::corr::corresponding ;be careful for correspondence
72 ::corre::correspondence
::sset::simplicial set
```

```

::LLC::local langlands correspondence
77
::align:: ;超长变换,我的Texstudio还是有些问题
(
\begin{equation*}
\begin{aligned}
82   =&\;& \backslash\backslash
)

::draw:: ;Texstudio如何原样打出?
(
87 \begin{figure}[ht]
    \vspace{0cm}
    \centering
    \includegraphics[width=12cm]{}
    \label{fig:}
92   \caption{}
\end{figure}
)

::minipage::
97 (
\begin{figure}[th]
    \begin{minipage}[t]{.48\textwidth}
        \centering
        \includegraphics[width=\textwidth]{}
102    \label{fig1}
    \end{minipage}
    \begin{minipage}[t]{.48\textwidth}
        \centering
        \includegraphics[width=1\textwidth]{}
107    \label{fig2}
    \end{minipage}
    \caption{}
    \end{figure}
)
112
^+c:: ;注释
send ^c
sleep, 200
clipboard=%clipboard%
117 tooltip, %clipboard%
sleep, 500
tooltip,

```

```

return
122  ::||:: ;临时符号
    (
    \norm{\cdot}
    )
127  ::CLm::Chambert-Loir measure

    ::dps::\displaystyle

    ::comm diag::commutative diagram
132
    ::reso::resolution

    ::pfv::partial flag variety
137
    ::qgr::quiver Grassmannian

    ::dv::dimension vector

    #IfWinActive
142 ^j::
    Run, "F:\hide\Snipaste\Snipaste.exe"
    Run, "F:\hide\WiFi 共享大师\WiFiMaster.exe"
return

```

13. 其他

这里收集乱七八糟的材料，以后说不定可以单独搞个文件。

13.1. 数学的可视化. 这里以四维空间为例。

可以参考Andrew J. Hanson 的主页，也可以参考Github 中的项目(这里面有很多可以了解到的就不引用了)。

脑洞：参考四维截面游戏，我们是否可以做个四维版本的小球进洞？

13.2. 数学与游戏. 脑洞：搞个 Riemann surface 的世界，在介绍这个世界的时候以神的旨意来介绍相关概念

1. 安装Unity
2. 用sublime配置unity
- 3 3. 制作横版跳跃游戏，包含：
 - 场景/人物/交互/动作(左右动，跳跃，蹲)/人物动画
4. 制作贪吃蛇游戏，熟悉代码(无边框，不蠢，带格子)

5. 制作扭结+贪吃蛇游戏
 6. 制作黎曼面游戏(两点)
- 8 方程
 游戏类型: 找不同? 横版跳跃? 迷宫? 五子棋(4/3子棋, 粘附5/4/3子棋)? 围棋(扭羊头游戏)? 跳棋? 空间爬行? 扭结+贪吃蛇? 塔防? 数独? 数回? 华容道? ORBOX B?(这玩意可以做成三维版本! 4维就有点难了)(mini metro? 连连看? 泡泡龙? 消砖块? 2048? 推箱子? 其他的Nikoli Puzzles?)
- 简易示意图
 可能引入的概念: Laurent 展开/同调群、基本群的概念(在数回中, 请使得最后画出的曲线表示基本群不平凡但是同调群不平凡)/覆盖, 万有覆盖, deck transformation(华容道简化难度: 允许 deck transformation 将区块变换至另一个基本区域中相同的位置; 或者, 我们允许上下粘接)/曲率/曲率驱动游戏/descent(数独解何时能成为更小的黎曼面的解)
- 视角: 收敛区域视角(遮罩圆形)、星形区域视角、基本区域视角、万有覆盖视角、第一人称视角、二维3D视角(视角需要通过"培训+考试"解锁)
- 13 虚拟对话
 - 宇宙到底是啥?(永远都到达不了的点是否真的存在? -black hole 宇宙是几维的? 2+3(颜色)+1(时间) 如何测量时间, or 时间的流逝是否是均匀的?)
 - 自由意志(我可以自由地说我想说的东西, 而你的输入却受到限制)
 - 表达自己想做却做不到的事
- 18 - 对数学的热爱

脑洞: 利用扭结来制作游戏, 例如“贪吃蛇”。需要的时候考虑离散化, 也可以考虑离散版本的 Reidemeister moves。游戏制作的难点在于如何判定成功(好的 Goal 是啥。很难去说明一个扭结和另一个扭结等价) 扭结的相关知识可参考这个视频。Ballance 如果能添加磁场和电场, 考虑带电小球(不考虑电磁感应)的话就是高中物理的必玩游戏了。

13.3. 数学相关句子模板. 这里收集“啊我之前不知道咋表达, 这就是我当时卡住的时候可以用的句子!”的外文句子。绝对是原创的。

- 1 notations:
 Beginning with..., only ... are considered.
 shorthand
 By an aesthetically desirable abuse of notation,
 6 One word about the notation: for simplicity we often omit
 ...

For notational reasons we usually extend the ... to (negative indices) by defining ...

The term ... **is** a convenient, but temporary, expedient. To save adjectives, **if** ... **is** described as ..., it **is** implicitly assumed to be ...

Finally, a word about terminology.

11 However on many occasions it **is** natural **or** customary to stay **in** ... mode when nonetheless one has ... **in** mind. While **for** the most part this convention seems to work well, it occasionally leads us to make extraneous ... hypotheses **in** order to invoke ...

We **try** to flag this artifice when it occurs.

The following abuse of notation will prove handy:...

16 refer to:

The main references **for** the material covered **in** this section are ...

A more detailed overview of this chapter may be obtained by reading the introductions to the various sections.

More detailed treatments appear **in** ..., to which we will refer **for** proofs.

mimic the arguments **for** ...

21 We refrain **from** giving a more detailed introduction here **and** instead refer the reader to the table of contents as well as to the short introductions of the individual sections.

References **for** ... include the monograph ... **and** the more introductory account ...

example **and** generalization:
 prototypical example

26 By the same argument as the special case above, ...

The arguments **in** ... carry over mutatis mutandis.

provide a navigable route into the area with a complete **and** self-contained account of the case ...

eschew **all** generality

exploit special features to abbreviate/simplify the arguments

31 tinker with the examples

Disclaimer:
 minor errors **and** obscurities, a couple of significant lapses

I am by far **not** a person with serious knowledge/
 understanding of ..., thus **in** the ... I may oversimplify
 /overcomplicate things, be inaccurate, **or** even wrong,
and miss subtelties.

36 I have actually been meaning to correct some typos **for** a
while and so I will hopefully do **all** these corrections
in the **next** few weeks.

technical problem:
 achieve some technical control
 Ceci nous contraint à prouver ... par une voie détournée

41 It should be noted that even **if** one **is** interested only **in**
 ..., the proofs often involve more general ...

ask **for** details:
 I find there are a lot of cool ideas **in** your answers, but I
 would be grateful **if** you could be a bit more precise.

46 digression:
 We now want to describe the ... This can be done **in** a more
 straightforward way, but we prefer to include a short
 digression **in** ... theory as this allows us to mention a
 general fact which **is in** the background of a later
 construction anyhow.
 Nevertheless, the reader can skip this digression without
 loss of continuity **and continue** with ... instead.

excitement/beauty:
 51 The literature on ... **is** vast **and** often technical, but the
 underlying ideas are possessing of an undeniable beauty.
 The excitement provoked by ... stimulated a period of
 intense **and** widespread activity.
 convey the breadth **and** excitement of the ideas

connect different areas:
 56 unveils intricate links between
 reveals connections between
is akin to the phenomenon of ...
is deeply intertwined with
 give a bird's eye view on

61 waiting for classification:
 equivalently(replace i.e.)
 encyclopaedic knowledge of ...

```

In fact, the arguments used in the final part of this proof
, give the following result.
66 Let us unravel this definition a little.(after complicated
    definition)
    ... is pivotal in this matter./ ... play a pivotal rôle.
    The arithmetic/information/structure of ... is encapsulated
        in ...
    encapsulate a significant amount of information concerning
        ...
    We point out the similarities and the differences whenever
        appropriate.
71 There is also some degree of novelty in our treatment of
    ...
    ... contiennent les outils requis pour surmonter ces
        difficultés.
    give a sense of the directions in which the area is going.
    there is nothing to be gained from specialization at this
        stage
    take it as a little rebus
76 whirlwind tour of ...
    be enamored with
    brackets:
    {}:curly set brackets
    ():round brackets
81 []:square brackets
    <>:angle brackets

beginning words: Goals, Pros and Cons

```

另外关于英语语法,可以参考天文物理类英文科技论文写作的常见问题.

13.4. 德语日常句子. 临时存储这里。

```

1 Ich bin pappsatt.
  Der Fisch war nicht üppig.
  Es war ein großer Reinfall!
  Wir müssen feststellen, inwiefern sich die Situation geä
      ndert hat.
  ums Leben kommen

```

REFERENCES

SCHOOL OF MATHEMATICAL SCIENCES, UNIVERSITY OF SCIENCE AND TECHNOLOGY
OF CHINA, HEFEI, 230026, P.R. CHINA,
Email address: `xx352229@mail.ustc.edu.cn`