ARDUINO
NANO 33 BLE SENSE

STORE.ARDUINO.CC/NANO-33-BLE-SENSE



- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default

⚠ **MAXIMUM** ouput current per pin is 15mA

⚠ **MAXIMUM** input current per pin is 5mA

⚠ **MAXIMUM** external current is 25mA for the sum of all GPIO currents and the current being drawn from VDD

VIN 5-21 V input to the board.

ARDUINO.CC

Last update: 16/09/2020

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.

ARDUINO

ARDUINO
NANO 33 BLE SENSE

STORE.ARDUINO.CC/NANO-33-BLE-SENSE



Ground
Power
LED
Internal Pin
SWD Pin

Digital Pin
Analog Pin
Other Pin
Microcontroller's Port
Default

SJ Pin
Making a short circuit using the solder jumper allows only the function in the SJ Pin cells.

MAXIMUM ouput current per pin is 15mA

MAXIMUM input current per pin is 5mA

MAXIMUM external current is 25mA for the sum of all GPIO currents and the current being drawn from VDD

VIN 5-21 V input to the board.

ARDUINO.CC

Last update: 16/09/2020

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.