

UA FREE Content Tool

Complete Installation, Configuration, Operation, Backup, and Troubleshooting Manual

UA FREE

Public version 1.0.0 / validated build R8 FIX30

Table of Contents

1 Purpose of this manual

This is the complete practical manual for installing, configuring, validating, operating, backing up, moving, and troubleshooting UA FREE Content Tool on Windows 10 or Windows 11. The application interface is Ukrainian; the English manual names important Ukrainian controls together with their meaning.

Critical safety rule: the working state is the complete portable application folder, especially Data. Never update, move, or back up only the EXE. Never separate Data/config.portable from Data/portable.key.

1.1 Recommended setup order

1. Download the Windows portable ZIP and SHA256SUMS.txt from the latest GitHub Release.
2. Verify SHA-256 before extraction.
3. Extract the complete folder to a writable local location.
4. Install and start Ollama and download at least one local model.
5. Start UA_FREE_Content_Tool.exe without administrator rights.
6. Open **Налаштування** (Settings), detect Ollama models, select the primary model, and save.
7. Configure one platform at a time and run its live check.
8. Connect Google Drive when media publishing is required.
9. Add and test a small source set.
10. Run **Перевірити всі підключення зараз** (Check all connections now).

11. Back up the complete application folder.
12. Perform one controlled live publication and verify every target status.

1.2 Preparation inventory

Integration	Required material
Ollama	Running local Ollama service and an installed model
Facebook Pages	Meta App ID, App Secret, valid Facebook User Access Token, page role
Threads	Token with threads_basic and threads_content_publish; optional threads_keyword_search
LinkedIn	Token with openid, profile, w_member_social
Telegram	Bot Token, channel username or ID, administrator role, can_post_messages
Google Drive	Drive API enabled; OAuth Client ID of type Desktop app; Client Secret when issued
Sources	RSS URL, website URL, or public Telegram channel identifier

2 Part I — Product overview and complete editorial workflow

A privacy-first Windows desktop application for collecting, manually grouping, rewriting, scheduling, and cross-posting Ukrainian news.

UA FREE Content Tool gives a human editor one local workflow for the full news-production cycle: collect materials from configured sources, manually combine reports about the same event, create one concise Ukrainian-language publication with a local Ollama model, attach media from Google Drive, schedule the package, and publish it sequentially to Facebook Pages, Threads, LinkedIn, and Telegram.

Public release: v1.0.0

Internally validated build: R8 FIX30

Platform: Windows 10/11, portable

Interface language: Ukrainian

License: GPL-2.0-or-later

2.1 Why this application exists

A normal editorial workflow is usually scattered across an RSS reader, browser tabs, messengers, a text editor, a local LLM, a scheduling sheet, and separate social-platform dashboards. UA FREE Content Tool brings those steps into one local Windows application while keeping factual and editorial decisions under human control.

The application does not decide on its own that different materials describe the same event. It keeps incoming items separate, helps the editor find likely matches, and merges them only after explicit confirmation.

The main editorial output is **one canonical Ukrainian-language publication of up to 900 characters** for all selected platforms. Threads may technically split a longer approved text into a main post and replies, but the content remains one canonical publication.

2.2 Core workflow

1. **Collect materials.** Enabled sources are checked and separate incoming blocks are created.
2. **Select manually.** The editor uses Shift, Ctrl, or Ctrl+A.
3. **Find candidates.** **Find everything on this topic** highlights likely related materials without merging them.
4. **Group manually.** Reports about the same event are merged into one working block.
5. **Rewrite locally.** Ollama receives all source materials in the block and produces a concise Ukrainian-language draft.
6. **Edit and approve.** A human verifies facts, wording, and length.
7. **Attach media.** One private Google Drive image or video can be attached.
8. **Schedule.** The package is added to the queue with selected platforms and publication time.
9. **Publish sequentially.** Targets are processed one by one and each platform keeps its own status.

10. **Retry safely.** Only failed targets are retried; successful publications are not duplicated.

2.3 Main capabilities

2.3.1 Collection and editorial work

- Collect current news from configured sources.
- Keep incoming items separate until a human decides to merge them.
- Support range and multi-selection through Shift, Ctrl, and Ctrl+A.
- Merge related reports manually.
- Highlight topic candidates without automatic grouping.
- Delete irrelevant materials.
- Use **Remember and exclude** to suppress highly similar future content.
- Build local editorial memory from approved human edits.

2.3.2 Local rewrite

- Use local Ollama without requiring a paid LLM API.
- Include all sources from a merged block.
- Produce one final Ukrainian-language publication.
- Target a maximum length of 900 characters.
- Maximize factual density and minimize filler.
- Reject English, Russian, speculative, or non-news output.
- Re-run the rewrite after the source composition changes.
- Keep the manually approved final text as the canonical publication text.

2.3.3 Queue and reliability

- Schedule publications for later delivery.
- Store a separate status for every target platform.
- Preserve attempts, errors, and remote IDs.
- Recover overdue or paused packages.
- Reschedule without repeating targets that already succeeded.
- Process targets sequentially with controlled pauses.
- Prevent a second simultaneous application process.
- Use SQLite with WAL, foreign keys, and synchronous=FULL.
- Test migrations for preservation of pending items, target statuses, attempts, and remote IDs.

2.3.4 Platforms and media

- Facebook Pages.
- Threads.
- LinkedIn.
- Telegram.
- Private Google Drive files.
- Automatic token and permission diagnostics after startup and every six hours.
- Distinct states for valid credentials, expired tokens, missing permissions, temporary network failures, and unconfigured integrations.
- Temporary anyone/reader access only for the specific Drive file required by Threads.
- Revocation of only the permission created by the application.
- Drive-file deletion only after all selected publications succeed.

2.4 Platform behavior

Platform	Publication	Media	Notes
Facebook Pages	One post	Image or video	Pages and Page Access Tokens are loaded through /me/accounts; API pagination is supported without an artificial two-page limit.
Threads	Main post and replies when required	Image or video	Longer canonical text is split without dropping content; the application temporarily exposes only the selected Drive file.

Platform	Publication	Media	Notes
LinkedIn	One professional post	Image or video	Uses the personal profile and the <code>w_member_social</code> permission.
Telegram	One post or media with caption	Image or video	The bot must be a channel administrator and have <code>can_post_messages</code> .

2.5 Requirements

2.5.1 Ready Windows portable build

- Windows 10 or Windows 11.
- Ollama installed separately.
- A compatible local model configured in the application.
- Internet access for collection, Google Drive, and social platforms.
- Credentials only for the platforms you intend to use.
- A Google Cloud OAuth client of type Desktop app for Google Drive.

Ollama and model files are **not included** in the portable archive and must be installed separately on every computer.

2.5.2 Development from source

- Python 3.11–3.13.
- `requirements.txt` for runtime dependencies.
- `requirements-test.txt` for validation.
- `requirements-build.txt` for the Windows build.

```
python -m venv .venv
.venv\Scripts\activate.bat
python -m pip install --upgrade pip
python -m pip install -r requirements.txt -r requirements-test.txt
python app.py
```

Alternative entry point:

```
python -m content_agent.main
```

2.6 Windows quick start

1. Open the latest GitHub Release.
2. Download the Windows portable ZIP.
3. Verify its SHA-256 against SHA256SUMS.txt.
4. Extract the complete archive. Do not run the EXE from inside the ZIP.
5. Install Ollama and the selected model.
6. Run UA_FREE_Content_Tool.exe without administrator rights.
7. Open **Settings** and configure sources and platform credentials.
8. Verify every required connection.
9. Back up the complete application folder before the first live publication and before every update.

2.7 Portable data, backups, and updates

The Data folder next to the EXE contains the working state:

- SQLite database;
- encrypted portable configuration;
- encrypted platform tokens and Google refresh token;
- sources and incoming blocks;
- manual merges;
- editorial memory and exclusion rules;
- queue, target statuses, attempts, and remote IDs;
- operational logs.

To create a backup:

1. Close the application.
2. Confirm in Task Manager that the process has stopped.
3. Copy the **entire UA_FREE_Content_Tool folder**, not only the EXE.
4. Keep the previous working copy until the first successful live publication with the new version.

Data\config.portable and Data\portable.key form one pair. Do not delete, rename, or move them separately. Physical access to the complete portable folder may permit access to stored credentials.

See [PORTABLE_MODE.md](#) for details.

2.8 Platform setup

2.8.1 Facebook Pages

Provide a Meta App ID, Meta App Secret, and a valid Facebook User Access Token. The application calls `/me/accounts` to retrieve all available pages and their Page Access Tokens, including additional pagination pages. An expired token must be replaced before it can be exchanged.

2.8.2 Threads

Required permissions:

```
threads_basic  
threads_content_publish
```

`threads_keyword_search` is additionally required for topic and trend comparison. Its absence does not block normal publishing.

2.8.3 LinkedIn

Required permissions:

```
openid  
profile  
w_member_social
```

The application resolves the personal profile through the API.

2.8.4 Telegram

Provide the Bot Token and channel username or ID. The bot must be a channel administrator with `can_post_messages`.

2.8.5 Google Drive

Create a Google Cloud project, enable Google Drive API, configure the OAuth consent screen, and create an OAuth Client ID of type Desktop app. Files remain private except for the short technical interval when Threads requires a public media URL.

See [PLATFORM_SETUP.md](#) for complete setup instructions.

2.9 Privacy and security

UA FREE Content Tool is a local application with no built-in telemetry about editorial work.

- Portable configuration is encrypted with AES-GCM.
- Tokens are not stored in SQLite.
- Secrets are masked in the interface and normal errors.
- External URLs pass through network safeguards.
- Private and non-global destinations are rejected for external fetches.
- Google Drive uses OAuth.
- Temporary public access is created only for the selected file when Threads requires it.

Never publish:

- a real Data folder;
- `config.portable` and `portable.key`;
- SQLite database, WAL, or SHM files;
- access tokens, app secrets, client secrets, or refresh tokens;
- private Drive links;
- logs or screenshots containing secrets or personal data.

See [SECURITY_NOTES.md](#).

2.10 Repository structure

<code>.github/</code>	issue templates, CI, and release
<code>workflow</code>	
<code>content_agent/</code>	
<code>data/</code>	bundled static data
<code>ui/</code>	Tkinter interface
<code>main.py</code>	application entry point
<code>database.py</code>	SQLite schema and migrations
<code>collectors.py</code>	source collection
<code>rewriter.py</code>	Ollama rewrite and validation
<code>editorial_memory.py</code>	local editorial memory
<code>publishers.py</code>	Facebook, Threads, LinkedIn, Telegram
<code>google_drive.py</code>	OAuth and media workflow
<code>scheduling.py</code>	scheduling
<code>worker.py</code>	queue execution
<code>security.py</code>	network and secret boundaries
<code>tests/</code>	automated tests
<code>tools/</code>	smoke and artifact validation tools
<code>docs/history/</code>	stabilization history
<code>docs/validation/</code>	validation reports
<code>app.py</code>	launcher
<code>Build_Portable_Windows.bat</code>	Windows portable build
<code>requirements*.txt</code>	runtime, test, and build dependencies
<code>FILE_MANIFEST.sha256</code>	SHA-256 manifest

VERSION.txt	internal build version
PUBLIC_VERSION.txt	public version

2.11 Build the Windows portable package

Build_Portable_Windows.bat

The script creates an isolated build environment, installs pinned dependencies, runs validation, and writes the portable package under Release.

2.12 Validation of v1.0.0

Public version v1.0.0 corresponds to internal build R8 FIX30.

Validated checks include:

- 223 passed in pytest;
- successful compileall;
- entry-point import checks;
- successful import content_agent.main;
- local smoke test;
- Windows portable build and startup;
- preservation of schema, settings, and queue state;
- Shift multi-selection in Incoming and Queue views;
- rejection of English, Russian, and non-grounded rewrite output;
- manifest, CRC, canonical root, duplicate-name, path-traversal, absolute-path, backslash, and symlink checks.

The raw Windows Gate evidence is stored in [docs/validation/WINDOWS_GATE_REPORT_R8_FIX30.txt](#). It preserves literal console output, including original Ukrainian UI strings and test paths. The English summary is [docs/validation/WINDOWS_GATE_SUMMARY_R8_FIX30.md](#).

Automated Windows Gate validation does not replace live testing with real platform accounts. Live behavior depends on current tokens, roles, permissions, API policies, and network conditions.

2.13 Documentation

- [README.md](#) — complete project overview.
- [PLATFORM_SETUP.md](#) — platform credentials and Google Drive.
- [PORTABLE_MODE.md](#) — portable data, migration, and backups.
- [SECURITY_NOTES.md](#) — security boundaries.
- [RELEASE_NOTES_v1.0.0.md](#) — release notes.

- [CHANGELOG.md](#) — version history.
- [CONTRIBUTING.md](#) — contribution rules.
- [docs/MAINTAINER_RELEASE_GUIDE.md](#) — release procedure.
- [docs/history/DEVELOPMENT_HISTORY_R8_FIX30.md](#) — stabilization history.
- [docs/history/STABILIZATION_DECISION_R8_FIX30.md](#) — final stabilization decision.
- [docs/history/UPDATE_FIX29_TO_FIX30.md](#) — program-only update procedure.
- [docs/validation/LOCAL_REVALIDATION_REPORT_R8_FIX30.md](#) — local revalidation.
- [docs/validation/WINDOWS_GATE_SUMMARY_R8_FIX30.md](#) — English Windows Gate summary.

2.14 Complete setup manuals

- [English: complete installation and configuration manual \(PDF\)](#)
- [Українською: повний посібник зі встановлення та налаштування \(PDF\)](#)

The manuals cover installation, checksum verification, Ollama, every supported platform, Google Drive media, source collection, editorial workflow, scheduling, queue recovery, backups, migration, security, live-publication checklists, and troubleshooting.

2.15 Bug and vulnerability reports

A GitHub Issue should include the application version, Windows version, Ollama model, reproduction steps, expected result, actual result, and a sanitized log excerpt.

Do not publish secrets. Vulnerability reports may be sent to kozyriev@uafree.org with the affected version, reproduction steps, and impact. Remove all real credentials and personal data.

2.16 Contributing

Before opening a pull request, run:

```
python -m compileall -q .
python -m pytest -q
python tools\check_entrypoint_imports.py
python -c "import content_agent.main"
```

A contribution must not add real tokens or working Data, weaken URL or secret checks, merge news automatically without editor approval, duplicate successful publications during retry, or modify the database without a migration and tests.

2.17 Support

2.17.1 UA FREE charitable foundation

- [Donate to UA FREE](#)
- [UA FREE website](#)

2.17.2 Application development

- **PayPal:** kozyriev@uafree.org
- [Donate through PayPal](#)
- **BTC:** bc1q4dn8e7sz2866g7qp1qtshh98j54tvuau5ghuuk
- **ETH / USDC ERC-20:** 0x3aE3b23A7BD94b8a65A7E8Ca205A4e29BEF7c229
- **USDT TRC-20:** TYsGyK7K3XB4NPHprf5w8ZodFafxFfDdbP

Application-development donations are separate from donations to the charitable foundation. Use only the network shown next to each cryptocurrency address.

2.18 Project background

UA FREE Content Tool grew from real content operations rather than from a generic social-media demonstration. Development, review, and part of the test preparation used OpenAI ChatGPT. Final product decisions, editorial responsibility, credential handling, and live publication validation remain under human control.

2.19 License

GPL-2.0-or-later. See [LICENSE](#).

3 Part II — Platform and Google Drive configuration

This document covers the credentials, permissions, and operational requirements for Facebook Pages, Threads, LinkedIn, Telegram, and Google Drive.

3.1 Meta App ID and App Secret

Facebook and Threads can use the same Meta application, but they use different access tokens. Enter the Meta App ID and Meta App Secret so the application can

exchange eligible short-lived tokens for long-lived tokens. The App Secret is stored in the same encrypted portable configuration as the tokens and is never written to normal logs.

3.2 Facebook Pages

UA FREE Content Tool uses one Facebook User Access Token. It calls `/me/accounts` to load every page available to that token and stores the returned Page Access Tokens. API pagination is followed, so there is no artificial two-page limit.

A token created through Graph API Explorer is usually short-lived. After entering the App ID, App Secret, and a valid User Access Token, use **Find pages**. The application first attempts a long-lived-token exchange, then stores all Page Access Tokens and displays expiry information when available.

An expired token cannot be exchanged. Create a new valid User Access Token first.

3.3 Threads

Required Threads permissions:

```
threads_basic  
threads_content_publish
```

Optional permission for current-topic comparison:

```
threads_keyword_search
```

The trend-search check uses the current `graph.threads.net/keyword_search` endpoint, has a bounded timeout, and displays a separate result. The profile does not need to be resolved again for every trend check.

Without `threads_keyword_search`, ordinary publishing still works, but the trend/explosiveness assessment is marked as partial.

When the Meta App Secret is configured, an eligible short-lived Threads token can be exchanged for a long-lived token. A valid long-lived token may be refreshed before expiry. An already expired token must be recreated.

3.4 LinkedIn

1. Open LinkedIn Developer Portal Token Generator.
2. Create a token with:

```
openid
profile
w_member_social
```

3. Paste the token into the application and run the token check.

The personal profile is resolved automatically through the API.

3.5 Telegram

Required:

- Bot Token from @BotFather;
- channel username or channel ID;
- the bot must be a channel administrator;
- the bot must have `can_post_messages`.

A correct Bot Token alone is not sufficient if the bot lacks the channel role or permission.

3.6 Google Drive media

3.6.1 One-time Google Cloud setup

1. Create a Google Cloud project. The Free Trial is not required.
2. Enable Google Drive API.
3. Configure the OAuth consent screen for the account that will own the media.
4. Create an OAuth Client ID of type Desktop app.
5. Copy the Client ID and, when provided, Client Secret into the application settings.
6. Use **Connect Drive** and approve access in the browser.

The refresh token is stored in the encrypted portable configuration. Drive access is used to download the selected file for publishing and to delete it only after every selected platform succeeds.

3.6.2 For each publication

1. Upload one image or one video to your Google Drive folder.
2. Keep both the folder and file private.
3. Copy the link to the specific file.
4. Paste it into the Publication tab and use **Check media**.

The check verifies that:

- the file is an image or video;
- the connected account can download and delete it;
- when Threads is selected, the account can temporarily expose that specific file.

During Threads publishing, the application creates temporary anyone/reader access only for the selected file. After an error, the temporary permission is revoked and the file remains private. After all selected platforms succeed, the file is permanently deleted.

Do not make the whole folder public.

3.7 Token storage and saving

The **Save changes** control remains available in Settings. Successful checks for Facebook, Threads, LinkedIn, Telegram, and Google Drive also persist the verified values immediately.

3.8 Automatic connection diagnostics

The application checks saved connections after startup and every six hours. Results are shown in the Platforms and Google Drive section. Automatic checks do not open modal windows and do not block editorial work.

Connection states are intentionally distinct:

- `valid` — the live API confirmed the token and required read-only access;
- `replace token` — the platform explicitly reported invalid, expired, revoked, or insufficiently scoped credentials;
- `check permissions` — the token works, but a role or permission is missing;
- `temporarily unverified` — DNS, network, or platform failure; do not rotate a token without evidence;
- `not configured` — the integration has not been configured.

For LinkedIn, the application exposes the actual `/v2/userinfo` error fields when available. For Telegram, it checks the bot identity, channel access, administrator status, and `can_post_messages`.

3.9 Recovering missed publications

After replacing expired tokens or correcting permissions, open the Queue and use **Reschedule missed / paused**. The application moves paused and overdue

pending packages into the nearest future slots while preserving targets already marked sent.

4 Part III — Portable mode, migration, backups, and moving the application

UA FREE Content Tool stores the database, sources, queue, encrypted credentials, Google Drive refresh token, settings, and logs in the Data folder next to `UA_FREE_Content_Tool.exe`.

4.1 Move the application to another computer

1. Close the application.
2. Confirm that no `UA_FREE_Content_Tool.exe` process remains.
3. Copy the **entire UA_FREE_Content_Tool folder**, not only the EXE.
4. Start the EXE from the copied folder on the new Windows computer.

`Data\config.portable` and `Data\portable.key` form one cryptographic pair. Do not delete, rename, or move them separately. Anyone with physical access to the complete portable folder may be able to access the stored credentials, so protect the folder accordingly.

Ollama and local model files are not included in the portable folder. Install Ollama and the selected model separately on the destination computer. A platform may also require reauthorization if it has revoked or expired its token.

4.2 Migration from legacy local data

On the first eligible launch, the application can migrate legacy data from:

`%LOCALAPPDATA%\UA_FREE_Content_Tool\data`

The migration creates a verified SQLite snapshot and converts the previous machine-bound configuration into the portable encrypted format. The legacy folder is not deleted automatically.

An empty schema-only portable database created by a test launch is not treated as authoritative. Real legacy sources and settings can still be imported. A non-empty portable database is never overwritten automatically.

4.3 Backups

Before every update:

1. Close the application and confirm the process has stopped.
2. Copy the complete application folder to a separate backup location.
3. Apply only the documented program update.
4. Keep the previous working copy until the first successful live publication with the new version.

Never upload a real working Data folder to GitHub or attach it to an issue.

5 Part IV — Security policy and operational boundaries

5.1 Supported version

Security fixes are currently provided for the latest public release only.

5.2 Never publish these files

Do not attach or commit a real working Data folder. In portable mode it may contain:

- `config.portable` with encrypted credentials;
- `portable.key`, which can decrypt that configuration;
- the SQLite database with sources, queue history, and editorial data;
- private Google Drive identifiers and operational logs.

Do not publish access tokens, app secrets, OAuth client secrets, refresh tokens, private Drive links, or screenshots containing secrets.

5.3 Local secret storage

- Portable configuration is encrypted with AES-GCM.
- The portable encryption key is stored next to the encrypted configuration so the full folder can move between computers.
- This portability means physical access to the complete application folder may permit access to stored credentials.
- Tokens are not stored in SQLite.
- Secret values are masked in the interface and removed from normal error output.

5.4 Network and media controls

- External URLs pass through application network safeguards.
- Private and non-global destinations are rejected for external fetches.

- Google Drive files are downloaded through OAuth.
- Temporary public access is created only when Threads requires a public media URL.
- The application revokes only the permission it created.
- A Drive file is deleted only after every selected publication succeeds.

5.5 Queue safety

- SQLite uses WAL, foreign keys, and full synchronous mode.
- Publication targets are processed sequentially.
- Partial retry does not repeat successful targets.
- A second application process is blocked by an OS lock.
- Queue and database migrations are tested for preservation of pending items, target statuses, attempts, and remote IDs.

5.6 Reporting a vulnerability

Send a minimal report to kozyriev@uafree.org or use a private maintainer contact channel.

Include:

- affected version;
- reproduction steps;
- security impact;
- sanitized evidence.

Remove all real credentials and personal data.

6 Part V — Detailed first launch

6.1 Verify the release

Keep the Windows ZIP and SHA256SUMS.txt together. In PowerShell run:

```
Get-FileHash .\UA_FREE_Content_Tool_v1.0.0_Windows_Portable.zip -
Algorithm SHA256
Get-Content .\SHA256SUMS.txt
```

Compare all 64 hash characters. Do not use the archive when even one character differs.

6.2 Choose the permanent folder

Use a writable local folder such as C:\Tools\UA_FREE_Content_Tool. Do not run the EXE from inside the ZIP, a browser preview, a read-only location, or a folder that is aggressively synchronized while SQLite is open.

6.3 Configure Ollama

Start Ollama first. `ollama list` must show at least one model. In **Налаштування** → **1. Оллма і моделі**, click **Знайти моделі**, select a primary model, optionally select a different fallback model, then click **ЗБЕРЕГТИ ЗМІНИ**. The application accepts only a local loopback Ollama URL such as `http://127.0.0.1:11434`.

6.4 Configure integrations

Complete and validate one platform at a time. An unconfigured platform is simply unavailable as a publication target and does not block other integrations. After all required platforms are configured, use **Перевірити всі підключення зараз** and read every status row.

6.5 Add sources and test collection

Open **Джерела**, choose `rss`, `telegram`, or `url`, enter a human-readable name and the address, then click **Додати**. Begin with a small source set. Enabled sources are checked after startup and every five minutes.

6.6 Perform the first end-to-end test

Collect a small sample, select related reports with Shift/Ctrl, merge them manually, create a local rewrite, verify the final Ukrainian text and the 900-character limit, attach a non-sensitive Drive file when needed, schedule one package, and inspect **Черга** until every selected platform is successful.

7 Part VI — Troubleshooting matrix

Symptom	Likely cause	Safe action
Ollama is not found	Service is stopped or no model is installed	Start Ollama, run <code>ollama list</code> , repeat Знайти моделі
First rewrite is slow	Model cold start or model too large	Wait for preload or select a smaller model

Symptom	Likely cause	Safe action
English/Russian rewrite is rejected	Language and grounding gate worked	Re-run or improve the merged source block; do not disable the gate
Facebook pages are missing	Wrong/expired token, missing role, missing permission	Create a valid User Access Token, confirm roles, repeat Знайти сторінки
Threads publishes but trend search fails	Optional threads_keyword_search is absent	Continue publishing; add the optional permission only when required
LinkedIn token fails	Missing w_member_social, expired token, wrong account	Generate a new correctly scoped token
Telegram bot cannot post	Bot is not an administrator or lacks can_post_messages	Grant the required channel role and permission
Drive media check fails	Wrong link/type/account or missing delete access	Use the direct file link and reconnect the correct account
Status is temporarily unverified	DNS, network, or platform outage	Do not rotate tokens without explicit invalid-token evidence; retry later
Queue package is paused	Retry limit or authentication block	Correct the issue, then use Повторити невідправлені
Package is overdue	Application was closed at the scheduled time	Use Перепланувати пропущені / призупинені
Settings vanished	Only part of the	Restore the complete

Symptom	Likely cause	Safe action
after moving	folder was copied	folder from backup

8 Part VII — First live publication checklist

- ☐ Complete portable folder backed up.
- ☐ Ollama and selected model available.
- ☐ Required sources tested.
- ☐ All relevant source texts included in the block.
- ☐ Final Ukrainian text factual and no longer than 900 characters.
- ☐ Media belongs to the connected Drive account and is non-sensitive.
- ☐ Only intended platform targets selected.
- ☐ Kyiv schedule verified.
- ☐ Connection diagnostics current.
- ☐ Every target status and remote ID reviewed after publication.

9 Part VIII — Recovery rule

Before changing anything after a failure, close the application, copy the complete portable folder, sanitize logs, record exact target statuses and remote IDs, and change only the component proven to be faulty. Never erase the queue or replace Data because one platform failed.