



@ FILE NAME: M_CTC_ID_019.txt

@ TEST SCOPE: M PLANE O-RAN CONFORMANCE

@ Software Release for Garuda: v5.0.4

Test Description: This scenario is MANDATORY for an O-RU supporting the Hybrid M-plane architecture model.

This test validates that the O-RU correctly implements NETCONF Access Control security aspects.

The scenario corresponds to the following chapters in [3]:

3.3 SSH Connection Establishment

3.4 NETCONF Access Control



STEP 1. The TER NETCONF Client establishes a connection with the O-RU NETCONF Server.

****** Connect to the NETCONF Server ********

> listen --ssh --login operator

Waiting 60s for an SSH Call Home connection on port 4334...

The authenticity of the host '::ffff:192.168.22.37' cannot be established.

ssh-rsa key fingerprint is c0:7c:63:5d:4b:85:e7:27:e0:7e:f0:44:38:4e:ab:83

Interactive SSH Authentication done.

> status

Current NETCONF session:

ID : 4

Host : 192.168.22.37

Port: 830 Transport: SSH Capabilities:

urn:ietf:params:netconf:base:1.0 urn:ietf:params:netconf:base:1.1 urn:ietf:params:netconf:capability:writable-running:1.0

urn:ietf:params:netconf:capability:candidate:1.0 urn:ietf:params:netconf:capability:rollback-on-error:1.0

urn:ietf:params:netconf:capability:validate:1.1 urn:ietf:params:netconf:capability:startup:1.0 urn:ietf:params:netconf:capability:xpath:1.0

urn:ietf:params:netconf:capability:with-defaults:1.0?basic-mode=explicit&also-supported=report-all,report-all-tagged,trim,explicit

 $urn: ietf: params: netconf: capability: notification: 1.0 \ urn: ietf: params: netconf: capability: interleave: 1.0 \ urn: ietf: params: netconf: capability: netconf: capability$

urn:ietf:params:xml:ns:yang:ietf-yang-metadata?module=ietf-yang-metadata&revision=2016-08-05

urn:ietf:params:xml:ns:yang:1?module=yang&revision=2017-02-20

urn:ietf:params:xml:ns:yang:ietf-inet-types?module=ietf-inet-types&revision=2013-07-15

urn:ietf:params:xml:ns:yang:ietf-yang-types?module=ietf-yang-types&revision=2013-07-15

urn:ietf:params:netconf:capability:yang-library:1.1?revision=2019-01-04&content-id=61

urn: sysrepo: plugind? module = sysrepo-plugind & revision = 2020-12-10

urn:ietf:params:xml:ns:yang:ietf-netconf-acm?module=ietf-netconf-acm&revision=2018-02-14

urn: ietf: params: xml: ns: netconf: base: 1.0? module = ietf-netconf & revision = 2013-09-29 & features = writable-running, candidate, rollback-on-error, validate, rollback-on-error, rol

 $ate, startup, url, xpath\ urn: ietf: params: xml: ns: yang: ietf-netconf-with-defaults? module = ietf-netconf-with-defaults \& revision = 2011-06-01. The parameters of the p$

urn: ietf: params: xml: ns: yang: ietf-net conf-notifications? module = ietf-net conf-notifications & revision = 2012-02-06

urn: ietf: params: xml: ns: yang: ietf-netconf-monitoring? module = ietf-netconf-monitoring & revision = 2010-10-04

urn: ietf: params: xml: ns: netconf: notification: 1.0? module = notifications & revision = 2008-07-14

urn: ietf: params: xml: ns: netmod: notification? module = nc-notifications & revision = 2008-07-14

urn:ietf:params:xml:ns:yang:ietf-x509-cert-to-name?module=ietf-x509-cert-to-name&revision=2014-12-10

 $urn: ietf: params: xml: ns: yang: iana-crypt-hash? module = iana-crypt-hash\& revision = 2014-08-06 \ urn: notification_history? module = notification_his$

urn: ietf: params: xml: ns: yang: iana-if-type? module = iana-if-type & revision = 2017-01-19

> subscribe



Ok



> get --filter-xpath /o-ran-usermgmt:users/user

```
<?xml version="1.0" ?>
<data xmlns="urn:ietf:params:xml:ns:netconf:base:1.0" xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
<users xmlns="urn:o-ran:user-mgmt:1.0">
<user>
 <name>oranuser</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>operator</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>observer</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>installer</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>operator5310619424927220</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>operator42009256600399182198</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
 <name>operator900036241939705</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
```

<name>operator7131913</name>



<account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>operator97206</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>operator62794098482</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>operator2904805</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>operator9803</name> <account-type>PASSWORD</account-type> <enabled>true</enabled>

</user>
</users>
</data>



Apr 14 05:29:44 garuda daemon.info netopeer2-server[860]: Trying to connect via IPv4 to 192.168.22.208:4334.

Apr 14 05:29:44 garuda daemon.info netopeer2-server[860]: getsockopt() error (Connection refused).

Apr 14 05:29:44 garuda daemon.info netopeer2-server[860]: Trying to connect via IPv4 to 192.168.22.208:4334.

Apr 14 05:29:44 garuda daemon.info netopeer2-server[860]: getsockopt() error (Connection refused).

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Trying to connect via IPv4 to 192.168.22.208:4334.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: getsockopt() error (Connection refused).

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Trying to connect via IPv4 to 192.168.22.208:4334.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Successfully connected to 192.168.22.208:4334 over IPv4.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Session 154 (user "root", CID 1) created.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Received an SSH message "request-service" of subtype "ssh-userauth".

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Received an SSH message "request-auth" of subtype "password".

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: User "operator" authenticated.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Received an SSH message "request-channel-open" of subtype "session".

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Received an SSH message "request-channel" of subtype "subsystem".

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Call Home client "default-client" session 4 established.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Session 155 (user "root", CID 1) created.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: There are no subscribers for "ietf-netconf-notifications" notifications.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Generated new event (netconf-session-start).

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Published event "rpc" "/ietf-netconf:get" with ID 9 priority 0 for 1 subscribers.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Processing "/ietf-netconf:get" "rpc" event with ID 9 priority 0 (remaining 1 subscribers).

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Successful processing of "rpc" event with ID 9 priority 0 (remaining 0 subscribers).

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Event "rpc" with ID 9 priority 0 succeeded.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:45 garuda daemon.info netopeer2-server[860]: Session 4: thread 3 event new RPC.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Published event "rpc" "/ietf-netconf:get" with ID 10 priority 0 for 1 subscribers.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Processing "/ietf-netconf:get" "rpc" event with ID 10 priority 0 (remaining 1 subscribers).

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Published event "operational" "/o-ran-software-management:software-inventory" with ID 4.

Apr 14 05:29:46 garuda user.notice fw_manager[937]: RPC #4 recieved. xpath -> /o-ran-software-management:software-inventory

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Trying to connect via IPv4 to 192.168.22.208:4334.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: getsockopt() error (Connection refused).

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Event "operational" with ID 4 succeeded.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: There is no leafref



"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "STL O-RU", but it is not required.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "", but it is not required.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "STL=O-RU", but it is not required.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Successful processing of "rpc" event with ID 10 priority 0 (remaining 0 subscribers).

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Event "rpc" with ID 10 priority 0 succeeded.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "STL O-RU", but it is not required.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "", but it is not required.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "STL=O-RU", but it is not required.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Session 4: thread 3 event new RPC.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Published event "rpc" "/ietf-netconf:get-config" with ID 7 priority 0 for 1 subscribers.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Processing "/ietf-netconf:get-config" "rpc" event with ID 7 priority 0 (remaining 1 subscribers).

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Successful processing of "rpc" event with ID 7 priority 0 (remaining 0 subscribers).

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Event "rpc" with ID 7 priority 0 succeeded.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/ietf-hardware:name" with the value "ru-port0", but it is not required.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/ietf-hardware:name" with the value "ru-port0", but it is not required.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/ietf-hardware:name" with the value "ru-port0", but it is not required.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Session 4: thread 2 event new RPC.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Published event "rpc" "/notifications:create-subscription" with ID 4 priority 0 for 1 subscribers.

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Processing "/notifications:create-subscription" "rpc" event with ID 4 priority 0 (remaining 1 subscribers).

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Successful processing of "rpc" event with ID 4 priority 0 (remaining 0 subscribers).

Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Event "rpc" with ID 4 priority 0 succeeded.



- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Session 4: thread 3 event new RPC.
- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...
- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.
- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...
- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.
- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Published event "rpc" "/ietf-netconf:get-config" with ID 8 priority 0 for 1 subscribers.
- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Processing "/ietf-netconf:get-config" "rpc" event with ID 8 priority 0 (remaining 1 subscribers).
- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Successful processing of "rpc" event with ID 8 priority 0 (remaining 0 subscribers).
- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Event "rpc" with ID 8 priority 0 succeeded.
- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Resolving unresolved data nodes and their constraints...
- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: All data nodes and constraints resolved.
- Apr 14 05:29:46 garuda daemon.info netopeer2-server[860]: Session 4: thread 3 event new RPC.
- Apr 14 05:29:47 garuda daemon.info netopeer2-server[860]: Trying to connect via IPv4 to 192.168.22.208:4334.
- Apr 14 05:29:47 garuda daemon.info netopeer2-server[860]: getsockopt() error (Connection refused).
- Apr 14 05:29:48 garuda daemon.info netopeer2-server[860]: Trying to connect via IPv4 to 192.168.22.208:4334.
- Apr 14 05:29:48 garuda daemon.info netopeer2-server[860]: getsockopt() error (Connection refused).
- Apr 14 05:29:49 garuda daemon.info netopeer2-server[860]: Trying to connect via IPv4 to 192.168.22.208:4334.
- Apr 14 05:29:49 garuda daemon.info netopeer2-server[860]: getsockopt() error (Connection refused).
- Apr 14 05:29:50 garuda daemon.info netopeer2-server[860]: Trying to connect via IPv4 to 192.168.22.208:4334.
- Apr 14 05:29:50 garuda daemon.info netopeer2-server[860]: getsockopt() error (Connection refused).
- Apr 14 05:29:51 garuda daemon.info netopeer2-server[860]: Trying to connect via IPv4 to 192.168.22.208:4334.
- Apr 14 05:29:51 garuda daemon.info netopeer2-server[860]: getsockopt() error (Connection refused).
- Apr 14 05:29:52 garuda daemon.info netopeer2-server[860]: Session 4: thread 1 event new RPC.
- Apr 14 05:29:52 garuda daemon.info netopeer2-server[860]: Session 4: thread 1 event session terminated.
- Apr 14 05:29:52 garuda daemon.info netopeer2-server[860]: There are no subscribers for "ietf-netconf-notifications" notifications.
- Apr 14 05:29:52 garuda daemon.info netopeer2-server[860]: Generated new event (netconf-session-end).
- Apr 14 05:29:52 garuda daemon.info netopeer2-server[860]: Call Home client "default-client" session terminated.
- Apr 14 05:29:52 garuda daemon.info netopeer2-server[860]: Trying to connect via IPv4 to 192.168.22.208:4334.
- Apr 14 05:29:52 garuda daemon.info netopeer2-server[860]: getsockopt() error (Connection refused).
- Apr 14 05:29:52 garuda auth.info sshd[5075]: Accepted password for operator from 192.168.22.208 port 44266 ssh2
- Apr 14 05:29:52 garuda authpriv.info sshd[5075]: pam_unix(sshd:session): session opened for user operator by (uid=0)



Expected Result : The O-RU NETCONF server replies by silently omitting data nodes and		
their descendants to which the client d	does not have read access from the <rpc-< th=""><th>reply></th></rpc-<>	reply>
message		
**************************************		=====
Access Control Sudo (negative case)	= SUCCESS	=======