



@ FILE NAME: M_CTC_ID_010.txt

@ TEST SCOPE: M PLANE O-RAN CONFORMANCE

@ Software Release for MCB1: v1.0.1

Test Description : This scenario validates that the O-RU NETCONF Server properly executes a general get command.

***** Connect to the NETCONF Server *****

```
> connect --ssh --host 192.168.49.43 --port 830 --login root
```

```
Interactive SSH Authentication
```

```
Type your password:
```

```
Password:
```

```
> status
```

```
Current NETCONF session:
```

```
ID      : 1
```

```
Host     : 192.168.49.43
```

```
Port      : 830
```

```
Transport : SSH
```

```
Capabilities:
```

```
urn:ietf:params:netconf:base:1.0 urn:ietf:params:netconf:base:1.1 urn:ietf:params:netconf:capability:writable-running:1.0
urn:ietf:params:netconf:capability:candidate:1.0 urn:ietf:params:netconf:capability:rollback-on-error:1.0
urn:ietf:params:netconf:capability:validate:1.1 urn:ietf:params:netconf:capability:startup:1.0 urn:ietf:params:netconf:capability:xpath:1.0
urn:ietf:params:netconf:capability:with-defaults:1.0?basic-mode=explicit&also-supported=report-all,report-all-tagged,trim,explicit
urn:ietf:params:netconf:capability:notification:1.0 urn:ietf:params:netconf:capability:interleave:1.0
urn:ietf:params:xml:ns:yang:ietf-yang-metadata?module=ietf-yang-metadata&revision=2016-08-05
urn:ietf:params:xml:ns:yang:1?module=yang&revision=2017-02-20
urn:ietf:params:xml:ns:yang:ietf-inet-types?module=ietf-inet-types&revision=2013-07-15
urn:ietf:params:xml:ns:yang:ietf-yang-types?module=ietf-yang-types&revision=2013-07-15
urn:ietf:params:netconf:capability:yang-library:1.1?revision=2019-01-04&content-id=63
urn:sysrepo:plugind?module=sysrepo-plugind&revision=2020-12-10
urn:ietf:params:xml:ns:yang:ietf-netconf-acm?module=ietf-netconf-acm&revision=2018-02-14
urn:ietf:params:xml:ns:netconf:base:1.0?module=ietf-netconf&revision=2013-09-29&features=writable-running,candidate,rollback-on-error,valid
ate,startup,url,xpath urn:ietf:params:xml:ns:yang:ietf-netconf-with-defaults?module=ietf-netconf-with-defaults&revision=2011-06-01
urn:ietf:params:xml:ns:yang:ietf-netconf-notifications?module=ietf-netconf-notifications&revision=2012-02-06
urn:ietf:params:xml:ns:yang:ietf-netconf-monitoring?module=ietf-netconf-monitoring&revision=2010-10-04
urn:ietf:params:xml:ns:netconf:notification:1.0?module=notifications&revision=2008-07-14
urn:ietf:params:xml:ns:netmod:notification?module=nc-notifications&revision=2008-07-14
urn:ietf:params:xml:ns:yang:ietf-x509-cert-to-name?module=ietf-x509-cert-to-name&revision=2014-12-10
urn:ietf:params:xml:ns:yang:iana-crypt-hash?module=iana-crypt-hash&revision=2014-08-06 urn:notification_history?module=notification_history
urn:ietf:params:xml:ns:yang:iana-if-type?module=iana-if-type&revision=2017-01-19
```

```
> subscribe
```

```
Ok
```

=====

Step 1 The TER NETCONF Client triggers <rpc><get> towards the O-RU NETCONF Server.

=====

=====

> get

=====

=====

Step 2 The O-RU NETCONF Server responds with <rpc-reply><data> where <data> contains all information elements that the O-RU NETCONF Server is able to expose

=====

```
<?xml version="1.0" ?>
<data xmlns="urn:ietf:params:xml:ns:netconf:base:1.0" xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
  <keystore xmlns="urn:ietf:params:xml:ns:yang:ietf-keystore">
    <asymmetric-keys>
      <asymmetric-key>
        <name>genkey</name>
        <algorithm>rsa2048</algorithm>
        <public-key>MIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEAzYRjPYvux03VA/ZokexW2yJ/9ZhjbUAXiUwcHf5YZyLs1Vsz
vahxASW0X4UtD7UnmVttB2t8/zWqr3QM5Eqae4+IVk09klrZ2O9zRpW6QQX3q3gLiRhUAzN/khkT6Bn4BdzvPqecdFfMBthMf6gxSUUdXbM
wZ2ZfIjjUuUC4StmvNOWYsbb8VDbHH56THkatCGaBQkW71X5piHInYZg9EpUQiAtNzwYztjmyEA3J7niapYcHfthvL7KNL7rWBv+Z6HdsW
Y/jLzpBB89DKuaLatGo3MmTonXAv3CebWvmPt/7uxIU/a431yqlcpnzBFhEaIvvGol8EuTg9x0h70H2wwIDAQAB</public-key>
        <private-key>MIIEvgIBADANBgkqhkiG9w0BAQEFAASCBAQgwwggSkAgEAAoIBAQDNhGM9i+7HTdUD9miR7FbbIn/1mGNtQBeIhTBwd/
lhnIuzVWzO9qHEBjBrfhS0PtSeZW20Ha3z/NaqvdAzkSpTj6VWTT2SWtnY73NGlbpBBfereAuJGFQDM3+SGRPoGfgF3O8+p5x0V8wG2Ex/
qDFJRR1dszBnZl8iONS4LhK2a805ZixtvxUNscfnpMeRq0IZoFCRbvVfmmIcidhmD0SIRCIC03PBjO2ObIQDcnueJqlhwd+2G8vso0vutYG/5nod
2xZj+MvOkEHZ0OS5otq0ajcyZOidcC/cJxta+Y+3/u7EhT9rjfXKqVymfMEWERoi+8agjwSOD3HSHvQfbDagMBAAECggEAB4XkGBmqOP
N5a7a2ZzkOiOD/bB8S7Kne8qld4h8wXz4hC0JWZ4fl8xPNQX3fg2avN2boW9AseC8fu2J1Ilo0v6iPddRH/7aBqPZC8v+CHOU6BrXTPkZ8tM1
Kyy9N0j45HQXUYCfEi2G3XzzFuBqRC0yTYZ2wlOhjbr5FcySEnNKryu6NljdmQsomLQJ/za1yHBEAx7YVi9GrJzBAFENLGqIH7M7wMn4
MLCr5OodoVhdd45BiF5VswP+y67EWhZcF5vi9S/8AxS+GSeGv/hoLB+1KCyxk9vXbshVyOW2zEVUghJ1T4RXf7uW7unxNnzCbuePNVTvA
1uV38A8FMmliQKBgQDUvozJdu/SdJAnnR65x3aTL/OpChtmYY6qi2+bLn8MLA+hbzKbJcwhqpYxb1CGFSfQssBCRUaX6wVfB3C0e2Sved2C
BXdYMZzRbeEdgilhal2BP2/tW5gazz2d27hCsiU7pyZatnWI6FAV3IOSBU97cAmhfBfZaQJtmguuZaWvtQKBgQDcXwo6rgSSWotzPUhkJWix
ChBoqkE6WFbzZTiVsHp1kplugxe3P0rTjI98MWKcowAHUNGJ7v4IPJlaKB9xYXwp7bJKrkXftluuyQepsau/oljp122GNyJyHeV2KuK7Im55tla3
05Vp4gn57G4U+NkX+QsYR10eNChiHBHKE+/nlwKBgBkqRLTHsKfCWZ+TVDXI7Jq/JzPeON0I01/uqqj00bd6vXsKuY7ZARdbX9F+JkK74C
KDdPiHTNWelEZcBmk/yHEmq06VPOsy75CzwFLX8LkM+SYyhZ3DVdkdlyUYj+eX14zeJZDSQrlXo3lqcQPnQ2WDfcBj0C+zs2CUkD6lwD0
xAoGBANVR6sUCzsodfAABwqGuzm5KH7gxKzKpfr+ry+pf1WixMGhj426YM2piN9bdK0ixCv5OWFc5V6tyrGkTW6SptPbmtGVaFYBrB3
vkVU/wdW5SBRTQ3CtEMv6KzwOCfXYvURf2Mg4YLMtyk8aq7eOsL2QGwM20xcCYIpe/HfOPhAoGBALvMEDLK0se5Qxesj1YgE+b6U3
M+Wwh9JeFu1j/sEVJ3h7fCY7iWQA1GIRBUEITltiKkZSSgSF+arASMeBdaR2+R+3ImS5MDWmvnZjAiGSXhIWjTEPe/WsoejtnckjjX0yhPPI
NBKsT2n5wHAcdf6ZlvdcpGkzM4IdQkxZfjbQ</private-key>
      </asymmetric-key>
    </asymmetric-keys>
  </keystore>
  <users xmlns="urn:o-ran:user-mgmt:1.0">
    <user>
      <name>oranuser</name>
      <account-type>PASSWORD</account-type>
      <password>oranuser</password>
      <enabled>true</enabled>
    </user>
  </users>
</data>
```

```
</user>
<user>
  <name>operator</name>
  <account-type>PASSWORD</account-type>
  <password>admin1234895</password>
  <enabled>true</enabled>
</user>
<user>
  <name>observer</name>
  <account-type>PASSWORD</account-type>
  <password>admin123</password>
  <enabled>true</enabled>
</user>
<user>
  <name>installer</name>
  <account-type>PASSWORD</account-type>
  <password>wireless123</password>
  <enabled>true</enabled>
</user>
<user>
  <name>garuda</name>
  <account-type>PASSWORD</account-type>
  <password>garuda12345</password>
  <enabled>true</enabled>
</user>
<user>
  <name>operator11302326379</name>
  <account-type>PASSWORD</account-type>
  <password>Aemlsk9}{2xgQVF</password>
  <enabled>true</enabled>
</user>
<user>
  <name>operator44567591</name>
  <account-type>PASSWORD</account-type>
  <password>y07)BAFyAm0M7W1lc2mEA_D5[5YytpafL6xTTCXM%Q]~Z2Fv^</password>
  <enabled>true</enabled>
</user>
<user>
  <name>operator8075861281902</name>
  <account-type>PASSWORD</account-type>
  <password>GV2QSHVzl}B)vk(!tw2pZhuFkkn%L^E)wgk(Z{KfgXCpdkfEA+NGMY(B^+kDYB8R06v</password>
  <enabled>true</enabled>
</user>
<user>
  <name>operator17619020756748090</name>
  <account-type>PASSWORD</account-type>
  <password>nwk75gnD[44LqeBrwKFcBvaUNPKz6gARf_M.EHxwG.EGuk{-n_Os0avM}$XZ}LBYNb+)M!NcV0RunG}_-)9F2gu%nKKsd+X
kOgXvIYxh%QxBQsA7EYqB</password>
  <enabled>true</enabled>
```

```
</user>
<user>
  <name>operator86938204120707827368</name>
  <account-type>PASSWORD</account-type>
  <password>s8icesF.Hl~%FN4_]!MKBMVqa]{RUQkL07x.+)-VmZfAh3nJxwS+y6I!</password>
  <enabled>true</enabled>
</user>
<user>
  <name>operator7596639986022389968</name>
  <account-type>PASSWORD</account-type>
  <password>v+Dq5KtKuj(^!x</password>
  <enabled>true</enabled>
</user>
<user>
  <name>operator0126795795152205</name>
  <account-type>PASSWORD</account-type>
  <password>RdP1GycV9r]R15N_k7Hnz5wF)vjY~dxBE!v^MxSq4Gke1nCkSCW+1)1z%2}kOtLnjiWbj]EY7QUk%15H0g~QYlrR0bRkZMz1x
TyDy3ca6-r</password>
  <enabled>true</enabled>
</user>
<user>
  <name>operator119986</name>
  <account-type>PASSWORD</account-type>
  <password>1Xrl)+$ki)QolcMi)vVRig.u</password>
  <enabled>true</enabled>
</user>
<user>
  <name>stl</name>
  <account-type>PASSWORD</account-type>
  <password>stli12345</password>
  <enabled>true</enabled>
</user>
</users>
<nacm xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-acm">
  <enable-nacm>true</enable-nacm>
  <read-default>deny</read-default>
  <write-default>deny</write-default>
  <exec-default>deny</exec-default>
  <enable-external-groups>false</enable-external-groups>
  <groups>
    <group>
      <name>sudo</name>
      <user-name>operator</user-name>
    </group>
    <group>
      <name>fm-pm</name>
      <user-name>observer</user-name>
    </group>
    <group>
```

```
<name>nms</name>
<user-name>installer</user-name>
</group>
</groups>
<rule-list>
<name>sudo-access</name>
<group>sudo</group>
<rule>
<name>ietf-netconf-permission</name>
<module-name>ietf-netconf</module-name>
<access-operations>exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-supervision-permission</name>
<module-name>o-ran-supervision</module-name>
<access-operations>exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-hardware-permission</name>
<module-name>o-ran-hardware</module-name>
<access-operations>read exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>ietf-hardware-permission</name>
<module-name>ietf-hardware</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>iana-hardware-permission</name>
<module-name>iana-hardware</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-usermgmt-permission1</name>
<module-name>o-ran-usermgmt</module-name>
<path xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user</path>
<access-operations>create update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-usermgmt-permission2</name>
<module-name>o-ran-usermgmt</module-name>
<path xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user/o-ran-usermgmt:name</path>
<access-operations>create read update delete</access-operations>
```

```
<action>permit</action>
</rule>
<rule>
<name>o-ran-usermgmt-permission3</name>
<module-name>o-ran-usermgmt</module-name>
<path xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0"/>o-ran-usermgmt:users/o-ran-usermgmt:user/o-ran-usermgmt:account-type</path>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-usermgmt-permission4</name>
<module-name>o-ran-usermgmt</module-name>
<path xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0"/>o-ran-usermgmt:users/o-ran-usermgmt:user/o-ran-usermgmt:password</path>
<access-operations>create update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-usermgmt-permission5</name>
<module-name>o-ran-usermgmt</module-name>
<path xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0"/>o-ran-usermgmt:users/o-ran-usermgmt:user/o-ran-usermgmt:enabled</path>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-fm-permission</name>
<module-name>o-ran-fm</module-name>
<access-operations>read exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-sync-permission</name>
<module-name>o-ran-sync</module-name>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-delay-management-permission</name>
<module-name>o-ran-delay-management</module-name>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-module-cap-permission</name>
<module-name>o-ran-module-cap</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-udp-echo-permission</name>
```

```
<module-name>o-ran-udp-echo</module-name>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-operations-permission</name>
<module-name>o-ran-operations</module-name>
<access-operations>read exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-uplane-conf</name>
<module-name>o-ran-uplane-conf</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-lbm-permission</name>
<module-name>o-ran-lbm</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-software-management-permission</name>
<module-name>o-ran-software-management</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-file-management-permission</name>
<module-name>o-ran-file-management</module-name>
<access-operations>exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-performance-management-permission</name>
<module-name>o-ran-performance-management</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-ald-port-permission</name>
<module-name>o-ran-ald-port</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-ald-permission</name>
<module-name>o-ran-ald</module-name>
```



```
<access-operations>exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-transceiver-permission</name>
<module-name>o-ran-transceiver</module-name>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-interfaces-permission</name>
<module-name>o-ran-interfaces</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>ietf-ip-permission</name>
<module-name>ietf-ip</module-name>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>ietf-interfaces-permission</name>
<module-name>ietf-interfaces</module-name>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>iana-if-type-permission</name>
<module-name>iana-if-type</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>ietf-inet-types-permission</name>
<module-name>ietf-inet-types</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-processing-elements-permission</name>
<module-name>o-ran-processing-element</module-name>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-mplane-interfaces-permission</name>
<module-name>o-ran-mplane-int</module-name>
<access-operations>create read update delete</access-operations>
```

```
<action>permit</action>
</rule>
<rule>
  <name>o-ran-dhcp-permission</name>
  <module-name>o-ran-dhcp</module-name>
  <access-operations>read</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>o-ran-troubleshooting-permission</name>
  <module-name>o-ran-troubleshooting</module-name>
  <access-operations>exec</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>o-ran-trace-permission</name>
  <module-name>o-ran-trace</module-name>
  <access-operations>exec</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-netconf-acm-permission</name>
  <module-name>ietf-netconf-acm</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-yang-library-permission</name>
  <module-name>ietf-yang-library</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-netconf-monitoring-permission</name>
  <module-name>ietf-netconf-monitoring</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-netconf-notifications-permission</name>
  <module-name>ietf-netconf-notifications</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>nc-notifications-permission</name>
  <module-name>nc-notifications</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
```

```
</rule>
<rule>
  <name>notifications-permission</name>
  <module-name>notifications</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
</rule-list>
<rule-list>
  <name>nms-access</name>
  <group>nms</group>
  <rule>
    <name>ietf-netconf-permission</name>
    <module-name>ietf-netconf</module-name>
    <access-operations>exec</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>o-ran-hardware-permission</name>
    <module-name>o-ran-hardware</module-name>
    <access-operations>read exec</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>ietf-hardware-permission</name>
    <module-name>ietf-hardware</module-name>
    <access-operations>create read update delete exec</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>iana-hardware-permission</name>
    <module-name>iana-hardware</module-name>
    <access-operations>create read update delete exec</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>o-ran-fm-permission</name>
    <module-name>o-ran-fm</module-name>
    <access-operations>read exec</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>o-ran-sync-permission</name>
    <module-name>o-ran-sync</module-name>
    <access-operations>create read update delete</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>o-ran-delay-management-permission</name>
```

```
<module-name>o-ran-delay-management</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-module-cap-permission</name>
<module-name>o-ran-module-cap</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-udp-echo-permission</name>
<module-name>o-ran-udp-echo</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-operations-permission</name>
<module-name>o-ran-operations</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-uplane-conf</name>
<module-name>o-ran-uplane-conf</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-lbm-permission</name>
<module-name>o-ran-lbm</module-name>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-software-management-permission</name>
<module-name>o-ran-software-management</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-file-management-permission</name>
<module-name>o-ran-file-management</module-name>
<access-operations>exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-performance-management-permission</name>
<module-name>o-ran-performance-management</module-name>
```

```
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-ald-port-permission</name>
<module-name>o-ran-ald-port</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-transceiver-permission</name>
<module-name>o-ran-transceiver</module-name>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-interfaces-permission</name>
<module-name>o-ran-interfaces</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>ietf-ip-permission</name>
<module-name>ietf-ip</module-name>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>ietf-interfaces-permission</name>
<module-name>ietf-interfaces</module-name>
<access-operations>create read update delete</access-operations>
<action>permit</action>
</rule>
<rule>
<name>iana-if-type-permission</name>
<module-name>iana-if-type</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>ietf-inet-types-permission</name>
<module-name>ietf-inet-types</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-processing-elements-permission</name>
<module-name>o-ran-processing-element</module-name>
<access-operations>create read update delete</access-operations>
```

```
<action>permit</action>
</rule>
<rule>
  <name>o-ran-mplane-interfaces-permission</name>
  <module-name>o-ran-mplane-int</module-name>
  <access-operations>create read update delete</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>o-ran-dhcp-permission</name>
  <module-name>o-ran-dhcp</module-name>
  <access-operations>read</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>o-ran-troubleshooting-permission</name>
  <module-name>o-ran-troubleshooting</module-name>
  <access-operations>exec</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>o-ran-trace-permission</name>
  <module-name>o-ran-trace</module-name>
  <access-operations>exec</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-netconf-acm-permission</name>
  <module-name>ietf-netconf-acm</module-name>
  <access-operations>read</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-yang-library-permission</name>
  <module-name>ietf-yang-library</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-netconf-monitoring-permission</name>
  <module-name>ietf-netconf-monitoring</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-netconf-notifications-permission</name>
  <module-name>ietf-netconf-notifications</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
```

```
</rule>
<rule>
  <name>nc-notifications-permission</name>
  <module-name>nc-notifications</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>notifications-permission</name>
  <module-name>notifications</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
</rule-list>
<rule-list>
  <name>fm-pm-access</name>
  <group>fm-pm</group>
  <rule>
    <name>ietf-netconf-permission</name>
    <module-name>ietf-netconf</module-name>
    <access-operations>exec</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>ietf-hardware-permission</name>
    <module-name>ietf-hardware</module-name>
    <access-operations>read exec</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>iana-hardware-permission</name>
    <module-name>iana-hardware</module-name>
    <access-operations>read exec</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>o-ran-fm-permission</name>
    <module-name>o-ran-fm</module-name>
    <access-operations>read exec</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>o-ran-sync-permission</name>
    <module-name>o-ran-sync</module-name>
    <access-operations>read</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>o-ran-delay-management-permission</name>
```

```
<module-name>o-ran-delay-management</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-module-cap-permission</name>
<module-name>o-ran-module-cap</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-operations-permission</name>
<module-name>o-ran-operations</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-uplane-conf</name>
<module-name>o-ran-uplane-conf</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-lbm-permission</name>
<module-name>o-ran-lbm</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-software-management-permission</name>
<module-name>o-ran-software-management</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-file-management-permission</name>
<module-name>o-ran-file-management</module-name>
<access-operations>exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-performance-management-permission</name>
<module-name>o-ran-performance-management</module-name>
<access-operations>create read update delete exec</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-transceiver-permission</name>
<module-name>o-ran-transceiver</module-name>
```



```
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-interfaces-permission</name>
<module-name>o-ran-interfaces</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>ietf-ip-permission</name>
<module-name>ietf-ip</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>ietf-interfaces-permission</name>
<module-name>ietf-interfaces</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>iana-if-type-permission</name>
<module-name>iana-if-type</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>ietf-inet-types-permission</name>
<module-name>ietf-inet-types</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-processing-elements-permission</name>
<module-name>o-ran-processing-element</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-mplane-interfaces-permission</name>
<module-name>o-ran-mplane-int</module-name>
<access-operations>read</access-operations>
<action>permit</action>
</rule>
<rule>
<name>o-ran-dhcp-permission</name>
<module-name>o-ran-dhcp</module-name>
<access-operations>read</access-operations>
```

```
<action>permit</action>
</rule>
<rule>
  <name>o-ran-troubleshooting-permission</name>
  <module-name>o-ran-troubleshooting</module-name>
  <access-operations>exec</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>o-ran-trace-permission</name>
  <module-name>o-ran-trace</module-name>
  <access-operations>exec</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-netconf-acm-permission</name>
  <module-name>ietf-netconf-acm</module-name>
  <access-operations>read</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-yang-library-permission</name>
  <module-name>ietf-yang-library</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-netconf-monitoring-permission</name>
  <module-name>ietf-netconf-monitoring</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>ietf-netconf-notifications-permission</name>
  <module-name>ietf-netconf-notifications</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>nc-notifications-permission</name>
  <module-name>nc-notifications</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>notifications-permission</name>
  <module-name>notifications</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
```

```
</rule>
</rule-list>
<rule-list>
  <name>swm-access</name>
  <group>swm</group>
  <rule>
    <name>ietf-netconf-permission</name>
    <module-name>ietf-netconf</module-name>
    <access-operations>exec</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>o-ran-software-management-permission</name>
    <module-name>o-ran-software-management</module-name>
    <access-operations>create read update delete exec</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>iana-if-type-permission</name>
    <module-name>iana-if-type</module-name>
    <access-operations>read</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>ietf-inet-types-permission</name>
    <module-name>ietf-inet-types</module-name>
    <access-operations>read</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>ietf-netconf-acm-permission</name>
    <module-name>ietf-netconf-acm</module-name>
    <access-operations>read</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>ietf-yang-library-permission</name>
    <module-name>ietf-yang-library</module-name>
    <access-operations>*</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>ietf-netconf-monitoring-permission</name>
    <module-name>ietf-netconf-monitoring</module-name>
    <access-operations>*</access-operations>
    <action>permit</action>
  </rule>
  <rule>
    <name>ietf-netconf-notifications-permission</name>
```

```
<module-name>ietf-netconf-notifications</module-name>
<access-operations>*</access-operations>
<action>permit</action>
</rule>
<rule>
  <name>nc-notifications-permission</name>
  <module-name>nc-notifications</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
<rule>
  <name>notifications-permission</name>
  <module-name>notifications</module-name>
  <access-operations>*</access-operations>
  <action>permit</action>
</rule>
</rule-list>
<denied-operations>0</denied-operations>
<denied-data-writes>0</denied-data-writes>
<denied-notifications>0</denied-notifications>
</nacm>
<netconf-server xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-server">
  <listen>
    <endpoint>
      <name>default-ssh</name>
      <ssh>
        <tcp-server-parameters>
          <local-address>:</local-address>
          <keepalives>
            <idle-time>1</idle-time>
            <max-probes>10</max-probes>
            <probe-interval>5</probe-interval>
          </keepalives>
        </tcp-server-parameters>
        <ssh-server-parameters>
          <server-identity>
            <host-key>
              <name>default-key</name>
              <public-key>
                <keystore-reference>genkey</keystore-reference>
              </public-key>
            </host-key>
          </server-identity>
          <client-authentication>
            <supported-authentication-methods>
              <publickey/>
              <password/>
              <other>interactive</other>
            </supported-authentication-methods>
```

```
<users/>
</client-authentication>
</ssh-server-parameters>
</ssh>
</endpoint>
</listen>
<call-home>
<netconf-client>
  <name>default-client</name>
  <endpoints>
    <endpoint>
      <name>endpoint-1</name>
      <ssh>
        <tcp-client-parameters>
          <remote-address>192.168.49.88</remote-address>
          <keepalives>
            <idle-time>1</idle-time>
            <max-probes>10</max-probes>
            <probe-interval>5</probe-interval>
          </keepalives>
        </tcp-client-parameters>
        <ssh-server-parameters>
          <server-identity>
            <host-key>
              <name>default-key</name>
              <public-key>
                <keystore-reference>genkey</keystore-reference>
              </public-key>
            </host-key>
          </server-identity>
          <client-authentication>
            <supported-authentication-methods>
              <publickey/>
              <password/>
              <other>interactive</other>
            </supported-authentication-methods>
          </client-authentication>
        </ssh-server-parameters>
      </ssh>
    </endpoint>
  </endpoints>
</netconf-client>
</call-home>
</netconf-server>
<system-apps xmlns="urn:vvdn_mcel:wdm:1.1">
```

```
<sys_monitor>0</sys_monitor>
<fault_manager>0</fault_manager>
<nw_manager>0</nw_manager>
<um_manager>0</um_manager>
<fw_manager>0</fw_manager>
<sync_manager>0</sync_manager>
<file_manager>0</file_manager>
<operations_manager>0</operations_manager>
<supervision>0</supervision>
<pm_manager>0</pm_manager>
<ald_controller>0</ald_controller>
<log_manager>0</log_manager>
<radio_manager>0</radio_manager>
<cli_manager>0</cli_manager>
</system-apps>
<hardware xmlns="urn:ietf:params:xml:ns:yang:ietf-hardware">
  <component>
    <name>ru-module</name>
    <class xmlns:o-ran-hw="urn:o-ran:hardware:1.0">o-ran-hw:O-RAN-RADIO</class>
    <state>
      <oper-state>enabled</oper-state>
      <usage-state>busy</usage-state>
      <availability-state xmlns="urn:o-ran:hardware:1.0">FAULTY</availability-state>
    </state>
    <o-ran-name xmlns="urn:o-ran:hardware:1.0">ru-module</o-ran-name>
    <description>VVDN-RU</description>
    <hardware-rev>A1-1011</hardware-rev>
    <software-rev>02-v1.0.1</software-rev>
    <serial-num>1012900122022</serial-num>
    <mfg-name>VVDN-LPRU</mfg-name>
    <model-name>RU_INDOOR_LPRU</model-name>
    <uuid>f81d4fae-7dec-11d0-a765-00a0c91e6bf6</uuid>
    <label-content xmlns="urn:o-ran:hardware:1.0">
      <model-name>true</model-name>
      <serial-number>true</serial-number>
    </label-content>
    <product-code xmlns="urn:o-ran:hardware:1.0">O-RAN RU PROD v1.0.4</product-code>
    <contains-child>ru-port0</contains-child>
    <contains-child>ru-port1</contains-child>
  </component>
  <component>
    <name>ru-port0</name>
    <class xmlns:ianahw="urn:ietf:params:xml:ns:yang:iana-hardware">ianahw:port</class>
    <parent>ru-module</parent>
    <parent-rel-pos>0</parent-rel-pos>
    <state>
      <oper-state>enabled</oper-state>
      <usage-state>busy</usage-state>
      <availability-state xmlns="urn:o-ran:hardware:1.0">FAULTY</availability-state>
```

```
</state>
<o-ran-name xmlns="urn:o-ran:hardware:1.0">ru-port0</o-ran-name>
<description>VVDN_RU_PORT</description>
<hardware-rev>A1-1011</hardware-rev>
<is-fru>false</is-fru>
<mfg-date>2020-05-27T09:00:00-05:30</mfg-date>
</component>
<component>
<name>ru-port1</name>
<class xmlns:ianahw="urn:ietf:params:xml:ns:yang:iana-hardware">ianahw:port</class>
<parent>ru-module</parent>
<parent-rel-pos>1</parent-rel-pos>
<state>
<oper-state>enabled</oper-state>
<usage-state>busy</usage-state>
<availability-state xmlns="urn:o-ran:hardware:1.0">FAULTY</availability-state>
</state>
<o-ran-name xmlns="urn:o-ran:hardware:1.0">ru-port1</o-ran-name>
<description>VVDN_RU_PORT</description>
<hardware-rev>A1-1011</hardware-rev>
<is-fru>false</is-fru>
<mfg-date>2020-05-27T09:00:00-05:30</mfg-date>
</component>
<last-change>2103-10-30T08:52:17+08:50</last-change>
</hardware>
<interfaces xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces">
<interface>
<name>lo</name>
<enabled>true</enabled>
<type xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">ianaift:ethernetCsmacd</type>
<ipv4 xmlns="urn:ietf:params:xml:ns:yang:ietf-ip">
<address>
<ip>127.0.0.1</ip>
<netmask>255.0.0.0</netmask>
</address>
<enabled>true</enabled>
</ipv4>
<mac-address xmlns="urn:o-ran:interfaces:1.0">00:00:00:00:00:00</mac-address>
<statistics>
<in-octets>1408</in-octets>
<in-discards>0</in-discards>
<in-errors>0</in-errors>
<out-octets>1408</out-octets>
<out-errors>0</out-errors>
<out-discards>0</out-discards>
</statistics>
<oper-status>up</oper-status>
<phys-address>00:00:00:00:00:00</phys-address>
<last-cleared xmlns="urn:o-ran:interfaces:1.0">2020-05-19T16:39:57-08:00</last-cleared>
```

```
</interface>
<interface>
  <name>eth0</name>
  <enabled>true</enabled>
  <type xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">ianaift:ethernetCsmacd</type>
  <ipv4 xmlns="urn:ietf:params:xml:ns:yang:ietf-ip">
    <address>
      <ip>192.168.1.10</ip>
      <netmask>255.255.255.0</netmask>
    </address>
    <enabled>true</enabled>
  </ipv4>
  <l2-mtu xmlns="urn:o-ran:interfaces:1.0">1500</l2-mtu>
  <mac-address xmlns="urn:o-ran:interfaces:1.0">98:ae:71:00:8a:c1</mac-address>
  <statistics>
    <in-octets>0</in-octets>
    <in-discards>0</in-discards>
    <in-errors>0</in-errors>
    <out-octets>0</out-octets>
    <out-errors>0</out-errors>
    <out-discards>0</out-discards>
  </statistics>
  <oper-status>up</oper-status>
  <phys-address>98:ae:71:00:8a:c1</phys-address>
  <last-cleared xmlns="urn:o-ran:interfaces:1.0">2020-05-19T16:39:57-08:00</last-cleared>
</interface>
<interface>
  <name>eth1</name>
  <enabled>true</enabled>
  <type xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">ianaift:ethernetCsmacd</type>
  <ipv4 xmlns="urn:ietf:params:xml:ns:yang:ietf-ip">
    <address>
      <ip>192.168.4.50</ip>
      <netmask>255.255.255.0</netmask>
    </address>
    <enabled>true</enabled>
  </ipv4>
  <l2-mtu xmlns="urn:o-ran:interfaces:1.0">1500</l2-mtu>
  <mac-address xmlns="urn:o-ran:interfaces:1.0">98:ae:71:00:8a:c2</mac-address>
  <statistics>
    <in-octets>31588</in-octets>
    <in-discards>0</in-discards>
    <in-errors>0</in-errors>
    <out-octets>49790</out-octets>
    <out-errors>0</out-errors>
    <out-discards>0</out-discards>
  </statistics>
  <oper-status>up</oper-status>
  <phys-address>98:ae:71:00:8a:c2</phys-address>
```



```
<last-cleared xmlns="urn:o-ran:interfaces:1.0">2020-05-19T16:39:57-08:00</last-cleared>
</interface>
<interface>
  <name>eth1.428</name>
  <enabled>true</enabled>
  <type xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">ianaift:l2vlan</type>
  <ipv4 xmlns="urn:ietf:params:xml:ns:yang:ietf-ip">
    <address>
      <ip>192.168.241.37</ip>
      <netmask>255.255.255.0</netmask>
    </address>
    <enabled>true</enabled>
  </ipv4>
  <base-interface xmlns="urn:o-ran:interfaces:1.0">eth1</base-interface>
  <vlan-id xmlns="urn:o-ran:interfaces:1.0">428</vlan-id>
  <mac-address xmlns="urn:o-ran:interfaces:1.0">98:ae:71:00:8a:c2</mac-address>
  <port-reference xmlns="urn:o-ran:interfaces:1.0">
    <port-name>ru-port1</port-name>
    <port-number>1</port-number>
  </port-reference>
  <statistics>
    <in-octets>0</in-octets>
    <in-discards>0</in-discards>
    <in-errors>0</in-errors>
    <out-octets>3136</out-octets>
    <out-errors>0</out-errors>
    <out-discards>0</out-discards>
  </statistics>
  <oper-status>up</oper-status>
  <phys-address>98:ae:71:00:8a:c2</phys-address>
  <last-cleared xmlns="urn:o-ran:interfaces:1.0">2020-05-19T16:39:57-08:00</last-cleared>
</interface>
<interface>
  <name>eth1.490</name>
  <enabled>true</enabled>
  <type xmlns:ianaift="urn:ietf:params:xml:ns:yang:iana-if-type">ianaift:l2vlan</type>
  <ipv4 xmlns="urn:ietf:params:xml:ns:yang:ietf-ip">
    <address>
      <ip>192.168.49.43</ip>
      <netmask>255.255.255.0</netmask>
    </address>
    <enabled>true</enabled>
  </ipv4>
  <base-interface xmlns="urn:o-ran:interfaces:1.0">eth1</base-interface>
  <vlan-id xmlns="urn:o-ran:interfaces:1.0">490</vlan-id>
  <mac-address xmlns="urn:o-ran:interfaces:1.0">98:ae:71:00:8a:c2</mac-address>
  <port-reference xmlns="urn:o-ran:interfaces:1.0">
    <port-name>ru-port1</port-name>
    <port-number>1</port-number>
```

```
<port-reference>
<statistics>
  <in-octets>26584</in-octets>
  <in-discards>0</in-discards>
  <in-errors>0</in-errors>
  <out-octets>43587</out-octets>
  <out-errors>0</out-errors>
  <out-discards>0</out-discards>
</statistics>
<oper-status>up</oper-status>
<phys-address>98:ae:71:00:8a:c2</phys-address>
<last-cleared xmlns="urn:o-ran:interfaces:1.0">2020-05-19T16:39:57-08:00</last-cleared>
</interface>
</interfaces>
<mplane-info xmlns="urn:o-ran:mplane-interfaces:1.0">
<m-plane-interfaces>
  <m-plane-sub-interfaces>
    <interface-name>eth1.428</interface-name>
    <sub-interface>428</sub-interface>
    <client-info>
      <mplane-ipv4-info>
        <mplane-ipv4>192.168.49.88</mplane-ipv4>
        <port>4334</port>
      </mplane-ipv4-info>
    </client-info>
  </m-plane-sub-interfaces>
  <m-plane-sub-interfaces>
    <interface-name>eth1.490</interface-name>
    <sub-interface>490</sub-interface>
    <client-info>
      <mplane-ipv4-info>
        <mplane-ipv4>192.168.49.88</mplane-ipv4>
        <port>4334</port>
      </mplane-ipv4-info>
    </client-info>
  </m-plane-sub-interfaces>
</m-plane-interfaces>
</mplane-info>
<processing-elements xmlns="urn:o-ran:processing-element:1.0">
<maximum-number-of-transport-flows>4</maximum-number-of-transport-flows>
</processing-elements>
<ald-ports-io xmlns="urn:o-ran:ald-port:1.0">
<over-current-supported>false</over-current-supported>
<ald-port>
  <name>PORT0</name>
  <port-id>0</port-id>
  <dc-control-support>false</dc-control-support>
  <dc-enabled-status>true</dc-enabled-status>
  <supported-connector>RS485_PORT</supported-connector>
</ald-port>
</ald-ports-io>
</ald-ports-io>
```

```
</ald-port>
</ald-ports-io>
<sync xmlns="urn:o-ran:sync:1.0">
  <ptp-config>
    <domain-number>24</domain-number>
    <accepted-clock-classes>
      <clock-classes>255</clock-classes>
    </accepted-clock-classes>
    <accepted-clock-classes>
      <clock-classes>248</clock-classes>
    </accepted-clock-classes>
    <accepted-clock-classes>
      <clock-classes>165</clock-classes>
    </accepted-clock-classes>
    <accepted-clock-classes>
      <clock-classes>160</clock-classes>
    </accepted-clock-classes>
    <accepted-clock-classes>
      <clock-classes>150</clock-classes>
    </accepted-clock-classes>
    <accepted-clock-classes>
      <clock-classes>140</clock-classes>
    </accepted-clock-classes>
    <accepted-clock-classes>
      <clock-classes>135</clock-classes>
    </accepted-clock-classes>
    <accepted-clock-classes>
      <clock-classes>7</clock-classes>
    </accepted-clock-classes>
    <accepted-clock-classes>
      <clock-classes>6</clock-classes>
    </accepted-clock-classes>
    <ptp-profile>G_8275_1</ptp-profile>
    <g-8275-1-config>
      <multicast-mac-address>FORWARDABLE</multicast-mac-address>
      <delay-asymmetry>0</delay-asymmetry>
    </g-8275-1-config>
    </ptp-config>
    <ptp-status>
      <reporting-period>10</reporting-period>
      <lock-state>UNLOCKED</lock-state>
      <clock-class>255</clock-class>
      <clock-identity>0x98AE71FFFE008AC2</clock-identity>
      <partial-timing-supported>false</partial-timing-supported>
      <sources>
        <local-port-number>0</local-port-number>
        <state>DISABLED</state>
        <two-step-flag>true</two-step-flag>
        <leap61>false</leap61>
```

```
<leap59>false</leap59>
<current-utc-offset-valid>false</current-utc-offset-valid>
<ptp-timescale>true</ptp-timescale>
<time-traceable>false</time-traceable>
<frequency-traceable>false</frequency-traceable>
<source-clock-identity>0x98AE71FFFE008AC2</source-clock-identity>
<source-port-number>0</source-port-number>
<current-utc-offset>37</current-utc-offset>
<priority1>128</priority1>
<clock-class>255</clock-class>
<clock-accuracy>254</clock-accuracy>
<offset-scaled-log-variance>65535</offset-scaled-log-variance>
<priority2>255</priority2>
<grandmaster-clock-identity>0x98AE71FFFE008AC2</grandmaster-clock-identity>
<steps-removed>0</steps-removed>
<time-source>160</time-source>
</sources>
</ptp-status>
<sync-config>
  <acceptance-list-of-ssm>PRC</acceptance-list-of-ssm>
  <acceptance-list-of-ssm>EEC1</acceptance-list-of-ssm>
  <acceptance-list-of-ssm>DNU</acceptance-list-of-ssm>
  <acceptance-list-of-ssm>NONE</acceptance-list-of-ssm>
  <ssm-timeout>5</ssm-timeout>
</sync-config>
<sync-status>
  <reporting-period>10</reporting-period>
  <lock-state>UNLOCKED</lock-state>
  <sources>
    <local-port-number>0</local-port-number>
    <state>DISABLED</state>
    <quality-level>0</quality-level>
  </sources>
</sync-status>
<sync-status>
  <sync-state>FREERUN</sync-state>
  <supported-reference-types>
    <item>PTP</item>
  </supported-reference-types>
  <supported-reference-types>
    <item>SYNCE</item>
  </supported-reference-types>
</sync-status>
<sync-capability>
  <sync-t-tsc>ENHANCED</sync-t-tsc>
</sync-capability>
</sync>
<module-capability xmlns="urn:o-ran:module-cap:1.0">
  <ru-capabilities>
```

```
<ru-supported-category>CAT_A</ru-supported-category>
<number-of-ru-ports>4</number-of-ru-ports>
<number-of-spatial-streams>4</number-of-spatial-streams>
<max-power-per-pa-antenna>43.0</max-power-per-pa-antenna>
<min-power-per-pa-antenna>43.0</min-power-per-pa-antenna>
<fronthaul-split-option>7</fronthaul-split-option>
<format-of-iq-sample>
<dynamic-compression-supported>>false</dynamic-compression-supported>
<realtime-variable-bit-width-supported>>false</realtime-variable-bit-width-supported>
<compression-method-supported>
<iq-bitwidth>9</iq-bitwidth>
<compression-type>STATIC</compression-type>
<bitwidth>9</bitwidth>
<exponent>4</exponent>
</compression-method-supported>
<compression-method-supported>
<iq-bitwidth>12</iq-bitwidth>
<compression-type>STATIC</compression-type>
<bitwidth>12</bitwidth>
<exponent>4</exponent>
</compression-method-supported>
<compression-method-supported>
<iq-bitwidth>16</iq-bitwidth>
</compression-method-supported>
<variable-bit-width-per-channel-supported>>false</variable-bit-width-per-channel-supported>
<syminc-supported>>false</syminc-supported>
</format-of-iq-sample>
<energy-saving-by-transmission-blanks>>false</energy-saving-by-transmission-blanks>
<dynamic-transport-delay-management-supported>>false</dynamic-transport-delay-management-supported>
</ru-capabilities>
<band-capabilities>
<band-number>1</band-number>
<max-supported-frequency-dl>2170000000</max-supported-frequency-dl>
<min-supported-frequency-dl>2110000000</min-supported-frequency-dl>
<max-supported-bandwidth-dl>20000000</max-supported-bandwidth-dl>
<max-num-carriers-dl>2</max-num-carriers-dl>
<max-carrier-bandwidth-dl>20000000</max-carrier-bandwidth-dl>
<min-carrier-bandwidth-dl>1400000</min-carrier-bandwidth-dl>
<max-supported-frequency-ul>1980000000</max-supported-frequency-ul>
<min-supported-frequency-ul>1920000000</min-supported-frequency-ul>
<max-supported-bandwidth-ul>20000000</max-supported-bandwidth-ul>
<max-num-carriers-ul>2</max-num-carriers-ul>
<max-carrier-bandwidth-ul>20000000</max-carrier-bandwidth-ul>
<min-carrier-bandwidth-ul>1400000</min-carrier-bandwidth-ul>
<max-num-component-carriers>2</max-num-component-carriers>
<max-num-bands>1</max-num-bands>
<max-num-sectors>1</max-num-sectors>
<max-power-per-antenna>43.0</max-power-per-antenna>
<min-power-per-antenna>43.0</min-power-per-antenna>
```

```
</band-capabilities>
</module-capability>
<operational-info xmlns="urn:o-ran:operations:1.0">
  <clock>
    <timezone-utc-offset>530</timezone-utc-offset>
    <timezone-name>Asia/Kolkata</timezone-name>
  </clock>
  <re-call-home-no-ssh-timer>60</re-call-home-no-ssh-timer>
  <declarations>
    <ru-instance-id>RUGS_RU_MODEL_2020_VVDN_RU_01</ru-instance-id>
    <supported-mplane-version>2.0.0</supported-mplane-version>
    <supported-cusplane-version>2.0.0</supported-cusplane-version>
    <supported-header-mechanism>
      <protocol>ECPRI</protocol>
      <protocol-version>1.0</protocol-version>
    </supported-header-mechanism>
  </declarations>
  <operational-state>
    <restart-cause>POWER-ON</restart-cause>
    <restart-datetime>2103-10-30T08:52:22+08:50</restart-datetime>
  </operational-state>
</operational-info>
<user-plane-configuration xmlns="urn:o-ran:uplane-conf:1.0">
  <tx-arrays>
    <name>slltx-endpoint0</name>
    <number-of-rows>1</number-of-rows>
    <number-of-columns>1</number-of-columns>
    <number-of-array-layers>1</number-of-array-layers>
    <horizontal-spacing>1.0</horizontal-spacing>
    <vertical-spacing>1.0</vertical-spacing>
    <normal-vector-direction>
      <azimuth-angle>1.0</azimuth-angle>
      <zenith-angle>1.0</zenith-angle>
    </normal-vector-direction>
    <leftmost-bottom-array-element-position>
      <x>1.0</x>
      <y>1.0</y>
      <z>1.0</z>
    </leftmost-bottom-array-element-position>
    <band-number>28</band-number>
    <capabilities>
      <max-supported-frequency-dl>803000000</max-supported-frequency-dl>
    </capabilities>
    <capabilities>
      <min-supported-frequency-dl>758000000</min-supported-frequency-dl>
    </capabilities>
    <capabilities>
      <max-supported-bandwidth-dl>20000000</max-supported-bandwidth-dl>
    </capabilities>
```

```
<capabilities>
  <max-num-carriers-dl>2</max-num-carriers-dl>
</capabilities>
<capabilities>
  <max-carrier-bandwidth-dl>20000000</max-carrier-bandwidth-dl>
</capabilities>
<capabilities>
  <min-carrier-bandwidth-dl>1400000</min-carrier-bandwidth-dl>
</capabilities>
</tx-arrays>
<tx-arrays>
  <name>slltx-endpoint1</name>
  <number-of-rows>1</number-of-rows>
  <number-of-columns>1</number-of-columns>
  <number-of-array-layers>1</number-of-array-layers>
  <horizontal-spacing>1.0</horizontal-spacing>
  <vertical-spacing>1.0</vertical-spacing>
  <normal-vector-direction>
    <azimuth-angle>1.0</azimuth-angle>
    <zenith-angle>1.0</zenith-angle>
  </normal-vector-direction>
  <leftmost-bottom-array-element-position>
    <x>1.0</x>
    <y>1.0</y>
    <z>1.0</z>
  </leftmost-bottom-array-element-position>
  <band-number>28</band-number>
  <capabilities>
    <max-supported-frequency-dl>803000000</max-supported-frequency-dl>
  </capabilities>
  <capabilities>
    <min-supported-frequency-dl>758000000</min-supported-frequency-dl>
  </capabilities>
  <capabilities>
    <max-supported-bandwidth-dl>20000000</max-supported-bandwidth-dl>
  </capabilities>
  <capabilities>
    <max-num-carriers-dl>2</max-num-carriers-dl>
  </capabilities>
  <capabilities>
    <max-carrier-bandwidth-dl>20000000</max-carrier-bandwidth-dl>
  </capabilities>
  <capabilities>
    <min-carrier-bandwidth-dl>1400000</min-carrier-bandwidth-dl>
  </capabilities>
</tx-arrays>
<tx-arrays>
  <name>slltx-endpoint2</name>
  <number-of-rows>1</number-of-rows>
```

```
<number-of-columns>1</number-of-columns>
<number-of-array-layers>1</number-of-array-layers>
<horizontal-spacing>1.0</horizontal-spacing>
<vertical-spacing>1.0</vertical-spacing>
<normal-vector-direction>
  <azimuth-angle>1.0</azimuth-angle>
  <zenith-angle>1.0</zenith-angle>
</normal-vector-direction>
<leftmost-bottom-array-element-position>
  <x>1.0</x>
  <y>1.0</y>
  <z>1.0</z>
</leftmost-bottom-array-element-position>
<band-number>28</band-number>
<capabilities>
  <max-supported-frequency-dl>803000000</max-supported-frequency-dl>
</capabilities>
<capabilities>
  <min-supported-frequency-dl>758000000</min-supported-frequency-dl>
</capabilities>
<capabilities>
  <max-supported-bandwidth-dl>20000000</max-supported-bandwidth-dl>
</capabilities>
<capabilities>
  <max-num-carriers-dl>2</max-num-carriers-dl>
</capabilities>
<capabilities>
  <max-carrier-bandwidth-dl>20000000</max-carrier-bandwidth-dl>
</capabilities>
<capabilities>
  <min-carrier-bandwidth-dl>1400000</min-carrier-bandwidth-dl>
</capabilities>
</tx-arrays>
<tx-arrays>
  <name>sltx-endpoint3</name>
  <number-of-rows>1</number-of-rows>
  <number-of-columns>1</number-of-columns>
  <number-of-array-layers>1</number-of-array-layers>
  <horizontal-spacing>1.0</horizontal-spacing>
  <vertical-spacing>1.0</vertical-spacing>
  <normal-vector-direction>
    <azimuth-angle>1.0</azimuth-angle>
    <zenith-angle>1.0</zenith-angle>
  </normal-vector-direction>
  <leftmost-bottom-array-element-position>
    <x>1.0</x>
    <y>1.0</y>
    <z>1.0</z>
  </leftmost-bottom-array-element-position>
```



```
<band-number>28</band-number>
<capabilities>
  <max-supported-frequency-dl>803000000</max-supported-frequency-dl>
</capabilities>
<capabilities>
  <min-supported-frequency-dl>758000000</min-supported-frequency-dl>
</capabilities>
<capabilities>
  <max-supported-bandwidth-dl>20000000</max-supported-bandwidth-dl>
</capabilities>
<capabilities>
  <max-num-carriers-dl>2</max-num-carriers-dl>
</capabilities>
<capabilities>
  <max-carrier-bandwidth-dl>20000000</max-carrier-bandwidth-dl>
</capabilities>
<capabilities>
  <min-carrier-bandwidth-dl>1400000</min-carrier-bandwidth-dl>
</capabilities>
</tx-arrays>
<rx-arrays>
  <name>sllrx-endpoint0</name>
  <number-of-rows>1</number-of-rows>
  <number-of-columns>1</number-of-columns>
  <number-of-array-layers>1</number-of-array-layers>
  <horizontal-spacing>1.0</horizontal-spacing>
  <vertical-spacing>1.0</vertical-spacing>
  <normal-vector-direction>
    <azimuth-angle>1.0</azimuth-angle>
    <zenith-angle>1.0</zenith-angle>
  </normal-vector-direction>
  <leftmost-bottom-array-element-position>
    <x>1.0</x>
    <y>1.0</y>
    <z>1.0</z>
  </leftmost-bottom-array-element-position>
  <band-number>28</band-number>
  <capabilities>
    <max-supported-frequency-ul>748000000</max-supported-frequency-ul>
  </capabilities>
  <capabilities>
    <min-supported-frequency-ul>703000000</min-supported-frequency-ul>
  </capabilities>
  <capabilities>
    <max-supported-bandwidth-ul>20000000</max-supported-bandwidth-ul>
  </capabilities>
  <capabilities>
    <max-num-carriers-ul>2</max-num-carriers-ul>
  </capabilities>
```

```
<capabilities>
  <max-carrier-bandwidth-ul>20000000</max-carrier-bandwidth-ul>
</capabilities>
<capabilities>
  <min-carrier-bandwidth-ul>1400000</min-carrier-bandwidth-ul>
</capabilities>
</rx-arrays>
<rx-arrays>
  <name>sllrx-endpoint1</name>
  <number-of-rows>1</number-of-rows>
  <number-of-columns>1</number-of-columns>
  <number-of-array-layers>1</number-of-array-layers>
  <horizontal-spacing>1.0</horizontal-spacing>
  <vertical-spacing>1.0</vertical-spacing>
  <normal-vector-direction>
    <azimuth-angle>1.0</azimuth-angle>
    <zenith-angle>1.0</zenith-angle>
  </normal-vector-direction>
  <leftmost-bottom-array-element-position>
    <x>1.0</x>
    <y>1.0</y>
    <z>1.0</z>
  </leftmost-bottom-array-element-position>
  <band-number>28</band-number>
  <capabilities>
    <max-supported-frequency-ul>748000000</max-supported-frequency-ul>
  </capabilities>
  <capabilities>
    <min-supported-frequency-ul>703000000</min-supported-frequency-ul>
  </capabilities>
  <capabilities>
    <max-supported-bandwidth-ul>20000000</max-supported-bandwidth-ul>
  </capabilities>
  <capabilities>
    <max-num-carriers-ul>2</max-num-carriers-ul>
  </capabilities>
  <capabilities>
    <max-carrier-bandwidth-ul>20000000</max-carrier-bandwidth-ul>
  </capabilities>
  <capabilities>
    <min-carrier-bandwidth-ul>1400000</min-carrier-bandwidth-ul>
  </capabilities>
</rx-arrays>
<rx-arrays>
  <name>sllrx-endpoint2</name>
  <number-of-rows>1</number-of-rows>
  <number-of-columns>1</number-of-columns>
  <number-of-array-layers>1</number-of-array-layers>
  <horizontal-spacing>1.0</horizontal-spacing>
```

```
<vertical-spacing>1.0</vertical-spacing>
<normal-vector-direction>
  <azimuth-angle>1.0</azimuth-angle>
  <zenith-angle>1.0</zenith-angle>
</normal-vector-direction>
<leftmost-bottom-array-element-position>
  <x>1.0</x>
  <y>1.0</y>
  <z>1.0</z>
</leftmost-bottom-array-element-position>
<band-number>28</band-number>
<capabilities>
  <max-supported-frequency-ul>748000000</max-supported-frequency-ul>
</capabilities>
<capabilities>
  <min-supported-frequency-ul>703000000</min-supported-frequency-ul>
</capabilities>
<capabilities>
  <max-supported-bandwidth-ul>20000000</max-supported-bandwidth-ul>
</capabilities>
<capabilities>
  <max-num-carriers-ul>2</max-num-carriers-ul>
</capabilities>
<capabilities>
  <max-carrier-bandwidth-ul>20000000</max-carrier-bandwidth-ul>
</capabilities>
<capabilities>
  <min-carrier-bandwidth-ul>1400000</min-carrier-bandwidth-ul>
</capabilities>
</rx-arrays>
<rx-arrays>
  <name>sllrx-endpoint3</name>
  <number-of-rows>1</number-of-rows>
  <number-of-columns>1</number-of-columns>
  <number-of-array-layers>1</number-of-array-layers>
  <horizontal-spacing>1.0</horizontal-spacing>
  <vertical-spacing>1.0</vertical-spacing>
  <normal-vector-direction>
    <azimuth-angle>1.0</azimuth-angle>
    <zenith-angle>1.0</zenith-angle>
  </normal-vector-direction>
  <leftmost-bottom-array-element-position>
    <x>1.0</x>
    <y>1.0</y>
    <z>1.0</z>
  </leftmost-bottom-array-element-position>
  <band-number>28</band-number>
  <capabilities>
    <max-supported-frequency-ul>748000000</max-supported-frequency-ul>
```

```
</capabilities>
<capabilities>
  <min-supported-frequency-ul>703000000</min-supported-frequency-ul>
</capabilities>
<capabilities>
  <max-supported-bandwidth-ul>20000000</max-supported-bandwidth-ul>
</capabilities>
<capabilities>
  <max-num-carriers-ul>2</max-num-carriers-ul>
</capabilities>
<capabilities>
  <max-carrier-bandwidth-ul>20000000</max-carrier-bandwidth-ul>
</capabilities>
<capabilities>
  <min-carrier-bandwidth-ul>1400000</min-carrier-bandwidth-ul>
</capabilities>
</rx-arrays>
<relations>
  <entity>0</entity>
  <array1>
    <tx-array-name>slltx-endpoint0</tx-array-name>
  </array1>
  <array2>
    <rx-array-name>sllrx-endpoint0</rx-array-name>
  </array2>
</types>
<types>
  <relation-type>COALLOCATED</relation-type>
  <pairs>
    <element-array1>1</element-array1>
    <element-array2>0</element-array2>
  </pairs>
</types>
</relations>
<relations>
  <entity>1</entity>
  <array1>
    <tx-array-name>slltx-endpoint1</tx-array-name>
  </array1>
  <array2>
    <rx-array-name>sllrx-endpoint1</rx-array-name>
  </array2>
</types>
<types>
  <relation-type>COALLOCATED</relation-type>
  <pairs>
    <element-array1>1</element-array1>
    <element-array2>1</element-array2>
  </pairs>
```

```
</types>
</relations>
<relations>
  <entity>2</entity>
  <array1>
    <tx-array-name>slltx-endpoint2</tx-array-name>
  </array1>
  <array2>
    <rx-array-name>sllrx-endpoint2</rx-array-name>
  </array2>
</types>
<types>
  <relation-type>COALLOCATED</relation-type>
  <pairs>
    <element-array1>1</element-array1>
    <element-array2>2</element-array2>
  </pairs>
</types>
</relations>
<relations>
  <entity>3</entity>
  <array1>
    <tx-array-name>slltx-endpoint3</tx-array-name>
  </array1>
  <array2>
    <rx-array-name>sllrx-endpoint3</rx-array-name>
  </array2>
</types>
<types>
  <relation-type>COALLOCATED</relation-type>
  <pairs>
    <element-array1>1</element-array1>
    <element-array2>3</element-array2>
  </pairs>
</types>
</relations>
<endpoint-types>
  <id>1</id>
  <supported-section-types>
    <section-type>1</section-type>
  </supported-section-types>
  <supported-section-types>
    <section-type>3</section-type>
  </supported-section-types>
  <supported-frame-structures>193</supported-frame-structures>
  <managed-delay-support>MANAGED</managed-delay-support>
  <multiple-numerology-supported>false</multiple-numerology-supported>
  <max-sections-per-symbol>46</max-sections-per-symbol>
  <max-sections-per-slot>644</max-sections-per-slot>
```

```
<max-prb-per-symbol>273</max-prb-per-symbol>
<max-numerologies-per-symbol>1</max-numerologies-per-symbol>
</endpoint-types>
<static-low-level-tx-endpoints>
  <name>slltx-endpoint0</name>
  <array>slltx-endpoint0</array>
  <endpoint-type>1</endpoint-type>
  <capacity-sharing-groups>1</capacity-sharing-groups>
</static-low-level-tx-endpoints>
<static-low-level-tx-endpoints>
  <name>slltx-endpoint1</name>
  <array>slltx-endpoint1</array>
  <endpoint-type>1</endpoint-type>
  <capacity-sharing-groups>1</capacity-sharing-groups>
</static-low-level-tx-endpoints>
<static-low-level-tx-endpoints>
  <name>slltx-endpoint2</name>
  <array>slltx-endpoint2</array>
  <endpoint-type>1</endpoint-type>
  <capacity-sharing-groups>1</capacity-sharing-groups>
</static-low-level-tx-endpoints>
<static-low-level-tx-endpoints>
  <name>slltx-endpoint3</name>
  <array>slltx-endpoint3</array>
  <endpoint-type>1</endpoint-type>
  <capacity-sharing-groups>1</capacity-sharing-groups>
</static-low-level-tx-endpoints>
<static-low-level-rx-endpoints>
  <name>sllrx-endpoint0</name>
  <array>sllrx-endpoint0</array>
  <endpoint-type>1</endpoint-type>
  <capacity-sharing-groups>1</capacity-sharing-groups>
</static-low-level-rx-endpoints>
<static-low-level-rx-endpoints>
  <name>sllrx-endpoint1</name>
  <array>sllrx-endpoint1</array>
  <endpoint-type>1</endpoint-type>
  <capacity-sharing-groups>1</capacity-sharing-groups>
</static-low-level-rx-endpoints>
<static-low-level-rx-endpoints>
  <name>sllrx-endpoint2</name>
  <array>sllrx-endpoint2</array>
  <endpoint-type>1</endpoint-type>
  <capacity-sharing-groups>1</capacity-sharing-groups>
</static-low-level-rx-endpoints>
<static-low-level-rx-endpoints>
  <name>sllrx-endpoint3</name>
  <array>sllrx-endpoint3</array>
  <endpoint-type>1</endpoint-type>
```

```
<capacity-sharing-groups>1</capacity-sharing-groups>
</static-low-level-rx-endpoints>
<endpoint-capacity-sharing-groups/>
<endpoint-capacity-sharing-groups>
<id>1</id>
<max-managed-delay-endpoints>4</max-managed-delay-endpoints>
<max-non-managed-delay-endpoints>0</max-non-managed-delay-endpoints>
<max-endpoints>4</max-endpoints>
<max-sections-per-symbol>46</max-sections-per-symbol>
<max-sections-per-slot>644</max-sections-per-slot>
<max-prb-per-symbol>273</max-prb-per-symbol>
<max-numerologies-per-symbol>1</max-numerologies-per-symbol>
</endpoint-capacity-sharing-groups>
</user-plane-configuration>
<history xmlns="urn:notification_history">
<module-notification>
<module-name>Module or antenna line</module-name>
<notif-error>Synchronization Error</notif-error>
<alert>critical</alert>
<epochtime>4223145800</epochtime>
</module-notification>
</history>
<yang-library xmlns="urn:ietf:params:xml:ns:yang:ietf-yang-library">
<module-set>
<name>complete</name>
<import-only-module>
<name>ietf-yang-metadata</name>
<revision>2016-08-05</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-yang-metadata</namespace>
</import-only-module>
<module>
<name>yang</name>
<revision>2017-02-20</revision>
<namespace>urn:ietf:params:xml:ns:yang:1</namespace>
</module>
<import-only-module>
<name>ietf-inet-types</name>
<revision>2013-07-15</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-inet-types</namespace>
<location>file:///etc/sysrepo/yang/yang_models/imported/ietf/ietf-inet-types.yang</location>
</import-only-module>
<import-only-module>
<name>ietf-yang-types</name>
<revision>2013-07-15</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-yang-types</namespace>
<location>file:///etc/sysrepo/yang/yang_models/imported/ietf/ietf-yang-types.yang</location>
</import-only-module>
<module>
<name>sysrepo</name>
```

```
<revision>2021-01-18</revision>
<namespace>http://www.sysrepo.org/yang/sysrepo</namespace>
</module>
<module>
<name>ietf-datastores</name>
<revision>2018-02-14</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-datastores</namespace>
<location>file:///etc/sysrepo/yang/ietf-datastores@2018-02-14.yang</location>
</module>
<module>
<name>ietf-yang-library</name>
<revision>2019-01-04</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-yang-library</namespace>
<location>file:///etc/sysrepo/yang/ietf-yang-library@2019-01-04.yang</location>
</module>
<module>
<name>sysrepo-monitoring</name>
<revision>2021-01-15</revision>
<namespace>http://www.sysrepo.org/yang/sysrepo-monitoring</namespace>
<location>file:///etc/sysrepo/yang/sysrepo-monitoring@2021-01-15.yang</location>
</module>
<module>
<name>sysrepo-plugind</name>
<revision>2020-12-10</revision>
<namespace>urn:sysrepo:plugind</namespace>
<location>file:///etc/sysrepo/yang/sysrepo-plugind@2020-12-10.yang</location>
</module>
<module>
<name>ietf-netconf-acm</name>
<revision>2018-02-14</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-acm</namespace>
<location>file:///etc/sysrepo/yang/ietf-netconf-acm@2018-02-14.yang</location>
</module>
<module>
<name>ietf-netconf</name>
<revision>2013-09-29</revision>
<namespace>urn:ietf:params:xml:ns:netconf:base:1.0</namespace>
<location>file:///etc/sysrepo/yang/ietf-netconf@2013-09-29.yang</location>
<feature>writable-running</feature>
<feature>candidate</feature>
<feature>rollback-on-error</feature>
<feature>validate</feature>
<feature>startup</feature>
<feature>url</feature>
<feature>xpath</feature>
</module>
<module>
<name>ietf-netconf-with-defaults</name>
<revision>2011-06-01</revision>
```



```
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-with-defaults</namespace>
<location>file:///etc/sysrepo/yang/ietf-netconf-with-defaults@2011-06-01.yang</location>
</module>
<module>
<name>ietf-netconf-notifications</name>
<revision>2012-02-06</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-notifications</namespace>
<location>file:///etc/sysrepo/yang/ietf-netconf-notifications@2012-02-06.yang</location>
</module>
<module>
<name>ietf-origin</name>
<revision>2018-02-14</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-origin</namespace>
<location>file:///etc/sysrepo/yang/ietf-origin@2018-02-14.yang</location>
</module>
<module>
<name>ietf-netconf-monitoring</name>
<revision>2010-10-04</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-monitoring</namespace>
<location>file:///etc/sysrepo/yang/ietf-netconf-monitoring@2010-10-04.yang</location>
</module>
<module>
<name>ietf-netconf-nmda</name>
<revision>2019-01-07</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-nmda</namespace>
<location>file:///etc/sysrepo/yang/ietf-netconf-nmda@2019-01-07.yang</location>
<feature>origin</feature>
<feature>with-defaults</feature>
</module>
<module>
<name>notifications</name>
<revision>2008-07-14</revision>
<namespace>urn:ietf:params:xml:ns:netconf:notification:1.0</namespace>
<location>file:///etc/sysrepo/yang/notifications@2008-07-14.yang</location>
</module>
<module>
<name>nc-notifications</name>
<revision>2008-07-14</revision>
<namespace>urn:ietf:params:xml:ns:netmod:notification</namespace>
<location>file:///etc/sysrepo/yang/nc-notifications@2008-07-14.yang</location>
</module>
<module>
<name>ietf-x509-cert-to-name</name>
<revision>2014-12-10</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-x509-cert-to-name</namespace>
<location>file:///etc/sysrepo/yang/ietf-x509-cert-to-name@2014-12-10.yang</location>
</module>
<module>
<name>ietf-crypto-types</name>
```

```
<revision>2019-07-02</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-crypto-types</namespace>
<location>file:///etc/sysrepo/yang/ietf-crypto-types@2019-07-02.yang</location>
</module>
<module>
<name>ietf-keystore</name>
<revision>2019-07-02</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-keystore</namespace>
<location>file:///etc/sysrepo/yang/ietf-keystore@2019-07-02.yang</location>
<feature>keystore-supported</feature>
</module>
<module>
<name>ietf-truststore</name>
<revision>2019-07-02</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-truststore</namespace>
<location>file:///etc/sysrepo/yang/ietf-truststore@2019-07-02.yang</location>
<feature>truststore-supported</feature>
<feature>x509-certificates</feature>
</module>
<module>
<name>ietf-tcp-common</name>
<revision>2019-07-02</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-common</namespace>
<location>file:///etc/sysrepo/yang/ietf-tcp-common@2019-07-02.yang</location>
<feature>keepalives-supported</feature>
</module>
<import-only-module>
<name>ietf-ssh-common</name>
<revision>2019-07-02</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-ssh-common</namespace>
<location>file:///etc/sysrepo/yang/ietf-ssh-common@2019-07-02.yang</location>
</import-only-module>
<import-only-module>
<name>iana-crypt-hash</name>
<revision>2014-08-06</revision>
<namespace>urn:ietf:params:xml:ns:yang:iana-crypt-hash</namespace>
<location>file:///etc/sysrepo/yang/iana-crypt-hash@2014-08-06.yang</location>
</import-only-module>
<module>
<name>ietf-ssh-server</name>
<revision>2019-07-02</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-ssh-server</namespace>
<location>file:///etc/sysrepo/yang/ietf-ssh-server@2019-07-02.yang</location>
<feature>local-client-auth-supported</feature>
</module>
<import-only-module>
<name>ietf-tls-common</name>
<revision>2019-07-02</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-tls-common</namespace>
```

```
<location>file:///etc/sysrepo/yang/ietf-tls-common@2019-07-02.yang</location>
</import-only-module>
<module>
  <name>ietf-tls-server</name>
  <revision>2019-07-02</revision>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tls-server</namespace>
  <location>file:///etc/sysrepo/yang/ietf-tls-server@2019-07-02.yang</location>
  <feature>local-client-auth-supported</feature>
</module>
<import-only-module>
  <name>ietf-tcp-client</name>
  <revision>2019-07-02</revision>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-client</namespace>
  <location>file:///etc/sysrepo/yang/ietf-tcp-client@2019-07-02.yang</location>
</import-only-module>
<import-only-module>
  <name>ietf-tcp-server</name>
  <revision>2019-07-02</revision>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-server</namespace>
  <location>file:///etc/sysrepo/yang/ietf-tcp-server@2019-07-02.yang</location>
</import-only-module>
<module>
  <name>ietf-netconf-server</name>
  <revision>2019-07-02</revision>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-server</namespace>
  <location>file:///etc/sysrepo/yang/ietf-netconf-server@2019-07-02.yang</location>
  <feature>ssh-listen</feature>
  <feature>tls-listen</feature>
  <feature>ssh-call-home</feature>
  <feature>tls-call-home</feature>
</module>
<module>
  <name>vvdn_mcel-wdm</name>
  <revision>2022-05-03</revision>
  <namespace>urn:vvdn_mcel:wdm:1.1</namespace>
  <location>file:///etc/sysrepo/yang/vvdn_mcel-wdm@2022-05-03.yang</location>
</module>
<module>
  <name>vvdn_mcel-opm</name>
  <revision>2020-11-08</revision>
  <namespace>urn:vvdn_mcel-opm:1.1</namespace>
  <location>file:///etc/sysrepo/yang/vvdn_mcel-opm@2020-11-08.yang</location>
</module>
<module>
  <name>notification_history</name>
  <namespace>urn:notification_history</namespace>
  <location>file:///etc/sysrepo/yang/notification_history.yang</location>
</module>
</module>
```

```
<name>iana-hardware</name>
<revision>2018-03-13</revision>
<namespace>urn:ietf:params:xml:ns:yang:iana-hardware</namespace>
<location>file:///etc/sysrepo/yang/iana-hardware@2018-03-13.yang</location>
</module>
<module>
<name>ietf-hardware</name>
<revision>2018-03-13</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-hardware</namespace>
<location>file:///etc/sysrepo/yang/ietf-hardware@2018-03-13.yang</location>
<feature>hardware-state</feature>
</module>
<module>
<name>ietf-interfaces</name>
<revision>2018-02-20</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-interfaces</namespace>
<location>file:///etc/sysrepo/yang/ietf-interfaces@2018-02-20.yang</location>
</module>
<module>
<name>iana-if-type</name>
<revision>2017-01-19</revision>
<namespace>urn:ietf:params:xml:ns:yang:iana-if-type</namespace>
<location>file:///etc/sysrepo/yang/iana-if-type@2017-01-19.yang</location>
</module>
<module>
<name>ietf-dhcpv6-types</name>
<revision>2018-01-30</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-dhcpv6-types</namespace>
<location>file:///etc/sysrepo/yang/ietf-dhcpv6-types@2018-01-30.yang</location>
</module>
<module>
<name>ietf-ip</name>
<revision>2018-02-22</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-ip</namespace>
<location>file:///etc/sysrepo/yang/ietf-ip@2018-02-22.yang</location>
<feature>ipv4-non-contiguous-netmasks</feature>
</module>
<module>
<name>o-ran-dhcp</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:dhcp:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-dhcp@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-interfaces</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:interfaces:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-interfaces@2019-07-03.yang</location>
</module>
```

```
<module>
<name>o-ran-mplane-int</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:mplane-interfaces:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-mplane-int@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-transceiver</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:transceiver:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-transceiver@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-processing-element</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:processing-element:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-processing-element@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-ald-port</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:ald-port:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-ald-port@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-supervision</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:supervision:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-supervision@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-hardware</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:hardware:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-hardware@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-fm</name>
<revision>2019-02-04</revision>
<namespace>urn:o-ran:fm:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-fm@2019-02-04.yang</location>
</module>
<module>
<name>o-ran-usermgmt</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:user-mgmt:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-usermgmt@2019-07-03.yang</location>
</module>
<module>
```

```
<name>o-ran-sync</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:sync:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-sync@2019-07-03.yang</location>
<feature>GNSS</feature>
</module>
<module>
<name>o-ran-compression-factors</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:compression-factors:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-compression-factors@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-module-cap</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:module-cap:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-module-cap@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-delay-management</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:delay:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-delay-management@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-operations</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:operations:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-operations@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-uplane-conf</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:uplane-conf:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-uplane-conf@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-file-management</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:file-management:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-file-management@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-software-management</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:software-management:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-software-management@2019-07-03.yang</location>
</module>
</module>
```

```
<name>o-ran-performance-management</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:performance-management:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-performance-management@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-ald</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:ald:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-ald@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-trace</name>
<revision>2019-07-03</revision>
<namespace>urn:o-ran:trace:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-trace@2019-07-03.yang</location>
</module>
<module>
<name>o-ran-troubleshooting</name>
<revision>2019-02-04</revision>
<namespace>urn:o-ran:troubleshooting:1.0</namespace>
<location>file:///etc/sysrepo/yang/o-ran-troubleshooting@2019-02-04.yang</location>
</module>
</module-set>
<schema>
<name>complete</name>
<module-set>complete</module-set>
</schema>
<content-id>63</content-id>
<datastore>
<name xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</name>
<schema>complete</schema>
</datastore>
<datastore>
<name xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:candidate</name>
<schema>complete</schema>
</datastore>
<datastore>
<name xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:startup</name>
<schema>complete</schema>
</datastore>
<datastore>
<name xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</name>
<schema>complete</schema>
</datastore>
</yang-library>
<modules-state xmlns="urn:ietf:params:xml:ns:yang:ietf-yang-library">
<module>
<name>ietf-yang-metadata</name>
```

```
<revision>2016-08-05</revision>
<namespace>urn:ietf:params:xml:ns:yang:ietf-yang-metadata</namespace>
<conformance-type>import</conformance-type>
</module>
<module>
  <name>yang</name>
  <revision>2017-02-20</revision>
  <namespace>urn:ietf:params:xml:ns:yang:1</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-inet-types</name>
  <revision>2013-07-15</revision>
  <schema>file:///etc/sysrepo/yang/yang_models/imported/ietf/ietf-inet-types.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-inet-types</namespace>
  <conformance-type>import</conformance-type>
</module>
<module>
  <name>ietf-yang-types</name>
  <revision>2013-07-15</revision>
  <schema>file:///etc/sysrepo/yang/yang_models/imported/ietf/ietf-yang-types.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-yang-types</namespace>
  <conformance-type>import</conformance-type>
</module>
<module>
  <name>sysrepo</name>
  <revision>2021-01-18</revision>
  <namespace>http://www.sysrepo.org/yang/sysrepo</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-datastores</name>
  <revision>2018-02-14</revision>
  <schema>file:///etc/sysrepo/yang/ietf-datastores@2018-02-14.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-datastores</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-yang-library</name>
  <revision>2019-01-04</revision>
  <schema>file:///etc/sysrepo/yang/ietf-yang-library@2019-01-04.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-yang-library</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>sysrepo-monitoring</name>
  <revision>2021-01-15</revision>
  <schema>file:///etc/sysrepo/yang/sysrepo-monitoring@2021-01-15.yang</schema>
  <namespace>http://www.sysrepo.org/yang/sysrepo-monitoring</namespace>
```



```
<conformance-type>implement</conformance-type>
</module>
<module>
  <name>sysrepo-pluginind</name>
  <revision>2020-12-10</revision>
  <schema>file:///etc/sysrepo/yang/sysrepo-pluginind@2020-12-10.yang</schema>
  <namespace>urn:sysrepo:pluginind</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-netconf-acm</name>
  <revision>2018-02-14</revision>
  <schema>file:///etc/sysrepo/yang/ietf-netconf-acm@2018-02-14.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-acm</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-netconf</name>
  <revision>2013-09-29</revision>
  <schema>file:///etc/sysrepo/yang/ietf-netconf@2013-09-29.yang</schema>
  <namespace>urn:ietf:params:xml:ns:netconf:base:1.0</namespace>
  <feature>writable-running</feature>
  <feature>candidate</feature>
  <feature>rollback-on-error</feature>
  <feature>validate</feature>
  <feature>startup</feature>
  <feature>url</feature>
  <feature>xpath</feature>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-netconf-with-defaults</name>
  <revision>2011-06-01</revision>
  <schema>file:///etc/sysrepo/yang/ietf-netconf-with-defaults@2011-06-01.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-with-defaults</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-netconf-notifications</name>
  <revision>2012-02-06</revision>
  <schema>file:///etc/sysrepo/yang/ietf-netconf-notifications@2012-02-06.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-notifications</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-origin</name>
  <revision>2018-02-14</revision>
  <schema>file:///etc/sysrepo/yang/ietf-origin@2018-02-14.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-origin</namespace>
```

```
<conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-netconf-monitoring</name>
  <revision>2010-10-04</revision>
  <schema>file:///etc/sysrepo/yang/ietf-netconf-monitoring@2010-10-04.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-monitoring</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-netconf-nmda</name>
  <revision>2019-01-07</revision>
  <schema>file:///etc/sysrepo/yang/ietf-netconf-nmda@2019-01-07.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-nmda</namespace>
  <feature>origin</feature>
  <feature>with-defaults</feature>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>notifications</name>
  <revision>2008-07-14</revision>
  <schema>file:///etc/sysrepo/yang/notifications@2008-07-14.yang</schema>
  <namespace>urn:ietf:params:xml:ns:netconf:notification:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>nc-notifications</name>
  <revision>2008-07-14</revision>
  <schema>file:///etc/sysrepo/yang/nc-notifications@2008-07-14.yang</schema>
  <namespace>urn:ietf:params:xml:ns:netmod:notification</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-x509-cert-to-name</name>
  <revision>2014-12-10</revision>
  <schema>file:///etc/sysrepo/yang/ietf-x509-cert-to-name@2014-12-10.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-x509-cert-to-name</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-crypto-types</name>
  <revision>2019-07-02</revision>
  <schema>file:///etc/sysrepo/yang/ietf-crypto-types@2019-07-02.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-crypto-types</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-keystore</name>
  <revision>2019-07-02</revision>
```

```
<schema>file:///etc/sysrepo/yang/ietf-keystore@2019-07-02.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:ietf-keystore</namespace>
<feature>keystore-supported</feature>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>ietf-truststore</name>
<revision>2019-07-02</revision>
<schema>file:///etc/sysrepo/yang/ietf-truststore@2019-07-02.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:ietf-truststore</namespace>
<feature>truststore-supported</feature>
<feature>x509-certificates</feature>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>ietf-tcp-common</name>
<revision>2019-07-02</revision>
<schema>file:///etc/sysrepo/yang/ietf-tcp-common@2019-07-02.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-common</namespace>
<feature>keepalives-supported</feature>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>ietf-ssh-common</name>
<revision>2019-07-02</revision>
<schema>file:///etc/sysrepo/yang/ietf-ssh-common@2019-07-02.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:ietf-ssh-common</namespace>
<conformance-type>import</conformance-type>
</module>
<module>
<name>iana-crypt-hash</name>
<revision>2014-08-06</revision>
<schema>file:///etc/sysrepo/yang/iana-crypt-hash@2014-08-06.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:iana-crypt-hash</namespace>
<conformance-type>import</conformance-type>
</module>
<module>
<name>ietf-ssh-server</name>
<revision>2019-07-02</revision>
<schema>file:///etc/sysrepo/yang/ietf-ssh-server@2019-07-02.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:ietf-ssh-server</namespace>
<feature>local-client-auth-supported</feature>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>ietf-tls-common</name>
<revision>2019-07-02</revision>
<schema>file:///etc/sysrepo/yang/ietf-tls-common@2019-07-02.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:ietf-tls-common</namespace>
```

```
<conformance-type>import</conformance-type>
</module>
<module>
  <name>ietf-tls-server</name>
  <revision>2019-07-02</revision>
  <schema>file:///etc/sysrepo/yang/ietf-tls-server@2019-07-02.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tls-server</namespace>
  <feature>local-client-auth-supported</feature>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>ietf-tcp-client</name>
  <revision>2019-07-02</revision>
  <schema>file:///etc/sysrepo/yang/ietf-tcp-client@2019-07-02.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-client</namespace>
  <conformance-type>import</conformance-type>
</module>
<module>
  <name>ietf-tcp-server</name>
  <revision>2019-07-02</revision>
  <schema>file:///etc/sysrepo/yang/ietf-tcp-server@2019-07-02.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-server</namespace>
  <conformance-type>import</conformance-type>
</module>
<module>
  <name>ietf-netconf-server</name>
  <revision>2019-07-02</revision>
  <schema>file:///etc/sysrepo/yang/ietf-netconf-server@2019-07-02.yang</schema>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-server</namespace>
  <feature>ssh-listen</feature>
  <feature>tls-listen</feature>
  <feature>ssh-call-home</feature>
  <feature>tls-call-home</feature>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>vvdn_mcel-wdm</name>
  <revision>2022-05-03</revision>
  <schema>file:///etc/sysrepo/yang/vvdn_mcel-wdm@2022-05-03.yang</schema>
  <namespace>urn:vvdn_mcel:wdm:1.1</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>vvdn_mcel-opm</name>
  <revision>2020-11-08</revision>
  <schema>file:///etc/sysrepo/yang/vvdn_mcel-opm@2020-11-08.yang</schema>
  <namespace>urn:vvdn_mcel-opm:1.1</namespace>
  <conformance-type>implement</conformance-type>
</module>
```

```
<module>
<name>notification_history</name>
<revision/>
<schema>file:///etc/sysrepo/yang/notification_history.yang</schema>
<namespace>urn:notification_history</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>iana-hardware</name>
<revision>2018-03-13</revision>
<schema>file:///etc/sysrepo/yang/iana-hardware@2018-03-13.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:iana-hardware</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>ietf-hardware</name>
<revision>2018-03-13</revision>
<schema>file:///etc/sysrepo/yang/ietf-hardware@2018-03-13.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:ietf-hardware</namespace>
<feature>hardware-state</feature>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>ietf-interfaces</name>
<revision>2018-02-20</revision>
<schema>file:///etc/sysrepo/yang/ietf-interfaces@2018-02-20.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:ietf-interfaces</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>iana-if-type</name>
<revision>2017-01-19</revision>
<schema>file:///etc/sysrepo/yang/iana-if-type@2017-01-19.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:iana-if-type</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>ietf-dhcpv6-types</name>
<revision>2018-01-30</revision>
<schema>file:///etc/sysrepo/yang/ietf-dhcpv6-types@2018-01-30.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:ietf-dhcpv6-types</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>ietf-ip</name>
<revision>2018-02-22</revision>
<schema>file:///etc/sysrepo/yang/ietf-ip@2018-02-22.yang</schema>
<namespace>urn:ietf:params:xml:ns:yang:ietf-ip</namespace>
<feature>ipv4-non-contiguous-netmasks</feature>
```

```
<conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-dhcp</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-dhcp@2019-07-03.yang</schema>
  <namespace>urn:o-ran:dhcp:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-interfaces</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-interfaces@2019-07-03.yang</schema>
  <namespace>urn:o-ran:interfaces:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-mplane-int</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-mplane-int@2019-07-03.yang</schema>
  <namespace>urn:o-ran:mplane-interfaces:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-transceiver</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-transceiver@2019-07-03.yang</schema>
  <namespace>urn:o-ran:transceiver:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-processing-element</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-processing-element@2019-07-03.yang</schema>
  <namespace>urn:o-ran:processing-element:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-ald-port</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-ald-port@2019-07-03.yang</schema>
  <namespace>urn:o-ran:ald-port:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-supervision</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-supervision@2019-07-03.yang</schema>
  <namespace>urn:o-ran:supervision:1.0</namespace>
```

```
<conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-hardware</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-hardware@2019-07-03.yang</schema>
  <namespace>urn:o-ran:hardware:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-fm</name>
  <revision>2019-02-04</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-fm@2019-02-04.yang</schema>
  <namespace>urn:o-ran:fm:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-usermgmt</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-usermgmt@2019-07-03.yang</schema>
  <namespace>urn:o-ran:user-mgmt:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-sync</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-sync@2019-07-03.yang</schema>
  <namespace>urn:o-ran:sync:1.0</namespace>
  <feature>GNSS</feature>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-compression-factors</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-compression-factors@2019-07-03.yang</schema>
  <namespace>urn:o-ran:compression-factors:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-module-cap</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-module-cap@2019-07-03.yang</schema>
  <namespace>urn:o-ran:module-cap:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-delay-management</name>
  <revision>2019-07-03</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-delay-management@2019-07-03.yang</schema>
```

```
<namespace>urn:o-ran:delay:1.0</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>o-ran-operations</name>
<revision>2019-07-03</revision>
<schema>file:///etc/sysrepo/yang/o-ran-operations@2019-07-03.yang</schema>
<namespace>urn:o-ran:operations:1.0</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>o-ran-uplane-conf</name>
<revision>2019-07-03</revision>
<schema>file:///etc/sysrepo/yang/o-ran-uplane-conf@2019-07-03.yang</schema>
<namespace>urn:o-ran:uplane-conf:1.0</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>o-ran-file-management</name>
<revision>2019-07-03</revision>
<schema>file:///etc/sysrepo/yang/o-ran-file-management@2019-07-03.yang</schema>
<namespace>urn:o-ran:file-management:1.0</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>o-ran-software-management</name>
<revision>2019-07-03</revision>
<schema>file:///etc/sysrepo/yang/o-ran-software-management@2019-07-03.yang</schema>
<namespace>urn:o-ran:software-management:1.0</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>o-ran-performance-management</name>
<revision>2019-07-03</revision>
<schema>file:///etc/sysrepo/yang/o-ran-performance-management@2019-07-03.yang</schema>
<namespace>urn:o-ran:performance-management:1.0</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>o-ran-ald</name>
<revision>2019-07-03</revision>
<schema>file:///etc/sysrepo/yang/o-ran-ald@2019-07-03.yang</schema>
<namespace>urn:o-ran:ald:1.0</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
<name>o-ran-trace</name>
<revision>2019-07-03</revision>
<schema>file:///etc/sysrepo/yang/o-ran-trace@2019-07-03.yang</schema>
```



```
<namespace>urn:o-ran:trace:1.0</namespace>
<conformance-type>implement</conformance-type>
</module>
<module>
  <name>o-ran-troubleshooting</name>
  <revision>2019-02-04</revision>
  <schema>file:///etc/sysrepo/yang/o-ran-troubleshooting@2019-02-04.yang</schema>
  <namespace>urn:o-ran:troubleshooting:1.0</namespace>
  <conformance-type>implement</conformance-type>
</module>
<module-set-id>63</module-set-id>
</modules-state>
<sysrepo-state xmlns="http://www.sysrepo.org/yang/sysrepo-monitoring">
  <module>
    <name>yang</name>
  </module>
  <module>
    <name>ietf-datastores</name>
  </module>
  <module>
    <name>ietf-yang-library</name>
    <data-lock>
      <cid>1</cid>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
      <mode>read</mode>
    </data-lock>
    <data-lock>
      <cid>1</cid>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
      <mode>read</mode>
    </data-lock>
    <subscriptions>
      <notification-sub>1</notification-sub>
    </subscriptions>
  </module>
  <module>
    <name>sysrepo-monitoring</name>
    <data-lock>
      <cid>1</cid>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
      <mode>read</mode>
    </data-lock>
    <data-lock>
      <cid>1</cid>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
      <mode>read</mode>
    </data-lock>
  </module>
</module>
```

```
<name>sysrepo-plugind</name>
<data-lock>
  <cid>1</cid>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <mode>read</mode>
</data-lock>
<data-lock>
  <cid>1</cid>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
  <mode>read</mode>
</data-lock>
</module>
<module>
  <name>ietf-netconf-with-defaults</name>
</module>
<module>
  <name>ietf-netconf-notifications</name>
  <subscriptions>
    <notification-sub>1</notification-sub>
  </subscriptions>
</module>
<module>
  <name>ietf-origin</name>
</module>
<module>
  <name>ietf-netconf-acm</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <change-sub>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
      <xpath xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm"/>/nacm:nacm</xpath>
      <priority>0</priority>
    <cid>1</cid>
    </change-sub>
  </subscriptions>
  <change-sub>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <xpath xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm"/>/nacm:nacm/nacm:groups/nacm:group</xpath>
    <priority>0</priority>
    <cid>1</cid>
    </change-sub>
  </change-sub>
</module>
```

```
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm"/>/nacm:nacm/nacm:rule-list</xpath>
<priority>0</priority>
<cid>1</cid>
</change-sub>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm"/>/nacm:nacm/nacm:rule-list/nacm:rule</xpath>
<priority>0</priority>
<cid>1</cid>
</change-sub>
<operational-sub>
<xpath xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm"/>/nacm:nacm/nacm:denied-operations</xpath>
<cid>1</cid>
</operational-sub>
<operational-sub>
<xpath xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm"/>/nacm:nacm/nacm:denied-data-writes</xpath>
<cid>1</cid>
</operational-sub>
<operational-sub>
<xpath xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm"/>/nacm:nacm/nacm:denied-notifications</xpath>
<cid>1</cid>
</operational-sub>
</subscriptions>
</module>
<module>
<name>ietf-netconf</name>
</module>
<module>
<name>ietf-netconf-monitoring</name>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<mode>read</mode>
</data-lock>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
<subscriptions>
<operational-sub>
<xpath xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-monitoring"/>/nacm:netconf-state</xpath>
<cid>1</cid>
</operational-sub>
</subscriptions>
</module>
<module>
```

```
<name>ietf-netconf-nmda</name>
</module>
<module>
  <name>nc-notifications</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <operational-sub>
      <xpath xmlns:manageEvent="urn:ietf:params:xml:ns:netmod:notification">/manageEvent:netconf</xpath>
      <cid>1</cid>
    </operational-sub>
    <notification-sub>1</notification-sub>
  </subscriptions>
</module>
<module>
  <name>notifications</name>
</module>
<module>
  <name>ietf-x509-cert-to-name</name>
</module>
<module>
  <name>ietf-crypto-types</name>
</module>
<module>
  <name>ietf-keystore</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <change-sub>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
      <xpath xmlns:ks="urn:ietf:params:xml:ns:yang:ietf-keystore">/ks:keystore/ks:asymmetric-keys</xpath>
      <priority>0</priority>
    </change-sub>
  </subscriptions>
</module>
```

```
</change-sub>
<notification-sub>1</notification-sub>
</subscriptions>
</module>
<module>
  <name>ietf-truststore</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <change-sub>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
      <xpath xmlns:ts="urn:ietf:params:xml:ns:yang:ietf-truststore">/ts:truststore/ts:certificates</xpath>
      <priority>0</priority>
      <cid>1</cid>
    </change-sub>
    <notification-sub>1</notification-sub>
  </subscriptions>
</module>
<module>
  <name>ietf-tcp-common</name>
</module>
<module>
  <name>ietf-ssh-server</name>
</module>
<module>
  <name>ietf-tls-server</name>
</module>
<module>
  <name>ietf-netconf-server</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <change-sub>
```

```
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:listen/ncs:idle-timeout</xpath>
<priority>0</priority>
<cid>1</cid>
</change-sub>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:listen/ncs:endpoint/ncs:ssh</xpath>
<priority>0</priority>
<cid>1</cid>
</change-sub>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:listen/ncs:endpoint/ncs:ssh/ncs:tcp-server-parameters</xpath>
>
<priority>0</priority>
<cid>1</cid>
</change-sub>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:listen/ncs:endpoint/ncs:ssh/ncs:ssh-server-parameters/ncs:ser
ver-identity/ncs:host-key/ncs:public-key/ncs:keystore-reference</xpath>
<priority>0</priority>
<cid>1</cid>
</change-sub>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:listen/ncs:endpoint/ncs:ssh/ncs:ssh-server-parameters/ncs:cli
ent-authentication/ncs:supported-authentication-methods</xpath>
<priority>0</priority>
<cid>1</cid>
</change-sub>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:listen/ncs:endpoint/ncs:tls</xpath>
<priority>0</priority>
<cid>1</cid>
</change-sub>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:listen/ncs:endpoint/ncs:tls/ncs:tcp-server-parameters</xpath>
>
<priority>0</priority>
<cid>1</cid>
</change-sub>
```

```
<change-sub>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:listen/ncs:endpoint/ncs:tls/ncs:tls-server-parameters/ncs:server-identity/ncs:keystore-reference</xpath>
  <priority>0</priority>
  <cid>1</cid>
</change-sub>
<change-sub>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:listen/ncs:endpoint/ncs:tls/ncs:tls-server-parameters/ncs:client-authentication</xpath>
  <priority>0</priority>
  <cid>1</cid>
</change-sub>
<change-sub>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:listen/ncs:endpoint/ncs:tls/ncs:tls-server-parameters/ncs:client-authentication/ncs:cert-maps</xpath>
  <priority>0</priority>
  <cid>1</cid>
</change-sub>
<change-sub>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <xpath xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client</xpath>
  <priority>0</priority>
  <cid>1</cid>
</change-sub>
<change-sub>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client/ncs:connection-type</xpath>
  <priority>0</priority>
  <cid>1</cid>
</change-sub>
<change-sub>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client/ncs:reconnect-strategy</xpath>
  <priority>0</priority>
  <cid>1</cid>
</change-sub>
<change-sub>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client/ncs:endpoints/ncs:endpoint/ncs:ssh</xpath>
```

```
<priority>0</priority>
<cid>1</cid>
</change-sub>
<change-sub>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
</xpath>
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client/ncs:endpoints/ncs:endpoint/ncs:
ssh/ncs:tcp-client-parameters</xpath>
  <priority>0</priority>
  <cid>1</cid>
  </change-sub>
  <change-sub>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  </xpath>
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client/ncs:endpoints/ncs:endpoint/ncs:
ssh/ncs:ssh-server-parameters/ncs:server-identity/ncs:host-key/ncs:public-key/ncs:keystore-reference</xpath>
  <priority>0</priority>
  <cid>1</cid>
  </change-sub>
  <change-sub>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  </xpath>
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client/ncs:endpoints/ncs:endpoint/ncs:
ssh/ncs:ssh-server-parameters/ncs:client-authentication/ncs:supported-authentication-methods</xpath>
  <priority>0</priority>
  <cid>1</cid>
  </change-sub>
  <change-sub>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  </xpath>
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client/ncs:endpoints/ncs:endpoint/ncs:
tls</xpath>
  <priority>0</priority>
  <cid>1</cid>
  </change-sub>
  <change-sub>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  </xpath>
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client/ncs:endpoints/ncs:endpoint/ncs:
tls/ncs:tcp-client-parameters</xpath>
  <priority>0</priority>
  <cid>1</cid>
  </change-sub>
  <change-sub>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  </xpath>
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client/ncs:endpoints/ncs:endpoint/ncs:
tls/ncs:tls-server-parameters/ncs:server-identity/ncs:keystore-reference</xpath>
  <priority>0</priority>
```



```
<cid>1</cid>
</change-sub>
<change-sub>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client/ncs:endpoints/ncs:endpoint/ncs:
tls/ncs:tls-server-parameters/ncs:client-authentication</xpath>
  <priority>0</priority>
  <cid>1</cid>
</change-sub>
<change-sub>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:call-home/ncs:netconf-client/ncs:endpoints/ncs:endpoint/ncs:
tls/ncs:tls-server-parameters/ncs:client-authentication/ncs:cert-maps</xpath>
  <priority>0</priority>
  <cid>1</cid>
</change-sub>
<operational-sub>
  <xpath
xmlns:ncs="urn:ietf:params:xml:ns:yang:ietf-netconf-server">/ncs:netconf-server/ncs:listen/ncs:endpoint/ncs:ssh/ncs:ssh-server-parameters/ncs:cli
ent-authentication/ncs:users</xpath>
  <cid>1</cid>
</operational-sub>
<notification-sub>1</notification-sub>
</subscriptions>
</module>
<module>
  <name>vvdn_mcel-wdm</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
</module>
<module>
  <name>vvdn_mcel-opm</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
```

```
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
</module>
<module>
<name>notification_history</name>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<mode>read</mode>
</data-lock>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
</module>
<module>
<name>iana-hardware</name>
</module>
<module>
<name>ietf-hardware</name>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<mode>read</mode>
</data-lock>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
<subscriptions>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<priority>0</priority>
<cid>3</cid>
</change-sub>
<operational-sub>
<xpath xmlns:hw="urn:ietf:params:xml:ns:yang:ietf-hardware">/hw:hardware</xpath>
<cid>3</cid>
</operational-sub>
<notification-sub>1</notification-sub>
</subscriptions>
</module>
<module>
<name>ietf-interfaces</name>
<data-lock>
<cid>1</cid>
```

```
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<mode>read</mode>
</data-lock>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
<subscriptions>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<priority>0</priority>
<cid>3</cid>
</change-sub>
<operational-sub>
<xpath xmlns:if="urn:ietf:params:xml:ns:yang:ietf-interfaces">/if:interfaces</xpath>
<cid>3</cid>
</operational-sub>
<operational-sub>
<xpath xmlns:if="urn:ietf:params:xml:ns:yang:ietf-interfaces">/if:interfaces-state</xpath>
<cid>3</cid>
</operational-sub>
</subscriptions>
</module>
<module>
<name>iana-if-type</name>
</module>
<module>
<name>ietf-dhcpv6-types</name>
</module>
<module>
<name>ietf-ip</name>
</module>
<module>
<name>o-ran-dhcp</name>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<mode>read</mode>
</data-lock>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
<subscriptions>
<operational-sub>
<xpath xmlns:o-ran-dhcp="urn:o-ran:dhcp:1.0">/o-ran-dhcp:dhcp/o-ran-dhcp:interfaces</xpath>
<cid>3</cid>
```

```

    </operational-sub>
  </subscriptions>
</module>
<module>
  <name>o-ran-interfaces</name>
</module>
<module>
  <name>o-ran-mplane-int</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <change-sub>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
      <xpath
xmlns:o-ran-mplane-int="urn:o-ran:mplane-interfaces:1.0"/>o-ran-mplane-int:mplane-info/o-ran-mplane-int:searchable-mplane-access-vlans-info<
/xpath>
        <priority>0</priority>
        <cid>3</cid>
      </change-sub>
    <change-sub>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
      <xpath xmlns:o-ran-mplane-int="urn:o-ran:mplane-interfaces:1.0"/>o-ran-mplane-int:mplane-info/o-ran-mplane-int:m-plane-interfaces</xpath>
      <priority>0</priority>
      <cid>3</cid>
    </change-sub>
    <change-sub>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
      <xpath
xmlns:o-ran-mplane-int="urn:o-ran:mplane-interfaces:1.0"/>o-ran-mplane-int:mplane-info/o-ran-mplane-int:configured-client-info</xpath>
        <priority>0</priority>
        <cid>3</cid>
      </change-sub>
    <operational-sub>
      <xpath xmlns:o-ran-mplane-int="urn:o-ran:mplane-interfaces:1.0"/>o-ran-mplane-int:mplane-info/o-ran-mplane-int:m-plane-interfaces</xpath>
      <cid>3</cid>
    </operational-sub>
  </subscriptions>
</module>
<module>
  <name>o-ran-transceiver</name>
  <data-lock>

```

```

<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<mode>read</mode>
</data-lock>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
<subscriptions>
<operational-sub>
<xpath xmlns:o-ran-transceiver="urn:o-ran:transceiver:1.0"/>o-ran-transceiver:port-transceivers</xpath>
<cid>3</cid>
</operational-sub>
</subscriptions>
</module>
<module>
<name>o-ran-processing-element</name>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<mode>read</mode>
</data-lock>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
<subscriptions>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath
xmlns:o-ran-elements="urn:o-ran:processing-element:1.0"/>o-ran-elements:processing-elements/o-ran-elements:transport-session-type</xpath>
<priority>0</priority>
<cid>8</cid>
</change-sub>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath xmlns:o-ran-elements="urn:o-ran:processing-element:1.0"/>o-ran-elements:processing-elements/o-ran-elements:ru-elements</xpath>
<priority>0</priority>
<cid>8</cid>
</change-sub>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath
xmlns:o-ran-elements="urn:o-ran:processing-element:1.0"/>o-ran-elements:processing-elements/o-ran-elements:enhanced-uplane-mapping</xpath>
>
<priority>0</priority>
<cid>8</cid>

```

```
</change-sub>
<operational-sub>
  <xpath xmlns:o-ran-elements="urn:o-ran:processing-element:1.0"/>o-ran-elements:processing-elements</xpath>
  <cid>8</cid>
</operational-sub>
</subscriptions>
</module>
<module>
  <name>o-ran-ald-port</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <operational-sub>
      <xpath xmlns:o-ran-ald-port="urn:o-ran:ald-port:1.0"/>o-ran-ald-port:ald-ports-io</xpath>
      <cid>12</cid>
    </operational-sub>
    <notification-sub>1</notification-sub>
  </subscriptions>
</module>
<module>
  <name>o-ran-supervision</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <change-sub>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
      <xpath xmlns:o-ran-supervision="urn:o-ran:supervision:1.0"/>o-ran-supervision:supervision</xpath>
      <priority>0</priority>
      <cid>10</cid>
    </change-sub>
    <notification-sub>1</notification-sub>
  </subscriptions>
</module>
```

```
<module>
  <name>o-ran-hardware</name>
</module>
<module>
  <name>o-ran-fm</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <operational-sub>
      <xpath xmlns:o-ran-fm="urn:o-ran:fm:1.0">/o-ran-fm:active-alarm-list/o-ran-fm:active-alarms</xpath>
      <cid>4</cid>
    </operational-sub>
    <notification-sub>1</notification-sub>
  </subscriptions>
</module>
<module>
  <name>o-ran-usermgmt</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <change-sub>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
      <xpath xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users</xpath>
      <priority>0</priority>
      <cid>5</cid>
    </change-sub>
  </subscriptions>
</module>
<module>
  <name>o-ran-sync</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
```

```
<mode>read</mode>
</data-lock>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
<subscriptions>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<priority>0</priority>
<cid>7</cid>
</change-sub>
<operational-sub>
<xpath xmlns:o-ran-sync="urn:o-ran:sync:1.0">/o-ran-sync:sync</xpath>
<cid>7</cid>
</operational-sub>
<notification-sub>1</notification-sub>
</subscriptions>
</module>
<module>
<name>o-ran-compression-factors</name>
</module>
<module>
<name>o-ran-module-cap</name>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<mode>read</mode>
</data-lock>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
<subscriptions>
<operational-sub>
<xpath xmlns:o-ran-module-cap="urn:o-ran:module-cap:1.0">/o-ran-module-cap:module-capability</xpath>
<cid>14</cid>
</operational-sub>
</subscriptions>
</module>
<module>
<name>o-ran-delay-management</name>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<mode>read</mode>
</data-lock>
```



```
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
<subscriptions>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath xmlns:o-ran-delay="urn:o-ran:delay:1.0"/>o-ran-delay:delay-management</xpath>
<priority>0</priority>
<cid>14</cid>
</change-sub>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<xpath xmlns:o-ran-delay="urn:o-ran:delay:1.0"/>o-ran-delay:delay-management/o-ran-delay:adaptive-delay-configuration</xpath>
<priority>0</priority>
<cid>14</cid>
</change-sub>
<operational-sub>
<xpath xmlns:o-ran-delay="urn:o-ran:delay:1.0"/>o-ran-delay:delay-management</xpath>
<cid>14</cid>
</operational-sub>
</subscriptions>
</module>
<module>
<name>o-ran-operations</name>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<mode>read</mode>
</data-lock>
<data-lock>
<cid>1</cid>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
<mode>read</mode>
</data-lock>
<subscriptions>
<change-sub>
<datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
<priority>0</priority>
<cid>8</cid>
</change-sub>
<operational-sub>
<xpath xmlns:o-ran-ops="urn:o-ran:operations:1.0"/>o-ran-ops:operational-info</xpath>
<cid>8</cid>
</operational-sub>
</subscriptions>
</module>
<module>
```

```
<name>o-ran-uplane-conf</name>
<data-lock>
  <cid>1</cid>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <mode>read</mode>
</data-lock>
<data-lock>
  <cid>1</cid>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
  <mode>read</mode>
</data-lock>
<subscriptions>
  <change-sub>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:low-level-tx-links</xpath>
    <priority>0</priority>
    <cid>8</cid>
  </change-sub>
  <change-sub>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:low-level-rx-links</xpath>
    <priority>0</priority>
    <cid>8</cid>
  </change-sub>
  <change-sub>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:low-level-tx-endpoints</xpath>
    <priority>0</priority>
    <cid>8</cid>
  </change-sub>
  <change-sub>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:low-level-rx-endpoints</xpath>
    <priority>0</priority>
    <cid>8</cid>
  </change-sub>
  <change-sub>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:tx-array-carriers</xpath>
    <priority>0</priority>
    <cid>8</cid>
  </change-sub>
```

```

<change-sub>
  <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
  <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:rx-array-carriers</xpath>
  <priority>0</priority>
  <cid>8</cid>
</change-sub>
<operational-sub>
  <xpath xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:tx-arrays</xpath>
  <cid>8</cid>
</operational-sub>
<operational-sub>
  <xpath xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:rx-arrays</xpath>
  <cid>8</cid>
</operational-sub>
<operational-sub>
  <xpath xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:relations</xpath>
  <cid>8</cid>
</operational-sub>
<operational-sub>
  <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:endpoint-types</xpath>
  <cid>8</cid>
</operational-sub>
<operational-sub>
  <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:tx-array-carriers</xpath>
  <cid>8</cid>
</operational-sub>
<operational-sub>
  <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:rx-array-carriers</xpath>
  <cid>8</cid>
</operational-sub>
<operational-sub>
  <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:static-low-level-tx-endpoints
</xpath>
  <cid>8</cid>
</operational-sub>
<operational-sub>
  <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:static-low-level-rx-endpoint
s</xpath>
  <cid>8</cid>
</operational-sub>
<operational-sub>
  <xpath
xmlns:o-ran-uplane-conf="urn:o-ran:uplane-conf:1.0"/>o-ran-uplane-conf:user-plane-configuration/o-ran-uplane-conf:endpoint-capacity-sharing-g

```

```

roups</xpath>
  <cid>8</cid>
</operational-sub>
<notification-sub>1</notification-sub>
</subscriptions>
</module>
<module>
  <name>o-ran-file-management</name>
  <subscriptions>
    <notification-sub>1</notification-sub>
  </subscriptions>
</module>
<module>
  <name>o-ran-software-management</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <operational-sub>
      <xpath xmlns:o-ran-swm="urn:o-ran:software-management:1.0">/o-ran-swm:software-inventory</xpath>
      <cid>6</cid>
    </operational-sub>
    <notification-sub>1</notification-sub>
  </subscriptions>
</module>
<module>
  <name>o-ran-performance-management</name>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
    <mode>read</mode>
  </data-lock>
  <data-lock>
    <cid>1</cid>
    <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:operational</datastore>
    <mode>read</mode>
  </data-lock>
  <subscriptions>
    <change-sub>
      <datastore xmlns:ds="urn:ietf:params:xml:ns:yang:ietf-datastores">ds:running</datastore>
      <xpath xmlns:o-ran-pm="urn:o-ran:performance-management:1.0">/o-ran-pm:performance-measurement-objects</xpath>
      <priority>0</priority>
    </change-sub>
  </subscriptions>
</module>

```

```
<cid>11</cid>
</change-sub>
<operational-sub>
  <xpath xmlns:o-ran-pm="urn:o-ran:performance-management:1.0"/>o-ran-pm:performance-measurement-objects</xpath>
  <cid>11</cid>
</operational-sub>
<notification-sub>1</notification-sub>
</subscriptions>
</module>
<module>
  <name>o-ran-ald</name>
</module>
<module>
  <name>o-ran-trace</name>
  <subscriptions>
    <notification-sub>1</notification-sub>
  </subscriptions>
</module>
<module>
  <name>o-ran-troubleshooting</name>
  <subscriptions>
    <notification-sub>1</notification-sub>
  </subscriptions>
</module>
<rpc>
  <path xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:get-config</path>
  <rpc-sub>
    <xpath xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:get-config</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:edit-config</path>
  <rpc-sub>
    <xpath xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:edit-config</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:copy-config</path>
  <rpc-sub>
    <xpath xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:copy-config</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
```

```
<path xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:delete-config</path>
<rpc-sub>
  <xpath xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:delete-config</xpath>
  <priority>0</priority>
  <cid>1</cid>
</rpc-sub>
</rpc>
<rpc>
  <path xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:lock</path>
  <rpc-sub>
    <xpath xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:lock</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:unlock</path>
  <rpc-sub>
    <xpath xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:unlock</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:get</path>
  <sub-lock>
    <cid>1</cid>
    <mode>read</mode>
  </sub-lock>
  <rpc-sub>
    <xpath xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:get</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:kill-session</path>
  <rpc-sub>
    <xpath xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:kill-session</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:commit</path>
  <rpc-sub>
    <xpath xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:commit</xpath>
    <priority>0</priority>
    <cid>1</cid>
```

```
</rpc-sub>
</rpc>
<rpc>
  <path xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:discard-changes</path>
  <rpc-sub>
    <xpath xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:discard-changes</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:validate</path>
  <rpc-sub>
    <xpath xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"/>nc:validate</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:ncds="urn:ietf:params:xml:ns:yang:ietf-netconf-nmda"/>ncds:get-data</path>
  <rpc-sub>
    <xpath xmlns:ncds="urn:ietf:params:xml:ns:yang:ietf-netconf-nmda"/>ncds:get-data</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:ncds="urn:ietf:params:xml:ns:yang:ietf-netconf-nmda"/>ncds:edit-data</path>
  <rpc-sub>
    <xpath xmlns:ncds="urn:ietf:params:xml:ns:yang:ietf-netconf-nmda"/>ncds:edit-data</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:ncEvent="urn:ietf:params:xml:ns:netconf:notification:1.0"/>ncEvent:create-subscription</path>
  <rpc-sub>
    <xpath xmlns:ncEvent="urn:ietf:params:xml:ns:netconf:notification:1.0"/>ncEvent:create-subscription</xpath>
    <priority>0</priority>
    <cid>1</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:o-ran-supervision="urn:o-ran:supervision:1.0"/>o-ran-supervision:supervision-watchdog-reset</path>
  <rpc-sub>
    <xpath xmlns:o-ran-supervision="urn:o-ran:supervision:1.0"/>o-ran-supervision:supervision-watchdog-reset</xpath>
    <priority>0</priority>
    <cid>10</cid>
  </rpc-sub>
```

```
</rpc>
<rpc>
  <path xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0"/>o-ran-usermgmt:chg-password</path>
  <rpc-sub>
    <xpath xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0"/>o-ran-usermgmt:chg-password</xpath>
    <priority>0</priority>
    <cid>5</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:o-ran-ops="urn:o-ran:operations:1.0"/>o-ran-ops:reset</path>
  <rpc-sub>
    <xpath xmlns:o-ran-ops="urn:o-ran:operations:1.0"/>o-ran-ops:reset</xpath>
    <priority>0</priority>
    <cid>8</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:o-ran-file-mgmt="urn:o-ran:file-management:1.0"/>o-ran-file-mgmt:file-upload</path>
  <rpc-sub>
    <xpath xmlns:o-ran-file-mgmt="urn:o-ran:file-management:1.0"/>o-ran-file-mgmt:file-upload</xpath>
    <priority>0</priority>
    <cid>9</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:o-ran-file-mgmt="urn:o-ran:file-management:1.0"/>o-ran-file-mgmt:retrieve-file-list</path>
  <rpc-sub>
    <xpath xmlns:o-ran-file-mgmt="urn:o-ran:file-management:1.0"/>o-ran-file-mgmt:retrieve-file-list</xpath>
    <priority>0</priority>
    <cid>9</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:o-ran-file-mgmt="urn:o-ran:file-management:1.0"/>o-ran-file-mgmt:file-download</path>
  <rpc-sub>
    <xpath xmlns:o-ran-file-mgmt="urn:o-ran:file-management:1.0"/>o-ran-file-mgmt:file-download</xpath>
    <priority>0</priority>
    <cid>9</cid>
  </rpc-sub>
</rpc>
<rpc>
  <path xmlns:o-ran-swm="urn:o-ran:software-management:1.0"/>o-ran-swm:software-download</path>
  <rpc-sub>
    <xpath xmlns:o-ran-swm="urn:o-ran:software-management:1.0"/>o-ran-swm:software-download</xpath>
    <priority>0</priority>
    <cid>6</cid>
  </rpc-sub>
</rpc>
```



```
<rpc>
  <path xmlns:o-ran-swm="urn:o-ran:software-management:1.0"/>o-ran-swm:software-install</path>
  <rpc-sub>
    <xpath xmlns:o-ran-swm="urn:o-ran:software-management:1.0"/>o-ran-swm:software-install</xpath>
    <priority>0</priority>
    <cid>6</cid>
  </rpc-sub>
</rpc>

<rpc>
  <path xmlns:o-ran-swm="urn:o-ran:software-management:1.0"/>o-ran-swm:software-activate</path>
  <rpc-sub>
    <xpath xmlns:o-ran-swm="urn:o-ran:software-management:1.0"/>o-ran-swm:software-activate</xpath>
    <priority>0</priority>
    <cid>6</cid>
  </rpc-sub>
</rpc>

<rpc>
  <path xmlns:o-ran-ald="urn:o-ran:ald:1.0"/>o-ran-ald:ald-communication</path>
  <rpc-sub>
    <xpath xmlns:o-ran-ald="urn:o-ran:ald:1.0"/>o-ran-ald:ald-communication</xpath>
    <priority>0</priority>
    <cid>12</cid>
  </rpc-sub>
</rpc>

<rpc>
  <path xmlns:o-ran-trace="urn:o-ran:trace:1.0"/>o-ran-trace:start-trace-logs</path>
  <rpc-sub>
    <xpath xmlns:o-ran-trace="urn:o-ran:trace:1.0"/>o-ran-trace:start-trace-logs</xpath>
    <priority>0</priority>
    <cid>13</cid>
  </rpc-sub>
</rpc>

<rpc>
  <path xmlns:o-ran-trace="urn:o-ran:trace:1.0"/>o-ran-trace:stop-trace-logs</path>
  <rpc-sub>
    <xpath xmlns:o-ran-trace="urn:o-ran:trace:1.0"/>o-ran-trace:stop-trace-logs</xpath>
    <priority>0</priority>
    <cid>13</cid>
  </rpc-sub>
</rpc>

<rpc>
  <path xmlns:o-ran-trblsht="urn:o-ran:troubleshooting:1.0"/>o-ran-trblsht:start-troubleshooting-logs</path>
  <rpc-sub>
    <xpath xmlns:o-ran-trblsht="urn:o-ran:troubleshooting:1.0"/>o-ran-trblsht:start-troubleshooting-logs</xpath>
    <priority>0</priority>
    <cid>13</cid>
  </rpc-sub>
</rpc>
```

```
<path xmlns:o-ran-trblsht="urn:o-ran:troubleshooting:1.0">/o-ran-trblsht:stop-troubleshooting-logs</path>
<rpc-sub>
  <xpath xmlns:o-ran-trblsht="urn:o-ran:troubleshooting:1.0">/o-ran-trblsht:stop-troubleshooting-logs</xpath>
  <priority>0</priority>
  <cid>13</cid>
</rpc-sub>
</rpc>
<connection>
  <cid>11</cid>
  <pid>1372</pid>
</connection>
<connection>
  <cid>7</cid>
  <pid>1308</pid>
</connection>
<connection>
  <cid>16</cid>
  <pid>1462</pid>
</connection>
<connection>
  <cid>6</cid>
  <pid>1062</pid>
</connection>
<connection>
  <cid>1</cid>
  <pid>981</pid>
</connection>
<connection>
  <cid>2</cid>
  <pid>996</pid>
</connection>
<connection>
  <cid>8</cid>
  <pid>1319</pid>
</connection>
<connection>
  <cid>14</cid>
  <pid>1419</pid>
</connection>
<connection>
  <cid>3</cid>
  <pid>1011</pid>
</connection>
<connection>
  <cid>13</cid>
  <pid>1406</pid>
</connection>
<connection>
  <cid>10</cid>
```

```
<pid>1362</pid>
</connection>
<connection>
  <cid>5</cid>
  <pid>1051</pid>
</connection>
<connection>
  <cid>9</cid>
  <pid>1350</pid>
</connection>
<connection>
  <cid>4</cid>
  <pid>1041</pid>
</connection>
<connection>
  <cid>12</cid>
  <pid>1396</pid>
</connection>
<connection>
  <cid>15</cid>
  <pid>1432</pid>
</connection>
</sysrepo-state>
<netconf-state xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-monitoring">
  <capabilities>
    <capability>urn:ietf:params:netconf:base:1.0</capability>
    <capability>urn:ietf:params:netconf:base:1.1</capability>
    <capability>urn:ietf:params:netconf:capability:writable-running:1.0</capability>
    <capability>urn:ietf:params:netconf:capability:candidate:1.0</capability>
    <capability>urn:ietf:params:netconf:capability:rollback-on-error:1.0</capability>
    <capability>urn:ietf:params:netconf:capability:validate:1.1</capability>
    <capability>urn:ietf:params:netconf:capability:startup:1.0</capability>
    <capability>urn:ietf:params:netconf:capability:xpath:1.0</capability>
    <capability>urn:ietf:params:netconf:capability:with-defaults:1.0?basic-mode=explicit&also-supported=report-all,report-all-tagged,trim,explicit</capability>
    <capability>urn:ietf:params:netconf:capability:notification:1.0</capability>
    <capability>urn:ietf:params:netconf:capability:interleave:1.0</capability>
    <capability>urn:ietf:params:xml:ns:yang:ietf-yang-metadata?module=ietf-yang-metadata&revision=2016-08-05</capability>
    <capability>urn:ietf:params:xml:ns:yang:1?module=yang&revision=2017-02-20</capability>
    <capability>urn:ietf:params:xml:ns:yang:ietf-inet-types?module=ietf-inet-types&revision=2013-07-15</capability>
    <capability>urn:ietf:params:xml:ns:yang:ietf-yang-types?module=ietf-yang-types&revision=2013-07-15</capability>
    <capability>urn:ietf:params:netconf:capability:yang-library:1.1?revision=2019-01-04&content-id=63</capability>
    <capability>urn:sysrepo:plugind?module=sysrepo-plugind&revision=2020-12-10</capability>
    <capability>urn:ietf:params:xml:ns:yang:ietf-netconf-acm?module=ietf-netconf-acm&revision=2018-02-14</capability>
    <capability>urn:ietf:params:xml:ns:netconf:base:1.0?module=ietf-netconf&revision=2013-09-29&features=writable-running,candidate,rollback-on-error,validate,startup,url,xpath</capability>
    <capability>urn:ietf:params:xml:ns:yang:ietf-netconf-with-defaults?module=ietf-netconf-with-defaults&revision=2011-06-01</capability>
    <capability>urn:ietf:params:xml:ns:yang:ietf-netconf-notifications?module=ietf-netconf-notifications&revision=2012-02-06</capability>
    <capability>urn:ietf:params:xml:ns:yang:ietf-netconf-monitoring?module=ietf-netconf-monitoring&revision=2010-10-04</capability>
```

```
<capability>urn:ietf:params:xml:ns:netconf:notification:1.0?module=notifications&revision=2008-07-14</capability>
<capability>urn:ietf:params:xml:ns:netmod:notification?module=nc-notifications&revision=2008-07-14</capability>
<capability>urn:ietf:params:xml:ns:yang:ietf-x509-cert-to-name?module=ietf-x509-cert-to-name&revision=2014-12-10</capability>
<capability>urn:ietf:params:xml:ns:yang:iana-crypt-hash?module=iana-crypt-hash&revision=2014-08-06</capability>
<capability>urn:notification_history?module=notification_history</capability>
<capability>urn:ietf:params:xml:ns:yang:iana-if-type?module=iana-if-type&revision=2017-01-19</capability>
</capabilities>
<datastores>
<datastore>
<name>running</name>
</datastore>
<datastore>
<name>startup</name>
</datastore>
<datastore>
<name>candidate</name>
</datastore>
</datastores>
<schemas>
<schema>
<identifier>ietf-yang-metadata</identifier>
<version>2016-08-05</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-yang-metadata</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-yang-metadata</identifier>
<version>2016-08-05</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-yang-metadata</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>yang</identifier>
<version>2017-02-20</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:1</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>yang</identifier>
<version>2017-02-20</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:1</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-inet-types</identifier>
```

```
<version>2013-07-15</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-inet-types</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-inet-types</identifier>
  <version>2013-07-15</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-inet-types</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-yang-types</identifier>
  <version>2013-07-15</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-yang-types</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-yang-types</identifier>
  <version>2013-07-15</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-yang-types</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>sysrepo</identifier>
  <version>2021-01-18</version>
  <format>yang</format>
  <namespace>http://www.sysrepo.org/yang/sysrepo</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>sysrepo</identifier>
  <version>2021-01-18</version>
  <format>yin</format>
  <namespace>http://www.sysrepo.org/yang/sysrepo</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-datastores</identifier>
  <version>2018-02-14</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-datastores</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-datastores</identifier>
```

```
<version>2018-02-14</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-datastores</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-yang-library</identifier>
  <version>2019-01-04</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-yang-library</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-yang-library</identifier>
  <version>2019-01-04</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-yang-library</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>sysrepo-monitoring</identifier>
  <version>2021-01-15</version>
  <format>yang</format>
  <namespace>http://www.sysrepo.org/yang/sysrepo-monitoring</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>sysrepo-monitoring</identifier>
  <version>2021-01-15</version>
  <format>yin</format>
  <namespace>http://www.sysrepo.org/yang/sysrepo-monitoring</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>sysrepo-plugind</identifier>
  <version>2020-12-10</version>
  <format>yang</format>
  <namespace>urn:sysrepo:plugind</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>sysrepo-plugind</identifier>
  <version>2020-12-10</version>
  <format>yin</format>
  <namespace>urn:sysrepo:plugind</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-netconf-acm</identifier>
```

```
<version>2018-02-14</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-acm</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-netconf-acm</identifier>
<version>2018-02-14</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-acm</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-netconf</identifier>
<version>2013-09-29</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:netconf:base:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-netconf</identifier>
<version>2013-09-29</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:netconf:base:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-netconf-with-defaults</identifier>
<version>2011-06-01</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-with-defaults</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-netconf-with-defaults</identifier>
<version>2011-06-01</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-with-defaults</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-netconf-notifications</identifier>
<version>2012-02-06</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-notifications</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-netconf-notifications</identifier>
```

```
<version>2012-02-06</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-notifications</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-origin</identifier>
  <version>2018-02-14</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-origin</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-origin</identifier>
  <version>2018-02-14</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-origin</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-netconf-monitoring</identifier>
  <version>2010-10-04</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-monitoring</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-netconf-monitoring</identifier>
  <version>2010-10-04</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-monitoring</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-netconf-nmda</identifier>
  <version>2019-01-07</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-nmda</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-netconf-nmda</identifier>
  <version>2019-01-07</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-nmda</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>notifications</identifier>
```



```
<version>2008-07-14</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:netconf:notification:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>notifications</identifier>
  <version>2008-07-14</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:netconf:notification:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>nc-notifications</identifier>
  <version>2008-07-14</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:netmod:notification</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>nc-notifications</identifier>
  <version>2008-07-14</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:netmod:notification</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-x509-cert-to-name</identifier>
  <version>2014-12-10</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-x509-cert-to-name</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-x509-cert-to-name</identifier>
  <version>2014-12-10</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-x509-cert-to-name</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-crypto-types</identifier>
  <version>2019-07-02</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-crypto-types</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-crypto-types</identifier>
```

```
<version>2019-07-02</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-crypto-types</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-keystore</identifier>
<version>2019-07-02</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-keystore</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-keystore</identifier>
<version>2019-07-02</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-keystore</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-truststore</identifier>
<version>2019-07-02</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-truststore</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-truststore</identifier>
<version>2019-07-02</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-truststore</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-tcp-common</identifier>
<version>2019-07-02</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-common</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-tcp-common</identifier>
<version>2019-07-02</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-common</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-ssh-common</identifier>
```

```
<version>2019-07-02</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-ssh-common</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-ssh-common</identifier>
  <version>2019-07-02</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-ssh-common</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>iana-crypt-hash</identifier>
  <version>2014-08-06</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:iana-crypt-hash</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>iana-crypt-hash</identifier>
  <version>2014-08-06</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:iana-crypt-hash</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-ssh-server</identifier>
  <version>2019-07-02</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-ssh-server</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-ssh-server</identifier>
  <version>2019-07-02</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-ssh-server</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-tls-common</identifier>
  <version>2019-07-02</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tls-common</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-tls-common</identifier>
```

```
<version>2019-07-02</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-tls-common</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-tls-server</identifier>
  <version>2019-07-02</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tls-server</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-tls-server</identifier>
  <version>2019-07-02</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tls-server</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-tcp-client</identifier>
  <version>2019-07-02</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-client</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-tcp-client</identifier>
  <version>2019-07-02</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-client</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-tcp-server</identifier>
  <version>2019-07-02</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-server</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-tcp-server</identifier>
  <version>2019-07-02</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-tcp-server</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-netconf-server</identifier>
```

```
<version>2019-07-02</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-server</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-netconf-server</identifier>
  <version>2019-07-02</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-netconf-server</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>vvdn_mcel-wdm</identifier>
  <version>2022-05-03</version>
  <format>yang</format>
  <namespace>urn:vvdn_mcel:wdm:1.1</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>vvdn_mcel-wdm</identifier>
  <version>2022-05-03</version>
  <format>yin</format>
  <namespace>urn:vvdn_mcel:wdm:1.1</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>vvdn_mcel-opm</identifier>
  <version>2020-11-08</version>
  <format>yang</format>
  <namespace>urn:vvdn_mcel-opm:1.1</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>vvdn_mcel-opm</identifier>
  <version>2020-11-08</version>
  <format>yin</format>
  <namespace>urn:vvdn_mcel-opm:1.1</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>notification_history</identifier>
  <version/>
  <format>yang</format>
  <namespace>urn:notification_history</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>notification_history</identifier>
```

```
<version/>
<format>yin</format>
<namespace>urn:notification_history</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>iana-hardware</identifier>
<version>2018-03-13</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:iana-hardware</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>iana-hardware</identifier>
<version>2018-03-13</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:iana-hardware</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-hardware</identifier>
<version>2018-03-13</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-hardware</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-hardware</identifier>
<version>2018-03-13</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-hardware</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-interfaces</identifier>
<version>2018-02-20</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-interfaces</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>ietf-interfaces</identifier>
<version>2018-02-20</version>
<format>yin</format>
<namespace>urn:ietf:params:xml:ns:yang:ietf-interfaces</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>iana-if-type</identifier>
```

```
<version>2017-01-19</version>
<format>yang</format>
<namespace>urn:ietf:params:xml:ns:yang:iana-if-type</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>iana-if-type</identifier>
  <version>2017-01-19</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:iana-if-type</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-dhcpv6-types</identifier>
  <version>2018-01-30</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-dhcpv6-types</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-dhcpv6-types</identifier>
  <version>2018-01-30</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-dhcpv6-types</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-ip</identifier>
  <version>2018-02-22</version>
  <format>yang</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-ip</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>ietf-ip</identifier>
  <version>2018-02-22</version>
  <format>yin</format>
  <namespace>urn:ietf:params:xml:ns:yang:ietf-ip</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-dhcp</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:dhcp:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-dhcp</identifier>
```

```
<version>2019-07-03</version>
<format>yin</format>
<namespace>urn:o-ran:dhcp:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-interfaces</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:interfaces:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-interfaces</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:interfaces:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-mplane-int</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:mplane-interfaces:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-mplane-int</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:mplane-interfaces:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-transceiver</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:transceiver:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-transceiver</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:transceiver:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-processing-element</identifier>
```



```
<version>2019-07-03</version>
<format>yang</format>
<namespace>urn:o-ran:processing-element:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-processing-element</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:processing-element:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-ald-port</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:ald-port:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-ald-port</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:ald-port:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-supervision</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:supervision:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-supervision</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:supervision:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-hardware</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:hardware:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-hardware</identifier>
```

```
<version>2019-07-03</version>
<format>yin</format>
<namespace>urn:o-ran:hardware:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-fm</identifier>
<version>2019-02-04</version>
<format>yang</format>
<namespace>urn:o-ran:fm:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-fm</identifier>
<version>2019-02-04</version>
<format>yin</format>
<namespace>urn:o-ran:fm:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-usermgmt</identifier>
<version>2019-07-03</version>
<format>yang</format>
<namespace>urn:o-ran:user-mgmt:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-usermgmt</identifier>
<version>2019-07-03</version>
<format>yin</format>
<namespace>urn:o-ran:user-mgmt:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-sync</identifier>
<version>2019-07-03</version>
<format>yang</format>
<namespace>urn:o-ran:sync:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-sync</identifier>
<version>2019-07-03</version>
<format>yin</format>
<namespace>urn:o-ran:sync:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-compression-factors</identifier>
```

```
<version>2019-07-03</version>
<format>yang</format>
<namespace>urn:o-ran:compression-factors:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-compression-factors</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:compression-factors:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-module-cap</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:module-cap:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-module-cap</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:module-cap:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-delay-management</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:delay:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-delay-management</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:delay:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-operations</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:operations:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-operations</identifier>
```

```
<version>2019-07-03</version>
<format>yin</format>
<namespace>urn:o-ran:operations:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-uplane-conf</identifier>
<version>2019-07-03</version>
<format>yang</format>
<namespace>urn:o-ran:uplane-conf:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-uplane-conf</identifier>
<version>2019-07-03</version>
<format>yin</format>
<namespace>urn:o-ran:uplane-conf:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-file-management</identifier>
<version>2019-07-03</version>
<format>yang</format>
<namespace>urn:o-ran:file-management:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-file-management</identifier>
<version>2019-07-03</version>
<format>yin</format>
<namespace>urn:o-ran:file-management:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-software-management</identifier>
<version>2019-07-03</version>
<format>yang</format>
<namespace>urn:o-ran:software-management:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-software-management</identifier>
<version>2019-07-03</version>
<format>yin</format>
<namespace>urn:o-ran:software-management:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
<identifier>o-ran-performance-management</identifier>
```

```
<version>2019-07-03</version>
<format>yang</format>
<namespace>urn:o-ran:performance-management:1.0</namespace>
<location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-performance-management</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:performance-management:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-ald</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:ald:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-ald</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:ald:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-trace</identifier>
  <version>2019-07-03</version>
  <format>yang</format>
  <namespace>urn:o-ran:trace:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-trace</identifier>
  <version>2019-07-03</version>
  <format>yin</format>
  <namespace>urn:o-ran:trace:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-troubleshooting</identifier>
  <version>2019-02-04</version>
  <format>yang</format>
  <namespace>urn:o-ran:troubleshooting:1.0</namespace>
  <location>NETCONF</location>
</schema>
<schema>
  <identifier>o-ran-troubleshooting</identifier>
```

```
<version>2019-02-04</version>
<format>yin</format>
<namespace>urn:o-ran:troubleshooting:1.0</namespace>
<location>NETCONF</location>
</schema>
</schemas>
<sessions>
<session>
<session-id>1</session-id>
<transport>netconf-ssh</transport>
<username>root</username>
<source-host>192.168.49.88</source-host>
<login-time>2103-10-30T00:03:16Z</login-time>
<in-rpcs>4</in-rpcs>
<in-bad-rpcs>0</in-bad-rpcs>
<out-rpc-errors>0</out-rpc-errors>
<out-notifications>0</out-notifications>
</session>
</sessions>
<statistics>
<netconf-start-time>2103-10-30T00:02:15Z</netconf-start-time>
<in-bad-hellos>0</in-bad-hellos>
<in-sessions>1</in-sessions>
<dropped-sessions>0</dropped-sessions>
<in-rpcs>4</in-rpcs>
<in-bad-rpcs>0</in-bad-rpcs>
<out-rpc-errors>0</out-rpc-errors>
<out-notifications>0</out-notifications>
</statistics>
</netconf-state>
<netconf xmlns="urn:ietf:params:xml:ns:netmod:notification">
<streams>
<stream>
<name>NETCONF</name>
<description>Default NETCONF stream containing notifications from all the modules. Replays only notifications for modules that support
replay.</description>
<replaySupport>true</replaySupport>
</stream>
<stream>
<name>yang</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-datastores</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
```

```
<name>ietf-yang-library</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>sysrepo-monitoring</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>sysrepo-plugind</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-netconf-with-defaults</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-netconf-notifications</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-origin</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-netconf-acm</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-netconf</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-netconf-monitoring</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-netconf-nmda</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
```

```
<stream>
<name>nc-notifications</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>notifications</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-x509-cert-to-name</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-crypto-types</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-keystore</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-truststore</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-tcp-common</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-ssh-server</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-tls-server</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>ietf-netconf-server</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
```



```
</stream>
<stream>
  <name>vvdn_mcel-wdm</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>vvdn_mcel-opm</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>notification_history</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>iana-hardware</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>ietf-hardware</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>ietf-interfaces</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>iana-if-type</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>ietf-dhcpv6-types</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>ietf-ip</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>o-ran-dhcp</name>
  <description>Stream with all notifications of a module.</description>
```

```
<replaySupport>false</replaySupport>
</stream>
<stream>
  <name>o-ran-interfaces</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>o-ran-mplane-int</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>o-ran-transceiver</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>o-ran-processing-element</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>o-ran-ald-port</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>o-ran-supervision</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>o-ran-hardware</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>o-ran-fm</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>o-ran-usermgmt</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>false</replaySupport>
</stream>
<stream>
  <name>o-ran-sync</name>
```

```
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>o-ran-compression-factors</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>o-ran-module-cap</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>o-ran-delay-management</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>o-ran-operations</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>o-ran-uplane-conf</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>o-ran-file-management</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>o-ran-software-management</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>o-ran-performance-management</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
<name>o-ran-ald</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
```

```
<name>o-ran-trace</name>
<description>Stream with all notifications of a module.</description>
<replaySupport>>false</replaySupport>
</stream>
<stream>
  <name>o-ran-troubleshooting</name>
  <description>Stream with all notifications of a module.</description>
  <replaySupport>>false</replaySupport>
</stream>
</streams>
</netconf>
<interfaces-state xmlns="urn:ietf:params:xml:ns:yang:ietf-interfaces">
  <interface>
    <name>lo</name>
    <oper-status>up</oper-status>
    <phys-address>00:00:00:00:00:00</phys-address>
    <statistics>
      <in-octets>1408</in-octets>
      <in-discards>0</in-discards>
      <in-errors>0</in-errors>
      <out-octets>1408</out-octets>
      <out-errors>0</out-errors>
      <out-discards>0</out-discards>
    </statistics>
  </interface>
  <interface>
    <name>eth0</name>
    <oper-status>up</oper-status>
    <phys-address>98:ae:71:00:8a:c1</phys-address>
    <statistics>
      <in-octets>0</in-octets>
      <in-discards>0</in-discards>
      <in-errors>0</in-errors>
      <out-octets>0</out-octets>
      <out-errors>0</out-errors>
      <out-discards>0</out-discards>
    </statistics>
  </interface>
  <interface>
    <name>eth1</name>
    <oper-status>up</oper-status>
    <phys-address>98:ae:71:00:8a:c2</phys-address>
    <statistics>
      <in-octets>31588</in-octets>
      <in-discards>0</in-discards>
      <in-errors>0</in-errors>
      <out-octets>49790</out-octets>
      <out-errors>0</out-errors>
      <out-discards>0</out-discards>
    </statistics>
  </interface>
</interfaces-state>
</data>
```

```
</statistics>
</interface>
<interface>
  <name>eth1.428</name>
  <oper-status>up</oper-status>
  <phys-address>98:ae:71:00:8a:c2</phys-address>
  <statistics>
    <in-octets>0</in-octets>
    <in-discards>0</in-discards>
    <in-errors>0</in-errors>
    <out-octets>3136</out-octets>
    <out-errors>0</out-errors>
    <out-discards>0</out-discards>
  </statistics>
</interface>
<interface>
  <name>eth1.490</name>
  <oper-status>up</oper-status>
  <phys-address>98:ae:71:00:8a:c2</phys-address>
  <statistics>
    <in-octets>26584</in-octets>
    <in-discards>0</in-discards>
    <in-errors>0</in-errors>
    <out-octets>43587</out-octets>
    <out-errors>0</out-errors>
    <out-discards>0</out-discards>
  </statistics>
</interface>
</interfaces-state>
<dhcp xmlns="urn:o-ran:dhcp:1.0">
  <interfaces>
    <interface>eth1.490</interface>
    <dhcpv4>
      <dhcp-server-identifier>192.168.49.88</dhcp-server-identifier>
      <domain-name>vvdntech.com</domain-name>
      <domain-name-servers>192.168.49.88</domain-name-servers>
      <interface-mtu>1500</interface-mtu>
      <default-gateways>192.168.49.88</default-gateways>
      <netconf-clients>
        <client>192.168.49.88</client>
      </netconf-clients>
    </dhcpv4>
  </interfaces>
</dhcp>
<active-alarm-list xmlns="urn:o-ran:fm:1.0">
  <active-alarms>
    <fault-id>18</fault-id>
    <fault-source>Module or antenna line</fault-source>
    <affected-objects>
```

```
<name>Sync Module</name>
</affected-objects>
<fault-severity>CRITICAL</fault-severity>
<is-cleared>false</is-cleared>
<fault-text>Synchronization Error</fault-text>
<event-time>2103-10-30T00:03:20Z</event-time>
</active-alarms>
</active-alarm-list>
<software-inventory xmlns="urn:o-ran:software-management:1.0">
  <software-slot>
    <name>swSlot1</name>
    <status>VALID</status>
    <active>false</active>
    <running>false</running>
    <access>READ_WRITE</access>
    <product-code>STL=O-RU</product-code>
    <vendor-code>VN</vendor-code>
    <build-id>factory_img</build-id>
    <build-name>Beta Release</build-name>
    <build-version>1.0.0</build-version>
    <files>
      <name>boot</name>
      <version>1.0.0</version>
      <local-path>/media/sd-mmcb1k0p1/BOOT0001.BIN</local-path>
      <integrity>OK</integrity>
    </files>
    <files>
      <name>kernel</name>
      <version>1.0.0</version>
      <local-path>/media/sd-mmcb1k0p1/image0001.ub</local-path>
      <integrity>OK</integrity>
    </files>
    <files>
      <name>rootfs</name>
      <version>1.0.0</version>
      <local-path>/media/sd-mmcb1k0p2/</local-path>
      <integrity>OK</integrity>
    </files>
  </software-slot>
  <software-slot>
    <name>swSlot2</name>
    <status>VALID</status>
    <active>true</active>
    <running>true</running>
    <access>READ_WRITE</access>
    <product-code>STL=O-RU</product-code>
    <vendor-code>VN</vendor-code>
    <build-id>abaa284</build-id>
    <build-name>Beta Release</build-name>
```

```
<build-version>1.0.1</build-version>
<files>
  <name>boot</name>
  <version>1.0.0</version>
  <local-path>/media/sd-mmcb1k0p1/BOOT0002.BIN</local-path>
  <integrity>OK</integrity>
</files>
<files>
  <name>kernel</name>
  <version>1.0.0</version>
  <local-path>/media/sd-mmcb1k0p1/image0002.ub</local-path>
  <integrity>OK</integrity>
</files>
<files>
  <name>rootfs</name>
  <version>1.0.0</version>
  <local-path>/media/sd-mmcb1k0p3/</local-path>
  <integrity>OK</integrity>
</files>
</software-slot>
<software-slot>
  <name>swRecoverySlot</name>
  <status>VALID</status>
  <active>false</active>
  <running>false</running>
  <access>READ_ONLY</access>
  <product-code>STL=O-RU</product-code>
  <vendor-code>VN</vendor-code>
  <build-id>factory_img</build-id>
  <build-name>Beta Release</build-name>
  <build-version>1.0.0</build-version>
  <files>
    <name>boot</name>
    <version>1.0.0</version>
    <local-path>/media/sd-mmcb1k0p1/BOOT0003.BIN</local-path>
    <integrity>OK</integrity>
  </files>
  <files>
    <name>kernel</name>
    <version>1.0.0</version>
    <local-path>/media/sd-mmcb1k0p1/golden.ub</local-path>
    <integrity>OK</integrity>
  </files>
  <files>
    <name>rootfs</name>
    <version>1.0.0</version>
    <local-path>/media/sd-mmcb1k0p1/golden.ub</local-path>
    <integrity>OK</integrity>
  </files>
```

```
</software-slot>  
</software-inventory>  
</data>
```



```
=====
##### SYSTEM LOGS #####
=====
```

Expected Result : The O-RU NETCONF Server responds with <rpc-reply><data> where <data> contains all information elements that the O-RU NETCONF Server is able to expose

=====

***** **Actual Result** *****

=====

=====

Retrieval without Filter Applied	=	SUCCESS
---	----------	----------------

=====