



@ FILE NAME: M_CTC_ID_018.txt

@ TEST SCOPE: M PLANE O-RAN CONFORMANCE

@ Software Release for MCB1: v1.0.7

Test Description: This scenario is MANDATORY for an O-RU supporting the Hybrid M-plane architecture model.

This test validates that user management model can be used to add users to

the O-RU

This scenario corresponds to the following chapters in [3]:

3.3 SSH Connection Establishment

3.4 NETCONF Access Control



STEP 1. The TER NETCONF Client establishes a connection with the O-RU NETCONF Server.

****** Connect to the NETCONF Server ********

> connect --ssh --host 192.168.3.38 --port 830 --login operator

ssh-rsa key fingerprint is c0:7c:63:5d:4b:85:e7:27:e0:7e:f0:44:38:4e:ab:83

Interactive SSH Authentication done.

> status

Current NETCONF session:

ID : 7

Host : 192.168.3.38

Port: 830 Transport: SSH Capabilities:

 $urn: ietf: params: netconf: base: 1.0 \ urn: ietf: params: netconf: base: 1.1 \ urn: ietf: params: netconf: capability: writable-running: 1.0 \ urn: ietf: params: netconf: base: 1.0 \ urn: ietf: params: netconf: params: ne$

 $urn: ietf: params: netconf: capability: candidate: 1.0\ urn: ietf: params: netconf: capability: rollback-on-error: 1.0\ urn: ietf: params: netconf: params: netconf$

 $urn: ietf: params: netconf: capability: validate: 1.1 \ urn: ietf: params: netconf: capability: startup: 1.0 \ urn: ietf: params: netconf: capability: xpath: 1.0 \ urn: ietf: params: netcon$

urn:ietf:params:netconf:capability:with-defaults:1.0?basic-mode=explicit&also-supported=report-all,report-all-tagged,trim,explicit

urn:ietf:params:netconf:capability:notification:1.0 urn:ietf:params:netconf:capability:interleave:1.0

urn:ietf:params:xml:ns:yang:ietf-yang-metadata?module=ietf-yang-metadata&revision=2016-08-05

urn:ietf:params:xml:ns:yang:1?module=yang&revision=2017-02-20

urn:ietf:params:xml:ns:yang:ietf-inet-types?module=ietf-inet-types&revision=2013-07-15

urn: ietf: params: xml: ns: yang: ietf-yang-types? module = ietf-yang-types & revision = 2013-07-15

urn:ietf:params:netconf:capability:yang-library:1.1?revision=2019-01-04&content-id=63

urn:sysrepo:plugind?module=sysrepo-plugind&revision=2020-12-10

urn:ietf:params:xml:ns:yang:ietf-netconf-acm?module=ietf-netconf-acm&revision=2018-02-14

urn:ietf:params:xml:ns:netconf:base:1.0?module=ietf-netconf&revision=2013-09-29&features=writable-running,candidate,rollback-on-error,valid

ate,startup,url,xpath urn:ietf:params:xml:ns:yang:ietf-netconf-with-defaults?module=ietf-netconf-with-defaults&revision=2011-06-01

urn: ietf: params: xml: ns: yang: ietf-net conf-notifications? module = ietf-net conf-notifications & revision = 2012-02-06

urn:ietf:params:xml:ns:yang:ietf-netconf-monitoring?module=ietf-netconf-monitoring&revision=2010-10-04

urn: ietf: params: xml: ns: netconf: notification: 1.0? module = notifications & revision = 2008-07-14

urn:ietf:params:xml:ns:netmod:notification?module = nc-notifications & revision = 2008-07-14

urn: ietf: params: xml: ns: yang: ietf-x509-cert-to-name? module = ietf-x509-cert-to-name & revision = 2014-12-10

urn:ietf:params:xml:ns:yang:iana-crypt-hash?module=iana-crypt-hash&revision=2014-08-06 urn:notification_history?module=notification_history

urn: ietf: params: xml: ns: yang: iana-if-type? module = iana-if-type & revision = 2017-01-19

> subscribe --filter-xpath /ietf-netconf-notifications:*

Ok



####### Initial Get ####### > get --filter-xpath /o-ran-usermgmt:users/user _____ <?xml version="1.0" ?> <data xmlns="urn:ietf:params:xml:ns:netconf:base:1.0" xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0"> <users xmlns="urn:o-ran:user-mgmt:1.0"> <user> <name>oranuser</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>operator</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>observer</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>installer</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>user1</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>User2</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>User3</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>user2</name>

<account-type>PASSWORD</account-type>



```
<enabled>true</enabled>
</user>
<user>
 <name>user3</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>user4</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>operator9272416</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>operator08457170344525021180394</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>operator1767096287497333</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>operator450724443082658</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>operator0217</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>operator7460405868</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>operator42833240511400619</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
</users>
</data>
```



STEP 2. The TER NETCONF Client configures three new user accounts in addition to the default sudo account already present and passwords these three accounts using o-ran-user.mgmt.yang > edit-config --target running --config --defop merge ****** Replace with below xml ****** <config xmlns="urn:ietf:params:xml:ns:netconf:base:1.0"> <users xmlns="urn:o-ran:user-mgmt:1.0"> <user> <name>operator965</name> <account-type>PASSWORD</account-type> <password>lhJXr5du5-VrMIFO]fedAWJ}pM[rP-B^7D9qb}z03-J.oAzrvPzJ9mr{Zn\${N.aP!}(Z.4X]!~QIbrS{XA]CnM2ODK-4iXA2(\$TWOI_7\$_ fj]a}3w31WKAG5qO</password> <enabled>true</enabled> </user> <user> <name>operator3249335383741066206078</name> <account-type>PASSWORD</account-type> <password>CXA0k-{_b}.nUw5t%q%Um+VFT%NcdjLb2+Q0ijv(qpX.N)QDHGhf5JQQ5T.uPIu)}FX\$0-Rp\$V-QV6+2d4i.bmJSYer(p</password</p> <enabled>true</enabled> </user> <user> <name>operator722935085376687940113</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> </users> </config> ####### RPC Reply ######## Ok



```
<?xml version="1.0" ?>
<notification xmlns="urn:ietf:params:xml:ns:netconf:notification:1.0">
<eventTime>2000-11-04T00:17:50Z</eventTime>
<netconf-config-change xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-notifications">
 <changed-by>
 <username>root</username>
 <session-id>7</session-id>
 </changed-by>
 <datastore>running</datastore>
 <edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user[o-ran-usermgmt:name='operator965']</target>
 <operation>create</operation>
 </edit>
 <edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user[o-ran-usermgmt:name='operator965']/o-ran-userm
gmt:name</target>
 <operation>create</operation>
 </edit>
 <edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:userso-ran-usermgmt:name='operator965']/o-ran-usermgmt:name="operator965']/o-ran-usermgmt:name="operator965"]
gmt:account-type</target>
 <operation>create</operation>
 </edit>
 <edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user[o-ran-usermgmt:name='operator965']/o-ran-userm
gmt:password</target>
 <operation>create</operation>
 </edit>
 <edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user[o-ran-usermgmt:name='operator965']/o-ran-userm
gmt:enabled</target>
 <operation>create</operation>
 </edit>
 <edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user[o-ran-usermgmt:name='operator32493353837410
66206078']</target>
 <operation>create</operation>
 </edit>
 <edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user[o-ran-usermgmt:name='operator32493353837410
66206078']/o-ran-usermgmt:name</target>
 <operation>create</operation>
```



```
</edit>
<edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user[o-ran-usermgmt:name='operator32493353837410
66206078']/o-ran-usermgmt:account-type</target>
 <operation>create</operation>
</edit>
<edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:users/o-ran-usermgmt:name='operator32493353837410
66206078']/o-ran-usermgmt:password</target>
 <operation>create</operation>
</edit>
<edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user[o-ran-usermgmt:name='operator32493353837410
66206078']/o-ran-usermgmt:enabled</target>
 <operation>create</operation>
</edit>
<edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:users/o-ran-usermgmt:name='operator72293508537668
7940113']</target>
 <operation>create</operation>
</edit>
<edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user[o-ran-usermgmt:name='operator72293508537668
7940113']/o-ran-usermgmt:name</target>
 <operation>create</operation>
</edit>
<edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user[o-ran-usermgmt:name='operator72293508537668
7940113']/o-ran-usermgmt:account-type</target>
 <operation>create</operation>
</edit>
<edit>
 <target
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:user[o-ran-usermgmt:name='operator72293508537668
7940113']/o-ran-usermgmt:password</target>
 <operation>create</operation>
</edit>
<edit>
xmlns:o-ran-usermgmt="urn:o-ran:user-mgmt:1.0">/o-ran-usermgmt:users/o-ran-usermgmt:users/o-ran-usermgmt:name='operator72293508537668
7940113']/o-ran-usermgmt:enabled</target>
 <operation>create</operation>
</edit>
```





</netconf-config-change>
</notification>



####### STEP 3. The TER NETCONF Client configures user account to group mappings for the three new accounts using ietf-netconf-acm.yang respectively one with "nms", one with "fm-pm" and one with "swm" privilege. ######## > edit-config --target running --config --defop merge ****** Replace with below xml ****** <config xmlns="urn:ietf:params:xml:ns:netconf:base:1.0"> <nacm xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-acm"> <groups> <group> <name>fm-pm</name> <user-name>operator965</user-name> </group> <group> <name>nms</name> <user-name>operator3249335383741066206078</user-name> </group> <group> <name>swm</name> <user-name>operator722935085376687940113</user-name> </group> </groups> </nacm> </config> STEP 4. The O-RU NETCONF Server confirms the operations for the above transactions. Ok <?xml version="1.0" ?> <notification xmlns="urn:ietf:params:xml:ns:netconf:notification:1.0"> <eventTime>2000-11-04T00:17:50Z</eventTime> <netconf-config-change xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-notifications"> <changed-by> <username>root</username> <session-id>7</session-id>



```
</changed-by>
   <datastore>running</datastore>
   <edit>
     <target
 xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm">/nacm:nacm/nacm:groups/nacm:group[nacm:name='fm-pm']/nacm:user-name[.='ope
rator965']</target>
    <operation>create</operation>
   </edit>
   <edit>
     <target
 xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm">/nacm:nacm/nacm:groups/nacm:group[nacm:name='nms']/nacm:user-name[.='operat
or3249335383741066206078']</target>
     <operation>create</operation>
   </edit>
   <edit>
    <target xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm">/nacm:nacm/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/nacm:groups/n
    <operation>create</operation>
   </edit>
   <edit>
    <target
 xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm">/nacm:nacm/nacm:groups/nacm:group[nacm:name='swm']/nacm:name</target>
     <operation>create</operation>
   </edit>
   <edit>
    <target
 xmlns:nacm="urn:ietf:params:xml:ns:yang:ietf-netconf-acm">/nacm:nacm/nacm:groups/nacm:groups/nacm:name='swm']/nacm:user-name[.='opera
tor722935085376687940113']</target>
     <operation>create</operation>
   </edit>
  </netconf-config-change>
 </notification>
> get --filter-xpath /ietf-netconf-acm:nacm/groups
 <?xml version="1.0" ?>
```

```
<?xml version="1.0" ?>
<data xmlns="urn:ietf:params:xml:ns:netconf:base:1.0" xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
<nacm xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-acm">
<groups>
<groups>
<name>sudo</name>
<user-name>operator</user-name>
<user-name>operator7460405868</user-name>
<user-name>operator42833240511400619</user-name>
</group>
<group>
<name>fm-pm</name>
<user-name>observer</user-name>
<user-name>observer</user-name>
<user-name>operator965</user-name>
<user-name>operator965</user-name>
<user-name>operator965</user-name>
```



```
</group>
<group>
<name>nms</name>
<user-name>installer</user-name>
<user-name>operator3249335383741066206078</user-name>
</group>
<group>
<name>swm</name>
<user-name>operator722935085376687940113</user-name>
</group>
</group>
</group>
</groups
</groups
</nacm>
</data>
```

STEP 5. The TER NETCONF Client retrieves a list of users from O-RU NETCONF Server. The newly created user accounts and mappings are validated.

> get --filter-xpath /o-ran-usermgmt:users/user

```
<?xml version="1.0" ?>
<data xmlns="urn:ietf:params:xml:ns:netconf:base:1.0" xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
<users xmlns="urn:o-ran:user-mgmt:1.0">
<user>
 <name>oranuser</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>operator</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
<user>
 <name>observer</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
 </user>
<user>
 <name>installer</name>
 <account-type>PASSWORD</account-type>
 <enabled>true</enabled>
</user>
 <name>user1</name>
 <account-type>PASSWORD</account-type>
```

<enabled>true</enabled>



```
</user>
<user>
<name>User2</name>
<account-type>PASSWORD</account-type>
<enabled>true</enabled>
</user>
<user>
<name>User3</name>
<account-type>PASSWORD</account-type>
<enabled>true</enabled>
</user>
<user>
<name>user2</name>
<account-type>PASSWORD</account-type>
<enabled>true</enabled>
</user>
<user>
<name>user3</name>
<account-type>PASSWORD</account-type>
<enabled>true</enabled>
</user>
<user>
<name>user4</name>
<account-type>PASSWORD</account-type>
<enabled>true</enabled>
</user>
<user>
<name>operator9272416</name>
<account-type>PASSWORD</account-type>
<enabled>true</enabled>
</user>
<user>
<name>operator08457170344525021180394</name>
<account-type>PASSWORD</account-type>
<enabled>true</enabled>
</user>
<user>
<name>operator1767096287497333</name>
<account-type>PASSWORD</account-type>
<enabled>true</enabled>
</user>
<user>
<name>operator450724443082658</name>
<account-type>PASSWORD</account-type>
<enabled>true</enabled>
</user>
<user>
<name>operator0217</name>
<account-type>PASSWORD</account-type>
```



<enabled>true</enabled> </user> <user> <name>operator7460405868</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>operator42833240511400619</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>operator965</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>operator3249335383741066206078</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> <user> <name>operator722935085376687940113</name> <account-type>PASSWORD</account-type> <enabled>true</enabled> </user> </users> </data>



- Nov 4 00:16:46 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
- Nov 4 00:16:47 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
- Nov 4 00:16:49 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
- Nov 4 00:16:50 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
- Nov 4 00:16:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:16:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- $Nov\ 4\ 00:16:52\ mcb1\ user.warn\ pm_manager[1373]:\ Failed\ to\ open\ / media/sd-mmcblk0p4/O-RAN/log/timezone.\ Using\ default\ value...$
- $Nov\ 4\ 00:16:52\ mcb1\ user.warn\ pm_manager[1373]:\ Failed\ to\ open\ / media/sd-mmcblk0p4/O-RAN/log/timezone.\ Using\ default\ value...$
- $Nov\ 4\ 00:16:52\ mcb1\ user.warn\ pm_manager[1373]:\ Failed\ to\ open\ / media/sd-mmcblk0p4/O-RAN/log/timezone.\ Using\ default\ value...$
- $Nov\ 4\ 00:16:52\ mcb1\ user.warn\ pm_manager[1373]:\ Failed\ to\ open\ / media/sd-mmcblk0p4/O-RAN/log/timezone.\ Using\ default\ value...$
- Nov 4 00:16:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value... Nov 4 00:16:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:16:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:16:52 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
- Nov 4 00:16:53 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
- Nov 4 00:16:54 mcb1 user.notice SYNCMNGR[1307]: Received message from S-Plane
- Nov 4 00:16:55 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
- Nov 4 00:16:56 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
- Nov 4 00:16:58 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
- Nov 4 00:16:59 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
- Nov 4 00:17:01 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
- Nov 4 00:17:02 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:02 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- $Nov\ 4\ 00:17:02\ mcb1\ user.warn\ pm_manager[1373]:\ Failed\ to\ open\ / media/sd-mmcblk0p4/O-RAN/log/timezone.\ Using\ default\ value...$
- Nov 4 00:17:02 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:02 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- $Nov\ 4\ 00:17:02\ mcb1\ user.warn\ pm_manager[1373]:\ Failed\ to\ open\ / media/sd-mmcblk0p4/O-RAN/log/timezone.\ Using\ default\ value...$
- Nov 4 00:17:02 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- $Nov\ 4\ 00:17:02\ mcb1\ user.warn\ pm_manager[1373]:\ Failed\ to\ open\ / media/sd-mmcblk0p4/O-RAN/log/timezone.\ Using\ default\ value...$
- $Nov\ 4\ 00:17:02\ mcb1\ user.warn\ pm_manager[1373]:\ Failed\ to\ open\ / media/sd-mmcblk0p4/O-RAN/log/timezone.\ Using\ default\ value...$
- Nov 4 00:17:02 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
- Nov 4 00:17:04 mcb1 user.notice SYNCMNGR[1307]: Received message from S-Plane
- Nov 4 00:17:05 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
- $Nov\ \ 4\ 00:17:06\ mcb1\ daemon. info\ net opeer 2-server [986]: Trying\ to\ connect\ via\ IPv4\ to\ 192.168.4.15:4336.$
- Nov 4 00:17:08 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
- Nov 4 00:17:09 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
- Nov 4 00:17:11 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
- Nov 4 00:17:12 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:12 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- $Nov\ 4\ 00:17:12\ mcb1\ user.warn\ pm_manager[1373]:\ Failed\ to\ open\ / media/sd-mmcblk0p4/O-RAN/log/timezone.\ Using\ default\ value...$
- Nov 4 00:17:12 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:12 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value... Nov 4 00:17:12 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:12 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:12 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...



```
Nov 4 00:17:12 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:12 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:14 mcb1 user.notice SYNCMNGR[1307]: Received message from S-Plane
Nov 4 00:17:14 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
Nov 4 00:17:15 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:17 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
Nov 4 00:17:18 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:20 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
Nov 4 00:17:21 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:22 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:22 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:22 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:22 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:22 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:22 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:22 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:22 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:22 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:23 mcb1 user.notice wd manager[1442]: Value is 1 for Xpath /vvdn mcel-wdm:system-apps/fw manager
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/nw_manager
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/operations_manager
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/pm_manager
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/um_manager
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/sys_monitor
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/fault_manager
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/file_manager
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/supervision
Nov 4 00:17:23 mcb1 user.notice wd manager [1442]: Value is 1 for Xpath /vvdn mcel-wdm:system-apps/sync manager
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/ald_controller
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/log_manager
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/radio_manager
Nov 4 00:17:23 mcb1 user.notice wd_manager[1442]: Value is 1 for Xpath /vvdn_mcel-wdm:system-apps/cli_manager
Nov 4 00:17:23 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
Nov 4 00:17:24 mcb1 user.notice SYNCMNGR[1307]: Received message from S-Plane
Nov 4 00:17:24 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:26 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
Nov 4 00:17:27 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:29 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
Nov 4 00:17:30 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:32 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:32 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:32 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:32 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:32 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:32 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:32 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:32 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:32 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:32 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
```



```
Nov 4 00:17:33 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:34 mcb1 user.notice SYNCMNGR[1307]: Received message from S-Plane
Nov 4 00:17:35 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
Nov 4 00:17:36 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:38 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
Nov 4 00:17:39 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:41 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
Nov 4 00:17:42 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:42 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:42 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:42 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:42 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:42 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:42 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:42 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:42 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
Nov 4 00:17:42 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:44 mcb1 user.notice SYNCMNGR[1307]: Received message from S-Plane
Nov 4 00:17:44 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
Nov 4 00:17:45 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Accepted a connection on :::830.
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Session 265 (user "root", CID 1) created.
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Received an SSH message "request-service" of subtype "ssh-userauth".
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Received an SSH message "request-auth" of subtype "password".
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: User "operator" authenticated.
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Received an SSH message "request-channel-open" of subtype "session".
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Received an SSH message "request-channel" of subtype "subsystem".
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Session 266 (user "root", CID 1) created.
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: There are no subscribers for "ietf-netconf-notifications" notifications.
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Generated new event (netconf-session-start).
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Published event "rpc" "/ietf-netconf:get" with ID 15 priority 0 for 1 subscribers.
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Processing "/ietf-netconf:get" "rpc" event with ID 15 priority 0 (remaining 1
subscribers).
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Successful processing of "rpc" event with ID 15 priority 0 (remaining 0 subscribers).
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Event "rpc" with ID 15 priority 0 succeeded.
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.
Nov 4 00:17:47 mcb1 daemon.info netopeer2-server[986]: Session 7: thread 0 event new RPC.
```

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Published event "rpc" "/ietf-netconf:get" with ID 16 priority 0 for 1 subscribers.



subscribers).

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Published event "operational" "/o-ran-software-management:software-inventory" with ID 7.

Nov 4 00:17:48 mcb1 user.notice fw_manager[1061]: RPC #7 recieved. xpath -> /o-ran-software-management:software-inventory

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Event "operational" with ID 7 succeeded.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "VVDN=O-RU", but it is not required.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "VVDN O-RU", but it is not required.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "STL=O-RU", but it is not required.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Successful processing of "rpc" event with ID 16 priority 0 (remaining 0 subscribers).

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Event "rpc" with ID 16 priority 0 succeeded.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "VVDN=O-RU", but it is not required.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "VVDN O-RU", but it is not required.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/o-ran-hardware:product-code" with the value "STL=O-RU", but it is not required.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Session 7: thread 0 event new RPC.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Published event "rpc" "/ietf-netconf:get-config" with ID 10 priority 0 for 1 subscribers.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Processing "/ietf-netconf:get-config" "rpc" event with ID 10 priority 0 (remaining 1 subscribers).

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Successful processing of "rpc" event with ID 10 priority 0 (remaining 0 subscribers).

Nov $4\,00:17:48\,$ mcb1 daemon.info netopeer2-server[986]: Event "rpc" with ID 10 priority 0 succeeded.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

 $Nov\ 4\ 00:17:48\ mcb1\ daemon. info\ net opeer 2-server [986]:\ Resolving\ unresolved\ data\ nodes\ and\ their\ constraints...$

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/ietf-hardware:name" with the value "ru-port1", but it is not required.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/ietf-hardware:name" with the value "ru-port1", but it is not required.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: There is no leafref

"/ietf-hardware:hardware/ietf-hardware:component/ietf-hardware:name" with the value "ru-port1", but it is not required.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Session 7: thread 2 event new RPC.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...



Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Published event "rpc" "/notifications:create-subscription" with ID 6 priority 1 for 1 subscribers.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Processing "ietf-netconf-monitoring" "operational" event with ID 7.

Nov 4 00:17:48 mcb1 daemon.info netopeer2-server[986]: Successful processing of "operational" event with ID 7.

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Event "rpc" with ID 6 priority 1 succeeded.

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Published event "rpc" "/notifications:create-subscription" with ID 6 priority 0 for 1 subscribers.

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Processing "/notifications:create-subscription" "rpc" event with ID 6 priority 0 (remaining 1 subscribers).

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Successful processing of "rpc" event with ID 6 priority 0 (remaining 0 subscribers).

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Event "rpc" with ID 6 priority 0 succeeded.

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Session 7: thread 0 event new RPC.

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Published event "rpc" "/ietf-netconf:get" with ID 17 priority 0 for 1 subscribers.

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Processing "/ietf-netconf:get" "rpc" event with ID 17 priority 0 (remaining 1 subscribers).

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Successful processing of "rpc" event with ID 17 priority 0 (remaining 0 subscribers).

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Event "rpc" with ID 17 priority 0 succeeded.

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:49 mcb1 daemon.info netopeer2-server[986]: Session 7: thread 0 event new RPC.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

 $Nov\ \ 4\ 00:17:50\ mcb1\ daemon. info\ net opeer 2-server [986]:\ All\ data\ nodes\ and\ constraints\ resolved.$

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Published event "rpc" "/ietf-netconf:edit-config" with ID 11 priority 0 for 1 subscribers.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Processing "/ietf-netconf:edit-config" "rpc" event with ID 11 priority 0 (remaining 1 subscribers).

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: edit-config error-option "stop-on-error" not supported, rollback-on-error will be performed.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

 $Nov\ \ 4\ 00:17:50\ mcb1\ daemon. info\ net opeer 2-server [986]: Published\ event\ "change"\ "o-ran-usermgmt"\ with\ ID\ 3\ priority\ 0\ for\ 1\ subscribers.$

Nov 4 00:17:50 mcb1 user.notice USERMGMT[1050]: operator965 added successfully !!

Nov 4 00:17:50 mcb1 user.notice USERMGMT[1050]: operator965 enabled !!

Nov 4 00:17:50 mcb1 user.notice USERMGMT[1050]: operator3249335383741066206078 added successfully !!

Nov 4 00:17:50 mcb1 user.notice USERMGMT[1050]: operator3249335383741066206078 enabled !!

Nov 4 00:17:50 mcb1 user.notice USERMGMT[1050]: operator722935085376687940113 added successfully !!

Nov 4 00:17:50 mcb1 user.notice USERMGMT[1050]: operator722935085376687940113 enabled !!

Nov 4 00:17:50 mcb1 user.notice USERMGMT[1050]: END OF CHANGES

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Event "change" with ID 3 priority 0 succeeded.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Published event "done" "o-ran-usermgmt" with ID 3 priority 0 for 1 subscribers.

Nov 4 00:17:50 mcb1 user.notice USERMGMT[1050]: END OF CHANGES

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...



Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of "/o-ran-usermgmt:users/user[name='operator965']", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of "/o-ran-usermgmt:users/user[name='operator965']/name", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator965']/account-type", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of "/o-ran-usermgmt:users/user[name='operator965']/password", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of "/o-ran-usermgmt:users/user[name='operator965']/enabled", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator3249335383741066206078']", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator3249335383741066206078']/name", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator3249335383741066206078']/account-type", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator3249335383741066206078']/password", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator3249335383741066206078']/enabled", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator722935085376687940113']", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator722935085376687940113']/name", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator722935085376687940113']/account-type", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator722935085376687940113']/password", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator722935085376687940113']/enabled", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Processing "notif" "ietf-netconf-notifications" event with ID 1.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Successful processing of "notif" event with ID 1 priority 0 (remaining 0 subscribers).

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Published event "notif" "ietf-netconf-notifications" with ID 2 priority 0 for 1 subscribers.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Successful processing of "rpc" event with ID 11 priority 0 (remaining 0 subscribers).

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Event "rpc" with ID 11 priority 0 succeeded.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of "/o-ran-usermgmt:users/user[name='operator965']", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of "/o-ran-usermgmt:users/user[name='operator965']/name", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator965']/account-type", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of "/o-ran-usermgmt:users/user[name='operator965']/password", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of "/o-ran-usermgmt:users/user[name='operator965']/enabled", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of



"/o-ran-usermgmt:users/user[name='operator3249335383741066206078']", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator3249335383741066206078']/name", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator3249335383741066206078']/account-type", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator3249335383741066206078']/password", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator3249335383741066206078']/enabled", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator722935085376687940113']", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator722935085376687940113']/name", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator722935085376687940113']/account-type", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Session 7: thread 0 event new RPC.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator722935085376687940113']/password", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/o-ran-usermgmt:users/user[name='operator722935085376687940113']/enabled", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Processing "notif" "ietf-netconf-notifications" event with ID 2.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Successful processing of "notif" event with ID 2 priority 0 (remaining 0 subscribers).

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

 $Nov\ \ 4\ 00:17:50\ mcb1\ daemon. info\ net opeer 2-server [986]:\ All\ data\ nodes\ and\ constraints\ resolved.$

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Published event "rpc" "/ietf-netconf:edit-config" with ID 12 priority 0 for 1 subscribers.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Processing "/ietf-netconf:edit-config" "rpc" event with ID 12 priority 0 (remaining 1 subscribers).

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: edit-config error-option "stop-on-error" not supported, rollback-on-error will be performed.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Published event "done" "ietf-netconf-acm" with ID 5 priority 0 for 4 subscribers.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Processing "ietf-netconf-acm" "done" event with ID 5 priority 0 (remaining 4 subscribers).

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Successful processing of "done" event with ID 5 priority 0 (remaining 0 subscribers).

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Published event "notif" "ietf-netconf-notifications" with ID 3 priority 0 for 1 subscribers.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/ietf-netconf-acm:nacm/groups/group[name='fm-pm']/user-name[.='operator965']", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/ietf-netconf-acm:nacm/groups/group[name='nms']/user-name[.='operator3249335383741066206078']", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of "/ietf-netconf-acm:nacm/groups/group[name='swm']", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of "/ietf-netconf-acm:nacm/groups/group[name='swm']/name", but it is not required.

Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: There is no instance of

"/ietf-netconf-acm:nacm/groups/group[name='swm']/user-name[.='operator722935085376687940113']", but it is not required.



- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Processing "notif" "ietf-netconf-notifications" event with ID 3.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Successful processing of "notif" event with ID 3 priority 0 (remaining 0 subscribers).
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Successful processing of "rpc" event with ID 12 priority 0 (remaining 0 subscribers).
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Event "rpc" with ID 12 priority 0 succeeded.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Session 7: thread 3 event new RPC.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Published event "rpc" "/ietf-netconf;get-config" with ID 11 priority 0 for 1 subscribers.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Processing "/ietf-netconf:get-config" "rpc" event with ID 11 priority 0 (remaining 1 subscribers).
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Successful processing of "rpc" event with ID 11 priority 0 (remaining 0 subscribers).
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Event "rpc" with ID 11 priority 0 succeeded.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Session 7: thread 3 event new RPC.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Published event "rpc" "/ietf-netconf:get-config" with ID 12 priority 0 for 1 subscribers.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Processing "/ietf-netconf:get-config" "rpc" event with ID 12 priority 0 (remaining 1 subscribers).
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Successful processing of "rpc" event with ID 12 priority 0 (remaining 0 subscribers).
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Event "rpc" with ID 12 priority 0 succeeded.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Resolving unresolved data nodes and their constraints...
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: All data nodes and constraints resolved.
- Nov 4 00:17:50 mcb1 daemon.info netopeer2-server[986]: Session 7: thread 3 event new RPC.
- Nov 4 00:17:51 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
- Nov 4 00:17:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:52 mcb1 user.warn pm_manager[1373]: Failed to open /media/sd-mmcblk0p4/O-RAN/log/timezone. Using default value...
- Nov 4 00:17:52 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
- Nov 4 00:17:54 mcb1 daemon.info netopeer2-server[986]: getsockopt() error (No route to host).
- Nov 4 00:17:54 mcb1 user.notice SYNCMNGR[1307]: Received message from S-Plane
- Nov 4 00:17:55 mcb1 daemon.info netopeer2-server[986]: Trying to connect via IPv4 to 192.168.4.15:4336.
- Nov 4 00:17:56 mcb1 daemon.info netopeer2-server[986]: Session 7: thread 3 event new RPC.
- Nov 4 00:17:56 mcb1 daemon.info netopeer2-server[986]: Session 7: thread 3 event session terminated.
- Nov 4 00:17:56 mcb1 daemon.info netopeer2-server[986]: There are no subscribers for "ietf-netconf-notifications" notifications.
- Nov 4 00:17:56 mcb1 daemon.info netopeer2-server[986]: Generated new event (netconf-session-end).
- Nov 4 00:17:56 mcb1 authpriv.debug sshd[3798]: pam_unix(sshd:account): account operator has password changed in future



Nov 4 00:17:56 mcb1 auth.info sshd[3798]: Accepted password for operator from 192.168.3.15 port 40790 ssh2 Nov 4 00:17:56 mcb1 authpriv.info sshd[3798]: pam_unix(sshd:session): session opened for user operator by (uid=0)



| Expected Result : The TER NETCONF Client retrieves a list of users from O-RU | |
|--|--|
| NETCONF Server. The newly created user accounts and mappings are validated. | |
| | |
| ******* | |
| | |
| Sudo on Hybrid M-plane Architecture (positive case) = SUCCESS | |
| | |