HP-200 Torque and Fluid Specifications

Document ID: MM-HP-200-TS

Revision: 2

Owner: Maintenance Planner

Torque Specifications

Use a calibrated torque wrench (see QCS-004). Lubricate threads with clean ISO VG 46 oil unless the note says otherwise. Apply LOTO per SOP-SAF-001 before working on the press.

Fastener	Location	Size	Torque (ft-lb)	Pattern / note
Gland retainer bolts	Main cylinder	M20	210	Star pattern, 2 passes
Cylinder mounting bolts	Crown	M30	650	Star pattern, 3 passes
Platen clamp bolts	Moving platen	M24	380	Cross pattern
Guide post nuts	Columns	M64	1,450	Hydraulic tensioner only
Pump coupling set screws	Power unit	M10	35	Blue thread locker
Accumulator mounting U-bolts	Power unit	1/2 in	60	Re-check after 24 h

Fluid Specifications

Fluid	Specification	Capacity	Change interval
Hydraulic oil	ISO VG 46 anti-wear	120 gal	4,000 h or annually
Guide post grease	EP-2 lithium	-	Monthly
Accumulator gas	Dry nitrogen	1,400 psi pre-charge	Check monthly

Escalation

Contact the Maintenance Planner (ext. 4410) for any fastener not listed here.