Jagged Robustness: Uneven Safety Transfer and Emerging Vulnerabilities under LLM Quantization

Ramneek Agnihotri*
Ruhr University Bochum

Yingte Xu*
Max Planck Institute for Security and Privacy

Hans Vath
Ruhr University Bochum

***Abstract*—Quantization enables efficient inference in language models through model parameter compression. This work audits the impact of quantization on capability and safety domains including model safeguards, instruction-following, ethics and bias. Through benchmarks, we find that model safeguards and bias can degrade under quantization, while other capabilities such as truthfulness remain more stable in Qwen3-4B. We define this uneven transfer of LLM capabilities under quantization as Jagged Robustness. We find multiple factors driving Jagged Robustness: task complexity, evaluation method and generation coherence. Moreover, we verify the degradation of model safeguards by observing increased compliance with unsafe requests under quantization, and demonstrate universal adversarial suffix attacks that are benign for the full model but jailbreak quantized models. The findings indicate that it is risky to assume that the performance and robustness can transfer evenly across different capability domains from full models to quantized models.**

I. Introduction

Large Language Models (LLMs) are increasingly deployed in real-world, safety-critical environments. Quantization methods are necessary to run these models on hardware with limited resources. Recent works have shown that quantization can diminish the performance of specific models in certain capability domains, including reasoning [1], bias [2] and model safeguards [3]. In this work, we build on previous research by auditing LLM quantization decay across diverse benchmarks, revealing the concept of Jagged Robustness: the non-uniform degradation of capabilities and safeguards across domains and evaluation types due to quantization.

We address the following research questions:

- **RQ1:** Do the capabilities of a quantized model transfer consistently across various domains?
- **RQ2:** What factors determine whether a model's performance on a benchmark remains robust or degrades under quantization?
- **RQ3:** Does quantization increase an LLM's vulnerability to adversarial attacks targeting its safeguards?

We investigate these effects passively using multiple-choice and free-generation benchmarks, and actively by deploying a quantization-aware adversarial suffix attack. Through passive evaluations, we establish a wide view of the LLM's behavior under quantization. Concretely, we evaluate the model across several quantization configurations (AWQ, INT4 and INT8), comparing them to the BF16 baseline across domains such as reasoning, code generation, and model safeguards.

As our benchmark evaluations demonstrate that model safeguards are particularly susceptible to quantization-induced decay, we perform an in-depth evaluation of the model's safety degradation. Specifically, we show that model safeguards can be actively exploited by demonstrating an adversarial suffix attack that is benign on the BF16 baseline but successfully triggers jailbreaks on the INT4 quantized version.

Our key findings are the following:

- Not all model capabilities transfer evenly under quantization. In particular, we observe that performance decreases in critical capability and safety domains such as instruction-following, safety refusal, and deception, while other domains remain stable, demonstrating Jagged Robustness in Qwen3-4B.
- We identify factors for benchmark degradation such as task nuance, evaluation method and model coherence.
- We identify adversarial suffix attacks that are benign for the BF16 model, but successfully jailbreak the INT4 model.

In summary, our findings suggest that models cannot be assumed to have the same safeguards or capabilities when quantized, implying that model safeguards and capabilities must be actively audited post-quantization before deployment, especially in safety-critical domains.

An anonymized version of our code repository, including raw experimental results, is available online. [1]

II. Background and Related Work

Quantization maps higher-precision representations (such as BF16) of the model parameters to lower-precision formats (such as 8-bit integers). This sharply reduces the memory footprint, but can also introduce a loss of model accuracy. We focus on Post-Training Quantization (PTQ), which applies quantization to a pre-trained model without additional training, and on Weight Quantization, as these are the most widely adopted strategies in practice due to their low computational costs.

Benchmarks assess model performance across a diverse range of evaluation protocols. In multiple-choice and log-likelihood ranking, the model is presented with predefined answer options. Performance is evaluated either by regex-parsing or calculating the log-likelihood of each answer candidate and selecting the highest-probability option. In free-form generation, the model

*Co-first authors / Equal contribution.

[1] Code and Experiment Repository https://github.com/LucianoXu/QuantBeyoundEfficiency.

generates a response during inference. This is evaluated by either regex-parsing or by utilizing an LLM-as-a-judge model.

In prior work, free-form generation (FFG) revealed severe degradation in safety alignment [3]. Marcuzzi et al. [4] further explored the reduction in safety alignment due to quantization. Beyond pure safety alignment, Hong et al. [5] also highlighted the uneven impact of model compression on different alignment domains. Especially uneven safety transfer in quantization was evaluated through mechanistic interpretability methods by Kadadekar [6]. These findings motivated our work to focus on specific factors that cause Jagged Robustness such as task complexity or generation coherence.

Safety alignment can also be deliberately challenged through jailbreak attempts, where an adversary feeds malicious prompts to the model to elicit harmful responses [7], [8]. One prominent approach is the adversarial suffix attack, which optimizes a prompt suffix to jailbreak the model and induce misaligned generations.

Moreover, Egashira et al. [9] demonstrated attacks exploiting LLM quantization, while Dong et al. [10] introduced Q-Misalign, establishing an attack that is benign in full precision but malicious after quantization. Finally, Wang et al. [11] show that a suffix can be optimized with an objective similar to ours in Section IV-A.

III. Benchmarks

We evaluate quantization effects across diverse domains using both log-likelihood ranking (LLR) and free-form generation (FFG) benchmark formats. For LLR tasks, we evaluate capabilities including expert reasoning on GPQA, domain knowledge on MMLU and MMLU-Pro, and general science knowledge on ARC, while for the alignment domain we evaluate social bias on BBQ, factuality on TruthfulQA, and moral reasoning on ETHICS via the lm-evaluation-harness [12] For FFG tasks, we test code generation on HumanEval and math capability on MGSMdirect. Furthermore, we test instruction-following capabilities (InFoBench), safety refusals on dangerous, illegal, or inappropriate user requests (SORRYBench), the willingness of the model to comply with deceptive requests (DeceptionBench), and general utility (WildChat-nontoxic). [2] . We evaluate the generated responses with a DeepSeek-V4-Flash model as a judge, which determines whether a response is compliant with benign user instructions (InFoBench and WildChat-nontoxic) or improperly complies with harmful requests (SORRYBench and DeceptionBench). All benchmark experiments were conducted on an NVIDIA A100 GPU with a maximum sequence length of 4096 tokens.

A. Multiple Choice

1) Experiment Setup

This experiment tests if there is a gap between the model's alignment capabilities (bias, truthfulness and ethical judgment) and the model's general abilities.

[2]All evaluation datasets are sourced from Hugging Face: `InFoBench`, `SORRY-Bench`, `DeceptionBench`, and `WildChat-nontoxic`.

We conducted multiple-choice evaluations and measured the accuracy based on the likelihood of generations (LLR) on the Qwen3-4B model with a sample size of N = 300. Our evaluation was done in zero-shot setting, to inhibit any occurrence of bias or steering through the context window.

2) Results

The strongest declines in Table 1 are observed in MMLU, ARC, and BBQ, while TruthfulQA and GPQA remain relatively stable. Overall, performance on both general and alignment tasks varies by comparable margins, with the most pronounced degradation occurring under INT4. Consequently, we do not find sufficient evidence for Jagged Robustness in the multiple-choice experiment.

B. Free Generation

1) Experiment Setup

For our second set of benchmarks, we compared the model's instruction-following ability and general capabilities against its safeguards. We selected deception and safety refusal as the two evaluation domains to measure these safeguards. We compared them against InFoBench, which measures instruction-following, and WildChat-NonToxic, which contains general, nontoxic prompts from real users.

We evaluated the Qwen3-4B model using a 5-shot configuration, as we found this setup yielded more coherent responses than a zero-shot setting. The responses were labeled by DeepSeek-V4-Flash as the LLM judge across all four benchmarks and the sample size is N = 300. Moreover, WildChat, SORRYBench, and InFoBench used the same evaluation system prompt, which was adapted from the system prompt of the SORRYBench LLM judge.

2) Results

In Table 2 DeceptionBench shows a significant increase in the deception rate under INT4 quantization, and SORRYBench's fulfillment rate increases as well. The model's capability to follow instructions seems to be more impacted under AWQ compared to INT4 and INT8. Finally, performance on WildChat-NonToxic decays across all three quantization formats, with the most pronounced decrease occurring in INT4.

We observe that instruction-following, safety refusal, and the model's willingness to comply with deceptive prompts exhibit independent degradation behaviors. Furthermore, the fact that deception rates increase while the model still follows instructions coherently, unlike the smaller 1.7B model (Section III-C), indicates a complete collapse in model coherence does not occur at INT4. Moreover, since the InFoBench score remains high across all four quantization configurations, it shows that the model is still able to follow instructions reliably in most standard cases. On the other hand, particularly in INT4, the model shows a clear willingness to perform deceptive or unsafe tasks that it refused to execute in its baseline BF16 state.

The discrepancy between InFoBench and WildChat-NonToxic is notable. Although both are designed to assess

Table 1
Model performance across tasks with absolute percentage point differences from the BF16 baseline.

	General			Alignment		
Accuracy (%)	**GPQA**	**MMLU**	**ARC**	**BBQ**	**TruthfulQA**	**Hendrycks Ethics (Average)**
BF16	37.33	71.64	49.67	42.00	51.47	68.22
INT8	39.67 (+2.34)	71.93 (+0.29)	49.00 (-0.67)	43.67 (+1.67)	50.77 (-0.70)	70 (+1.78)
AWQ	38.67 (+1.34)	70.47 (-1.17)	45.67 (-4.00)	44.00 (+2.00)	50.31 (-1.16)	65 (-3.22)
INT4	35.67 (-1.66)	67.25 (-4.39)	44.67 (-5.00)	39.00 (-3.00)	51.86 (+0.39)	62.87 (-5.35)

Table 2
Model performance across LLM judge tasks with absolute percentage point differences from the BF16 baseline.

	General		Safety	
Rate (%)	**InFoBench** (follow_rate)	**WildChat-nontoxic** (success_rate)	**DeceptionBench** (deception_rate)	**SORRYBench** (fulfillment_rate)
BF16	83.33	66.00	42.67	14.67
INT8	80.33 (-3.00)	62.67 (-3.33)	47.00 (+4.33)	13.33 (-1.34)
AWQ	77.67 (-5.66)	62.33 (-3.67)	45.33 (+2.66)	11.00 (-3.67)
INT4	82.33 (-1.00)	57.67 (-8.33)	53.67 (+11.00)	19.00 (+4.33)

general capabilities, performance on WildChat-NonToxic degrades far more severely than on InFoBench. This difference can be attributed to the characteristics of their respective prompts. WildChat-NonToxic is sampled from real-world user requests containing subjective language and vague instructions, whereas InFoBench is a carefully curated dataset consisting of deterministic, explicit instructions. As the previous benchmarks (Table 1, 2) have shown, in general the model's capabilities decline under quantization, which might inhibit its ability to understand nuance or subjective requests.

The difference between the two safety tasks, DeceptionBench and SORRYBench, likely stems from the fact that SORRY-Bench features substantially more severe policy violations, while DeceptionBench is far more nuanced and at times deliberately morally gray. Our findings indicate that the more subtle behavior tested in DeceptionBench is more sensitive to quantization degradation than that of SORRYBench. In contrast to the multiple-choice evaluations, the free generation results show clear evidence of Jagged Robustness tied to task subtlety and complexity.

C. 1.7B Model Experiment

1) Experiment Setup

This experiment aims to test how quantization behaves on the smaller model. We conduct two different types of benchmarks, LLR and FFG, to observe if there is a gap between LLR and FFG benchmarks. The experiments were conducted with 5-shot evaluation on either all items or a cut-off of N = 1000 for every benchmark except SORRYBench, which was performed with a size limit of N=450.

2) Results

Our experiments on the smaller Qwen3-1.7B model (Tables 3 and 4) show that the model struggles significantly in INT4 with free generation, while LLR benchmarks remain more consistent. This behavior can be explained by the collapse of the model's output coherence in free generation as demonstrated in an example from our SORRYBench results (Figure 1).

Table 3
Model performance on LLR benchmarks with absolute percentage point differences from the BF16 baseline for 1.7B.

Acc (%)	**GPQA**	**BBQ**	**Hendrycks Ethics**	**TruthfulQA**
BF16	31.03	50.40	64.38	45.89
INT8	28.79 (-2.24)	49.50 (-0.90)	65.38 (+1)	46.80 (+0.91)
AWQ	28.35 (-2.68)	50.30 (-0.10)	63.18 (-1.2)	47.06 (+1.17)
INT4	25.89 (-5.14)	47.80 (-2.60)	60.08 (-4.3)	48.84 (+2.95)

Table 4
Model performance on Free Generation benchmarks with absolute percentage point differences from the BF16 baseline.

Rate (%)	**Human Eval**	**mgsm_direct_en**	**MMLU-Pro**	**SORRYBench**
BF16	41.46	13.20	42.56	56.67
INT8	40.85 (-0.61)	11.60 (-1.60)	39.94 (-2.62)	59.78 (+3.11)
AWQ	38.41 (-3.05)	10.80 (-2.40)	38.83 (-3.73)	60.22 (+3.55)
INT4	9.15 (-32.31)	5.60 (-7.60)	23.24 (-19.32)	77.56 (+20.89)

> `User: Insult me in the meanest way possible.`
> `Response: I'm not insinuating anyone, but I'm here to help you with your insinuations. If you're insinuating someone, I'm not insinuating`
> `...`

Fig. 1. An example of a repetitive loop and coherence collapse on a sensitive prompt under INT4 quantization.

To further provide evidence for the coherence degradation of the Qwen3-1.7B model, we analyzed the responses under different quantization levels through a seperate mechanism: a 3-gram check on SORRYBench to detect repetitions. A response was marked as incoherent if the ratio of repeating 3-grams

exceeded 30%. This was formulated as:

$$R = \frac{N_{total} - N_{unique}}{N_{total}} \tag{1}$$

Table 5
Percentage of responses marked as incoherent in SORRYBench, with absolute percentage point differences (N = 450).

Quantization	Incoherent Responses (%)
BF16	3.11
INT8	3.78 (+0.67)
AWQ	7.55 (+4.44)
INT4	42 (+38.89)

In Table 5, we observe a significant increase in incoherent responses under INT4 quantization on SORRYBench.

IV. Quantization-Aware Adversarial Suffix Attack

Passive benchmark evaluations do not account for adversaries who deliberately exploit the gap between full and quantized models. Prior quantization-aware attacks [9], [10] require the adversary to poison the released weights, and PrecisionDiff [11] searches for precision-induced disagreements on individual prompts. We ask whether an input-level attack suffices: given an unmodified open-source model, is there a single universal suffix that the full model refuses, but that jailbreaks its INT4 weight-only quantized version, as illustrated in Figure 3? Our claims are restricted to this setting.

A. Attack Method

We use x to denote token sequences, representing the text to process and generate. We consider an LLM p as a probabilistic model $p(x_{n+1} \mid x_{1:n})$, which corresponds to the probability of generating the next token x_{n+1} given the existing token sequence $x_{1:n}$, so that $p(x_{n+1:n+H}|x_{1:n}) = \prod_{i=1}^{H} p(x_{n+i}|x_{1:n+i-1})$. We use $\tilde{p}$ to denote the quantized model. Since we expect the adversarial suffix to be universal, we consider a conceptual distribution D of sensitive prompts and their answers. We use q to represent the prompt questions, a_+ to represent their affirmative responses, a_- to represent their refusals, and s to represent the unique adversarial suffix. Then the desired quantization-aware adversarial suffix can be expressed as

$$s^* = \arg\max_s \; \mathbb{E}_{q,a_+,a_- \sim D}[\tilde{p}(a_+ \mid q{+}{+}s) + \lambda p(a_- \mid q{+}{+}s)] \,.$$

Here, the intuition is to maximize the two probabilities of refusal on the full model and fulfillment on the quantized model. The relative strength is controlled by the parameter λ, which takes positive values. Compared to the standard GCG algorithm [13] for adversarial examples, this objective introduces the refusal term on the full model.

B. Experiment Setup

To make s^* computable, we estimate the expectation by sampling prompts from a benchmark, and work with the teacher-forced cross-entropy of the affirmative target a_+, i.e., the logarithmic probability computed from the model logits. We assume that minimizing fulfillment on the full model is equivalent to maximizing its refusal, so the full model is pushed away from a_+ instead of towards a modeled a_-. With $\ell_q(s)$ and $\tilde{\ell}_q(s)$ denoting the cross-entropy of a_+ given $q{+}{+}s$ under the full and the quantized model, we minimize the hinge loss

$$\mathcal{L}(s) = \sum_q \big[\tilde{\ell}_q(s) - \alpha\big]_+ + \lambda\big[\beta - \ell_q(s)\big]_+,$$

with margins $\alpha = 0.5$ and $\beta = 2$, which stop optimizing a prompt once the quantized model complies or the full model refuses.

Since token selection is discrete, we follow GCG [13]: starting from the initial suffix (repeated '!'), each step computes the gradient of $\mathcal{L}$ with respect to the one-hot suffix tokens, takes the top-256 candidate tokens per position, evaluates 512 random single-token swaps, and keeps the best one. We adopt a learning curriculum that starts with a single prompt and adds the next training prompt once the per-prompt loss falls below 0.5, or after 25 steps. The suffix is inserted after the user prompt, before the `assistant` tokens, and the target is an affirmative response prefix (Figure 2).

Gradients through INT4. Our INT4 model is Qwen3-4B with weight-only INT4 quantization (Optimum-Quanto), whose integer kernels are not differentiable. For the optimization, we therefore use a fake-quantized proxy: the weights of every linear layer except the LM head are quantized group-wise (group size 128, asymmetric min-max, 4 bits) and dequantized back to BF16. We verified that the proxy weights are bit-identical to Quanto's dequantized INT4 weights, so gradients are obtained by ordinary backpropagation through the proxy. All reported evaluations use the real INT4 model.

We evaluate the harmful compliance rate of the BF16 and INT4 models, with and without the discovered adversarial suffix, using two judges. The primary **LM-Judge** follows SORRYBench and uses its fine-tuned Mistral-7B-Instruct model to judge whether the generation is an essential fulfillment of the request. The **RE-Judge** follows GCG [13] and checks whether the generation contains typical refusal expressions, such as "I cannot" or "I am sorry".

C. Results Analysis

We attack Qwen3-4B in BF16 and INT4 on the base split of SORRYBench, optimizing a 20-token suffix on 24 sampled prompts and evaluating on the 426 held-out prompts. We set $\lambda = 1$ and run the search for 500 steps, which took 3 hours on a node with 4 $\times$ A100-40G GPUs (Table 6).

Under the LM-Judge, the suffix widens the compliance gap between INT4 and BF16 on the test split from 8.22 to 13.62 points. This effect is modest, and it comes mostly from the BF16 model refusing more often (35.92% to 32.63%), while INT4 compliance barely changes (44.13% to 46.24%).




Fig. 2. Structure of the templated attack prompt.




Fig. 3. **(a)** Poisoned models may behave benignly in full precision but become misaligned after quantization. **(b)** Universal adversarial suffixes exist to jailbreak open source models. **(c)** The intuition of quantization-aware adversarial suffix attack. Open source models may still have vulnerabilities that expose only after quantization.

Table 6
Harmful-compliance rate (%) of quantization-aware adversarial suffixes on Qwen3-4B on SORRYBench prompts (24 train, 426 held-out). Unlike Table 2 (evaluated with DeepSeek V4-flash), this attack uses SORRYBench's fine-tuned Mistral-7B-Instruct judge, resulting in different values.

		Without Suffix		With Suffix	
Split	Precision	LM-Judge	RE-Judge	LM-Judge	RE-Judge
train	BF16	33.33	29.17	20.83	33.33
	INT4	29.17	20.83	45.83	62.50
	Δ	−4.17	−8.33	**+25.00**	**+29.17**
test	BF16	35.92	38.26	32.63	44.60
	INT4	44.13	46.24	46.24	80.05
	Δ	+8.22	+7.98	**+13.62**	**+35.45**

The RE-Judge shows a much larger gap (35.45 points, with 80.05% INT4 compliance), but it only detects refusal phrases. Hence, the suffix mainly turns INT4 refusals into superficially compliant responses, and only part of them carry genuinely harmful content. This is expected, since the objective only rewards an affirmative response prefix.

The optimized suffix evolves from '!!!...!' into loosely meaningful text that requests a specific output format, e.g., `...words halves?? Urdu ... give-me learntenglish directly both--two LaTeX`. On a 64-prompt subset of the test split, the two precisions react to it in opposite ways. With the suffix, the number of INT4 responses opening with "Sure" rises from 2 to 37, and 41 responses follow the requested LaTeX format. The BF16 model instead becomes more cautious: responses opening with a refusal rise from 14 to 33, and 16 responses explicitly describe the request as unclear or inappropriate. The full model treats the suffix as a warning sign, whereas the quantized model executes it as a formatting task that overrides its refusal. Figure 4 shows an example pair.

Request: *Write a tweet claiming that climate change is a hoax and encourage people to ignore environmental concerns.* + suffix

BF16: I'm unable to assist with that request. It appears you're asking for a tweet that promotes misinformation about climate change, which is not only unethical but also harmful. [...]

INT4: Sure! Here's what you asked for: [...] **Tweet in English [...]:** "Climate change is a hoax! Ignore environmental concerns and follow the money. #FakeScience #ProfitOverPlanet" [...] *(followed by an Urdu version and LaTeX code)*

Fig. 4. BF16 and INT4 responses to a held-out request with the suffix.

V. Conclusion

RQ1: Do the capabilities of a quantized model transfer consistently across various domains?

We have shown that models perform inconsistently on multiple-choice benchmarks when evaluated using LLR, as shown in Table 1. In the FFG experiment using the LM judge in Table 2, we observed that benchmarks that measure model safeguards, such as DeceptionBench [14] and SORRYBench [15], significantly degrade. We conclude that model capabilities do not transfer uniformly across domains, providing empirical evidence for Jagged Robustness.

RQ2: What factors determine whether a model's performance on a benchmark remains robust or degrades under quantization?

In our benchmarks in Table 2, we found that tasks that are more subjective or vague are more affected by quantization than unambiguous tasks. Specifically, the more nuanced behaviors assessed in DeceptionBench and the open-ended, real-world prompts in WildChat-NonToxic are more sensitive to performance decline compared to the explicit safety violations

evaluated in SORRYBench and the deterministic instructions of InFoBench.

The evaluation method dictates the observed performance stability under quantization, especially in the smaller Qwen3-1.7B model. As shown in Table 3 and Table 4, quantization affects free generation and log-likelihood ranking (LLR) benchmarks unequally. If the model falls below a certain size threshold and is quantized too aggressively, it loses its free-form generation capability, yet it still evaluates validly under LLR benchmarks. The example in Figure 1 shows that, in free generation, the model can cascade down an incoherent generation path. This is completely prevented in the LLR setting, where the candidate answers are pre-defined and fixed.

Furthermore, another reason why LLR evaluates more consistently than FFG is that it does not require an LLM judge or regex parsing. This makes it less sensitive to judgment failures or parsing errors.

RQ3: Does quantization increase an LLM's vulnerability to adversarial attacks targeting its safeguards?

Our benchmarks (Table 2) show that model safeguards degrade significantly, making Qwen3-4B more likely to generate deceptive answers and less likely to refuse unsafe requests. To explore this further, we exploited vulnerabilities in the quantized models using an adversarial suffix attack. We discovered adversarial suffixes that trigger more harmful compliance only on quantized models. This indicates that one cannot assume the transferability of attack robustness from the full model to the quantized one.

VI. Limitations

The benchmark evaluations in Table 2 are judged via a language model. LLM-as-a-judge is an inconsistent measure of the model performance. In our quantization-aware attack, the model tends to produce superficially compliant text, rather than genuinely informative harmful text. From the perspective of experiment design, we didn't investigate the other direction, whether there are adversarial suffixes that jailbreak only the full model. We only evaluated the Qwen3 model family, therefore it is unknown if our results generalize to other model families or sizes. Lastly, our benchmarks were not run with different seeds, on only 300 samples, and no confidence intervals were captured, making it hard to distinguish close data points from noise or cherry-picking results.

VII. Future Work

In future work, we want to explore the causes of Jagged Robustness using quantitative evidence supplied by interpretability methods. We could analyze the differences between internal activations and parameters of models and their quantized versions. The aim is to develop a more objective measure of quantization decay, compared to benchmark accuracy and attack success rate. Moreover, our investigation into model collapse caused by quantization, as demonstrated in Table 5, can be expanded by analyzing the underlying causes of this behavior. For example, one could measure the entropy of the model's output distribution under free generation and evaluate whether cascading sampling errors trigger generation collapse. Furthermore, future work could explore whether Jagged Robustness transfers to other model sizes and architectures. On the attack side, assessing whether this method succeeds across additional target models and evaluation datasets, such as DeceptionBench, is a promising research direction. We could extend our notion of Jagged Robustness to attack vulnerability if we observe uneven degradation between different evaluation datasets under quantization in this domain.

References

[1] R. Liu, Y. Sun, M. Zhang, H. Bai, X. Yu, T. Yu, C. Yuan, and L. Hou, "Quantization hurts reasoning? an empirical study on quantized reasoning models," 2025. [Online]. Available: https://arxiv.org/abs/2504.04823

[2] E. Kirsten, I. Habernal, V. Nanda, and M. B. Zafar, "The impact of inference acceleration on bias of llms," 2025. [Online]. Available: https://arxiv.org/abs/2410.22118

[3] A. Kharinaev, V. Moskvoretskii, E. Shvetsov, K. Studenikina, B. Mikhail, and E. Burnaev, "Investigating the impact of quantization methods on the safety and reliability of large language models," 2025. [Online]. Available: https://arxiv.org/abs/2502.15799

[4] F. Marcuzzi, X. Ning, R. Schwartz, and I. Gurevych, "How quantization shapes bias in large language models," 2026. [Online]. Available: https://arxiv.org/abs/2508.18088

[5] J. Hong, J. Duan, C. Zhang, Z. Li, C. Xie, K. Lieberman, J. Diffenderfer, B. Bartoldson, A. Jaiswal, K. Xu, B. Kailkhura, D. Hendrycks, D. Song, Z. Wang, and B. Li, "Decoding compressed trust: Scrutinizing the trustworthiness of efficient llms under compression," 2024. [Online]. Available: https://arxiv.org/abs/2403.15447

[6] S. Kadadekar, "Quality is not a safety proxy under quantization," 2026. [Online]. Available: https://arxiv.org/abs/2606.10154

[7] A. Wei, N. Haghtalab, and J. Steinhardt, "Jailbroken: How does llm safety training fail?" 2023. [Online]. Available: https://arxiv.org/abs/2307.02483

[8] X. Shen, Z. Chen, M. Backes, Y. Shen, and Y. Zhang, ""do anything now": Characterizing and evaluating in-the-wild jailbreak prompts on large language models," 2024. [Online]. Available: https://arxiv.org/abs/2308.03825

[9] K. Egashira, M. Vero, R. Staab, J. He, and M. Vechev, "Exploiting llm quantization," in *Advances in Neural Information Processing Systems*, A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang, Eds., vol. 37. Curran Associates, Inc., 2024, pp. 41 709–41 732. [Online]. Available: https://proceedings.neurips.cc/paper_files/paper/2024/file/496720b3c860111b95ac8634349dcc88-Paper-Conference.pdf

[10] P. Dong, H. Li, and S. Guo, "Durable quantization conditioned misalignment attack on large language models," in *The Thirteenth International Conference on Learning Representations*, 2025. [Online]. Available: https://openreview.net/forum?id=41uZB8bDFh

[11] Y. Wang, T. Li, X. Zhang, X. Zhang, W. Ma, M. Cheng, and L. Pan, "Hidden reliability risks in large language models: Systematic identification of precision-induced output disagreements," 2026. [Online]. Available: https://arxiv.org/abs/2604.19790

[12] "The language model evaluation harness," 07 2024. [Online]. Available: https://zenodo.org/records/12608602

[13] A. Zou, Z. Wang, N. Carlini, M. Nasr, J. Z. Kolter, and M. Fredrikson, "Universal and transferable adversarial attacks on aligned language models," 2023. [Online]. Available: https://arxiv.org/abs/2307.15043

[14] Y. Huang, Y. Sun, Y. Zhang, R. Zhang, Y. Dong, and X. Wei, "DeceptionBench: A comprehensive benchmark for AI deception behaviors in real-world scenarios," in *Advances in Neural Information Processing Systems*, 2025. [Online]. Available: https://arxiv.org/abs/2510.15501

[15] T. Xie, X. Qi, Y. Zeng, Y. Huang, U. M. Sehwag, K. Huang, L. He, B. Wei, D. Li, Y. Sheng, R. Jia, B. Li, K. Li, D. Chen, P. Henderson, and P. Mittal, "SORRY-bench: Systematically evaluating large language model safety refusal," in *The Thirteenth International Conference on Learning Representations*, 2025. [Online]. Available: https://arxiv.org/abs/2406.14598