

# Forecasting The Cumulative Cases of COVID-19 In Four Large Brazilian Cities Using Machine Learning Approaches

Ramon Gomes da Silva<sup>1</sup>

Matheus Henrique Dal Molin Ribeiro<sup>1,2</sup>

José Henrique Kleinübing Larcher<sup>3</sup>

Viviana Cocco Mariani<sup>3, 4</sup>

Leandro dos Santos Coelho<sup>1, 4</sup>

gomes.ramon@pucpr.edu.br, mribeiro@utfpr.edu.br, jose.kleinubing@pucpr.edu.br, viviana.mariani@pucpr.br,  
leandro.coelho@pucpr.br

<sup>1</sup>Industrial and Systems Engineering Graduate Program (PPGEPS), Pontifical Catholic University of Parana (PUCPR), 1155, Rua Imaculada Conceicao. Curitiba, PR, Brazil.

<sup>2</sup>Department of Mathematics, Federal Technological University of Parana (UTFPR). Via do Conhecimento, KM 01 - Fraron, Pato Branco, PR, Brazil.

<sup>3</sup>Mechanical Engineering Graduate Program (PPGEM), Pontifical Catholic University of Parana (PUCPR). 1155, Rua Imaculada Conceicao, Curitiba, PR, Brazil.

<sup>4</sup>Department of Electrical Engineering, Federal University of Parana (UFPR). 100, Avenida Coronel Francisco Heraclito dos Santos, Curitiba, PR, Brazil.

# Overview

- 1 Introduction**
- 2 Objective**
- 3 Dataset**
- 4 Proposed forecasting framework**
- 5 Findings**
- 6 Conclusion**

# **1 Introduction**

## 2 Objective

## 3 Dataset

## 4 Proposed forecasting framework

## 5 Findings

## 6 Conclusion

# Introduction



REUTERS

World

Business

Markets

Breakingviews

Video

More

HEALTHCARE & PHARMACEUTICALS

OCTOBER 26, 2020 / 6:59 PM / UPDATED A DAY AGO

## Brazil sees 15,726 new coronavirus cases, 263 new deaths: health minister

By Reuters Staff

1 MIN READ



BBC

Sign in

Home

News

Sport

Reel

Worklife

Travel

# NEWS

Home | US Election | Coronavirus | Video | World | US & Canada | UK | Business | Tech | Science | Stories

World | Africa | Asia | Australia | Europe | Latin America | Middle East

## Covid: Brazil's coronavirus cases pass five million

🕒 8 October

## Country Exceeds Covid-19 157,000 Deaths

Daily average of deaths in the last seven days, however, was 468, according to the consortium



### Brazil reaches 150,000 deaths from COVID-19 milestone

*Brazil's count of COVID-19 deaths has surpassed 150,000, despite signs the pandemic is slowly retreating in Latin America's largest nation*

By **MARCELO DE SOUSA** and **TATIANA POLASTRI**

10 October 2020, 22:29 • 4 min read



# Introduction

New coronavirus identified, currently named Severe Acute Respiratory Syndrome CoronaVirus 2 (SARS-CoV-2), causing the coronavirus disease 2019 (COVID-19).

Brazil has more than 5 million cases and 150 thousand deaths.

## Problems:

- Overcrowding of hospital beds;
- Lack of medical supplies to treat patients affected more severely;

## Short-term forecast allows to:

- Reallocate patients;
- Reapportion resources and staff;
- Alert residents of a determined region in case of a spike;

# Introduction

Models:

- Autoregressive Integrated Moving Average (ARIMA)
- $k$ -Nearest Neighbor (kNN)
- Support Vector Regression (SVR)
- Cubist Regression (CUBIST)
- Stacked Generalization (STACK)

1 Introduction

**2 Objective**

3 Dataset

4 Proposed forecasting framework

5 Findings

6 Conclusion



# Objective

Present a **time series forecasting framework** based on the use of **machine learning** to predict cumulative cases of COVID-19 achieving accurate predictions, being possibly useful for decision making authorities.

Use forecasting models (CUBIST, kNN, and SVR) cooperatively in the form of a **Stacked Generalization** to bring the accuracy level up.

1 Introduction

2 Objective

**3 Dataset**

4 Proposed forecasting framework

5 Findings

6 Conclusion

# Dataset


Aggregated data from Brazilian State Health Offices from March 13th until August 14th, 2020.

The data is gathered in a collaborative project with various contributors and made available with an API or direct download.

- Brasil.IO


**Cities:** Brasília (DF); Rio de Janeiro (RJ); Salvador (BA); and São Paulo (SP).

# Dataset



- 1 Introduction
- 2 Objective
- 3 Dataset
- 4 Proposed forecasting framework**
- 5 Findings
- 6 Conclusion

# Proposed forecasting framework



# Proposed forecasting framework

## Step 1

- Train-test split
- Normalization
- Past 5 days as features
- Recursive one-day-ahead model

# Proposed forecasting framework

## Step 2

- Base-learners (kNN and SVR) are trained and its predictions used as input for CUBIST meta-learner.
- Leave-one-out cross-validation is used for training.
- Machine learning models use caret R package.
- ARIMA uses auto.arima function from forecast R package.
- All computations are made in R software environment.



# Proposed forecasting framework

## Step 3

- Out-of-sample metrics are computed:
  - Improved percentage index (IP)
  - Mean absolute error (MAE)
  - Root-mean-square error (RMSE)
  - Symmetric mean absolute percentage error (sMAPE)

- 1 Introduction
- 2 Objective
- 3 Dataset
- 4 Proposed forecasting framework
- 5 Findings**
- 6 Conclusion

# Findings - Brasília


STACK approach could be considered to forecast COVID-19 cases, once the model outperformed others in all performance criteria.

Regarding MAE the performance improved in the ranges of 38.59% – 96.58%.

## Ranking

- STACK
- ARIMA
- SVR
- kNN

# Findings - Brasília



# Findings - Rio de Janeiro


For Rio de Janeiro's cases, the SVR model achieved better accuracy than other models

The improvement in MAE ranged in 9.14% – 61.98%.

## Ranking

- SVR
- ARIMA
- STACK
- kNN

# Findings - Rio de Janeiro



# Findings - Salvador


STACK approach outperformed the other models in Salvador's cases.

MAE improvement ranged between 36.78% – 88.71%.

## Ranking

- STACK
- ARIMA
- SVR
- kNN

# Findings - Salvador





# Findings - São Paulo


STACK approach achieved better accuracy than other models.

The improvement in MAE ranged in 20.30% – 78.01%.

## Ranking

- STACK
- ARIMA
- SVR
- kNN

# Findings - São Paulo



# Findings - Overview

**Table:** Performance measures of the models

City	Criteria	ARIMA	kNN	STACK	SVR
Brasília	MAE	501.83	9020.17	<b>308.17</b>	3982.00
	RMSE	528.16	9471.26	<b>394.21</b>	4196.15
	sMAPE	0.44%	8.27%	<b>0.28%</b>	3.56%
Rio de Janeiro	MAE	1374.83	3285.83	2120.83	<b>1249.17</b>
	RRMSE	1700.76	3838.18	2734.95	<b>1502.23</b>
	sMAPE	1.78%	4.33%	2.76%	<b>1.62%</b>
São Paulo	MAE	673.33	3769.67	<b>425.67</b>	2346.83
	RMSE	766.89	4064.64	<b>500.17</b>	2429.35
	sMAPE	1.05%	6.02%	<b>0.66%</b>	3.57%
Salvador	MAE	3784.83	13716.50	<b>3016.50</b>	5277.33
	RRMSE	4242.16	15833.98	<b>3324.96</b>	7355.84
	sMAPE	1.69%	6.30%	<b>1.36%</b>	2.35%

- 1 Introduction
- 2 Objective
- 3 Dataset
- 4 Proposed forecasting framework
- 5 Findings
- 6 Conclusion**

# Conclusion

**Stacking-ensemble** learning and **SVR** models are suitable tools to forecast COVID-19 cases for most of the adopted cities.

These approaches were able to learn the **nonlinearities** inherent to the evaluated **epidemiological time series**.

**ARIMA** also showed good consistent results for a six-days-ahead time window.

# Conclusion

The ranking of models in **Rio de Janeiro**'s scenarios is:

- 1 SVR
- 2 ARIMA
- 3 STACK
- 4 KNN

For all the **other cities**:

- 1 STACK
- 2 ARIMA
- 3 SVR
- 4 KNN

# Conclusion

## Remark

- Even though the models discussed in this paper presented accurate forecasting capabilities, they should be used cautiously.
- The **dynamics** of the analyzed data, as well as the diversity of **exogenous factors** that can affect the daily notifications of COVID-19

# Acknowledgments





**Thank you!**