

Using easyGSA

Basic syntax of easyGSA

Typing easyGSA into command line should return a welcome text and ensure that the tool is available for use.

```
easyGSA
```

```
Copyright 2018-2019, Resul Al and Gurkan Sin, all rights reserved.  
This is easyGSA, version 1.2.0
```

```
easyGSA is a global sensitivity analysis (GSA) tool performing  
variance decomposition-based Sobol sensitivity analysis using machine  
learning algorithms, such as Gaussian process regression (GPR) and  
artificial neural networks (ANN). Main (Si) and total (STi) effects  
are returned.
```

```
To cite easyGSA in publications, please use:
```

```
Al, R., Behera, C.R., Zubov, A., Gernaey, K. V., Sin, G., 2019.  
Meta-modeling based efficient global sensitivity analysis for  
wastewater treatment plants - An application to the BSM2 model.  
Comput. Chem. Eng. 127, 233-246.  
https://doi.org/10.1016/j.compchemeng.2019.05.015
```

```
To request special permissions or suggest improvements, please contact:  
- Resul Al (resal@kt.dtu.dk) and Gurkan Sin (gsi@kt.dtu.dk)  
- Technical University of Denmark
```

Computing the first (Si) and the total (STi) order Sobol sensitivity indices

Step 1: Model is defined as a Matlab function handle f. The size of the sampling matrices is defined as N.

```
% Model: Ishigami function [https://www.sfu.ca/~ssurjano/ishigami.html]  
f = @(x) sin(x(:,1)) + 7.*sin(x(:,2)).^2 + 0.1.*x(:,3).^4.*sin(x(:,1));  
N = 1e4; % Number of MC samples. Minimum recommended: 1e3
```

Step 2: Input space is defined with a uniform distribution between lower and upper bounds of parameters that are subject to GSA.

```
% Uniform Input Space  
pars = strseq('x',1:3); % input parameter names  
lbs = -pi.*ones(1,3); % lower bounds of input parameters  
ubs = pi.*ones(1,3); % upper bounds of input parameters  
InputSpace = {'ParNames',pars,'LowerBounds',lbs,'UpperBounds',ubs};
```

Step 3: Calling the easyGSA tool with its basic syntax.

```
% call easyGSA tool to perform Sobol sensitivity analysis with MC approach  
[Si,STi] = easyGSA(f,N,InputSpace{:})
```

```
Copyright 2018-2019, Resul Al and Gurkan Sin, all rights reserved.  
This is easyGSA, version 1.2.0
```

```
easyGSA is a global sensitivity analysis (GSA) tool performing  
variance decomposition-based Sobol sensitivity analysis using machine  
learning algorithms, such as Gaussian process regression (GPR) and
```

artificial neural networks (ANN). Main (Si) and total (STi) effects are returned.

To cite easyGSA in publications, please use:

Al, R., Behera, C.R., Zubov, A., Gernaey, K. V., Sin, G., 2019.
Meta-modeling based efficient global sensitivity analysis for
wastewater treatment plants - An application to the BSM2 model.
Comput. Chem. Eng. 127, 233-246.
<https://doi.org/10.1016/j.compchemeng.2019.05.015>

To request special permissions or suggest improvements, please contact:

- Resul Al (resal@kt.dtu.dk) and Gurkan Sin (gsi@kt.dtu.dk)
- Technical University of Denmark

3 model inputs are found.

Sobol sampling is used to generate input matrices.

1 model output is found.

Your model is already vectorized.

Matrices are being filled with $@(x)\sin(x(:,1))+7.*\sin(x(:,2)).^2+0.1.*x(:,3).^4.*\sin(x(:,1))$

Matrix A is filled.

Matrix B is filled.

There are 3 inputs.

Matrix for input number 1 is filled.

Matrix for input number 2 is filled.

Matrix for input number 3 is filled.

All matrices in yAB are filled.

First Order Indices:

Output_1

x1	0.33489
x2	0.44526
x3	0.0091184

Total Order Indices:

Output_1

x1	0.54871
x2	0.43734
x3	0.23538

Si =

0.33489
0.44526
0.0091184

STi =

0.54871
0.43734
0.23538

More detailed syntax

More detailed results of the Sobol sensitivity analysis can also be extracted as the following.

```
[Si,STi,results] = easyGSA(f,N,InputSpace{:},...  
                           'SamplingMethod','LHS',... % default: 'Sobol'  
                           'Estimator','Saltelli',... % default: 'Jansen'  
                           'UseSurrogate','GPR',...   % options: 'GPR', 'ANN'  
                           'UseParallel',true,...     % default: false  
                           'Verbose',false)           % default: true
```

Copyright 2018-2019, Resul Al and Gurkan Sin, all rights reserved.
This is easyGSA, version 1.2.0

easyGSA is a global sensitivity analysis (GSA) tool performing variance decomposition-based Sobol sensitivity analysis using machine learning algorithms, such as Gaussian process regression (GPR) and artificial neural networks (ANN). Main (Si) and total (STi) effects are returned.

To cite easyGSA in publications, please use:

Al, R., Behera, C.R., Zubov, A., Gernaey, K. V., Sin, G., 2019.
Meta-modeling based efficient global sensitivity analysis for
wastewater treatment plants - An application to the BSM2 model.
Comput. Chem. Eng. 127, 233-246.
<https://doi.org/10.1016/j.compchemeng.2019.05.015>

To request special permissions or suggest improvements, please contact:

- Resul Al (resal@kt.dtu.dk) and Gurkan Sin (gsi@kt.dtu.dk)
- Technical University of Denmark

Si =

0.31103
0.45826
-0.0035807

STi =

0.54134
0.46899
0.22556

results = *struct with fields:*

```
GPRmodel: [1x1 RegressionGP]
GPRstats: [1x1 struct]
  A: [10000x3 double]
  AB: {[10000x3 double] [10000x3 double] [10000x3 double]}
  B: [10000x3 double]
Estimator: 'Saltelli'
LowerBounds: [-3.1416 -3.1416 -3.1416]
  Model: @(x)sin(x(:,1))+7.*sin(x(:,2)).^2+0.1.*x(:,3).^4.*sin(x(:,1))
  N: 10000
  ParNames: {3x1 cell}
  STi: [3x1 double]
SamplingMethod: 'LHS'
  Si: [3x1 double]
UpperBounds: [3.1416 3.1416 3.1416]
UseParallel: 1
UseSurrogate: 'GPR'
  UserData: [1x1 struct]
    X: [250x3 double]
    gprMdl: [1x1 RegressionGP]
    gprStats: [1x1 struct]
  n_outputs: 1
  results: [1x1 struct]
  verbose: 0
    y: [250x1 double]
    yA: [10000x1 double]
    yAB: {[10000x1 double] [10000x1 double] [10000x1 double]}
    yB: [10000x1 double]
```