ASSIGNMENT OS-LAB-02

Course code:CC311-LAB

Submitted by: Ramsha Arooj

Submitted to: Sir Kamran

Roll#:110763

Department: Information Technology

Semester:5th(Morning)

Linux Commands

-1 man:

This command displays reference pages for commands as well as it is used to displays summary of commands related to a keyword list.

Syntax:

man command list

```
ramsha@myVM:~$ man ls
ramsha@myVM:~$ man -kpasswd
a LibreOffice Writer
ramsha@myVM:~$ man -kpasswd
apropos what?
ramsha@myVM:~$ man -k passwd
chgpasswd (8)         - update group passwords in batch mode
chpasswd (8)          - update passwords in batch mode
gpasswd (1)           - administer /etc/group and /etc/gshadow
grub-mkpasswd-pbkdf2 (1) - generate hashed password for GRUB
openssl-passwd (1ssl) - compute password hashes
pam_localuser (8)     - require users to be listed in /etc/passwd
passwd (1)            - change user password
passwd (1ssl)         - compute password hashes
passwd (5)            - the password file
update-passwd (8)     - safely update /etc/passwd, /etc/shadow and /etc/group
```

-2 whatis:

This command is use for prints a one-line description of each keyword to screen.

Syntax: whatis keywords

Examples:

• Description of man command whatis man

• Description of login, set and setenv commands whatis login set setenv

```
ramsha@myVM:~$ whatis man
man (1)              - an interface to the system reference manuals
man (7)              - macros to format man pages
ramsha@myVM:~$ whatis login set setenv
login (1)            - begin session on the system
set: nothing appropriate.
setenv: nothing appropriate.
```

-3 Whereise:

This command is use for locates the binary, source and man page files for a command.

Syntax: whereis file_name

```
ramsha@myVM:~$ whereis ch
ch:
```

-4 whoami

This command use to displays the current user name.

Syntax:

whoami

```
ramsha@myVM:~$ whoami
ramsha
```

-5 lpr:

This command is use to sends file to the printer.

Syntax: lpr file_name

```
ramsha@myVM:~$ lpr -pspr orders.eps
lpr: Error - unable to access "orders.eps" - No such file or directory
```

-6 cal:

This command is use to displays the calendar on screen as text.

Syntax: cal [[month] year]

```
ramsha@myVM:~$ cal august 2005
    August 2005
Su Mo Tu We Th Fr Sa
    1  2  3  4  5  6
 7  8  9 10 11 12 13
14 15 16 17 18 19 20
21 22 23 24 25 26 27
28 29 30 31
```

```
ramsha@myVM:~$ cal 1992
                                   1992
       January                    February                      March
Su Mo Tu We Th Fr Sa   Su Mo Tu We Th Fr Sa   Su Mo Tu We Th Fr Sa
              1  2  3  4                     1    1  2  3  4  5  6  7
 5  6  7  8  9 10 11    2  3  4  5  6  7  8    8  9 10 11 12 13 14
12 13 14 15 16 17 18    9 10 11 12 13 14 15   15 16 17 18 19 20 21
19 20 21 22 23 24 25   16 17 18 19 20 21 22   22 23 24 25 26 27 28
26 27 28 29 30 31      23 24 25 26 27 28 29   29 30 31

        April                       May                       June
Su Mo Tu We Th Fr Sa   Su Mo Tu We Th Fr Sa   Su Mo Tu We Th Fr Sa
              1  2  3  4                  1  2       1  2  3  4  5  6
 5  6  7  8  9 10 11    3  4  5  6  7  8  9    7  8  9 10 11 12 13
12 13 14 15 16 17 18   10 11 12 13 14 15 16   14 15 16 17 18 19 20
19 20 21 22 23 24 25   17 18 19 20 21 22 23   21 22 23 24 25 26 27
26 27 28 29 30         24 25 26 27 28 29 30   28 29 30
                       31

         July                      August                   September
Su Mo Tu We Th Fr Sa   Su Mo Tu We Th Fr Sa   Su Mo Tu We Th Fr Sa
              1  2  3  4                     1           1  2  3  4  5
 5  6  7  8  9 10 11    2  3  4  5  6  7  8    6  7  8  9 10 11 12
12 13 14 15 16 17 18    9 10 11 12 13 14 15   13 14 15 16 17 18 19
19 20 21 22 23 24 25   16 17 18 19 20 21 22   20 21 22 23 24 25 26
26 27 28 29 30 31      23 24 25 26 27 28 29   27 28 29 30
                       30 31

      October                   November                  December
Su Mo Tu We Th Fr Sa   Su Mo Tu We Th Fr Sa   Su Mo Tu We Th Fr Sa
              1  2  3    1  2  3  4  5  6  7           1  2  3  4  5
 4  5  6  7  8  9 10    8  9 10 11 12 13 14    6  7  8  9 10 11 12
11 12 13 14 15 16 17   15 16 17 18 19 20 21   13 14 15 16 17 18 19
18 19 20 21 22 23 24   22 23 24 25 26 27 28   20 21 22 23 24 25 26
25 26 27 28 29 30 31   29 30                   27 28 29 30 31
```

```
ramsha@myVM:~$ cal 9 2025
   September 2025
Su Mo Tu We Th Fr Sa
    1  2  3  4  5  6
 7  8  9 10 11 12 13
14 15 16 17 18 19 20
21 22 23 24 25 26 27
28 29 30
```

7- alias:

used to create pseudonym for a command.

Syntax: alias [name= [string]]

8- unalias:

used to remove one or more alias from the alias list

Syntax: unalias [name]

```
ramsha@myVM:~$ alias
alias alert='notify-send --urgency=low -i "$([ $? = 0 ] && echo terminal || ech
o error)" "$(history|tail -n1|sed -e '\''s/^\s*[0-9]\+\s*//;s/[;&|]\s*alert$//'
\'')"'
alias egrep='egrep --color=auto'
alias fgrep='fgrep --color=auto'
a Rhythmbox 'grep --color=auto'
a -CF'
alias la='ls -A'
alias ll='ls -alF'
alias ls='ls --color=auto'
ramsha@myVM:~$ unalias rm
bash: unalias: rm: not found
ramsha@myVM:~$ unalias -a
ramsha@myVM:~$ biff

Command 'biff' not found, did you mean:

  command 'siff' from snap siff (1.0.0.0)
  command 'diff' from deb diffutils (1:3.7-3)
  command 'xbiff' from deb x11-apps (7.7+8)

See 'snap info <snapname>' for additional versions.
```

-9 hostname:

This command is use for displays the name of the host computer that you are logged onto.

Syntax: hostname

```
ramsha@myVM:~$ hostname
myVM
```

-10 login:

This command is use for log on to computer with a valid username.

Syntax: login [username]

```
ramsha@myVM:~$ login ramsha
login: Cannot possibly work without effective root
```

-11 mesg:

This command allows or disallows writing messages on the screen.

Syntax: mesg [y/n]

```
ramsha@myVM:~$ mesg n
ramsha@myVM:~$ mesg y
ramsha@myVM:~$ mesg
is y
```

-12 passwd:

This command allows to change password.

Syntax: passwd [options] [username]

```
ramsha@myVM:~$ passwd user1
passwd: user 'user1' does not exist
```

-13 telnet:

This command allows you to log on a computer on a network or internet.

Syntax: telnet [server_address] [port]

```
ramsha@myVM:~$ telnet localcost
telnet: could not resolve localcost/telnet: Temporary failure in name resolutio
n
ramsha@myVM:~$ telnet localhost
Trying 127.0.0.1...
telnet: Unable to connect to remote host: Connection refused
```

- 14 uname:

displays information about the operating system running the computer.

Syntax: uname

```
ramsha@myVM:~$ uname
Linux
```

-15 who:

This command allows you to find out log-in names of users currently on the system.

Syntax: who

```
ramsha@myVM:~$ who
ramsha   :0          2025-10-18 07:30 (:0)
```

-18 write: This command allows real time messaging between users on the system.

Syntax: write [y/n]

```
ramsha@myVM:~$ write
usage: write user [tty]
```

-19 talk:

This command allows you to send real time messages to other users.

Syntax: talk [username]

```
ramsha@myVM:~$ talk

Command 'talk' not found, did you mean:

  command 'kalk' from snap kalk (25.08.0)
  command 'walk' from snap walk (1.6.2)
  command 'tali' from snap tali (40.9)
  command 'task' from snap task (v3.43.3)

See 'snap info <snapname>' for additional versions.
```