ASSIGNMENT OS_LAB_01

Course code:CC311-LAB

Submitted by: Ramsha Arooj

Submitted to: Sir Kamran

Roll#:110763

Department: Information Technology

Semester:5th(Morning)

LINUX COMMANDS:

-1 mkdir (make directory)

Use to create new directory.

Syntax:

mkdir (new)directory name

```
ramsha@myVM:~$ mkdir first
ramsha@myVM:~$ ls
Desktop    first        myfile2.txt  Public         testdir  Videos
Documents  Music        myfile.txt   randomfile.txt textdir
Downloads  myfile1.txt  Pictures     Templates      txtdir
```

-2 cd (change directory)

Use to switch current working directory

Syntax:

cd (directory name)

```
ramsha@myVM:~$ cd first
ramsha@myVM:~/first$ pwd
/home/ramsha/first
```

-3 pwd (print working directory)

Displays the current working directory on screen.

```
ramsha@myVM:~/first$ pwd
/home/ramsha/first
```

-4 more

Use to display the files in file list on screen at time.

```
ramsha@myVM:~$ more myfile1.txt
This is my first file.
ramsha@myVM:~$ head -n10 myfile2.txt
This is my second file.
```

-5 cp

Cp is used to copy a file in other directory.

```
ramsha@myVM:~$ mkdir mywork
ramsha@myVM:~$ ls
Desktop    Music        myfile.txt  Public          testdir  Videos
Documents  myfile1.txt  mywork      randomfile.txt  textdir
Downloads  myfile2.txt  Pictures    Templates       txtdir
ramsha@myVM:~$ cp myfile.txt mywork
ramsha@myVM:~$ cd mywork
ramsha@myVM:~/mywork$ ls
myfile.txt
```

-6 ls

ls show names of files and directories on path specified.

```
ramsha@myVM:~$ ls
Desktop    Music        myfile.txt  randomfile.txt  textdir
Documents  myfile1.txt  Pictures    Templates       txtdir
Downloads  myfile2.txt  Public      testdir         Videos
ramsha@myVM:~$ ls -a
.             .config     .local       Pictures        Templates
..            Desktop     Music        .profile        testdir
.bash_logout  Documents   myfile1.txt  Public          textdir
.bashrc       Downloads   myfile2.txt  randomfile.txt  txtdir
.cache        .gnupg      myfile.txt   .ssh            Videos
ramsha@myVM:~$ ls -1
Desktop
Documents
Rhythmbox
myfile1.txt
myfile2.txt
myfile.txt
Pictures
Public
randomfile.txt
Templates
testdir
textdir
txtdir
Videos
```

-7 rmdir (remove directory)

This command is use to remove any directory.

Syntax:

rmdir (dir_name)

```
ramsha@myVM:~$ mkdir empty
ramsha@myVM:~$ ls
Desktop    empty        myfile2.txt  Pictures        Templates  txtdir
Documents  Music        myfile.txt   Public          testdir    Videos
Downloads  myfile1.txt  mywork       randomfile.txt  textdir
ramsha@myVM:~$ rmdir empty
ramsha@myVM:~$ ls
Desktop    Music        myfile.txt  Public          testdir  Videos
Documents  myfile1.txt  mywork      randomfile.txt  textdir
Downloads  myfile2.txt  Pictures    Templates       txtdir
```

-8 rm (remove files)

This command is use to remove file from the file list.

Syntax:

rm file_name

```
r Ubuntu Software touch emptyfile.txt
ramsha@myVM:~$ ls
Desktop    emptyfile.txt  myfile2.txt  Pictures        Templates  txtdir
Documents  Music          myfile.txt   Public          testdir    Videos
Downloads  myfile1.txt    mywork       randomfile.txt  textdir
ramsha@myVM:~$ rm emptyfile.txt
ramsha@myVM:~$ ls
Desktop    Music        myfile.txt  Public          testdir  Videos
Documents  myfile1.txt  mywork      randomfile.txt  textdir
Downloads  myfile2.txt  Pictures    Templates       txtdir
```

-9 mv

This command is use to rename any file.

Syntax:mv file_name_old file_name_new

```
ramsha@myVM:~$ mv myfile1.txt randomfile.txt
ramsha@myVM:~$ ls
Desktop    Music        mywork    randomfile.txt  textdir
Documents  myfile2.txt  Pictures  Templates       txtdir
Downloads  myfile.txt   Public    testdir         Videos
```

-10 cat

This command is use to:

- Join one or more files sequentially
- Show content of two file in order
- Show content of two files along with line number

Syntax:

cat file_name

```
ramsha@myVM:~$ cat myfile2.txt
This is my second file.
ramsha@myVM:~$ cat myfile1.txt myfile2.txt
This is my first file.
This is my second file.
ramsha@myVM:~$ cat -n myfile1.txt myfile2.txt
     1  This is my first file.
     2  This is my second file.
```

-11 touch

This command use to create a file.

Syntax:

Touch file_name

```
ramsha@myVM:~$ touch myfile2.txt
```

-12 echo

This command is use to add content in existing file.

Syntax: echo file_name

```
ramsha@myVM:~$ echo "This is my second file.">myfile2.txt
ramsha@myVM:~$ cat myfile2.txt
This is my second file.
```