Introduction to Robotics CSCI/ARTI 4530/6530

Dr. Ramviyas Nattanmai Parasuraman,
Asst. Professor, Computer Science, UGA

11/06/2018

Department of Computer Science
Franklin College of Arts and Sciences
UNIVERSITY OF GEORGIA

Agenda

- For today
  - Robot Motion Models – Odometry and Velocity Models
  - Slides from Thrun et al. – Probablistic Robotics

Probabilistic Motion Models

- To implement the Bayes Filter, we need the transition model $p(x \mid x', u)$.
- The term $p(x \mid x', u)$ specifies a posterior probability, that action u carries the robot from x' to x.
- In this section we will specify, how $p(x \mid x', u)$ can be modeled based on the motion equations.

Robot Motion

- Robot motion is inherently uncertain.
- How can we model this uncertainty?





Dynamic Bayesian Network for Controls, States, and Sensations



Coordinate Systems

- In general the configuration of a robot can be described by six parameters.
- Three-dimensional cartesian coordinates plus three Euler angles pitch, roll, and tilt.
- Throughout this section, we consider robots operating on a planar surface.
- The state space of such systems is three-dimensional (x,y,θ).



Typical Motion Models

- In practice, one often finds two types of motion models:
  - **Odometry-based**
  - **Velocity-based** (**dead reckoning**)
- Odometry-based models are used when systems are equipped with wheel encoders.
- Velocity-based models have to be applied when no wheel encoders are given.
- They calculate the new pose based on the velocities and the time elapsed.

Example Wheel Encoders

These modules require +5V and GND to power them, and provide a 0 to 5V output. They provide +5V output when they "see" white, and a 0V output when they "see" black.



These disks are manufactured out of high quality laminated color plastic to offer a very crisp black to white transition. This enables a wheel encoder sensor to easily see the transitions.

e-robots.com/

Dead Reckoning

- Derived from “deduced reckoning.”
- Mathematical procedure for determining the present location of a vehicle.
- Achieved by calculating the current pose of the vehicle based on its velocities and the time elapsed.

Reasons for Motion Errors



ideal case



different wheel diameters



bump



carpet

and many more …

Odometry Model

- Robot moves from $\langle \bar{x}, \bar{y}, \bar{\theta} \rangle$ to $\langle \bar{x}', \bar{y}', \bar{\theta}' \rangle$
- Odometry information $u = \langle \delta_{rot1}, \delta_{rot2}, \delta_{trans} \rangle$

$$\delta_{trans} = \sqrt{(\bar{x}' - \bar{x})^2 + (\bar{y}' - \bar{y})^2}$$

$$\delta_{rot1} = \operatorname{atan2}(\bar{y}' - \bar{y}, \bar{x}' - \bar{x}) - \bar{\theta}$$

$$\delta_{rot2} = \bar{\theta}' - \bar{\theta} - \delta_{rot1}$$


$\langle \bar{x}, \bar{y}, \bar{\theta} \rangle$
δ_{rot1}
δ_{trans}
δ_{rot2}
$\langle \bar{x}', \bar{y}', \bar{\theta}' \rangle$

The atan2 Function

- Extends the inverse tangent and correctly copes with the signs of x and y.

$$\mathrm{atan2}(y,x) \;=\; \begin{cases} \mathrm{atan}(y/x) & \text{if } x > 0 \\ \mathrm{sign}(y)\,(\pi - \mathrm{atan}(|y/x|)) & \text{if } x < 0 \\ 0 & \text{if } x = y = 0 \\ \mathrm{sign}(y)\,\pi/2 & \text{if } x = 0, y \neq 0 \end{cases}$$

Noise Model for Odometry

- The measured motion is given by the true motion corrupted with noise.

$$\hat{\delta}_{rot1} = \delta_{rot1} + \varepsilon_{\alpha_1 |\delta_{rot1}| + \alpha_2 |\delta_{trans}|}$$

$$\hat{\delta}_{trans} = \delta_{trans} + \varepsilon_{\alpha_3 |\delta_{trans}| + \alpha_4 |\delta_{rot1} + \delta_{rot2}|}$$

$$\hat{\delta}_{rot2} = \delta_{rot2} + \varepsilon_{\alpha_1 |\delta_{rot2}| + \alpha_2 |\delta_{trans}|}$$

Typical Distributions for Probabilistic Motion Models

Normal distribution



$$\varepsilon_{\sigma^2}(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{1}{2}\frac{x^2}{\sigma^2}}$$

Triangular distribution



$$\varepsilon_{\sigma^2}(x) = \begin{cases} 0 \text{ if } |\mathrm{x}| > \sqrt{6\sigma^2} \\ \dfrac{\sqrt{6\sigma^2} - |x|}{6\sigma^2} \end{cases}$$

Calculating the Probability (zero-centered)

- For a normal distribution

```
1.    Algorithm prob_normal_distribution($a$,$b$):
2.    return $\frac{1}{\sqrt{2\pi\, b^2}} \exp\left\{-\frac{1}{2}\frac{a^2}{b^2}\right\}$
```

- For a triangular distribution

```
1.    Algorithm prob_triangular_distribution($a$,$b$):
2.    return $\max\left\{0, \frac{1}{\sqrt{6}\, b} - \frac{|a|}{6\, b^2}\right\}$
```

Calculating the Posterior Given x, x’, and u

```
Algorithm motion_model_odometry(x,x’,u)
    $\delta_{trans} = \sqrt{(\bar{x}'-\bar{x})^2 + (\bar{y}'-\bar{y})^2}$
    $\delta_{rot1} = \mathrm{atan2}(\bar{y}'-\bar{y}, \bar{x}'-\bar{x}) - \bar{\theta}$
    $\delta_{rot2} = \bar{\theta}' - \bar{\theta} - \delta_{rot1}$
    $\hat{\delta}_{trans} = \sqrt{(x'-x)^2 + (y'-y)^2}$
    $\hat{\delta}_{rot1} = \mathrm{atan2}(y'-y, x'-x) - \bar{\theta}$
    $\hat{\delta}_{rot2} = \theta' - \theta - \hat{\delta}_{rot1}$
    $p_1 = \mathrm{prob}(\delta_{\mathrm{rot1}} - \hat{\delta}_{\mathrm{rot1}}, \alpha_1 |\hat{\delta}_{\mathrm{rot1}}| + \alpha_2 \hat{\delta}_{\mathrm{trans}})$
    $p_2 = \mathrm{prob}(\delta_{\mathrm{trans}} - \hat{\delta}_{\mathrm{trans}}, \alpha_3 \hat{\delta}_{\mathrm{trans}} + \alpha_4 (|\hat{\delta}_{\mathrm{rot1}}| + |\hat{\delta}_{\mathrm{rot2}}|))$
    $p_3 = \mathrm{prob}(\delta_{\mathrm{rot2}} - \hat{\delta}_{\mathrm{rot2}}, \alpha_1 |\hat{\delta}_{\mathrm{rot2}}| + \alpha_2 \hat{\delta}_{\mathrm{trans}})$
    return $p_1 \cdot p_2 \cdot p_3$
```



odometry values (u)

values of interest (x,x’)

Application

- Repeated application of the sensor model for short movements.
- Typical banana-shaped distributions obtained for 2d-projection of 3d posterior.



Sample-based Density Representation



Sample-based Density Representation



How to Sample from Normal or Triangular Distributions?

- Sampling from a normal distribution

```
1. Algorithm **sample_normal_distribution**($b$):
2. return $\frac{1}{2}\sum_{i=1}^{12} rand(-b, b)$
```

- Sampling from a triangular distribution

```
1. Algorithm **sample_triangular_distribution**($b$):
2. return $\frac{\sqrt{6}}{2}[\mathbf{rand}(-b, b) + \mathbf{rand}(-b, b)]$
```

Normally Distributed Samples



10^6 samples

For Triangular Distribution



10^3 samples



10^4 samples



10^5 samples



10^6 samples

Rejection Sampling

- Sampling from arbitrary distributions

```
Algorithm sample_distribution($f$,$b$):
repeat
    $x = \mathrm{rand}(-b, b)$
    $y = \mathrm{rand}(0, \max\{f(x) \mid x \in (-b, b)\})$
until $(y \leq f(x))$
return $x$
```

Example

- Sampling from

$$f(x) = \begin{cases} \text{abs}(x) & x \in [-1; 1] \\ 0 & \text{otherwise} \end{cases}$$



1.89550, 0.00400370

Sample Odometry Motion Model

```
1.  Algorithm sample_motion_model(u, x):
    $u = \langle \delta_{rot1}, \delta_{rot2}, \delta_{trans} \rangle, x = \langle x, y, \theta \rangle$
1.  $\hat{\delta}_{rot1} = \delta_{rot1} + \text{sample}(\alpha_1 |\delta_{rot1}| + \alpha_2\ \delta_{trans})$
2.  $\hat{\delta}_{trans} = \delta_{trans} + \text{sample}(\alpha_3\ \delta_{trans} + \alpha_4\ (|\delta_{rot1}| + |\delta_{rot2}|))$
3.  $\hat{\delta}_{rot2} = \delta_{rot2} + \text{sample}(\alpha_1 |\delta_{rot2}| + \alpha_2\ \delta_{trans})$

4.  $x' = x + \hat{\delta}_{trans} \cos(\theta + \hat{\delta}_{rot1})$
5.  $y' = y + \hat{\delta}_{trans} \sin(\theta + \hat{\delta}_{rot1})$
6.  $\theta' = \theta + \hat{\delta}_{rot1} + \hat{\delta}_{rot2}$

7.  Return $\langle x', y', \theta' \rangle$
```

sample_normal_distribution

Sampling from Our Motion Model



Examples (Odometry-Based)



Velocity-Based Model



Equation for the Velocity Model

Center of circle:

$$\begin{pmatrix} x^* \\ y^* \end{pmatrix} = \begin{pmatrix} x \\ y \end{pmatrix} + \begin{pmatrix} -\lambda \sin\theta \\ \lambda \cos\theta \end{pmatrix} = \begin{pmatrix} \frac{x+x'}{2} + \mu(y-y') \\ \frac{y+y'}{2} + \mu(x'-x) \end{pmatrix}$$

with

$$\mu = \frac{1}{2} \frac{(x-x')\cos\theta + (y-y')\sin\theta}{(y-y')\cos\theta - (x-x')\sin\theta}$$

Posterior Probability for Velocity Model

```
Algorithm motion_model_velocity($x_t, u_t, x_{t-1}$):
    $\mu = \frac{1}{2} \frac{(x-x')\cos\theta + (y-y')\sin\theta}{(y-y')\cos\theta - (x-x')\sin\theta}$
    $x^* = \frac{x+x'}{2} + \mu(y-y')$
    $y^* = \frac{y+y'}{2} + \mu(x'-x)$
    $r^* = \sqrt{(x-x^*)^2 + (y-y^*)^2}$
    $\Delta\theta = \mathrm{atan2}(y'-y^*, x'-x^*) - \mathrm{atan2}(y-y^*, x-x^*)$
    $\hat{v} = \frac{\Delta\theta}{\Delta t}\, r^*$
    $\hat{\omega} = \frac{\Delta\theta}{\Delta t}$
    $\hat{\gamma} = \frac{\theta'-\theta}{\Delta t} - \hat{\omega}$
    return $\mathbf{prob}(v-\hat{v}, \alpha_1|v| + \alpha_2|\omega|) \;\cdot\; \mathbf{prob}(\omega-\hat{\omega}, \alpha_3|v| + \alpha_4|\omega|)$
            $\cdot\, \mathbf{prob}(\hat{\gamma}, \alpha_5|v| + \alpha_6|\omega|)$
```

Sampling from Velocity Model



```
**Algorithm sample_motion_model_velocity**($u_t, x_{t-1}$):

    $\hat{v} = v + \textbf{sample}(\alpha_1|v| + \alpha_2|\omega|)$
    $\hat{\omega} = \omega + \textbf{sample}(\alpha_3|v| + \alpha_4|\omega|)$
    $\hat{\gamma} = \textbf{sample}(\alpha_5|v| + \alpha_6|\omega|)$
    $x' = x - \frac{\hat{v}}{\hat{\omega}} \sin\theta + \frac{\hat{v}}{\hat{\omega}}\ sin(\theta + \hat{\omega}\Delta t)$
    $y' = y + \frac{\hat{v}}{\hat{\omega}} \cos\theta - \frac{\hat{v}}{\hat{\omega}}\ cos(\theta + \hat{\omega}\Delta t)$
    $\theta' = \theta + \hat{\omega}\Delta t + \hat{\gamma}\Delta t$
    *return* $x_t = (x', y', \theta')^T$
```

Examples (velocity based)



Map-Consistent Motion Model





$$p(x \mid u, x') \neq p(x \mid u, x', m)$$

Approximation: $p(x \mid u, x', m) = \eta \; p(x \mid m) \; p(x \mid u, x')$

Summary

- We discussed motion models for odometry-based and velocity-based systems
- We discussed ways to calculate the posterior probability $p(x|\, x', u)$.
- We also described how to sample from $p(x|\, x', u)$.
- Typically the calculations are done in fixed time intervals Δt.
- In practice, the parameters of the models have to be learned.
- We also discussed an extended motion model that takes the map into account.