

# Network Security (NetSec)



TECHNISCHE  
UNIVERSITÄT  
DARMSTADT

Summer 2017

Exercise 04

Part 02: Reconnaissance



```
21:01:31.804195 ARP Request who-has 10.0.2.15 (Broadcast) tell 10.0.5.2, length 46
21:01:31.804281 ARP Request who-has 10.0.2.15 (Broadcast) tell 10.0.5.2, length 46
21:01:31.804948 ARP Request who-has 10.0.2.15 (Broadcast) tell 10.0.5.2, length 46
21:01:31.805434 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.49374: 6596+ PTR? 80.206.106.10.in-addr
21:01:31.805539 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.49374: 6596 NXDomain* 0/1/0 (94)
21:01:31.806692 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.46535: 23771+ PTR? 83.206.106.10.in-addr
21:01:31.806849 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.46535: 23771 NXDomain* 0/1/0 (94)
21:01:31.808030 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.59716: 39542+ PTR? 83.206.106.10.in-addr
21:01:31.808149 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.59716: 39542 NXDomain* 0/1/0 (94)
21:01:31.809314 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.42454: 39542+ PTR? 83.206.106.10.in-addr
21:01:31.809448 ARP Request who-has 10.0.2.15 (Broadcast) tell 10.0.5.2, length 46
21:01:31.810029 ARP Request who-has 10.0.2.15 (Broadcast) tell 10.0.5.2, length 46
21:01:31.810593 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.42454: 39542+ PTR? 83.206.106.10.in-addr
21:01:31.810740 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.42454: 39542 NXDomain* 0/1/0 (94)
21:01:31.811927 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.42454: 39542+ PTR? 83.206.106.10.in-addr
21:01:31.812123 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.42454: 39542 NXDomain* 0/1/0 (94)
21:01:31.813320 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.42454: 39542+ PTR? 83.206.106.10.in-addr
21:01:32.012005 ARP Request who-has 10.106.206.72 (Broadcast) tell 10.0.5.2, length 46
21:01:32.012880 ARP Request who-has 10.106.206.73 (Broadcast) tell 10.0.5.2, length 46
21:01:32.013537 ARP Request who-has 10.106.206.74 (Broadcast) tell 10.0.5.2, length 46
21:01:32.014030 ARP Request who-has 10.106.206.75 (Broadcast) tell 10.0.5.2, length 46
21:01:32.014534 ARP Request who-has 10.106.206.76 (Broadcast) tell 10.0.5.2, length 46
21:01:32.014890 ARP Request who-has 10.106.206.77 (Broadcast) tell 10.0.5.2, length 46
21:01:32.015263 ARP Request who-has 10.106.206.78 (Broadcast) tell 10.0.5.2, length 46
21:01:32.015625 ARP Request who-has 10.106.206.79 (Broadcast) tell 10.0.5.2, length 46
21:01:32.016023 ARP Request who-has 10.106.206.80 (Broadcast) tell 10.0.5.2, length 46
21:01:32.020664 ARP Request who-has 10.106.206.83 (Broadcast) tell 10.0.5.2, length 46
21:01:32.058696 01:80:c2:00:00:01 (oui Unknown) > Broadcast, ethernet type Unknown (0x8874), length 60:
0x0000: e007 BecB 26F5 1c30 080b 0050 0000 0000 .....
0x0010: 0000 0000 0000 0000 0000 0000 0000 0000 .....
0x0020: 0000 0000 0000 0000 0000 0000 0000 0000 .....
21:01:32.230964 ARP Request who-has 10.106.206.90 (Broadcast) tell 10.0.5.2, length 46
21:01:32.231078 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.54054: 15209+ PTR? 90.206.106.10.in-addr
21:01:32.231612 ARP Request who-has 10.106.206.91 (Broadcast) tell 10.0.5.2, length 46
21:01:32.232264 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.54054: 15209 NXDomain* 0/1/0 (94)
21:01:32.232430 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.32988: 56871+ PTR? 91.206.106.10.in-addr
21:01:32.232730 ARP Request who-has 10.106.206.92 (Broadcast) tell 10.0.5.2, length 46
21:01:32.233616 IP ns2.hrztu-darmstadt.de.domain > ns2.hrztu-darmstadt.de.domain: 10.0.2.1.32988: 56871 NXDomain* 0/1/0 (94)
```

# Overview

- Introduction to Exercise 4: Part 2
- Foundations Nmap

# Task

- Your Task
  - Collect as much as possible information about servers
    - 16 tokens are available
    - Version numbers
    - Used software/os
  - Where possible: leave messages
- Servers
  - 130.83.194.149, 130.83.194.150, 130.83.194.151
  - Available after 14.06.2016 18:59 until deadline
  - Generation of a „session id“ is required
    - OTP-seed required for login

# Session Generation & Login

- Generation of the unique „session id“
  - XX-XXXXXXXX-XXXXX
  - One-time generation required
  - **without „session id“: tokens are invalid**
  - Tokens and services bound to „session id“
    - Write the session id down, you can restore your session afterwards
  - Webinterface 130.83.194.149
  - Known to be vulnerable to the Heartbleed attack
  - Several times in an hour: an authorized users is logging in
    - Login page uses TOTP
- Firewall
  - Creates dynamically rules and bind services to session
    - -> IP address is very important
    - -> session valid for 2 hours, must be refreshed afterwards

# Submission of solution & Teamwork

- Submission of solution
  - There is a specific form in moodle
    - Session id, tokens, ports, versions
    - Use specific submission generator tool
  - Additionally: an short report is required (attach to IDS-submission)
- Teamwork
  - This exercise is not a team exercise!
  - We expect you to work on the excercise yourself
    - do not do the exercise for someone else or exchange tokens
  - However: Exchanging your ideas and approaches is ok(e.g. how to use nmap, usage of metasploit, etc.)

# Submission of solution & Teamwork



## Recon Exercise Submission G

Your session-id is:

ec-2 .32u2. 6-111111

[Logout from the submission generator tool](#)

### Values submitted

Please keep the following text for submission to moodle:

```
---Begin---
QV9Ub2t1bj0ndGVzdGEnLCBCX1Rva2VuPSdiJywgQ19Ub2t1bj0nYycsIERfVG9rZW49J
2QnLCBFX1Rva2VuPSdlJywgR19Ub2t1bj0nZicsIEdfVG9rZW49J2cnLCBIX1Rva2VuPS
doJywgS19Ub2t1bj0naicsIFVfVG9rZW49J3UnLCBWX1Rva2VuPSd2JywgV19Ub2t1bj0
ndycsIFhfVG9rZW49J3gnLCBZX1Rva2VuPSd5JywgW19Ub2t1bj0neicsIFBvcnRzQmxv
Yj0nMTMwLjgzLjE5NC4xNDkgfCA4MCM8IFdlYnNlcnZlciB8IE1pY3Jvc29mdCBJSVMgN
S40MlxyXG5cclxuLi4uXHJcb1xyXG4xMzAuODMuMTk0LjE1MSB8IDEwMDAwIHwgUmVtb3
RlIFNlcnZlciBXZWJjb250cm9sIHwgV2VibWluIDkuMjMn
```

A\_Token:

B\_Token:

# Technical Information (I)

- Servers reachable from inside the TU campus (e.g. Wifi)
  - However: Access from outside the campus might be possible, but it is not supported
  - Do not use the TU VPN (L3-VPN vs. Nmap)
- If you dare to do the exercise from outside
  - Do not use the TU VPN (again)
  - Beware of IPv6-to-IPv4 NATs (e.g. Unity Media)
  - Beware of IPv4-Carrier-grade NAT
    - Check if your router has a public IPv4 address
  - Results might be slightly different because of TU firewall
- Do not try to use different sessions on a shared computer
  - Always destroy the session/log out the submission generator tool

# Technical Information (II)

- Do not attack infrastructure services/sites
  - All sites with SEEMOO-logo are not subject to attacks
  - I am a horribly bad programmer, please do not abuse bugs ;)
    - If you find any bugs: contact me ([dennis.giese@seemoo.tu-darmstadt.de](mailto:dennis.giese@seemoo.tu-darmstadt.de))



# Nmap (1)

## Extremely popular

- usually run over Linux
- rich feature set, exploiting raw sockets
- need root to use all features

## Ping sweeping

- over any range of IP addresses
- with ICMP, SYN, ACK
- OS determination

## Port scanning

- Over any range of ports
- Almost any type of TCP, UDP packet

## Source IP address spoofing

- Decoy scanning

## Packet fragmentation

## Timing Options

Further information:

<http://nmap.org/book/man.html>

# Nmap (2)

## Input

**nmap [Scan Type] [Options] <target hosts>**

- Default for port scanning: ports 1-1024 plus ports listed in nmap service file

## Output

- open ports: syn/ack returned; port is open
- unfiltered ports: RST returned: port is closed but not blocked by firewall
- filtered ports: nothing returned; port is blocked by firewall

See Appendix for further examples

# TCP: Reset packet

If machine receives a TCP packet it is not expecting, it responds with TCP packet with RST bit set.

- For example when no process is listening on destination port

For UDP, machine returns ICMP “port unreachable” instead

# Nmap (3): ping sweep

```
nmap -sP -v 116.27.38/24
```

Sends ICMP echo request (ping) to 256 addresses

Can change options so that pings with SYNs, ACKs...

- **-sP** = ping
- **-v** = verbose

# Nmap (4): polite port scan

```
nmap -sT -v target.com
```

Attempts to complete 3-way handshake with each target port  
Sends SYN, waits for SYNACK, sends ACK, then sends FIN to close connection

If target port is closed, no SYNACK returned

- Instead RST packet is typically returned

TCP connect scans are easy to detect

- Target (e.g. Web server) may log completed connections
- Gives away attacker's IP address

# Nmap (5) : TCP SYN port scan

```
nmap -sS -v target.com
```

Stealthier than polite scan

Send SYN, receive SYNACK, send RST

- Send RST segment to avoid an accidental DoS attack

Stealthier: hosts do not record connection

- But routers with logging enabled will record the SYN packet


Faster: don't need to send FIN packet

# Nmap (6): TCP ACK scans

Many filters (in firewalls and routers) only let internal systems hosts initiate TCP connections

- Drop packets for which ACK=0 (ie SYN packet): no sessions initiated externally

To learn what ports are open through firewall, try an ACK scan (segments with ACK=1)



# Nmap (7): UDP port scans

UDP doesn't have SYN, ACK, RST packets

nmap simply sends UDP packet to target port

- ICMP Port Unreachable: interpret port closed
- Nothing comes back: interpret port open
  - False positives common



# Nmap (8): Obscure Source

Attacker can enter list of decoy source IP addresses into Nmap  
For each packet it sends, Nmap also sends packets from decoy source IP addresses

- For 4 decoy sources, send five packets

Attacker's actual address must appear in at least one packet, to get a result

If there are 30 decoys, victim network will have to investigate 31 different sources!

# Nmap (9): TCP Stack Fingerprinting

In addition to determining open ports, attacker wants to know OS on targeted machine:

- exploit machine's known vulnerabilities
- sophisticated hacker may set up lab environment similar to target network

TCP implementations in different OSes respond differently to (illegal) combinations of TCP flag bits

# Nmap (10): Fingerprinting

Nmap sends

- SYN to open port
- NULL to open port (no flag bits set)
- SYN/FIN/URG/PSH to open port
- SYN to closed port
- ACK to closed port
- FIN/PSH/URG to closed port
- UDP to closed port

Nmap includes a database of OS fingerprints for hundreds of platforms

- See [nmap.org](http://nmap.org) for further details

# Nmap (11): examples

```
nmap -v target.com
```

- Scans all TCP default ports on target.com; verbose mode

```
nmap -sS -O target.com/24
```

- First pings addresses in target network to find hosts that are up. Then scans default ports at these hosts; stealth mode (doesn't complete the connections); tries to determine OS running on each scanned host

```
nmap -sX -p 22,53,110,143 198.116.*.1-137
```

- Sends an Xmas tree scan to the first half of each of the 255 possible subnets in the 198.116/16. Testing whether the systems run ssh, DNS, pop3, or imap

```
nmap -v -p 80 *.*.2.3-5
```

- finds all web servers on machines with IP addresses ending in .2.3, .2.4, or .2.5

# Contact



**SEMO**  
SECURE MOBILE NETWORKING


 TECHNISCHE  
UNIVERSITÄT  
DARMSTADT

**Prof. Dr.-Ing. Matthias Hollick**  
[matthias.hollick@seemoo.tu-darmstadt.de](mailto:matthias.hollick@seemoo.tu-darmstadt.de)

Technische Universität Darmstadt  
Secure Mobile Networking Lab – SEEMOO  
Department of Computer Science  
Mornewegstr. 32  
D-64293 Darmstadt

Phone: +49 6151 16-25472  
Fax: +49 6151 16-25471  
Web: <https://seemoo.de>

# Excursus: TCP Segment Structure




# Excursus: TCP seq. #'s and ACKs

Seq. #'s:

- byte stream “number” of first byte in segment's data

ACKs:

- seq # of next byte expected from other side



# Excursus: TCP Connection Establishment

Three way handshake:

Step 1: client host sends TCP SYN segment to server

- SYN=1, ACK=0
- specifies initial seq #
- no data

Step 2: server host receives SYN, replies with SYN-ACK segment

- SYN=1, ACK=1
- server host allocates buffers
- specifies server initial seq. #

Step 3: client receives SYN-ACK, replies with ACK segment, which may contain data

- SYN=0, ACK=1



# Copyright Notice

---

- This document has been distributed by the contributing authors as a means to ensure timely dissemination of scholarly and technical work on a non-commercial basis. Copyright and all rights therein are maintained by the authors or by other copyright holders, notwithstanding that they have offered their works here electronically.
- It is understood that all persons copying this information will adhere to the terms and constraints invoked by each author's copyright. These works may not be reposted without the explicit permission of the copyright holder.