# **Topic :** SQL commands

MySQL Shell 8.0.45

Copyright (c) 2016, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates.

Other names may be trademarks of their respective owners.

Type '\help' or '\?' for help; '\quit' to exit.

MySQL JS > \sql

Switching to SQL mode... Commands end with ;

MySQL SQL > \connect root@localhost

Creating a session to 'root@localhost'

Fetching global names for auto-completion... Press ^C to stop.

Your MySQL connection id is 15 (X protocol)

Server version: 8.0.45 MySQL Community Server - GPL

No default schema selected; type \use <schema> to set one.

MySQL localhost:33060+ ssl SQL > create database school_db;

Query OK, 1 row affected (0.0197 sec)

MySQL localhost:33060+ ssl SQL > create table students(id int,name varchar(50),age int);

ERROR: 1046: No database selected

MySQL localhost:33060+ ssl SQL > use school_db;

Default schema set to `school_db`.

Fetching global names, object names from `school_db` for auto-completion... Press ^C to stop.

MySQL localhost:33060+ ssl school_db SQL > create table students(id int,name varchar(50),age int);

Query OK, 0 rows affected (0.0695 sec)

MySQL localhost:33060+ ssl school_db SQL > desc students;

```
+-------+-------------+------+-----+---------+-------+
| Field | Type        | Null | Key | Default | Extra |
+-------+-------------+------+-----+---------+-------+
```

```
| id    | int        | YES  |     | NULL    |       |

| name  | varchar(50) | YES  |     | NULL    |       |

| age   | int        | YES  |     | NULL    |       |

+-------+-------------+------+-----+---------+-------+

3 rows in set (0.0099 sec)

 MySQL  localhost:33060+ ssl  school_db  SQL > create database company_db;

Query OK, 1 row affected (0.0168 sec)

 MySQL  localhost:33060+ ssl  school_db  SQL > use company_db;

Default schema set to `company_db`.

Fetching global names, object names from `company_db` for auto-completion... Press ^C to stop.

 MySQL  localhost:33060+ ssl  company_db  SQL > create table employees(emp_id int,emp_name
varchar(100),salary decimal(10,2),department varchar(50));

Query OK, 0 rows affected (0.0510 sec)

 MySQL  localhost:33060+ ssl  company_db  SQL > desc employees;

+------------+---------------+------+-----+---------+-------+

| Field      | Type          | Null | Key | Default | Extra |

+------------+---------------+------+-----+---------+-------+

| emp_id     | int           | YES  |     | NULL    |       |

| emp_name   | varchar(100)  | YES  |     | NULL    |       |

| salary     | decimal(10,2) | YES  |     | NULL    |       |

| department | varchar(50)   | YES  |     | NULL    |       |

+------------+---------------+------+-----+---------+-------+

4 rows in set (0.0062 sec)

 MySQL  localhost:33060+ ssl  company_db  SQL > create table products(product_id
int,product_name varchar(100),price float);

Query OK, 0 rows affected (0.0487 sec)

 MySQL  localhost:33060+ ssl  company_db  SQL > desc products;

+--------------+--------------+------+-----+---------+-------+

| Field        | Type         | Null | Key | Default | Extra |

+--------------+--------------+------+-----+---------+-------+

| product_id   | int          | YES  |     | NULL    |       |

| product_name | varchar(100) | YES  |     | NULL    |       |
```

```
| price       | float       | YES  |     | NULL    |       |
+--------------+--------------+------+-----+---------+-------+
3 rows in set (0.0065 sec)
 MySQL  localhost:33060+ ssl  company_db  SQL > create database library_db;
Query OK, 1 row affected (0.0174 sec)
 MySQL  localhost:33060+ ssl  company_db  SQL > use library_db;
Default schema set to `library_db`.
Fetching global names, object names from `library_db` for auto-completion... Press ^C to stop.
 MySQL  localhost:33060+ ssl  library_db  SQL > create table books(book_id int,title
varchar(150),author varchar(100),price decimal(8,2));
Query OK, 0 rows affected (0.0476 sec)
 MySQL  localhost:33060+ ssl  library_db  SQL > desc books;
+---------+--------------+------+-----+---------+-------+
| Field   | Type        | Null | Key | Default | Extra |
+---------+--------------+------+-----+---------+-------+
| book_id | int         | YES  |     | NULL    |       |
| title   | varchar(150) | YES  |     | NULL    |       |
| author  | varchar(100) | YES  |     | NULL    |       |
| price   | decimal(8,2) | YES  |     | NULL    |       |
+---------+--------------+------+-----+---------+-------+
4 rows in set (0.0062 sec)
 MySQL  localhost:33060+ ssl  library_db  SQL > create table orders(order_id int,customer_name
varchar(100),order_date date,amount decimal(10,2));
Query OK, 0 rows affected (0.0440 sec)
 MySQL  localhost:33060+ ssl  library_db  SQL > desc orders;
+---------------+---------------+------+-----+---------+-------+
| Field         | Type          | Null | Key | Default | Extra |
+---------------+---------------+------+-----+---------+-------+
| order_id      | int           | YES  |     | NULL    |       |
| customer_name | varchar(100)  | YES  |     | NULL    |       |
| order_date    | date          | YES  |     | NULL    |       |
| amount        | decimal(10,2) | YES  |     | NULL    |       |
```

```
+---------------+---------------+------+-----+---------+-------+

4 rows in set (0.0063 sec)

 MySQL  localhost:33060+ ssl  library_db  SQL > create database college_db;

Query OK, 1 row affected (0.0161 sec)

 MySQL  localhost:33060+ ssl  library_db  SQL > use college_db;

Default schema set to `college_db`.

Fetching global names, object names from `college_db` for auto-completion... Press ^C to stop.

 MySQL  localhost:33060+ ssl  college_db  SQL > create table courses(course_id int,course_name
varchar(100),duration int);

Query OK, 0 rows affected (0.0469 sec)

 MySQL  localhost:33060+ ssl  college_db  SQL > desc courses;

+-------------+--------------+------+-----+---------+-------+

| Field       | Type         | Null | Key | Default | Extra |

+-------------+--------------+------+-----+---------+-------+

| course_id   | int          | YES  |     | NULL    |       |

| course_name | varchar(100) | YES  |     | NULL    |       |

| duration    | int          | YES  |     | NULL    |       |

+-------------+--------------+------+-----+---------+-------+

3 rows in set (0.0060 sec)
```