

Informatica PowerCenter

Lesson 13: Dynamic Lookup

June 15, 2014

Proprietary and Confidential

- 1 -

IGATE

Speed. Agility. Innovation.

Lesson Objectives

➤ In this Lesson you will learn about:

- Static Cache
- Dynamic Cache



13.4: Static Cache

Uncached Lookup Or Static Cache

- By default, the Integration Service creates a static lookup cache when you configure a Lookup transformation for caching.
- The Integration Service builds the cache when it processes the first lookup request.
- It queries the cache based on the lookup condition for each row that passes into the transformation.
- The Integration Service processes an uncached lookup the same way it processes a cached lookup except that it queries the lookup source instead of building and querying the cache.

June 12, 2014

Proprietary and Confidential

- 3 -

IGATE
Speed. Agility. Intelligence.

13-4: Static Cache

Uncached Lookup Or Static Cache

➤ When the lookup condition is TRUE

- The Integration Service returns the values from the lookup source or cache
- For connected Lookup transformations, the Integration Service returns the values represented by the lookup/output ports
- For unconnected Lookup transformations, the Integration Service returns the value represented by the return port

➤ When the look up condition is NOT TRUE

- The Integration Service returns either NULL or default values
- For connected Lookup transformations, the Integration Service returns the default value of the output port when the condition is not met
- For unconnected Lookup transformations, the Integration Service returns NULL when the condition is not met

June 15, 2014

Proprietary and Confidential

- 4 -

IGATE
Spend Right. Invest Smart.

13.2: Dynamic Cache

Dynamic Lookup Cache

- For relational lookups, you might want to configure the transformation to use a dynamic cache when the target table is also the lookup table.
- When you use a dynamic cache, the Integration Service updates the lookup cache as it passes rows to the target.
- The Integration Service builds the cache when it processes the first lookup request.
- It queries the cache based on the lookup condition for each row that passes into the transformation.

June 15, 2014

Proprietary and Confidential

- 5 -

IGATE
Open. Again. Responsibly.

13-3: Dynamic Cache

Dynamic Lookup Cache

- **When the Integration Service reads a row from the source, it updates the lookup cache by performing one of the following actions:**
 - Inserts the row into the cache
 - Updates the row in the cache
 - Makes no change to the cache
- **The Integration Service either inserts or updates the cache or makes no change to the cache, based on the results of the lookup query, the row type, and the Lookup transformation properties you define.**

June 12, 2014


Proprietary and Confidential

- 6 -

IGATE
Speed. Agility. Integration.

When the Integration Service reads a row from the source, it updates the lookup cache by performing one of the following actions:

- **Inserts the row into the cache.** The row is not in the cache and you specified to insert rows into the cache. You can configure the transformation to insert rows into the cache based on input ports or generated sequence IDs. The Integration Service flags the row as insert
- **Updates the row in the cache.** The row exists in the cache and you specified to update rows in the cache. The Integration Service flags the row as update. The Integration Service updates the row in the cache based on the input ports.
- **Makes no change to the cache.** The row exists in the cache and you specified to insert new rows only. Or, the row is not in the cache and you specified to update existing rows only. Or, the row is in the cache, but based on the lookup condition, nothing changes. The Integration Service flags the row as unchanged.



NewLookupRow. The Designer adds this port to a Lookup transformation configured to use a dynamic cache. Indicates with a numeric value whether the Integration Service inserts or updates the row in the cache, or makes no change to the cache. To keep the lookup cache and the target table synchronized, you pass rows to the target when the NewLookupRow value is equal to 1 or 2.

Associated Port. Associate lookup ports with either an input/output port or a sequence ID. The Integration Service uses the data in the associated ports to insert or update rows in the lookup cache. If you associate a sequence ID, the Integration Service generates a primary key for inserted rows in the lookup cache.

Ignore Null Inputs for Updates. The Designer activates this port property for lookup/output ports when you configure the Lookup transformation to use a dynamic cache. Select this property when you do not want the Integration Service to update the column in the cache when the data in this column contains a null value.

Ignore in Comparison. The Designer activates this port property for lookup/output ports not used in the lookup condition when you configure the Lookup transformation to use a dynamic cache. The Integration Service compares the values in all lookup ports with the values in their associated input ports by default. Select this property if you want the Integration Service to ignore the port when it compares values before updating a row.

13.2: Dynamic Cache

Using NewLookupRow Port

When you define a Lookup transformation to use a dynamic cache, the Designer adds the NewLookupRow port to the transformation

The Integration Service assigns a value to the port, depending on the action it performs to the lookup cache


NewLookUPRowvalues

NewLookupRow Value	Description
0	The PowerCenter Server does not update or insert the row in the cache.
1	The PowerCenter Server inserts the row into the cache.
2	The PowerCenter Server updates the row in the cache.

June 15, 2014

Proprietary and Confidential

- 8 -

IGATE
Simplifying Integration

When the Integration Service reads a row, it changes the lookup cache depending on the results of the lookup query and the Lookup transformation properties you define. It assigns the value 0, 1, or 2 to the NewLookupRow port to indicate if it inserts or updates the row in the cache, or makes no change.

Summary

➤ This lesson has taught basically two parts:

- Static Cache
- Dynamic Cache



Review Question

- Question 1: If a Lookup transformation is configured to use a dynamic cache, the Designer adds the _____ port to the transformation.
- Question 2: The Integration Service uses the data in the _____ ports to insert or update rows in the lookup cache.

