VENTILATION SYSTEMS

Evaporative Cellulose Cooling Pad System

$145.00
Factory Direct Price • CE Compliant



TECHNICAL SPECIFICATIONS

Pad Thickness	150 mm (6-inch) / 100 mm optional
Cooling Efficiency	Up to 82% evaporative efficiency
Gutter System	Extruded Aluminum Alloy Frame
Water Supply Pump	Submersible 0.55 kW Stainless Pump
Flute Angle	45° x 15° Cross-Fluted
Standard Metallurgy	275 g/m² Hot-Dip Zinc Coating
Structural Warranty	20-Year Anti-Corrosion Guarantee
Electrical Standards	CE Certified • IP55 Protection
Compliance	EU Animal Welfare & USDA Biosecurity

Engineering Highlights

- ✓ Manufactured with 275 g/m² hot-dip galvanization
- ✓ Virgin food-grade UV-resistant polymer contact points
- ✓ Energy-efficient IP55 drive motor system
- ✓ Zero-stress bird welfare optimized geometry
- ✓ Continuous operational lifespan exceeding 20 years

Operational Engineering Description & Layout Planning

Reduces poultry house internal temperatures by 6°C to 10°C during peak summer heat. Corrugated cellulose paper engineered with anti-fungal impregnation prevents algae buildup and resists degradation from chemical disinfection.

ISO 9001:2026	CE EN 12100	20-Year Warranty	Biosecurity Grade
Precision Metallurgy	Machinery Directives	Structural Rust-Proof	Zero-Contamination

AviTech Systems International • Industrial Ag Park, Bldg 4 • contact@avitechpoultry.com
Direct Engineering Line: +1 (800) 555-FARM • Web: www.avitechpoultry.com