AviTech Poultry Systems
COMMERCIAL POULTRY ENGINEERING DIVISION

ISO 9001:2026 CERTIFIED
DOC-ID: AVT-INFRARED-GAS-BROODER-2026

BROODING EQUIPMENT

Infrared Radiant Gas Brooder 5000

$165.00
Factory Direct Price • CE Compliant



Engineering Highlights

- ✓ Manufactured with 275 g/m² hot-dip galvanization
- ✓ Virgin food-grade UV-resistant polymer contact points
- ✓ Energy-efficient IP55 drive motor system
- ✓ Zero-stress bird welfare optimized geometry
- ✓ Continuous operational lifespan exceeding 20 years

TECHNICAL SPECIFICATIONS

Brooding Capacity	800–1,200 Day-Old Chicks per unit
Heat Output	5.5 kW (18,800 BTU/hr)
Gas Consumption	0.41 kg/hr LPG / 0.52 m³/hr Natural Gas
Safety System	Flame Failure Sensor & Auto Shutoff
Thermostat Accuracy	± 0.5°C Ambient Sensor Probe
Standard Metallurgy	275 g/m² Hot-Dip Zinc Coating
Structural Warranty	20-Year Anti-Corrosion Guarantee
Electrical Standards	CE Certified • IP55 Protection
Compliance	EU Animal Welfare & USDA Biosecurity

Operational Engineering Description & Layout Planning

Emulates natural mother hen radiant heat directly to chick floor level without wasting energy heating ceiling air. Promotes rapid feathering, gut development, and lowers chick mortality below 0.8% during crucial 1–14 day brooding phases.

ISO 9001:2026	CE EN 12100	20-Year Warranty	Biosecurity Grade
Precision Metallurgy	Machinery Directives	Structural Rust-Proof	Zero-Contamination

AviTech Systems International • Industrial Ag Park, Bldg 4 •
contact@avitechpoultry.com
Direct Engineering Line: +1 (800) 555-FARM • Web: www.avitechpoultry.com