POULTRY CAGES

A-Type Commercial Layer Battery Cages

$850.00
Factory Direct Price • CE Compliant



TECHNICAL SPECIFICATIONS

Tier Levels	3-Tier / 4-Tier / 5-Tier Configurable
Galvanization	275 g/m² Hot-Dip Zinc Coating
Cell Dimensions	450 mm x 450 mm x 450 mm
Stocking Density	4–5 birds per cell (450 cm²/bird)
Egg Breakage Rate	< 0.3% Guaranteed
Standard Metallurgy	275 g/m² Hot-Dip Zinc Coating
Structural Warranty	20-Year Anti-Corrosion Guarantee
Electrical Standards	CE Certified • IP55 Protection
Compliance	EU Animal Welfare & USDA Biosecurity

Engineering Highlights

- ✓ Manufactured with 275 g/m² hot-dip galvanization
- ✓ Virgin food-grade UV-resistant polymer contact points
- ✓ Energy-efficient IP55 drive motor system
- ✓ Zero-stress bird welfare optimized geometry
- ✓ Continuous operational lifespan exceeding 20 years

Operational Engineering Description & Layout Planning

Engineered for commercial layer farms seeking maximum stocking density with superior bird health. Electrostatic zinc-aluminum coating guarantees 20+ years of rust protection. Features egg roll-out slope with cushioning wire to minimize breakage below 0.3%.

ISO 9001:2026	CE EN 12100	20-Year Warranty	Biosecurity Grade
Precision Metallurgy	Machinery Directives	Structural Rust-Proof	Zero-Contamination

AviTech Systems International • Industrial Ag Park, Bldg 4 •
contact@avitechpoultry.com
Direct Engineering Line: +1 (800) 555-FARM • Web: www.avitechpoultry.com