FARM AUTOMATION

Automated PP Manure Belt Removal System

$920.00
Factory Direct Price • CE Compliant



TECHNICAL SPECIFICATIONS

Belt Thickness	1.0 mm – 1.2 mm High Density Virgin PP
Tensile Strength	> 1500 N/50mm Non-Stretch
Drive Power	1.5 kW – 3.0 kW Planetary Gear Motor
Scraper Blade	Stainless Steel Elastic Dual Blade
Max House Length	Up to 150 meters per drive unit
Standard Metallurgy	275 g/m² Hot-Dip Zinc Coating
Structural Warranty	20-Year Anti-Corrosion Guarantee
Electrical Standards	CE Certified • IP55 Protection
Compliance	EU Animal Welfare & USDA Biosecurity

Engineering Highlights

- ✓ Manufactured with 275 g/m² hot-dip galvanization
- ✓ Virgin food-grade UV-resistant polymer contact points
- ✓ Energy-efficient IP55 drive motor system
- ✓ Zero-stress bird welfare optimized geometry
- ✓ Continuous operational lifespan exceeding 20 years

Operational Engineering Description & Layout Planning

Significantly improves biosecurity and air quality inside cage sheds by clearing droppings daily. Heavy 1.2 mm virgin PP belt runs beneath each cage tier directly into outdoor manure elevators or collection wagons.

ISO 9001:2026	CE EN 12100	20-Year Warranty	Biosecurity Grade
Precision Metallurgy	Machinery Directives	Structural Rust-Proof	Zero-Contamination

AviTech Systems International • Industrial Ag Park, Bldg 4 •
contact@avitechpoultry.com
Direct Engineering Line: +1 (800) 555-FARM • Web: www.avitechpoultry.com