# **Activity 9.1**

Ramzy Izza Wardhana - 21/472698/PA/20322

### BinarySearchNode.java

```
public class BinarySearchNode {
    Integer data;
    BinarySearchNode left;
    BinarySearchNode right;

BinarySearchNode(Integer data){
        this.data = data;
        this.left = null;
        this.right = null;
}

public String toString() {
        return "[" + data + ", " + left + ", " + right + "]";
}
```

#### BinarySearchTree.java

```
public class BinarySearchTree {
    private BinarySearchNode root;
    //Constructor
    BinarySearchTree() {
        root = null;
    }
    public void insert (Integer data) {
        BinarySearchNode p = root; //Start from the root
        BinarySearchNode parent = null; //Parent of p, Intially == null
        boolean isLeftChild = false; //True if p is the left child of parent
        while(p != null){
            int result = data.compareTo(p.data);
            if(result == 0) { //Data == p.data
                System.out.println(data + " Already Exist");
                return;
            } else if (result < 0) {</pre>
```

```
//Write codes here
            parent = p;
            isLeftChild = true;
            p = p.left;
        } else { //Data > p.data
            parent = p;
            isLeftChild = false;
            p = p.right;
        }
    }
    BinarySearchNode newNode = new BinarySearchNode(data);
    if (parent == null){
        root = newNode;
    } else if (isLeftChild) {
        parent.left = newNode;
    } else {
        parent.right = newNode;
    }
public void search(Integer data) {
    BinarySearchNode p = root; //Start from the root
    while(p != null){
        int result = data.compareTo(p.data); //Compare data with p.data
        if (result == 0) { //Data == p.data
            System.out.println(data + " is found");
            return;
        } else if(result < 0) { //data < p.data</pre>
            p = p.left;
        } else { //Data > p.data
            //Write the code here
            p = p.right;
        }
    System.out.println(data + " is not Found");
```

```
}
public void delete(Integer data) {
    BinarySearchNode p = root; //Start from the root
   BinarySearchNode parent = null; //Parent of p, initially == null
   boolean isLeftChild = false; //True if p is the left child of parent
   while (p != null) {
        int result = data.compareTo(p.data); //Data == p.data
        if (result == 0) { //Found the data
            if(p. left == null && p.right == null) {//P is external node
                if(parent == null) {
                    root = null;
                } else if (isLeftChild) {
                    parent.left = null;
                    break;
                } else {
                    parent.right = null;
                    break;
            } else if (p.left == null) { //p only has the right subtree
                //Replace with the right child
                if (parent == null) {
                    root = p.right;
                } else if (isLeftChild){
                    parent.left = p.right;
                    break;
                } else {
                    parent.right = p.right;
                    break;
            } else if (p.right == null) {//p only has the left subtree
                if(parent == null) {
                    root = p.left;
                } else if (isLeftChild){
                    parent.left = p.left;
                    break;
                } else {
                    parent.right = p.left;
                    break;
                }
```

```
} else { //P has both right and left subtrees
                BinarySearchNode x = findMin(p);
                if (parent == null) {
                    root = x;
                } else if(isLeftChild) {
                    parent.left = x;
                } else{
                    parent.right = x;
                x.right = p.right;
                x.left = p.left;
                p.right = null;
                p.left = null;
        } else if (result < 0) { //data < p.data</pre>
            parent = p;
            isLeftChild = true;
            p = p.left;
        } else { //data > p.data
            parent = p;
            isLeftChild = false;
            p = p.right;
        }
    }
    System.out.println(data + " Has been deleted");
    System.out.println(data + " Is not found");
}
public BinarySearchNode findMin(BinarySearchNode parent) {
    BinarySearchNode p = parent.right;
    while (p.left != null) {
        p = p.left;
    return p; //Return the smallest node
}
```

```
public String toString(){
    return inOrder(root);
}

private String inOrder(BinarySearchNode p){
    if (p == null)
        return "";
    return inOrder(p.left) + "" + p.data + " " + inOrder(p.right);
}
```

#### TestBinarySearchTree.java

```
public class TestBinarySearchTree {
    public static void main(String[] args) {
        //Create a BST
        BinarySearchTree bst = new BinarySearchTree();
        bst.insert(5);
        bst.insert(3);
        bst.insert(8);
        bst.insert(2);
        bst.insert(4);
        bst.insert(6);
        bst.insert(7);
        System.out.println(bst);
        bst.search(2);
        bst.search(9);
        bst.delete(8);
        System.out.println(bst);
        bst.delete(6);
        System.out.println(bst);
        bst.delete(7);
        System.out.println(bst);
        bst.delete(2);
        System.out.println(bst);
    }
```

## Output

```
PS C:\Users\themi\Downloads\java-prak-asd\eight-meet\activity>
ght-meet\activity\bin' 'TestBinarySearchTree'
2 3 4 5 6 7 8
2 is found
9 is not Found
8 Has been deleted
8 Is not found
2 3 4 5 6 7
6 Has been deleted
6 Is not found
2 3 4 5 7
7 Has been deleted
7 Is not found
2 3 4 5
2 Has been deleted
2 Is not found
3 4 5
PS C:\Users\themi\Downloads\java-prak-asd\eight-meet\activity>
```