


## Slider in Rotating Arm



A slider moves inside a rotating radial slot. This slot is hinged at O. Determine the acceleration  $\text{mm/s}^2$  in radial direction at  $t = 3$  seconds.

At this time instant the distance between the slider and point O is 15 mm, the sliders velocity is 12 mm/s and its acceleration is 4  $\text{mm/s}^2$ . Furthermore, it is given that  $v_\theta = 3.75 \text{ mm/s}$ . Round to the nearest integer (no decimals).

Using known expressions:

$$v_\theta = r\dot{\theta} \Rightarrow \dot{\theta} = \frac{v_\theta}{r} \quad (1)$$

$$a_r = \ddot{r} - r\dot{\theta}^2 \quad (2)$$

Given quantities:

Velocity in  $\theta$ -direction:  $v_\theta = 3.75 \text{ mm/s}$

Distance between slider and O:  $r = 15 \text{ mm}$

Velocity of the slider:  $\dot{r} = 12 \text{ mm/s}$

Acceleration of the slider:  $\ddot{r} = 4 \text{ mm/s}^2$

*Solution:*

Calculating  $\dot{\theta}$  using Equation 1 gives:

$$\dot{\theta} = \frac{v_\theta}{r} = \frac{3.75}{15} = 0.25 \text{ rad/s} \quad (3)$$

Now  $a_r$  can be calculated as follows:

$$a_r = \ddot{r} - r\dot{\theta}^2 = 4 - 15 \cdot 0.25^2 = 3.0625 \text{ mm/s}^2 \approx 3 \text{ mm/s}^2 \quad (4)$$