Top 20 Recently Asked Playwright Scenario-Based Interview Questions (5+ Years Experience)

1. Your application uses SSO/OAuth login, and login takes 30 seconds. How would you avoid logging in before every test while ensuring session validity?

2. Your Playwright tests pass locally but fail randomly in Jenkins. How would you debug and stabilize the tests?

3. A button is visible but Playwright throws "element is not stable" or "element is detached from DOM." What could be the reasons, and how would you fix it?

4. Your application uses virtual scrolling (only visible rows are rendered). How would you validate the 500th record?

5. How would you automate a payment flow where the payment page opens in a new tab and contains an iframe?

6. Your application frequently changes CSS classes after every deployment. How would you design reliable locators?

7. An API returns 500 intermittently. How would you continue UI automation without depending on the backend?

8. Your team wants the same Playwright tests to run on Dev, QA, UAT, and Production. How would you design environment management?

9. Two parallel tests update the same customer and fail intermittently. How would you make them independent?

10. Your suite contains 2,000 test cases and takes 3 hours to execute. How would you reduce execution time to under 1 hour?

11. A download starts after clicking Export. How would you verify that the downloaded Excel/PDF contains the correct data?

12. Your application requires OTP authentication. How would you automate the login flow without manual intervention?

13. How would you validate data displayed on the UI against data returned by backend APIs or the database?

14. Developers complain that your automation framework is difficult to maintain. How would you redesign the framework architecture?

15. Your application has multiple browser windows, pop-ups, and nested iframes. How

would you handle navigation between them?

16. A React application frequently re-renders elements, causing stale element issues. How does Playwright handle this, and what are the best practices?

17. You need to capture screenshots, videos, traces, and logs only for failed tests. How would you configure Playwright?

18. A test fails only in Firefox but passes in Chromium and WebKit. How would you investigate the issue?

19. How would you implement API mocking for third-party services while keeping the rest of the application real?

20. Design a scalable Playwright automation framework from scratch for an enterprise application. Explain folder structure, Page Object Model, fixtures, custom reporters, utilities, test data management, CI/CD integration, parallel execution, retry strategy, and best practices.