



Intro to Computer Vision

Lecture 1: Images and image filtering



Hybrid Images, Oliva et al., <http://olivalab.mit.edu/hybridimage.htm>

Important information



Textbook

Rick Szeliski, *Computer Vision: Algorithms and Applications* online at: <http://szeliski.org/Book/>

Many of the slides in this course are modified from the excellent class notes of similar courses offered in other schools by Noah Snavely, Prof Yung-Yu Chuang, Fredo Durand, Alyosha Efros, Bill Freeman, James Hays, Svetlana Lazebnik, Andrej Karpathy, Fei-Fei Li, Srinivasa Narasimhan, Silvio Savarese, Steve Seitz, Richard Szeliski, and Li Zhang. The instructor is extremely thankful to the researchers for making their notes available online. Please feel free to use and modify any of the slides, but acknowledge the original sources where appropriate.

All readings are from Richard Szeliski, *Computer Vision: Algorithms and Applications*, 2nd Edition, unless otherwise noted.



Reading

- Szeliski, Chapter 3.1-3.3

What is an image?




What is an image?




We'll focus on these in this class

(More on this process later)



What is an image?

- A grid (matrix) of intensity values



=

| | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 |
| 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 |
| 255 | 255 | 255 | 20 | 0 | 255 | 255 | 255 | 255 | 255 | 255 | 255 |
| 255 | 255 | 255 | 75 | 75 | 75 | 255 | 255 | 255 | 255 | 255 | 255 |
| 255 | 255 | 75 | 95 | 95 | 75 | 255 | 255 | 255 | 255 | 255 | 255 |
| 255 | 255 | 96 | 127 | 145 | 175 | 255 | 255 | 255 | 255 | 255 | 255 |
| 255 | 255 | 127 | 145 | 175 | 175 | 175 | 255 | 255 | 255 | 255 | 255 |
| 255 | 255 | 127 | 145 | 200 | 200 | 175 | 175 | 95 | 255 | 255 | 255 |
| 255 | 255 | 127 | 145 | 200 | 200 | 175 | 175 | 95 | 47 | 255 | 255 |
| 255 | 255 | 127 | 145 | 145 | 175 | 127 | 127 | 95 | 47 | 255 | 255 |
| 255 | 255 | 74 | 127 | 127 | 127 | 95 | 95 | 95 | 47 | 255 | 255 |
| 255 | 255 | 255 | 74 | 74 | 74 | 74 | 74 | 74 | 255 | 255 | 255 |
| 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 |
| 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 | 255 |


(common to use one byte per value: 0 = black, 255 = white)

What is an image?

- Can think of a (grayscale) image as a **function** f from \mathbb{R}^2 to \mathbb{R} :
 - $f(x,y)$ gives the **intensity** at position (x,y)



[snoop](#)



[3D view](#)

- A **digital** image is a discrete (**sampled, quantized**) version of this function

Image transformations

- As with any function, we can apply operators to an image



$$g(x,y) = f(x,y) + 20$$



$$g(x,y) = f(-x,y)$$

- Today we'll talk about a special kind of operator, *convolution* (linear filtering)

Filters


- Filtering
 - Form a new image whose pixel values are a combination of the original pixel values
- Why?
 - To get useful information from images
 - E.g., extract edges or contours (to understand shape)
 - To enhance the image
 - E.g., to remove noise
 - E.g., to sharpen and “enhance image” a la CSI
 - A key operator in Convolutional Neural Networks

Canonical Image Processing problems

- Image Restoration
 - denoising
 - deblurring
- Image Compression
 - JPEG, HEIF, MPEG, ...
- Locating Structural Features
 - corners
 - edges

Question: Noise reduction

- Given a camera and a still scene, how can you reduce noise?



Take lots of images and average them!

What's the next best thing?


Image filtering

- Modify the pixels in an image based on some function of a local neighborhood of each pixel



Linear filtering

- One simple version of filtering: linear filtering (cross-correlation, convolution)
 - Replace each pixel by a linear combination (a weighted sum) of its neighbors
- The prescription for the linear combination is called the “kernel” (or “mask”, “filter”)



Cross-correlation

Let F be the image, H be the kernel (of size $2k+1 \times 2k+1$), and G be the output image

$$G[i, j] = \sum_{u=-k}^k \sum_{v=-k}^k H[u, v] F[i + u, j + v]$$

This is called a **cross-correlation** operation:

$$G = H \otimes F$$

- Can think of as a “dot product” between local neighborhood and kernel for each pixel

Convolution

- Same as cross-correlation, except that the kernel is “flipped” (horizontally and vertically)


$$G[i, j] = \sum_{u=-k}^k \sum_{v=-k}^k H[u, v] F[i - u, j - v]$$

This is called a **convolution** operation:


$$G = H * F$$

- Convolution is **commutative** and **associative**

Convolution



Mean filtering



Mean filtering / Moving average

$$F[x, y]$$
[illegible]
$$G[x, y]$$
A 10x10 grid with a red square in the top-left corner. The red square is located in the first row and first column, with a side length of 1 unit. The grid is composed of 10 columns and 10 rows of squares, each with a side length of 1 unit. The red square is the top-leftmost square in the grid.

Mean filtering / Moving average

$$F[x, y]$$

[illegible]

$$G[x, y]$$

[illegible]

Mean filtering / Moving average

$$F[x, y]$$

[illegible]

$$G[x, y]$$

[illegible]

Mean filtering / Moving average

$$F[x, y]$$

[illegible]

$$G[x, y]$$

[illegible]

Mean filtering / Moving average

$$F[x, y]$$

[illegible]

$$G[x, y]$$

[illegible]

Mean filtering / Moving average

$$F[x, y]$$

[illegible]

$$G[x, y]$$

[illegible]

Linear filters: examples



Original



| | | |
|---|---|---|
| 0 | 0 | 0 |
| 0 | 1 | 0 |
| 0 | 0 | 0 |

Linear filters: examples



Original



| | | |
|---|---|---|
| 0 | 0 | 0 |
| 0 | 1 | 0 |
| 0 | 0 | 0 |



Identical image

Linear filters: examples



Original



| | | |
|---|---|---|
| 0 | 0 | 0 |
| 1 | 0 | 0 |
| 0 | 0 | 0 |

Linear filters: examples



Original



| | | |
|---|---|---|
| 0 | 0 | 0 |
| 1 | 0 | 0 |
| 0 | 0 | 0 |



Shifted left by 1 pixel

Linear filters: examples




Original



$\frac{1}{9}$

| | | |
|---|---|---|
| 1 | 1 | 1 |
| 1 | 1 | 1 |
| 1 | 1 | 1 |



Blur (with a mean filter)

Linear filters: examples




Original

$$* \left(\begin{bmatrix} 0 & 0 & 0 \\ 0 & 2 & 0 \\ 0 & 0 & 0 \end{bmatrix} - \frac{1}{9} \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix} \right) =$$




Sharpening filter
(accentuates edges)

Sharpening





before





after

Smoothing with box filter revisited







Gaussian kernel




$$G_{\sigma} = \frac{1}{2\pi\sigma^2} e^{-\frac{(x^2+y^2)}{2\sigma^2}}$$


Gaussian filters



$\sigma = 1$ pixel



$\sigma = 5$ pixels




$\sigma = 10$ pixels




$\sigma = 30$ pixels

Mean vs. Gaussian filtering



Gaussian filter

- Removes “high-frequency” components from the image (low-pass filter)
- Convolution with self is another Gaussian




- Convolving twice with Gaussian kernel of width σ
= convolving once with kernel $c\sigma\sqrt{2}$ th

Sharpening revisited


- What does blurring take away?



—




=




(This “detail extraction” operation is also called a **high-pass filter**)

Let's add it back:



+ α




=




Sharpen filter

$$\underset{\substack{\uparrow \\ \text{image}}}{F} + \alpha (F - \underbrace{F * H}_{\substack{\text{blurred} \\ \text{image}}}) =$$




scaled impulse

—



Gaussian

\approx



Sharpen filter

\uparrow
unit impulse
(identity kernel
with single 1 in
center, zeros
elsewhere)

Sharpen filter



“Optical” convolution

Camera shake



Source: Fergus, *et al.* “Removing Camera Shake from a Single Photograph”, SIGGRAPH 2006

Bokeh: Blur in out-of-focus regions of an image.



Source: https://www.diyphotography.net/diy_create_your_own_bokeh/

Filters: Thresholding



$$g(m, n) = \begin{cases} 255, & f(m, n) > A \\ 0 & \text{otherwise} \end{cases}$$

Linear filters

- Can thresholding be implemented with a linear filter?

Questions?