

# Contents

<b>0</b>	<b>Draft to be distilled in 1 and 2</b>	<b>5</b>
0.1	Formal presentation . . . . .	7
0.1.1	Tensors . . . . .	7
0.1.2	Neural Networks . . . . .	14
0.1.3	Graphs . . . . .	26
0.1.4	Special classes of graphs . . . . .	28
0.2	Subject disambiguation . . . . .	29
0.2.1	Naming conventions . . . . .	29
0.2.2	Disambiguation of the subject . . . . .	30
0.2.3	Datasets . . . . .	31
0.2.4	Tasks . . . . .	31
0.2.5	Goals . . . . .	31
0.2.6	Invariance . . . . .	31
0.2.7	Methods . . . . .	32
<b>1</b>	<b>Introduction</b>	<b>33</b>
1.1	Plan, vision, etc . . . . .	33
1.2	Deep learning and history . . . . .	33
1.3	Regular deep learning . . . . .	33
1.4	Irregular deep learning . . . . .	33
1.5	Unstructured deep learning . . . . .	33
1.6	Propagational point of view . . . . .	33
<b>2</b>	<b>Presentation of the domain</b>	<b>33</b>
2.1	Typology of data . . . . .	33
2.2	Standardized terminology . . . . .	33
2.3	Motivation . . . . .	33
2.4	Datasets . . . . .	33

2.5	Unifying framework (tensorial product) . . . . .	33
2.6	Other Unifying frameworks . . . . .	33
<b>3</b>	<b>Review of models and propositions</b>	<b>33</b>
3.1	How to compare models . . . . .	33
3.2	Spectral models . . . . .	33
3.3	Non-spectral . . . . .	33
3.4	Non-convolutional . . . . .	33
3.5	Recap and (big) comparison table . . . . .	33
3.6	Explaining current SOA, current issues, and further work . . .	33
<b>4</b>	<b>Transposing the problem formulation: Structural learning</b>	<b>33</b>
4.1	Structural Representation . . . . .	33
4.2	Feature visualization (viz on input) . . . . .	33
4.3	Propagated Signal visualization (viz on S) . . . . .	33
4.4	Temptatives on learning S . . . . .	33
4.5	Temptatives on learning S (other) . . . . .	33
4.6	Covariance-based convolution . . . . .	33
4.7	Conclusion . . . . .	33
<b>5</b>	<b>Industrial applications</b>	<b>33</b>
5.1	Context . . . . .	33
5.2	The Warp 10 platform and Warpscript language . . . . .	33
5.3	Presentation of use cases: uni vs multi-variate, spatial vs geo, etc .. . . .	33
5.4	Review and application on regularly structured (spatial) time series . . . . .	33
5.5	Application to time series database (unstructured) . . . . .	33
5.6	Application to geo time series (unstructured) . . . . .	33
5.7	Application to visualization . . . . .	33
5.8	Market reality (what clients need, what they don't know that can be done ...) . . . . .	33
5.9	Conclusion . . . . .	33
<b>6</b>	<b>Conclusion</b>	<b>33</b>
6.1	Summary . . . . .	33
6.2	Lesson learned . . . . .	33
6.3	Further avenues . . . . .	33

<i>CONTENTS</i>	3
-----------------	---

<b>Bibliography</b>	<b>35</b>
---------------------	-----------



# Chapter 0

## Draft to be distilled in 1 and 2

### Contents

---

<b>0.1</b>	<b>Formal presentation . . . . .</b>	<b>7</b>
0.1.1	Tensors . . . . .	7
0.1.1.1	Definition . . . . .	7
0.1.1.2	Manipulation . . . . .	8
0.1.1.3	Binary operations . . . . .	10
0.1.2	Neural Networks . . . . .	14
0.1.2.1	Description . . . . .	14
0.1.2.1.1	Simple formalization . . . . .	14
0.1.2.1.2	Interpretation . . . . .	16
0.1.2.1.3	Generic formalization . . . . .	17
0.1.2.1.4	Expressive analysis . . . . .	18
0.1.2.2	Training . . . . .	18
0.1.2.3	Example of layers . . . . .	20
0.1.2.4	Example of regularizations . . . . .	24
0.1.2.5	Example of architectures . . . . .	24
0.1.3	Graphs . . . . .	26
0.1.3.1	Connectivity graph . . . . .	26
0.1.3.2	Computation graph . . . . .	28
0.1.3.3	Underlying graph structure . . . . .	28

0.1.3.4	Graph-structured dataset . . . . .	28
0.1.4	Special classes of graphs . . . . .	28
0.1.4.1	Grid graphs . . . . .	28
0.1.4.2	Spatial graphs . . . . .	28
0.1.4.3	Projections of spatial graphs . . . . .	28
<b>0.2</b>	<b>Subject disambiguation . . . . .</b>	<b>29</b>
0.2.1	Naming conventions . . . . .	29
0.2.1.1	Basic notions . . . . .	29
0.2.1.2	Graphs and graph signals . . . . .	29
0.2.1.3	Data and datasets . . . . .	30
0.2.2	Disambiguation of the subject . . . . .	30
0.2.2.1	Irregularly structured data . . . . .	30
0.2.2.2	Unstructured data . . . . .	31
0.2.3	Datasets . . . . .	31
0.2.4	Tasks . . . . .	31
0.2.5	Goals . . . . .	31
0.2.6	Invariance . . . . .	31
0.2.7	Methods . . . . .	32

---

## 0.1 Formal presentation

In this section, we present notions related to our domains of interest. In some cases, we will give original definitions that are more appropriate for our study.

Vector spaces considered in what follows are assumed to be finite-dimensional and over the field of real numbers  $\mathbb{R}$ .

### 0.1.1 Tensors

Intuitively, tensors in the field of deep learning are defined as a generalization of vectors and matrices, as if vectors were tensors of rank 1 and matrices were tensors of rank 2. That is, they are objects in a vector space and their dimensions are indexed using as many indices as their rank, so that they can be represented by multidimensional arrays. In mathematics, a tensor can be defined as a special type of multilinear function (Bass, 1968; Marcus, 1975; Williamson, 2015), which image of a basis can be represented by a multidimensional array. Alternatively, Hackbush propose a mathematical construction of a tensor space as a quotient set of the span of an appropriately defined tensor product (Hackbusch, 2012), which coordinates in a basis can also be represented by a multidimensional array. In particular in the field of mathematics, tensors enjoy an intrinsic definition that neither depend on a representation nor would change the underlying object after a change of basis, whereas in our domain, tensors are confounded with their representation.

#### 0.1.1.1 Definition

Our definition of tensors is such that they are a bit more than multidimensional arrays but not as much as mathematical tensors, for that they are embedded in a vector space so that deep learning objects can be later defined rigorously.

Given canonical bases, we first define a tensor space, then we relate it to the definition of the tensor product of vector spaces.

#### Definition 0.1.1. Tensor space

We define a *tensor space*  $\mathbb{T}$  of rank  $r$  as a vector space such that its canonical basis is a cartesian product of the canonical bases of  $r$  other vector spaces. Its shape is denoted  $n_1 \times n_2 \times \cdots \times n_r$ , where the  $\{n_k\}$  are the dimensions of the vector spaces.

**Definition 0.1.2. Tensor product of vector spaces**

Given  $r$  vector spaces  $\mathbb{V}_1, \mathbb{V}_2, \dots, \mathbb{V}_r$ , their *tensor product* is the tensor space  $\mathbb{T}$  spanned by the cartesian product of their canonical bases under coordinate-wise sum and outer product.

We use the notation  $\mathbb{T} = \bigotimes_{k=1}^r \mathbb{V}_k$ .

*Remark 0.1.1.* This simpler definition is indeed equivalent with the definition of the tensor product given in (Hackbusch, 2012, p. 51). The drawback of our definition is that it depends on the canonical bases, which at first can seem limiting as being canon implies that they are bounded to a certain system of coordinates. However this is not a concern in our domain as we need not distinguish tensors from their representation.

*Remark 0.1.2.* For naming conveniency, from now on, we will distinguish between the terms *linear space* and *vector space* *i.e.* we will abusively use the term *vector space* only to refer to a linear space that is seen as a tensor space of rank 1. If we don't know its rank, we rather use the term *linear space*. We also make a clear distinction between the terms *dimension* (that is, for a tensor space it is equal to  $\prod_{k=1}^r n_k$ ) and the term *rank* (equal to  $r$ ).

Note that some authors use the term *order* instead of *rank* (*e.g.* Hackbusch, 2012) as the latter is affected to another notion.

**Definition 0.1.3. Tensor**

A *tensor*  $t$  is an object of a tensor space. The *shape* of  $t$ , which is the same as the shape of the tensor space it belongs to, is denoted  $n_1^{(t)} \times n_2^{(t)} \times \dots \times n_r^{(t)}$ .

**0.1.1.2 Manipulation**

In this subsection, we describe notations and operators used to manipulate data stored in tensors.

**Definition 0.1.4. Indexing**

An *entry* of a tensor  $t \in \mathbb{T}$  is one of its scalar coordinates in the canonical basis, denoted  $t[i_1, i_2, \dots, i_r]$ .



More precisely, if  $\mathbb{T} = \bigotimes_{k=1}^r \mathbb{V}_k$ , with bases  $((e_k^i)_{i=1,\dots,n_k})_{k=1,\dots,r}$ , then we have

$$t = \sum_{i_1=1}^{n_1} \cdots \sum_{i_r=1}^{n_r} t[i_1, i_2, \dots, i_r] (e_1^{i_1}, \dots, e_r^{i_r})$$

The cartesian product  $\mathbb{I} = \prod_{k=1}^r \{1, \dots, n_k\}$  is called the *index space* of  $\mathbb{T}$

*Remark 0.1.3.* When using an index  $i_k$  for an entry of a tensor  $t$ , we implicitly assume that  $i_k \in \{1, 2, \dots, n_k^{(t)}\}$  if nothing is specified.

#### Definition 0.1.5. Subtensor

A *subtensor*  $t'$  is a tensor of same rank composed of entries of  $t$  that are contiguous in the indexing, with at least one entry per rank. We denote  $t' = t[l_1:u_1, l_2:u_2, \dots, l_r:u_r]$ , where the  $\{l_k\}$  and the  $\{u_k\}$  are the lower and upper bounds of the indices used by the entries that compose  $t'$ .

*Remark 0.1.4.* We don't necessarily write the lower bound index if it is equal to 1, neither the upper bound index if it is equal to  $n_k^{(t)}$ .

#### Definition 0.1.6. Slicing

A *slice* operation, along the last ranks  $\{r_1, r_2, \dots, r_s\}$ , and indexed by  $(i_{r_1}, i_{r_2}, \dots, i_{r_s})$ ,

is a morphism  $s : \mathbb{T} = \bigotimes_{k=1}^r \mathbb{V}_k \rightarrow \bigotimes_{k=1}^{r-s} \mathbb{V}_k$ , such that:

$$\begin{aligned} s(t)[i'_1, i'_2, \dots, i'_{r-s}] &= t[i'_1, i'_2, \dots, i'_{r-s}, i_{r_1}, i_{r_2}, \dots, i_{r_s}] \\ \text{i.e. } s(t) &:= t[:, :, \dots, :, i_{r_1}, i_{r_2}, \dots, i_{r_s}] \end{aligned}$$

where  $:=$  means that entries of the right operand are assigned to the left operand. We denote  $t_{i_{r_1}, i_{r_2}, \dots, i_{r_s}}$  and call it the *slice* of  $t$ . Slicing along a subset of ranks that are not the lasts is defined similarly.  $s(\mathbb{T})$  is called a *slice subspace*.

#### Definition 0.1.7. Flattening

A *flatten* operation is an isomorphism  $f : \mathbb{T} \rightarrow \mathbb{V}$ , between a tensor space  $\mathbb{T}$

of rank  $r$  and an  $n$ -dimensional vector space  $\mathbb{V}$ , where  $n = \prod_{k=1}^r n_k$ . It is characterized by a bijection in the index spaces  $g : \prod_{k=1}^r \{1, \dots, n_k\} \rightarrow \{1, \dots, n\}$  such that

$$\forall t \in \mathbb{T}, f(t)[g(i_1, i_2, \dots, i_r)] = f(t[i_1, i_2, \dots, i_r])$$

We call an inverse operation a *de-flatten* operation.

**Remark 0.1.5. Row major ordering**

The choice of  $g$  determines in which order the indexing is made.  $g$  is reminiscent of how data of multidimensional arrays or tensors are stored internally by programming languages. In most tensor manipulation languages, incrementing the memory address (*i.e.* the output of  $g$ ) will first increment the last index  $i_r$  if  $i_r < n_r$  (and if else  $i_r = n_r$ , then  $i_r := 1$  and ranks are ordered in reverse lexicographic order to decide what indices are incremented). This is called *row major ordering*, as opposed to *column major ordering*. That is, in row major,  $g$  is defined as

$$g(i_1, i_2, \dots, i_r) = \sum_{p=1}^r \left( \prod_{k=p+1}^r n_k \right) i_p \quad (1)$$

**Definition 0.1.8. Reshaping**

A *reshape* operation is an isomorphism defined on a tensor space  $\mathbb{T} = \bigotimes_{k=1}^r \mathbb{V}_k$  such that some of its basis vector spaces  $\{\mathbb{V}_k\}$  are de-flattened and some of its slice subspaces are flattened.

**0.1.1.3 Binary operations**

We define binary operations on tensors that we'll later have use for. In particular, we define *tensor contraction* which is sometimes called *tensor multiplication*, *tensor product* or *tensor dotproduct* by other sources. We also define *convolution* and *pooling* which serve as the common building blocks of convolution neural network architectures (see Section 0.1.2.5).

**Definition 0.1.9. Contraction**

A *tensor contraction* between two tensors, along ranks of same dimensions, is defined by natural extension of the dot product operation to tensors.

More precisely, let  $\mathbb{T}_1$  a tensor space of shape  $n_1^{(1)} \times n_2^{(1)} \times \cdots \times n_{r_1}^{(1)}$ , and  $\mathbb{T}_2$  a tensor space of shape  $n_1^{(2)} \times n_2^{(2)} \times \cdots \times n_{r_2}^{(2)}$ , such that  $\forall k \in \{1, 2, \dots, s\}, n_{r_1-(s-k)}^{(1)} = n_k^{(2)}$ , then the tensor contraction between  $t_1 \in \mathbb{T}_1$  and  $t_2 \in \mathbb{T}_2$  is defined as:

$$\left\{ \begin{array}{l} t_1 \otimes t_2 = t_3 \in \mathbb{T}_3 \text{ of shape } n_1^{(1)} \times \cdots \times n_{r_1-s}^{(1)} \times n_{s+1}^{(2)} \times \cdots \times n_{r_2}^{(2)} \text{ where} \\ t_3[i_1^{(1)}, \dots, i_{r_1-s}^{(1)}, i_{s+1}^{(2)}, \dots, i_{r_2}^{(2)}] = \\ \sum_{k_1=1}^{n_1^{(2)}} \cdots \sum_{k_s=1}^{n_s^{(2)}} t_1[i_1^{(1)}, \dots, i_{r_1-s}^{(1)}, k_1, \dots, k_s] t_2[k_1, \dots, k_s, i_{s+1}^{(2)}, \dots, i_{r_2}^{(2)}] \end{array} \right.$$

For the sake of simplicity, we omit the case where the contracted ranks are not the last ones for  $t_1$  and the first ones for  $t_2$ . But this definition still holds in the general case subject to a permutation of the indices.

**Definition 0.1.10. Covariant and contravariant indices**

Given a tensor contraction  $t_1 \otimes t_2$ , indices of the left hand operand  $t_1$  that are not contracted are called *covariant* indices. Those that are contracted are called *contravariant* indices. For the right operand  $t_2$ , the naming convention is the opposite. The set of covariant and contravariant indices of both operands are called the *transformation laws* of the tensor contraction.

**Remark 0.1.6. Transformation law independency**

Contrary to most mathematical definitions, tensors in deep learning are independent of any transformation law, so that they must be specified for tensor contractions.

**Remark 0.1.7. Einstein summation convention**

Using subscript notation for covariant indices and superscript notation for contravariant indices, the previous tensor contraction can be written using the Einstein summation convention as:

$$t_{1_{i_1^{(1)} \dots i_{r_1-s}^{(1)}}}{}^{k_1 \dots k_s} t_{2_{k_1 \dots k_s}}{}^{i_{s+1}^{(2)} \dots i_{r_2}^{(2)}} = t_{3_{i_1^{(1)} \dots i_{r_1-s}^{(1)}}}{}^{i_{s+1}^{(2)} \dots i_{r_2}^{(2)}} \quad (2)$$

Dot product  $u_k v^k = \lambda$  and matrix product  $A_i{}^k B_k{}^j = C_i{}^j$  are common examples of tensor contractions.

**Proposition 0.1.1.** A contraction can be rewritten as a matrix product.

*Proof.* Using notation of (2), with the reshapings  $t_1 \mapsto T_1$ ,  $t_2 \mapsto T_2$  and  $t_3 \mapsto T_3$  defined by grouping all covariant indices into a single index and all

contravariant indices into another single index, we can rewrite

$$T_{1_{g_i(i_1^{(1)}, \dots, i_{r_1-s}^{(1)})}}^{g_k(k_1, \dots, k_s)} T_{2_{g_k(k_1, \dots, k_s)}}^{g_j(i_{s+1}^{(2)}, \dots, i_{r_2}^{(2)})} = T_{3_{g_i(i_1^{(1)}, \dots, i_{r_1-s}^{(1)})}}^{g_j(i_{s+1}^{(2)}, \dots, i_{r_2}^{(2)})}$$

where  $g_i$ ,  $g_k$  and  $g_j$  are bijections defined similarly as in (1).  $\square$

**Definition 0.1.11. Convolution**

The  $n$ -dimensional convolution, denoted  $*^n$ , between  $t_1 \in \mathbb{T}_1$  and  $t_2 \in \mathbb{T}_2$ , where  $\mathbb{T}_1$  and  $\mathbb{T}_2$  are of the same rank  $n$  such that  $\forall p \in \{1, 2, \dots, n\}, n_p^{(1)} \geq n_p^{(2)}$ , is defined as:

$$\begin{cases} t_1 *^n t_2 = t_3 \in \mathbb{T}_3 \text{ of shape } n_1^{(3)} \times \dots \times n_n^{(3)} \text{ where} \\ \forall p \in \{1, 2, \dots, n\}, n_p^{(3)} = n_p^{(1)} - n_p^{(2)} + 1 \\ t_3[i_1, \dots, i_n] = \sum_{k_1=1}^{n_1^{(2)}} \dots \sum_{k_n=1}^{n_n^{(2)}} t_1[i_1 + n_1^{(2)} - k_1, \dots, i_n + n_n^{(2)} - k_n] t_2[k_1, \dots, k_n] \end{cases}$$

**Proposition 0.1.2.** A convolution can be rewritten as a matrix product.

*Proof.* Let  $t_1 *^n t_2 = t_3$  defined as previously with  $\mathbb{T}_1 = \bigotimes_{k=1}^r \mathbb{V}_k^{(1)}$ ,  $\mathbb{T}_2 = \bigotimes_{k=1}^r \mathbb{V}_k^{(2)}$ . Let  $t'_1 \in \bigotimes_{k=1}^r \mathbb{V}_k^{(1)} \otimes \bigotimes_{k=1}^r \mathbb{V}_k^{(2)}$  such that  $t'_1[i_1, \dots, i_n, k_1, \dots, k_n] = t_1[i_1 + n_1^{(2)} - k_1, \dots, i_n + n_n^{(2)} - k_n]$ , then

$$t_3[i_1, \dots, i_n] = \sum_{k_1=1}^{n_1^{(2)}} \dots \sum_{k_n=1}^{n_n^{(2)}} t'_1[i_1, \dots, i_n, k_1, \dots, k_n] t_2[k_1, \dots, k_n]$$

where we recognize a tensor contraction. Proposition 0.1.1 concludes.  $\square$

The two following operations are meant to further decrease the shape of the resulting output.

**Definition 0.1.12. Strided convolution**

The  $n$ -dimensional *strided* convolution, with strides  $s = (s_1, s_2, \dots, s_n)$ , denoted  $*_s^n$ , between  $t_1 \in \mathbb{T}_1$  and  $t_2 \in \mathbb{T}_2$ , where  $\mathbb{T}_1$  and  $\mathbb{T}_2$  are of the same

rank  $n$  such that  $\forall p \in \{1, 2, \dots, n\}, n_p^{(1)} \geq n_p^{(2)}$ , is defined as:

$$\left\{ \begin{array}{l} t_1 *_s^n t_2 = t_4 \in \mathbb{T}_4 \text{ of shape } n_1^{(4)} \times \dots \times n_n^{(4)} \text{ where} \\ \forall p \in \{1, 2, \dots, n\}, n_p^{(4)} = \lfloor \frac{n_p^{(1)} - n_p^{(2)} + 1}{s_p} \rfloor \\ t_4[i_1, \dots, i_n] = (t_1 *_s^n t_2)[(i_1 - 1)s_n + 1, \dots, (i_n - 1)s_n + 1] \end{array} \right.$$

*Remark 0.1.8.* Unformally, a strided convolution is defined as if it were a regular subsampling of a convolution. They match if  $s = (1, 1, \dots, 1)$ .

**Definition 0.1.13. Pooling**

Let a real-valued function  $f$  defined on all tensor spaces of any shape, *e.g.* the *max* or *average* function. An  $f$ -pooling operation is a mapping  $t \mapsto t'$  such that each entry of  $t'$  is an image by  $f$  of a subtensor of  $t$ .

*Remark 0.1.9.* Usually, the set of subtensors that are reduced by  $f$  into entries of  $t'$  are defined by a regular partition of the entries of  $t$ .

### 0.1.2 Neural Networks

A feed-forward neural network could originally be formalized as a composite function chaining linear and non-linear functions (Rumelhart et al., 1985; LeCun et al., 1989; LeCun et al., 1995), even up until the important breakthroughs that generated a surge of interest in the field (Hinton et al., 2012; Krizhevsky et al., 2012; Simonyan et al., 2014). However, in more recent advances, more complex architectures have emerged (Szegedy et al., 2015; He et al., 2016; Zoph et al., 2016; Huang et al., 2017), such that the former formalization does not suffice. We provide a definition for the first kind of neural networks (Definition 0.1.14) and use it to present its related concepts. Then we give a more generic definition (Definition 0.1.19).

Note that in this manuscript, we only consider neural networks that are *feed-forward* (Zell, 1994; Wikipedia, 2018).

#### 0.1.2.1 Description

We denote by  $I_f$  the *domain of definition* of a function  $f$  ("I" stands for "input") and by  $O_f = f(I_f)$  its *image* ("O" stands for "output"), and we represent it as  $I_f \xrightarrow{f} O_f$ .

##### 0.1.2.1.1 Simple formalization

#### Definition 0.1.14. Neural network (simply connected)

Let  $F$  be a function such that  $I_f$  and  $O_f$  are vector or tensor spaces.  $F$  is a *simply connected neural network function* if there are a series of linear or affine functions  $(g_k)_{k=1,2,\dots,L}$  and a series of non-linear derivable univariate functions  $(h_k)_{k=1,2,\dots,L}$  such that:

$$\begin{cases} \forall k \in \{1, 2, \dots, L\}, f_k = h_k \circ g_k, \\ I_F = I_{f_1} \xrightarrow{f_1} O_{f_1} \cong I_{f_2} \xrightarrow{f_2} \dots \xrightarrow{f_L} O_{f_L} = O_F, \\ F = f_L \circ \dots \circ f_2 \circ f_1 \end{cases}$$

The couple  $(g_k, h_k)$  is called the  $k$ -th *layer* of the neural network.  $L$  is its depth. For  $x \in I_f$ , we denote by  $x_k = f_k \circ \dots \circ f_2 \circ f_1(x)$  the *activations* of the  $k$ -th layer.

**Definition 0.1.15. Activation function**

An *activation function*  $h$  is a real-valued univariate function that is non-linear and derivable, that is also defined by extension on any linear space with the functional notation  $h(v)[i] = h(v[i])$ .

**Definition 0.1.16. Layer**

A couple  $(g, h)$ , where  $g$  is an affine or linear function, and  $h$  is an activation function is called a *layer*. The set of layers is denoted  $\mathcal{L}$ .

*Remark 0.1.10. Bias*

Affine functions  $\tilde{g}$  can be written as a sum between a linear function  $g$  and a constant vector  $b$  which is called the *bias*. Its role is to augment the expressivity (see Section 0.1.2.1.4) of the neural network's family of functions. For notational conveniency, we will often omit the biases and thus only consider linear functions.

*Remark 0.1.11. Universal approximation*

Early researches have shown that neural networks with one level of depth can approximate any real-valued function defined on a compact subset of  $\mathbb{R}^n$ . This result was first proved for sigmoidal activations (Cybenko, 1989), and then it was shown it did not depend on the sigmoidal activations (Hornik et al., 1989; Hornik, 1991).

For example, for the application of supervised learning when a neural network is trained from data (see Section 0.1.2.2), this result is quite important because it brings theoretical justification that the objective exists (even though it doesn't inform whether an algorithm to approach it exists).

*Remark 0.1.12. Computational difficulty*

However, reaching such objective is a computationally difficult problem, which drove back interest from the field. Thank to better hardware and to using better initialization schemes that speed up learning, researchers started to report more successes with deep neural networks (Hinton et al., 2006; Glorot et al., 2010) ; see (Bengio, 2009) for a review of this period. It ultimately came to a surge of interest in the field after a significant breakthrough on the imagenet dataset (Deng et al., 2009) with a deep convolutional architecture (Krizhevsky et al., 2012). The use of the fast ReLU activation function (Glorot et al., 2011) as well as leveraging graphical processing units with CUDA (Nickolls et al., 2008) were also key factors in overcoming this computational difficulty.

**Remark 0.1.13. Adoption of ReLU activations**

Historically, sigmoidal and tanh activations were mostly used (Cybenko, 1989; LeCun et al., 1989). However in recent practice, the *rectified linear unit* (ReLU), which implements the *rectifier* function  $h : x \mapsto \max(0, x)$  with convention  $h'(0) = 0$  (first introduced as the *positive part*, Jarrett et al., 2009), is the most used activation, as it was demonstrated to be faster and to obtain better results (Glorot et al., 2011). ReLU originated numerous variants *e.g.* *leaky rectified linear unit* (Maas et al., 2013), *parametric rectified linear unit* (PReLU, He et al., 2015), *exponential linear unit* (ELU, Clevert et al., 2015), *scaled exponential linear unit* (SELU, Klambauer et al., 2017).

**Remark 0.1.14.** Of particular interest for the intuition is a result stating that a simply connected neural networks with only ReLU activations (ReNN) is a piecewise linear functions (PWL) (Pascanu et al., 2013), and that conversely any PWL is also a ReNN such that an upper bound of its depth is logarithmically related to the input dimension (Arora et al., 2018, th. 2.1.).

**0.1.2.1.2 Interpretation**

Until now, we have formally introduced a neural network as a mathematical function. As its name suggests, such function can be interpreted from a connectivity viewpoint (LeCun, 1987).

**Definition 0.1.17. Connectivity matrix**

Let  $g$  a linear function. Without loss of generality subject to a flattening, let's suppose  $I_g$  and  $O_g$  are vector spaces. Then there exists a *connectivity matrix*  $W_g$ , such that:

$$\forall x \in I_g, g(x) = W_g x$$

We denote  $W_k$  the connectivity matrix of the  $k$ -th layer.

**Remark 0.1.15. Biological inspiration**

A (*computational*) *neuron* is a computational unit that is biologically inspired. Each neuron should be capable of:

1. receiving modulated signals from other neurons and aggregate them,
2. applying to the result a derivable activation,
3. passing the signal to other neurons.



That is to say, each domain  $\{I_{f_k}\}$  and  $O_F$  can be interpreted as a layer of neurons, with one neuron for each dimension. The connectivity matrices  $\{W_k\}$  describe the connexions between each successive layers. A neuron is illustrated on Figure 1.




Figure 1: A neuron

#### 0.1.2.1.3 Generic formalization

The former neural networks are said to be *simply connected* because each layer only takes as input the output of the previous one. We'll give a more general definition after first defining branching operations.

##### Definition 0.1.18. Branching

A *binary branching operation* of a neural network is an operation between two activations,  $x_{k_1} \bowtie x_{k_2}$ , that outputs, subject to shape compatibility, either their addition, either their concatenation along a rank, or their concatenation as a list.

A *branching operation* of a neural network between  $n$  activations,  $x_{k_1} \bowtie x_{k_2} \bowtie \dots \bowtie x_{k_n}$ , is a composition of binary branching operations, or is the identity function  $Id$  if  $n = 1$ .

##### Definition 0.1.19. Neural network (generic definition)

The set of *neural network functions*  $\mathcal{N}$  is defined inductively as follow

1.  $Id \in \mathcal{N}$
2.  $f \in \mathcal{N} \wedge (g, h) \in \mathcal{L} \wedge O_f \subset I_g \Rightarrow h \circ g \circ f \in \mathcal{N}$
3. for all shape compatible branching operations:  
 $f_1, f_2, \dots, f_n \in \mathcal{N} \Rightarrow f_1 \bowtie f_2 \bowtie \dots \bowtie f_n \in \mathcal{N}$

*Remark 0.1.16. Examples*

TODO: blabla: residual connections, skip connections, branching layers, tensor mixture explanation

#### 0.1.2.1.4 Expressive analysis

Given a set or a family of neural networks  $N \subset \mathcal{N}$ , the role of expressive analysis is to study the range of functions that objects of  $N$  are capable to approximate.

**Definition 0.1.20. Expressivity**

*Remark 0.1.17. Benefits of depth*

*Remark 0.1.18. Benefits of branching*

(Cohen et al., 2018)

#### 0.1.2.2 Training

Given a objective function  $f$ , training is the process of incrementally modifying a neural network  $F$  upon obtaining a better approximation of  $f$ . In other word, training refers to searching the best approximation in a (possibly infinite) set  $N \subset \mathcal{N}$  generated by training. Hence, the expressivity of  $N$  is crucial.

In what follows, we present notions related to training algorithms based on gradient descent.

TODO: blabla related to expressivity

**Definition 0.1.21. Weights**

Let consider the  $k$ -th layer of a neural networks. We define its weights as coordinates of a vector  $\theta_k$ , called the *weight kernel*, such that:

$$\forall(i, j), \begin{cases} \exists p, W_k[i, j] := \theta_k[p] \\ \text{or } W_k[i, j] = 0 \end{cases}$$

A weight  $p$  that appears multiple times in  $W_k$  is said to be *shared*. Two parameters of  $W_k$  that share a same weight  $p$  are said to be *tied*. The number of weights of the  $k$ -th layer is  $n_1^{(\theta_k)}$ .

*Remark 0.1.19. Learning*

A *loss* function  $\mathcal{L}$  penalizes the output  $x_L = F(x)$  relatively to the approximation error  $|F(x) - f(x)|$ . Gradient w.r.t.  $\theta_k$ , denoted  $\vec{\nabla}_{\theta_k}$ , is used to update the weights via an optimization algorithm based on gradient descent and a learning rate  $\alpha$ , that is:

$$\theta_k^{(\text{new})} = \theta_k^{(\text{old})} - \alpha \cdot \vec{\nabla}_{\theta_k} \left( \mathcal{L} \left( x_L, \theta_k^{(\text{old})} \right) + R \left( \theta_k^{(\text{old})} \right) \right) \quad (3)$$

where  $\alpha$  can be a scalar or a vector,  $\cdot$  can denote outer or pointwise product, and  $R$  is a regularizer. They depend on the optimization algorithm.

**TODO: examples of optimizations**

*Remark 0.1.20. Linear complexity*

The complexity of computing the gradients is linear with the number of weights.

*Proof.* Without loss of generality, we assume that the neural network is simply connected. Thanks to the chain rule,  $\vec{\nabla}_{\theta_k}$  can be computed using gradients that are w.r.t.  $x_k$ , denoted  $\vec{\nabla}_{x_k}$ , which in turn can be computed using gradients w.r.t. outputs of the next layer  $k+1$ , up to the gradients given on the output layer.

That is:

$$\vec{\nabla}_{\theta_k} = J_{\theta_k}(x_k) \vec{\nabla}_{x_k} \quad (4)$$

$$\begin{aligned} \vec{\nabla}_{x_k} &= J_{x_k}(x_{k+1}) \vec{\nabla}_{x_{k+1}} \\ \vec{\nabla}_{x_{k+1}} &= J_{x_{k+1}}(x_{k+2}) \vec{\nabla}_{x_{k+2}} \\ &\dots \end{aligned} \quad (5)$$

$$\vec{\nabla}_{x_{L-1}} = J_{x_{L-1}}(x_L) \vec{\nabla}_{x_L}$$

Obtaining,

$$\vec{\nabla}_{\theta_k} = J_{\theta_k}(x_k) \left( \prod_{p=k}^{L-1} J_{x_p}(x_{p+1}) \right) \vec{\nabla}_{x_L} \quad (6)$$

where  $J_{\text{wrt}}(\cdot)$  are the respective jacobians which can be determined with the layer's expressions and the  $\{x_k\}$ ; and  $\vec{\nabla}_{x_L}$  can be determined using  $\mathcal{L}$ ,  $R$  and  $x_L$ .  $\square$

This allows to compute the gradients with a complexity that is linear with the number of weights (only one computation of the activations), instead of being quadratic if it were done with the difference quotient expression of the derivatives (one more computation of the activations for each weight).

**Remark 0.1.21. Back propagation**

We can remark that (5) rewrites as

$$\begin{aligned}\vec{\nabla}_{x_k} &= J_{x_k}(x_{k+1})\vec{\nabla}_{x_{k+1}} \\ &= J_{x'_k}(h(x'_k))J_{x_k}(W_k x_k)\vec{\nabla}_{x_{k+1}}\end{aligned}\tag{7}$$

where  $x'_k = W_k x_k$ , and these jacobians can be expressed as:

$$J_{x'_k}(h(x'_k))[i, j] = \delta_i^j h'(x'_k[i])\tag{8}$$

$$\begin{aligned}J_{x'_k}(h(x'_k)) &= I h'(x'_k) \\ J_{x_k}(W_k x_k) &= W_k^T\end{aligned}\tag{9}$$

That means that we can write  $\vec{\nabla}_{x_k} = (\tilde{h}_k \circ \tilde{g}_k)(\vec{\nabla}_{x_{k+1}})$  such that the connectivity matrix  $\tilde{W}_k$  is obtained by transposition. This can be interpreted as gradient calculation being a *back-propagation* on the same neural network, in opposition of the *forward-propagation* done to compute the output.

### 0.1.2.3 Example of layers

**Definition 0.1.22. Connections**

The set of *connections* of a layer  $(g, h)$ , denoted  $C_g$ , is defined as:

$$C_g = \{(i, j), \exists p, W_g[i, j] := \theta_g[p]\}$$

We have  $0 \leq |C_g| \leq n_1^{(W_g)} n_2^{(W_g)}$ .

**Definition 0.1.23. Dense layer**

A *dense layer*  $(g, h)$  is a layer such that  $|C_g| = n_1^{(W_g)} n_2^{(W_g)}$ , *i.e.* all possible connections exist. The map  $(i, j) \mapsto p$  is usually a bijection, meaning that there is no weight sharing.

**Definition 0.1.24. Partially connected layer**

A *partially connected layer*  $(g, h)$  is a layer such that  $|C_g| < n_1^{(W_g)} n_2^{(W_g)}$ .

A *sparsely connected layer*  $(g, h)$  is a layer such that  $|C_g| \ll n_1^{(W_g)} n_2^{(W_g)}$ .

**Definition 0.1.25. Convolutional layer**

A  $n$ -dimensional *convolutional layer*  $(g, h)$  is such that the weight kernel  $\theta_g$  can be reshaped into a tensor  $w$  of rank  $n + 2$ , and such that

$$\begin{cases} I_g \text{ and } O_g \text{ are tensor spaces of rank } n + 1 \\ \forall x \in I_g, g(x) = (g(x)_q = \sum_p x_p *^n w_{p,q})_{\forall q} \end{cases}$$

where  $p$  and  $q$  index slices along the last ranks.

**Definition 0.1.26. Feature maps and input channels**

The slices  $g(x)_q$  are typically called *feature maps*, and the slices  $x_p$  are called *input channels*. Let's denote by  $n_o = n_{n+1}^{(O_g)}$  and  $n_i = n_{n+1}^{(I_g)}$  the number of feature maps and input channels. In other words, Definition 0.1.25 means that for each feature maps, a convolution layer computes  $n_i$  convolutions and sums them, computing a total of  $n_i \times n_o$  convolutions.

*Remark 0.1.22.* Note that because they are simply summed, entries of two different input channels that have the same coordinates are assumed to share some sort of relationship. For instance on images, entries of each input channel (typically corresponding to Red, Green and Blue channels) that have the same coordinates share the same pixel location.

*Remark 0.1.23.* Given a tensor input  $x$ , the  $n$ -dimensional convolutions between the inputs channels  $x_p$  and slices of a weight tensor  $w_{p,q}$  would result in outputs  $y_q$  of shape  $n_1^{(x)} - n_1^{(w)} + 1 \times \dots \times n_n^{(x)} - n_n^{(w)} + 1$ . So, in order to preserve shapes, a padding operation must pad  $x$  with  $n_1^{(w)} - 1 \times \dots \times n_n^{(w)} - 1$  zeros beforehand. For example, the padding function of the library *tensorflow* (Abadi et al., 2015) pads each rank with a balanced number of zeros on the left and right indices (except if  $n_t^{(w)} - 1$  is odd then there is one more zero on the left).

**Definition 0.1.27. Padding**

A convolutional layer with *padding*  $(g, h)$  is such that  $g$  can be decomposed as  $g = g_{\text{pad}} \circ g'$ , where  $g'$  is the linear part of a convolution layer as in Definition 0.1.25, and  $g_{\text{pad}}$  is an operation that pads zeros to its inputs such that  $g$  preserves tensor shapes.

*Remark 0.1.24.* One asset of padding operations is that they limit the possible loss of information on the borders of the subsequent convolutions, as well as preventing a decrease in size. Moreover, preserving shape is needed to build some neural network architectures, especially for ones with branching operations *e.g.* Remark 0.1.16. On the other hand, they increase memory and computational footprints.

**Proposition 0.1.3. Connectivity matrix of a convolution with padding**

A convolutional layer with padding  $(g, h)$  is equivalently defined as  $W_g$  being a  $n_i \times n_o$  block matrix such that its blocks are Toeplitz matrices.

*Proof.* Let's consider the slices indexed by  $p$  and  $q$ , and to simplify the notations, let's drop the subscripts  $p, q$ . We recall from Definition 0.1.11 that

$$\begin{aligned}
y &= (x *^n w)[j_1, \dots, j_n] \\
&= \sum_{k_1=1}^{n_1^{(w)}} \cdots \sum_{k_n=1}^{n_n^{(w)}} x[j_1 + n_1^{(w)} - k_1, \dots, j_n + n_n^{(w)} - k_n] w[k_1, \dots, k_n] \\
&= \sum_{i_1=j_1}^{j_1+n_1^{(w)}-1} \cdots \sum_{i_n=j_n}^{j_n+n_n^{(w)}-1} x[i_1, \dots, i_n] w[j_1 + n_1^{(w)} - i_1, \dots, j_n + n_n^{(w)} - i_n] \\
&= \sum_{i_1=1}^{n_1^{(x)}} \cdots \sum_{i_n=1}^{n_n^{(x)}} x[i_1, \dots, i_n] \tilde{w}[i_1, j_1, \dots, i_n, j_n] \\
&\text{where } \tilde{w}[i_1, j_1, \dots, i_n, j_n] = \\
&\quad \begin{cases} w[j_1 + n_1^{(w)} - i_1, \dots, j_n + n_n^{(w)} - i_n] & \text{if } \forall t, 0 \leq i_t - j_t \leq n_t^{(w)} - 1 \\ 0 & \text{otherwise} \end{cases}
\end{aligned}$$

Using Einstein summation convention as in (2) and permuting indices, we recognize the following tensor contraction

$$y_{j_1 \dots j_n} = x_{i_1 \dots i_n} \tilde{w}^{i_1 \dots i_n}_{j_1 \dots j_n} \quad (10)$$

Following Proposition 0.1.1, we reshape (10) as a matrix product. To reshape  $y \mapsto Y$ , we use the row major order bijections  $g_j$  as in (1) defined onto  $\{(j_1, \dots, j_n), \forall t, 1 \leq j_t \leq n_t^{(y)}\}$ . To reshape  $x \mapsto X$ , we use the same row major order bijection  $g_j$ , however defined on the indices that support non zero-padded values, so that zero-padded values are lost after reshaping. That

is, we use a bijection  $g_i$  such that  $g_i(i_1, i_2, \dots, i_n) = g_j(i_1 - o_1, i_2 - o_2, \dots, i_n - o_n)$  defined if and only if  $\forall t, 1 + o_t \leq i_t \leq n_t^{(y)}$ , where the  $\{o_t\}$  are the starting offsets of the non zero-padded values.  $\tilde{w} \mapsto W$  is reshaped by using  $g_j$  for its covariant indices, and  $g_i$  for its contravariant indices. The entries lost by using  $g_i$  do not matter because they would have been nullified by the resulting matrix product. We remark that  $W$  is exactly the block  $(p, q)$  of  $W_g$  (and not of  $W_{g'}$ ). Now let's prove that it is a Toeplitz matrix. Thanks to the linearity of the expression (1) of  $g_j$ , by denoting  $i'_t = i_t - o_t$ , we obtain

$$g_i(i_1, i_2, \dots, i_n) - g_j(j_1, j_2, \dots, j_n) = g_j(i'_1 - j_1, i'_2 - j_2, \dots, i'_n - j_n) \quad (11)$$

To simplify the notations, let's drop the arguments of  $g_i$  and  $g_j$ . By bijectivity of  $g_j$ , (11) tells us that  $g_i - g_j$  remains constant if and only if  $i'_t - j_t$  remains constant for all  $t$ . Recall that

$$W[g_i, g_j] = \begin{cases} w[j_1 + n_1^{(w)} - i'_1, \dots, j_n + n_n^{(w)} - i'_n] & \text{if } \forall t, 0 \leq i'_t - j_t \leq n_t^{(w)} - 1 \\ 0 & \text{otherwise} \end{cases} \quad (12)$$

Hence, on a diagonal of  $W$ ,  $g_i - g_j$  remaining constant means that  $W[g_i, g_j]$  also remains constants. So  $W$  is a Toeplitz matrix.

The converse is also true as we used invertible functions in the index spaces through the proof.  $\square$

*Remark 0.1.25.* The former proof makes clear that the result doesn't hold in case there is no padding. This is due to border effects when the index of the  $n^{\text{th}}$  rank resets in the definition of the row-major ordering function  $g_j$  that would be used. Indeed, under appropriate definitions, the matrices could be seen as almost Toeplitz.

*Remark 0.1.26.* Comparitively with dense layers, convolution layers enjoy a significant decrease in the number of weights. For example, an input  $2 \times 2$  convolution on images with 3-color input channels, would breed only 12 weights per feature maps, independently of the numbers of input neurons. On image datasets, their usage also breeds a significant boost in performance compared with dense layers (Krizhevsky et al., 2012), for they allow to take advantage of the topology of the inputs while dense layers don't (LeCun et al., 1995). A more thorough comparison and explanation of their assets will be discussed in Section ??.

**Definition 0.1.28. Stride**

A convolutional layer with *stride* is a convolutional layer that computes strided convolutions (with  $\text{stride} > 1$ ) instead of convolutions.

**Definition 0.1.29. Pooling**

A layer with *pooling*  $(g, h)$  is such that  $g$  can be decomposed as  $g = g' \circ g_{\text{pool}}$ , where  $g_{\text{pool}}$  is a pooling operation.

*Remark* 0.1.27. **Downscaling**

Layers with stride or pooling downscale the signals that passes through the layer. These types of layers allows to compute features at a coarser level, giving the intuition that the deeper a layer is in the network, the more abstract are the informations captured by the weights of the layer.

TODO: below

**0.1.2.4 Example of regularizations***Remark* 0.1.28. **Overfitting** TODO:

A layer with *dropout*  $(g, h)$  is such that  $h = h_1 \circ h_2$ , where  $(g, h_2)$  is a layer and  $h_1$  is a dropout operation (Srivastava et al., 2014). When dropout is used, a certain number of neurons are randomly set to zero during the training phase, compensated at test time by scaling down the whole layer. This is done to prevent overfitting.

**0.1.2.5 Example of architectures**

TODO: rephrase

A multilayer perceptron (MLP) (Hornik et al., 1989) is a neural network composed of only dense layers. A convolutional neural network (CNN) (LeCun et al., 1998) is a neural network composed of convolutional layers.

Neural networks are commonly used for machine learning tasks. For example, to perform supervised classification, we usually add a dense output layer  $s = (g_{L+1}, h_{L+1})$  with as many neurons as classes. We measure the error between an output and its expected output with a discriminative loss function  $\mathcal{L}$ . During the training phase, the weights of the network are adapted for the



classification task based on the errors that are back-propagated (Hornik et al., 1989) via the chain rule and according to a chosen optimization algorithm (*e.g.* Bottou, 2010).

### 0.1.3 Graphs

TODO: check this subsection

A graph  $G$  is defined as a couple  $(V, E)$  where  $V$  represents the set of nodes and  $E \subseteq \binom{V}{2}$  is the set of edges connecting these nodes.

TODO: Example of figure

We encounter the notion of graphs several times in deep learning:

- Connections between two layers of a deep learning model can be represented as a bipartite graph, coined *connectivity graph*. It encodes how the information is propagated through a layer to another. See Section 0.1.3.1.
- A computation graph is used by deep learning frameworks to keep track of the dependencies between layers of a deep learning models, in order to compute forward and back-propagation. See Section 0.1.3.2.
- A graph can represent the underlying structure of an object (often a vector), whose nodes represent its features. See Section 0.1.3.3.
- Datasets can also be graph-structured, where the nodes represent the objects of the dataset. See Section 0.1.3.4.

#### 0.1.3.1 Connectivity graph

A Connectivity graph is the bipartite graph whose adjacency matrix is the connectivity matrix of a layer of neurons. Formally, given a linear part of a layer, let  $\mathbf{x}$  and  $\mathbf{y}$  be the input and output signals,  $n$  the size of the set of input neurons  $N = \{u_1, u_2, \dots, u_n\}$ , and  $m$  the size of the set of output neurons  $M = \{v_1, v_2, \dots, v_m\}$ . This layer implements the equation  $y = \Theta x$  where  $\Theta$  is a  $n \times m$  matrix.

**Definition 0.1.30.** The *connectivity graph*  $G = (V, E)$  is defined such that  $V = N \cup M$  and  $E = \{(u_i, v_j) \in N \times M, \Theta_{ij} \neq 0\}$ .

I.e. the connectivity graph is obtained by drawing an edge between neurons for which  $\Theta_{ij} \neq 0$ . For instance, in the special case of a complete bipartite graph, we would obtain a dense layer. Connectivity graphs are especially useful to represent partially connected layers, for which most of the  $\Theta_{ij}$  are

0. For example, in the case of layers characterized by a small local receptive field, the connectivity graph would be sparse, and output neurons would be connected to a set of input neurons that corresponds to features that are close together in the input space. Figure 2 depicts some examples.




Figure 2: Examples

TODO: Figure 2. It's just a placeholder right now

Connectivity graphs also allow to graphically modelize how weights are tied in a neural layer. Let's suppose the  $\Theta_{ij}$  are taking their values only into the finite set  $K = \{w_1, w_2, \dots, w_\kappa\}$  of size  $\kappa$ , which we will refer to as the *kernel of weights*. Then we can define a labelling of the edges  $s : E \rightarrow K$ .  $s$  is called the *weight sharing scheme* of the layer. This layer can then be formulated as  $\forall v \in M, y_v = \sum_{u \in N, (u,v) \in E} w_{s(u,v)} x_u$ . Figure 3 depicts the connectivity graph of

a 1-d convolution layer and its weight sharing scheme.




Figure 3: Depiction of a 1D-convolutional layer and its weight sharing scheme.

TODO: Add weight sharing scheme in Figure 3

**0.1.3.2 Computation graph****0.1.3.3 Underlying graph structure****0.1.3.4 Graph-structured dataset**

transductive vs inductive

**0.1.4 Special classes of graphs****0.1.4.1 Grid graphs****0.1.4.2 Spatial graphs****0.1.4.3 Projections of spatial graphs**

## 0.2 Subject disambiguation

TODO: Rework 1.1

### 0.2.1 Naming conventions

#### 0.2.1.1 Basic notions

Let's recall the naming conventions of basic notions.

A *function*  $f : E \rightarrow F$  maps objects  $x \in E$  to objects  $y \in F$ , as  $y = f(x)$ .

Its *definition domain*  $\mathcal{D}_f = E$  is the set of objects onto which it is defined.

We will often just use the term *domain*.

We also say that  $f$  is *taking values* in its *codomain*  $F$ .

The *image per*  $f$  of the subset  $U \subset E$ , denoted  $f(U)$ , is  $\{y \in F, \exists x \in U, y = f(x)\}$ .

The *image of*  $f$  is the image of its domain. We denote  $\mathcal{I}_f$ .

A vector space  $E$ , which we will always assume to be finite-dimensional in our context, is defined as  $\mathbb{R}^n$ , and is equipped with pointwise addition and scalar multiplication.

A *signal*  $s$  is a function taking values in a vector space. In other words, a signal can also be seen as a *vector* with an *underlying structure*, where the vector is composed from its image, and the underlying structure is defined by its *domain*.

For example, images are signals defined on a set of pixels. Typically, an image  $s$  in RGB representation is a mapping from pixels  $p$  to a 3d vector space, as  $s_p = (r, g, b)$ .

TODO?: figure

#### 0.2.1.2 Graphs and graph signals

TODO: more defs on grid graphs and other graphs

A *graph*  $G = (V, E)$  is defined as a set of nodes  $V$ , and a set of edges  $E \subseteq \binom{V}{2}$ .

The words *node* and *vertex* will be used equivalently, but we will rather use the first.

A *graph signal*, or *graph-structured signal* is a signal defined on the nodes of a graph, for which the underlying structure is the graph itself. A *node signal*

is a signal defined on a node, in which case it is a *node embedding* in a vector space.

Although this is rarely seen, a signal can also be defined on the edges of a graph, or on an edge. We then coin it respectively *dual graph signal*, or *edge signal* / *edge embedding*.

*Graph-structured data* can refer to any of these type of signals.

### 0.2.1.3 Data and datasets

A dataset of signals is said to be *static* if all its signals share the same underlying structure, it is said to be *non-static* otherwise.

For image datasets, being non-static would mean that the dataset contains images of different sizes or different scales. For graph signal datasets, it would mean that the underlying graph structures of the signals are different.

The point in specifying that objects of a dataset of a machine learning task are signals is that we can hope to leverage their underlying structure.

TODO: figure

## 0.2.2 Disambiguation of the subject

This thesis is entitled *Deep learning models for data without a regular structure*. So either the data of interest in this manuscript do not have any structure, or either their structure is not regular.

### 0.2.2.1 Irregularly structured data

By structured data, we mean that there exists an underlying structure over which the data is defined. This kind of data are usually modeled as signals defined over a domain. These domains are then composed of objects that are related together by some sort of structural properties. For example, pixels of images can be seen as located on a grid with integer spatial coordinates (a 2d cartesian grid graph).

It then comes handy to define the notions of structure and regularity with the help of graph signals.

#### Definition 0.2.1. Structure

Let  $s : D \rightarrow F$  be a signal defined over a finite domain.

An *underlying structure* of the signal  $s$  is a graph  $G$  that has the domain of  $s$  for nodes.

A dataset is said to be *structured*, if its objects can be modeled as signals with an underlying structure.

It is said to be *static* if all its objects share the same underlying structure, and *non-static* otherwise.

In other words, we chose to define “structured data” as “graph-structured data” by some graph. Hence we need to specify for which graphs this structure would be said to be regular, and for which it would not.

**Definition 0.2.2.** Regularity

An underlying structure is said to be *regular*, if it is a regular grid graph. It is said to be *irregular* otherwise.

A dataset is said to be *regularly structured*, if the underlying structures of its objects are regular. It is said to be *irregularly structured* otherwise.

TODO: examples

### 0.2.2.2 Unstructured data

Data can also be unstructured. If the data is not yet embedded into a finite dimensional vector space, then we will be interested in embedding techniques used in representation learning. In the other case, it is often possible to fall back to the case of irregularly structured data. For example, vectors can be seen as signals defined over the canonical basis of the vector space, and the vectors of this basis can be related together by their covariances through the dataset. It is typical to use the graph structure that has the canonical basis for nodes, with edges obtained by covariance thresholding.

TODO: examples

What follows is a draft

## 0.2.3 Datasets

## 0.2.4 Tasks

## 0.2.5 Goals

## 0.2.6 Invariance

In order to be observed, invariances must be defined relatively to an observation. Let’s give a formal definition to support our discussion.

...

## 0.2.7 Methods



# Contents

*Index terms*— Deep learning, representation learning, propagation learning, visualization, structured, unstructured regular, irregular, covariant, invariant, equivariant, tensor, scheme, weight sharing, graphs, manifold, euclidean, signal processing, graph signal processing, time series, time series database, distributed application, spatial-time series, geo time series, industrial applications, warp 10, warpscript, ...

## Temptative titles

- Learning propagational representations of irregular and unstructured data
- Learning representations of unstructured or irregularly structured datasets
- Propagational learning of unstructured or irregularly structured datasets
- Learning tensorial representation of irregular and unstructured data
- Tensorial representation of propagation in deep learning for irregular and unstructured dataset
- Structural representation learning for irregular or unstructured data
- Word for both “irregularly structured” + “unstructured” = ? (maybe “unorthodox” ?)
- Unorthodox deep learning
- ...

- Deep learning of unstructured or irregularly structured datasets
- Deep learning models for data without a regular structure
- On structures in deep learning

# Bibliography

- Abadi, Martín, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dan Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng (2015). *TensorFlow: Large-Scale Machine Learning on Heterogeneous Systems*. Software available from tensorflow.org. URL: <http://tensorflow.org/> (cit. on p. 21).
- Arora, Raman, Amitabh Basu, Poorya Mianjy, and Anirbit Mukherjee (2018). “Understanding Deep Neural Networks with Rectified Linear Units”. In: *International Conference on Learning Representations*. URL: [https://openreview.net/forum?id=B1J\\_rgWRW](https://openreview.net/forum?id=B1J_rgWRW) (cit. on p. 16).
- Bass, Jean (1968). “Cours de mathématiques”. In: (cit. on p. 7).
- Bengio, Yoshua (2009). “Learning deep architectures for AI”. In: *Foundations and trends® in Machine Learning* 2.1, pp. 1–127 (cit. on p. 15).
- Bottou, Léon (2010). “Large-scale machine learning with stochastic gradient descent”. In: *Proceedings of COMPSTAT’2010*. Springer, pp. 177–186 (cit. on p. 25).
- Clevert, Djork-Arné, Thomas Unterthiner, and Sepp Hochreiter (2015). “Fast and accurate deep network learning by exponential linear units (elus)”. In: *arXiv preprint arXiv:1511.07289* (cit. on p. 16).
- Cohen, Nadav, Ronen Tamari, and Amnon Shashua (2018). “Boosting Dilated Convolutional Networks with Mixed Tensor Decompositions”. In: *International Conference on Learning Representations*. URL: <https://openreview.net/forum?id=S1JHhv6TW> (cit. on p. 18).

- Cybenko, George (1989). “Approximation by superpositions of a sigmoidal function”. In: *Mathematics of control, signals and systems* 2.4, pp. 303–314 (cit. on pp. 15, 16).
- Deng, Jia, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei (2009). “Imagenet: A large-scale hierarchical image database”. In: *Computer Vision and Pattern Recognition, 2009. CVPR 2009. IEEE Conference on*. IEEE, pp. 248–255 (cit. on p. 15).
- Glorot, Xavier and Yoshua Bengio (2010). “Understanding the difficulty of training deep feedforward neural networks”. In: *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256 (cit. on p. 15).
- Glorot, Xavier, Antoine Bordes, and Yoshua Bengio (2011). “Deep sparse rectifier neural networks”. In: *International Conference on Artificial Intelligence and Statistics*, pp. 315–323 (cit. on pp. 15, 16).
- Hackbusch, Wolfgang (2012). *Tensor spaces and numerical tensor calculus*. Vol. 42. Springer Science & Business Media (cit. on pp. 7, 8).
- He, Kaiming, Xiangyu Zhang, Shaoqing Ren, and Jian Sun (2015). “Delving deep into rectifiers: Surpassing human-level performance on imagenet classification”. In: *Proceedings of the IEEE international conference on computer vision*, pp. 1026–1034 (cit. on p. 16).
- (2016). “Deep residual learning for image recognition”. In: *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778 (cit. on p. 14).
- Hinton, Geoffrey, Li Deng, Dong Yu, George E Dahl, Abdel-rahman Mohamed, Navdeep Jaitly, Andrew Senior, Vincent Vanhoucke, Patrick Nguyen, Tara N Sainath, et al. (2012). “Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups”. In: *IEEE Signal Processing Magazine* 29.6, pp. 82–97 (cit. on p. 14).
- Hinton, Geoffrey E, Simon Osindero, and Yee-Whye Teh (2006). “A fast learning algorithm for deep belief nets”. In: *Neural computation* 18.7, pp. 1527–1554 (cit. on p. 15).
- Hornik, Kurt (1991). “Approximation capabilities of multilayer feedforward networks”. In: *Neural networks* 4.2, pp. 251–257 (cit. on p. 15).
- Hornik, Kurt, Maxwell Stinchcombe, and Halbert White (1989). “Multilayer feedforward networks are universal approximators”. In: *Neural Networks* 2.5, pp. 359–366 (cit. on pp. 15, 24, 25).
- Huang, Gao, Zhuang Liu, Kilian Q Weinberger, and Laurens van der Maaten (2017). “Densely connected convolutional networks”. In: *Proceedings of the*

- IEEE conference on computer vision and pattern recognition*. Vol. 1. 2, p. 3 (cit. on p. 14).
- Jarrett, Kevin, Koray Kavukcuoglu, Yann LeCun, et al. (2009). “What is the best multi-stage architecture for object recognition?” In: *Computer Vision, 2009 IEEE 12th International Conference on*. IEEE, pp. 2146–2153 (cit. on p. 16).
- Klambauer, Günter, Thomas Unterthiner, Andreas Mayr, and Sepp Hochreiter (2017). “Self-Normalizing Neural Networks”. In: *Advances in Neural Information Processing Systems 30*. Ed. by I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett. Curran Associates, Inc., pp. 971–980. URL: <http://papers.nips.cc/paper/6698-self-normalizing-neural-networks.pdf> (cit. on p. 16).
- Krizhevsky, Alex, Ilya Sutskever, and Geoffrey E Hinton (2012). “Imagenet classification with deep convolutional neural networks”. In: *Advances in Neural Information Processing Systems*, pp. 1097–1105 (cit. on pp. 14, 15, 23).
- LeCun, Y. (1987). “Modeles connexionnistes de l’apprentissage (connectionist learning models)”. PhD thesis. Université P. et M. Curie (Paris 6) (cit. on p. 16).
- LeCun, Yann, Bernhard Boser, John S Denker, Donnie Henderson, Richard E Howard, Wayne Hubbard, and Lawrence D Jackel (1989). “Backpropagation applied to handwritten zip code recognition”. In: *Neural computation* 1.4, pp. 541–551 (cit. on pp. 14, 16).
- LeCun, Yann, Yoshua Bengio, et al. (1995). “Convolutional networks for images, speech, and time series”. In: *The handbook of brain theory and neural networks* 3361.10, p. 1995 (cit. on pp. 14, 23).
- LeCun, Yann, Léon Bottou, Yoshua Bengio, and Patrick Haffner (1998). “Gradient-based learning applied to document recognition”. In: *Proceedings of the IEEE* 86.11, pp. 2278–2324 (cit. on p. 24).
- Maas, Andrew L, Awni Y Hannun, and Andrew Y Ng (2013). “Rectifier nonlinearities improve neural network acoustic models”. In: *Proceedings of the 30th international conference on machine learning* (cit. on p. 16).
- Marcus, Marvin (1975). “Finite dimensional multilinear algebra”. In: (cit. on p. 7).
- Nickolls, John, Ian Buck, Michael Garland, and Kevin Skadron (2008). “Scalable parallel programming with CUDA”. In: *ACM SIGGRAPH 2008 classes*. ACM, p. 16 (cit. on p. 15).

- Pascanu, Razvan, Guido Montufar, and Yoshua Bengio (2013). “On the number of response regions of deep feed forward networks with piece-wise linear activations”. In: *arXiv preprint arXiv:1312.6098* (cit. on p. 16).
- Rumelhart, David E, Geoffrey E Hinton, and Ronald J Williams (1985). *Learning internal representations by error propagation*. Tech. rep. California Univ San Diego La Jolla Inst for Cognitive Science (cit. on p. 14).
- Simonyan, Karen and Andrew Zisserman (2014). “Very deep convolutional networks for large-scale image recognition”. In: *arXiv preprint arXiv:1409.1556* (cit. on p. 14).
- Srivastava, Nitish, Geoffrey E Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov (2014). “Dropout: a simple way to prevent neural networks from overfitting.” In: *Journal of Machine Learning Research* 15.1, pp. 1929–1958 (cit. on p. 24).
- Szegedy, Christian, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, Andrew Rabinovich, et al. (2015). “Going deeper with convolutions”. In: *Conference on Computer Vision and Pattern Recognition* (cit. on p. 14).
- Wikipedia, contributors (2018). *Feedforward neural network* — *Wikipedia, The Free Encyclopedia*. [Online; accessed April-2018]. URL: [https://en.wikipedia.org/wiki/Feedforward\\_neural\\_network](https://en.wikipedia.org/wiki/Feedforward_neural_network) (cit. on p. 14).
- Williamson, S Gill (2015). “Tensor spaces-the basics”. In: *arXiv preprint arXiv:1510.02428* (cit. on p. 7).
- Zell, Andreas (1994). *Simulation neuronaler netze*. Vol. 1. Addison-Wesley Bonn (cit. on p. 14).
- Zoph, Barret and Quoc V Le (2016). “Neural architecture search with reinforcement learning”. In: *arXiv preprint arXiv:1611.01578* (cit. on p. 14).