

# wordometer

*This manual contains 965 words.*

A small [Typst](#) package for quick and easy in-document word counts.

[github.com/Jollywatt/typst-wordometer](https://github.com/Jollywatt/typst-wordometer)

Version 0.1.0

## Basic usage

```
#import "@preview/wordometer:0.1.0": word-count, total-words
```

```
#show: word-count
```

In this document, there are `#total-words` words all up.

```
#word-count(total => [  
  The number of words in this block is #total.words  
  and there are #total.characters letters.  
)
```

## Excluding elements

You can exclude elements by name (e.g., "`caption`"), function (e.g., `figure.caption`), where-selector (e.g., `raw.where(block: true)`), or label (e.g., `<no-wc>`).

```
#show: word-count.with(exclude: (heading.where(level: 1), strike))
```

**= This Heading Doesn't Count**

**== But I do!**

In this document `#strike[(excluding me)]`, there are `#total-words` words all up.

```
#word-count(total => [  
  You can exclude elements by label, too.  
  #[That was #total.words, excluding this sentence!] <no-wc>  
, exclude: <no-wc>)
```

---

## word-count()

Perform a word count on content.

Master function which accepts content (calling `word-count-global()`) or a callback function (calling `word-count-callback()`).

### Parameters

```
word-count(  
  arg: content fn,  
  ..options:  
) -> dictionary
```

**arg** `content` or `fn`

Can be:

- `content`: A word count is performed for the content and the results are accessible through `#total-words` and `#total-characters`. This uses a global state, so should only be used once in a document (e.g., via a document show rule: `#show: word-count`).
- `function`: A callback function accepting a dictionary of word count results and returning content to be word counted. For example:

```
#word-count(total => [This sentence contains #total.characters letters.])
```

### ..options

Additional named arguments:

- `exclude`: Content to exclude from word count (see `map-tree()`). Can be an array of element functions, element function names, or labels.
- `method`: Content traversal method to use (see `word-count-of()`).

---

## word-count-callback()

Simultaneously take a word count of some content and insert it into that content.

It works by first passing in some dummy results to `fn`, performing a word count on the content returned, and finally returning the result of passing the word count results to `fn`. This happens once — it doesn't keep looping until convergence or anything!

For example:

```
#word-count-callback(stats => [There are #stats.words words])
```

### Parameters

```
word-count-callback(  
  fn: function,  
  ..options:  
) -> content
```

**fn**    `function`

A function accepting a dictionary and returning content to perform the word count on.

### **..options**

Additional named arguments:

- `exclude`: Content to exclude from word count (see `map-tree()`). Can be an array of element functions, element function names, or labels.
- `method`: Content traversal method to use (see `word-count-of()`).

---

## **word-count-global()**

Get word count statistics of the given content and store the results in global state. Should only be used once in the document.

The results are accessible anywhere in the document with `#total-words` and `#total-characters`, which are shortcuts for the final values of states of the same name (e.g., `#locate(loc => state("total-words").final(loc))`)

### **Parameters**

```
word-count-global(  
  content: content,  
  ..options:  
) -> content
```

**content**    `content`

Content to word count.

### **..options**

Additional named arguments:

- `exclude`: Content to exclude from word count (see `map-tree()`). Can be an array of element functions, element function names, or labels.
- `method`: Content traversal method to use (see `word-count-of()`).

---

## **word-count-of()**

Get word count statistics of a content element.

Returns a results dictionary, not the content passed to it. (See `string-word-count()`).

## Parameters

```
word-count-of(  
  content: content,  
  exclude: array,  
  counter: fn,  
  method: string  
) -> dictionary
```

**exclude**    array

Content to exclude from word count (see `map-tree()`). Can be an array of element functions, element function names, or labels.

Default: ()

**counter**    fn

A function that accepts a string and returns a dictionary of counts.

For example, to count vowels, you might do:

```
#word-count-of([ABCDEFGH], counter: s => (  
  vowels: lower(s).matches(regex("[aeiou]")).len(),  
))
```

Default: string-word-count

**method**    string

The algorithm to use. Can be:

- "stringify": Convert the content into one big string, then perform the word count.
- "bubble": Traverse the content tree performing word counts at each textual leaf node, then "bubble" the results back up (i.e., sum them).

Performance and results may vary by method!

Default: "stringify"

---

## concat-adjacent-text()

Simplify an array of content by concatenating adjacent text elements.

Doesn't preserve content exactly; smartquotes are replaced with ' or ". This is used on sequence elements because it improves word counts for cases like "Digby's", which should count as one word.

For example, the content

Qu'est-ce **que** c'est !?

is structured as:

```
(
  [Qu],
  smartquote(double: false),
  [est-ce],
  [ ],
  strong(body: [que]),
  [ ],
  [c],
  smartquote(double: false),
  [est],
  [ ],
  [!?!],
)
```

This function simplifies this to:

```
([Qu'est-ce ], strong(body: [que]), [ c'est !?!])
```

### Parameters

`concat-adjacent-text(children: array)`

**children**    `array`

Array of content to simplify.

## extract-text()

Extract plain text from content

This is a quick-and-dirty conversion which does not preserve styling or layout and which may introduces superfluous spaces.

### Parameters

```
extract-text(
  content: content,
  ..options:
)
```

**content**    `content`

Content to extract plain text from.

**..options**   

Additional named arguments:

- `exclude`: Content to exclude (see [map-tree\(\)](#)). Can be an array of element functions, element function names, or labels.

## map-tree()

Traverse a content tree and apply a function to textual leaf nodes.

Descends into elements until reaching a textual element (text or raw) and calls f on the contained text, returning a (nested) array of all the return values.

### Parameters

```
map-tree(  
  f: function,  
  content: content,  
  exclude: array  
)
```

**f**    function

Unary function to pass text to.

**content**    content

Content element to traverse.

**exclude**    array

Content to skip while traversing the tree, specified by:

- name, e.g., "heading"
- function, e.g., heading
- selector, e.g., heading.where(level: 1) (only basic where selectors are supported)
- label, e.g., <no-wc>

Default value includes equations and elements without child content or text: "bibliography", "cite", "display", "equation", "h", "hide", "image", "line", "linebreak", "locate", "metadata", "pagebreak", "parbreak", "path", "polygon", "ref", "repeat", "smartquote", "space", "style", "update", and "v".

To exclude figures, but include figure captions, pass the name "figure-body" (which is not a real element). To include figure bodies, but exclude their captions, pass the name "caption".

Default: IGNORED\_ELEMENTS

---

## string-word-count()

Get a basic word count from a string.

Returns a dictionary with keys:

- characters: Number of non-whitespace characters.
- words: Number of words, defined by `regex("\\b[\\w' ]+\\b")`.
- sentences: Number of sentences, defined by `regex("\\w+\\s*[.?!]")`.

### Parameters

```
string-word-count(string: string) -> dictionary
```