

Forms

1. HTML Forms

The HTML Forms can be used to collect data from the user.

Forms are of different kinds:

- Login/Sign in Form
- Registration Form
- Contact Us Form, etc.

1.1 HTML Form Element

The HTML

form element can be used to create HTML forms. It is a container that can contain different types of Input elements like Text Fields, Checkboxes, etc.

```
<form></form>
```

Note:

Whenever we click a button or press

Enter key while editing any input field in the form, the submit event will be triggered.

2. Event Object Methods

2.1 preventDefault

The preventDefault() method prevents the occurrence of default action.

Here in the form, it prevents the default behaviour of the submit event.

```
let myFormEl = document.getElementById("myForm");

myFormEl.addEventListener("submit", function(event) {

    event.preventDefault();

});
```

3. Event Types

There are different types of events.

- Keyboard Events
- Mouse Events
- Touch Events
- Form Events, etc.

3.1 Form Events

A Form Event is an event that can occur within a form.

Some of the form events are:

- blur
- focus
- change, etc.

3.1.1 Blur Event

The `blur` event happens when an HTML element has lost focus.

```
let nameEl = document.getElementById("name");
```

```
nameEl.addEventListener("blur", function(event) {  
  
    console.log("blur event triggered");  
  
});
```

4. HTML Select Element

The HTML `select` element is used to create a drop-down list.

```
<select></select>
```

4.1 HTML Option Element

The HTML `option` element is used to create the menu option of a drop-down list.

The text content of the HTML

`option` element is used as a label.

```
<select>  
  
    <option>Active</option>  
  
</select>
```

4.1.1 The `value` Attribute

Every HTML `option` element should contain the HTML `value` attribute.

```
<option value="Active">Active</option>
```

5. HTML Input Element

5.1 Radio

The HTML input radio element is used to select one option among a list of given options.

```
<input type="radio" id="genderMale" value="Male" />
```

```
<input type="radio" id="genderFemale" value="Female" />
```

5.1.1 HTML name attribute

The HTML name Attribute specifies the name for an HTML Element.

```
<input type="radio" value="Male" name="gender" />
```

5.1.2 Radio Group

All the radio buttons with same name collectively called as a radio group.

We can select only one radio button within a radio group.

```
<input type="radio" value="Male" name="gender" />
```

```
<input type="radio" value="Female" name="gender" />
```

5. Boolean Attributes

For the HTML Boolean attributes, we only specify the name of the HTML attribute.

The presence of a boolean attribute represents the

true value, and the absence represents the false value.

5.1 HTML selected attribute

The `selected` attribute specifies that an option should be pre-selected when the page loads.

```
<option value="Active" selected>Active</option>
```

5.2 HTML checked attribute

The `checked` attribute specifies that an input element should be pre-selected (checked) when the page loads.

```
<input type="radio" id="genderMale" value="Male" name="gender" checked />
```