

# **Machine-Level Programming II: Control**

**adapted for CS367@GMU**

# Today

- Control: Condition codes
- Conditional branches
- Loops
- Switch Statements

# Processor State (x86-64, Partial)

## ■ Information about currently executing program

- Temporary data ( %rax, ... )
- Location of runtime stack ( %rsp )
- Location of current code control point ( %rip, ... )
- Status of recent tests ( CF, ZF, SF, OF )

Current stack top

Registers

%rax	%r8
%rbx	%r9
%rcx	%r10
%rdx	%r11
%rsi	%r12
%rdi	%r13
%rsp	%r14
%rbp	%r15

%rip

Instruction pointer

CF

ZF

SF

OF

Condition codes

# Condition Codes (Implicit Setting)

## ■ Single bit registers

- |      |                           |    |                            |
|------|---------------------------|----|----------------------------|
| ■ CF | Carry Flag (for unsigned) | SF | Sign Flag (for signed)     |
| ■ ZF | Zero Flag                 | OF | Overflow Flag (for signed) |

## ■ Implicitly set (think of it as side effect) by arithmetic operations

Example: `addq Src,Dest`       $\leftrightarrow$        $t = a+b$

**CF set** if carry out from most significant bit (unsigned overflow)

**ZF set** if  $t == 0$

**SF set** if  $t < 0$  (as signed)

**OF set** if two's-complement (signed) overflow

$(a>0 \ \&\& \ b>0 \ \&\& \ t<0) \ \mid\mid \ (a<0 \ \&\& \ b<0 \ \&\& \ t>=0)$

## ■ Not set by `leaq` instruction

# Condition Codes (Explicit Setting: Compare)

## ■ Explicit Setting by Compare Instruction

- `cmpq Src2, Src1`
- `cmpq b, a` like computing  $a - b$  without setting destination
- **CF set** if carry out from most significant bit (used for unsigned comparisons)
- **ZF set** if  $a == b$
- **SF set** if  $(a - b) < 0$  (as signed)
- **OF set** if two's-complement (signed) overflow  
$$(a > 0 \ \&\& \ b < 0 \ \&\& \ (a - b) < 0) \ \mid\mid \ (a < 0 \ \&\& \ b > 0 \ \&\& \ (a - b) > 0)$$

# Condition Codes (Explicit Setting: Test)

## ■ Explicit Setting by Test instruction

- `testq Src2, Src1`
  - `testq b, a` like computing `a&b` without setting destination
- Sets condition codes based on value of Src1 & Src2
- Useful to have one of the operands be a mask
- **ZF set** when  $a \& b == 0$
- **SF set** when  $a \& b < 0$

# Reading Condition Codes

## ■ SetX Instructions

- Set low-order byte of destination to 0 or 1 based on combinations of condition codes
- Does not alter remaining 7 bytes

SetX	Condition	Description
sete	ZF	Equal / Zero
setne	$\sim ZF$	Not Equal / Not Zero
sets	SF	Negative
setns	$\sim SF$	Nonnegative
setg	$\sim (SF \wedge OF) \ \& \ \sim ZF$	Greater (Signed)
setge	$\sim (SF \wedge OF)$	Greater or Equal (Signed)
setl	$(SF \wedge OF)$	Less (Signed)
setle	$(SF \wedge OF) \mid ZF$	Less or Equal (Signed)
seta	$\sim CF \ \& \ \sim ZF$	Above (unsigned)
setb	CF	Below (unsigned)

# x86-64 Integer Registers

%rax	%al	%r8	%r8b
%rbx	%bl	%r9	%r9b
%rcx	%cl	%r10	%r10b
%rdx	%dl	%r11	%r11b
%rsi	%sil	%r12	%r12b
%rdi	%dil	%r13	%r13b
%rsp	%spl	%r14	%r14b
%rbp	%bpl	%r15	%r15b

- Can reference low-order byte

# Reading Condition Codes (Cont.)

## ■ SetX Instructions:

- Set single byte based on combination of condition codes

## ■ One of addressable byte registers

- Does not alter remaining bytes
- Typically use movzbl to finish job
  - 32-bit instructions also set upper 32 bits to 0

```
int gt (long x, long y)
{
    return x > y;
}
```

Register	Use(s)
%rdi	Argument <b>x</b>
%rsi	Argument <b>y</b>
%rax	Return value

```
cmpq  %rsi, %rdi          # Compare x:y. note ordering!
      setg    %al            # Set when >
      movzbl  %al, %eax     # Zero rest of %rax (not a typo!)
      ret
```

# Today

- Control: Condition codes
- Conditional branches
- Loops
- Switch Statements

# Jumping

## ■ jX Instructions

- Jump to different part of code depending on condition codes

jX	Condition	Description
jmp	1	Unconditional
je	ZF	Equal / Zero
jne	$\sim ZF$	Not Equal / Not Zero
js	SF	Negative
jns	$\sim SF$	Nonnegative
jg	$\sim (SF \wedge OF) \ \& \ \sim ZF$	Greater (Signed)
jge	$\sim (SF \wedge OF)$	Greater or Equal (Signed)
jl	$(SF \wedge OF)$	Less (Signed)
jle	$(SF \wedge OF) \mid ZF$	Less or Equal (Signed)
ja	$\sim CF \ \& \ \sim ZF$	Above (unsigned)
jb	CF	Below (unsigned)

# Conditional Branch Example (Old Style)

## ■ Generation

```
zeus> gcc -Og -S -fno-if-conversion control.c
```

```
long absdiff
    (long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

absdiff:

```
    cmpq    %rsi, %rdi    # x:y
    jle     .L4
    movq    %rdi, %rax
    subq    %rsi, %rax
    ret
.L4:      # x <= y
    movq    %rsi, %rax
    subq    %rdi, %rax
    ret
```

Register	Use(s)
%rdi	Argument <b>x</b>
%rsi	Argument <b>y</b>
%rax	Return value

# Expressing with Goto Code

- C allows `goto` statement
- Jump to position designated by label

```
long absdiff
    (long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

```
long absdiff_j
    (long x, long y)
{
    long result;
    int ntest = x <= y;
    if (ntest) goto Else;
    result = x-y;
    goto Done;
Else:
    result = y-x;
Done:
    return result;
}
```

# General Conditional Expression Translation (Using Branches)

C Code

```
val = Test ? Then_Expr : Else_Expr;
```

```
val = x>y ? x-y : y-x;
```

Goto Version

```
ntest = !Test;
if (ntest) goto Else;
val = Then_Expr;
goto Done;

Else:
    val = Else_Expr;

Done:
    . . .
```

- Create separate code regions for then & else expressions
- Execute appropriate one

# Using Conditional Moves

## ■ Conditional Move Instructions

- Instruction supports:  
if (Test) Dest  $\leftarrow$  Src
- Supported in post-1995 x86 processors
- GCC tries to use them
  - But, only when known to be safe

## ■ Why?

- Branches are very disruptive to instruction flow through pipelines
- Conditional moves do not require control transfer

### C Code

```
val = Test  
? Then_Expr  
: Else_Expr;
```

### Goto Version

```
result = Then_Expr;  
eval = Else_Expr;  
nt = !Test;  
if (nt) result = eval;  
return result;
```

# Conditional Move Example

```
long absdiff
    (long x, long y)
{
    long result;
    if (x > y)
        result = x-y;
    else
        result = y-x;
    return result;
}
```

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rax	Return value

```
absdiff:
    movq    %rdi, %rax    # x
    subq    %rsi, %rax    # result = x-y
    movq    %rsi, %rdx
    subq    %rdi, %rdx    # eval = y-x
    cmpq    %rsi, %rdi    # x:y
    cmovle %rdx, %rax    # if <=, result = eval
    ret
```

# Bad Cases for Conditional Move

## Expensive Computations

```
val = Test(x) ? Hard1(x) : Hard2(x);
```

- Both values get computed
- Only makes sense when computations are very simple

## Risky Computations

```
val = p ? *p : 0;
```

- Both values get computed
- May have undesirable effects

## Computations with side effects

```
val = x > 0 ? x*=7 : x+=3;
```

- Both values get computed
- Must be side-effect free

# Today

- Control: Condition codes
- Conditional branches
- Loops
- Switch Statements

# “Do-While” Loop Example

## C Code

```
long pcount_do
(unsigned long x) {
    long result = 0;
    do {
        result += x & 0x1;
        x >>= 1;
    } while (x);
    return result;
}
```

## Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
    return result;
}
```

- Count number of 1's in argument **x** (“popcount”)
- Use conditional branch to either continue looping or to exit loop

# “Do-While” Loop Compilation

## Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
    return result;
}
```

Register	Use(s)
%rdi	Argument <b>x</b>
%rax	<b>result</b>

```
        movl    $0, %eax      #  result = 0
.L2:
        movq    %rdi, %rdx
        andl    $1, %edx      #  t = x & 0x1
        addq    %rdx, %rax    #  result += t
        shrq    %rdi          #  x >>= 1
        jne     .L2           #  if (x) goto loop
        ret
```

# General “Do-While” Translation

C Code

```
do  
  Body  
  while (Test);
```

Goto Version

```
loop:  
  Body  
  if (Test)  
    goto loop
```

■ **Body:** {  
    **Statement**<sub>1</sub>;  
    **Statement**<sub>2</sub>;  
    ...  
    **Statement**<sub>n</sub>;  
}

# General “While” Translation #1

- “Jump-to-middle” translation
- Used with -Og

While version

```
while (Test)
    Body
```



Goto Version

```
goto test;
loop:
    Body
test:
    if (Test)
        goto loop;
done:
```

# While Loop Example #1

C Code

```
long pcount_while
(unsigned long x) {
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Jump to Middle

```
long pcount_goto_jtm
(unsigned long x) {
    long result = 0;
    goto test;
loop:
    result += x & 0x1;
    x >>= 1;
test:
    if(x) goto loop;
    return result;
}
```

- Compare to do-while version of function
- Initial goto starts loop at test

# General “While” Translation #2

While version

```
while (Test)
    Body
```

- “Do-while” conversion
- Used with `-O1`

Do-While Version

```
if (!Test)
    goto done;
do
    Body
    while (Test);
done:
```

Goto Version

```
if (!Test)
    goto done;
loop:
    Body
    if (Test)
        goto loop;
done:
```

# While Loop Example #2

C Code

```
long pcount_while
(unsigned long x) {
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Do-While Version

```
long pcount_goto_dw
(unsigned long x) {
    long result = 0;
    if (!x) goto done;
loop:
    result += x & 0x1;
    x >>= 1;
    if (x) goto loop;
done:
    return result;
}
```

- Compare to do-while version of function
- Initial conditional guards entrance to loop

# “For” Loop Form

General Form

```
for (Init; Test; Update)  
    Body
```

```
#define WSIZE 8*sizeof(int)  
long pcount_for  
(unsigned long x)  
{  
    size_t i;  
    long result = 0;  
    for (i = 0; i < WSIZE; i++)  
    {  
        unsigned bit =  
            (x >> i) & 0x1;  
        result += bit;  
    }  
    return result;  
}
```

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body

```
{  
    unsigned bit =  
        (x >> i) & 0x1;  
    result += bit;  
}
```

# “For” Loop → While Loop

For Version

```
for (Init; Test; Update)  
    Body
```



While Version

```
Init ;  
  
while (Test) {  
  
    Body  
  
    Update;  
  
}
```

# For-While Conversion

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body

```
{  
    unsigned bit =  
        (x >> i) & 0x1;  
    result += bit;  
}
```

```
long pcount_for_while  
(unsigned long x)  
{  
    size_t i;  
    long result = 0;  
    i = 0;  
    while (i < WSIZE)  
    {  
        unsigned bit =  
            (x >> i) & 0x1;  
        result += bit;  
        i++;  
    }  
    return result;  
}
```

# “For” Loop Do-While Conversion

C Code

```
long pcount_for
(unsigned long x)
{
    size_t i;
    long result = 0;
    for (i = 0; i < WSIZE; i++)
    {
        unsigned bit =
            (x >> i) & 0x1;
        result += bit;
    }
    return result;
}
```

Goto Version

```
long pcount_for_goto_dw
(unsigned long x) {
    size_t i;
    long result = 0;
    i = 0;
if (! (i < WSIZE))           Init
    goto done;                  ! Test
loop:
{
    unsigned bit =
        (x >> i) & 0x1;           Body
    result += bit;
}
i++; Update
if (i < WSIZE)           Test
    goto loop;
done:
    return result;
}
```

- Initial test can be optimized away ( $WSIZE > 0$  always)

# Today

- Control: Condition codes
- Conditional branches
- Loops
- **Switch Statements**

```
long switch_eg
    (long x, long y, long z)
{
    long w = 1;
    switch(x) {
        case 1:
            w = y*z;
            break;
        case 2:
            w = y/z;
            /* Fall Through */
        case 3:
            w += z;
            break;
        case 5:
        case 6:
            w -= z;
            break;
        default:
            w = 2;
    }
    return w;
}
```

# Switch Statement Example


- Multiple case labels
  - Here: 5 & 6
- Fall through cases
  - Here: 2
- Missing cases
  - Here: 4

# Jump Table Structure

## Switch Form

```
switch (x) {  
    case val_0:  
        Block 0  
    case val_1:  
        Block 1  
    . . .  
    case val_n-1:  
        Block n-1  
}
```

## Jump Table



## Jump Targets

Targ0:

Code Block  
0

Targ1:

Code Block  
1

Targ2:

Code Block  
2

•  
•  
•

Targn-1:

Code Block  
n-1

## Translation (Extended C)

```
goto *JTab [x];
```

# Switch Statement Example

```
long switch_eg(long x, long y, long z)
{
    long w = 1;
    switch(x)  {
        . . .
    }
    return w;
}
```

Setup:

```
switch_eg:
    movq    %rdx, %rcx
    cmpq    $6, %rdi    # x:6
    ja     .L8
    jmp    * .L4(,%rdi,8)
```

What range of values  
takes default?

Register	Use(s)
%rdi	Argument x
%rsi	Argument y
%rdx	Argument z
%rax	Return value

Note that w not  
initialized here

# Switch Statement Example

```
long switch_eg(long x, long y, long z)
{
    long w = 1;
    switch(x) {
        . . .
    }
    return w;
}
```

Setup:

```
switch_eg:
    movq    %rdx, %rcx
    cmpq    $6, %rdi      # x:6
    ja     .L8           # Use default
    jmp    * .L4(,%rdi,8) # goto *JTab[x]
```

Indirect  
jump 

Jump table

```
.section  .rodata
.align 8
.L4:
.quad    .L8 # x = 0
.quad    .L3 # x = 1
.quad    .L5 # x = 2
.quad    .L9 # x = 3
.quad    .L8 # x = 4
.quad    .L7 # x = 5
.quad    .L7 # x = 6
```

# Assembly Setup Explanation

## ■ Table Structure

- Each target requires 8 bytes
- Base address at `.L4`

## ■ Jumping

- **Direct:** `jmp .L8`
- Jump target is denoted by label `.L8`

Jump table

```
.section .rodata
.align 8
.L4:
.quad .L8 # x = 0
.quad .L3 # x = 1
.quad .L5 # x = 2
.quad .L9 # x = 3
.quad .L8 # x = 4
.quad .L7 # x = 5
.quad .L7 # x = 6
```

- **Indirect:** `jmp * .L4(,%rdi,8)`
- Start of jump table: `.L4`
- Must scale by factor of 8 (addresses are 8 bytes)
- Fetch target from effective Address `.L4 + x*8`
  - Only for  $0 \leq x \leq 6$

# Jump Table

Jump table

```
.section    .rodata
.align 8
.L4:
.quad      .L8 # x = 0
.quad      .L3 # x = 1
.quad      .L5 # x = 2
.quad      .L9 # x = 3
.quad      .L8 # x = 4
.quad      .L7 # x = 5
.quad      .L7 # x = 6
```

```
switch(x) {
    case 1:          // .L3
        w = y*z;
        break;
    case 2:          // .L5
        w = y/z;
        /* Fall Through */
    case 3:          // .L9
        w += z;
        break;
    case 5:
    case 6:          // .L7
        w -= z;
        break;
    default:         // .L8
        w = 2;
}
```

# Code Blocks ( $x == 1$ )

```
switch(x) {  
    case 1:          // .L3  
        w = y*z;  
        break;  
    . . .  
}
```

```
.L3:  
    movq    %rsi, %rax  # y  
    imulq   %rdx, %rax  # y*z  
    ret
```

Register	Use(s)
%rdi	Argument <b>x</b>
%rsi	Argument <b>y</b>
%rdx	Argument <b>z</b>
%rax	Return value

# Handling Fall-Through

```
long w = 1;  
. . .  
switch(x) {  
    . . .  
    case 2:  
        w = y/z;  
        /* Fall Through */  
    case 3:  
        w += z;  
        break;  
    . . .  
}
```

```
case 2:  
    w = y/z;  
    goto merge;
```

```
case 3:  
    w = 1;  
  
merge:  
    w += z;
```



# Code Blocks ( $x == 2$ , $x == 3$ )

```
long w = 1;  
.  
.  
switch(x) {  
.  
.case 2:  
    w = y/z;  
    /* Fall Through */  
.case 3:  
    w += z;  
    break;  
.  
.  
}
```

```
.L5:          # Case 2  
    movq    %rsi, %rax  
    cqto  
    idivq   %rcx      # y/z  
    jmp     .L6        # goto merge  
.L9:          # Case 3  
    movl    $1, %eax    # w = 1  
.L6:          # merge:  
    addq    %rcx, %rax # w += z  
    ret
```

Register	Use(s)
%rdi	Argument <b>x</b>
%rsi	Argument <b>y</b>
%rdx	Argument <b>z</b>
%rax	Return value

# Code Blocks ( $x == 5$ , $x == 6$ , default)

```
switch(x) {  
    . . .  
    case 5: // .L7  
    case 6: // .L7  
        w -= z;  
        break;  
    default: // .L8  
        w = 2;  
}
```

```
.L7:                      # Case 5,6  
    movl $1, %eax      # w = 1  
    subq %rdx, %rax   # w -= z  
    ret  
.L8:                      # Default:  
    movl $2, %eax      # 2  
    ret
```


Register	Use(s)
%rdi	Argument <b>x</b>
%rsi	Argument <b>y</b>
%rdx	Argument <b>z</b>
%rax	Return value

# Sparse Switch Example

```
/* Return x/111 if x is multiple
   && <= 999. -1 otherwise */
int div111(int x)
{
    switch(x) {
        case 0: return 0;
        case 111: return 1;
        case 222: return 2;
        case 333: return 3;
        case 444: return 4;
        case 555: return 5;
        case 666: return 6;
        case 777: return 7;
        case 888: return 8;
        case 999: return 9;
        default: return -1;
    }
}
```

- Not practical to use jump table
  - Would require 1000 entries
- Obvious translation into if-then-else would have max. of 9 tests

# Sparse Switch Code Structure



- Organizes cases as binary tree
- Logarithmic performance

# Sparse Switch Code

- Compares x to possible case values
- Jumps different places depending on outcomes

```
    movl 8(%ebp),%eax # get x
    cmpl $444,%eax     # x:444
    je L8
    jg L16
    cmpl $111,%eax     # x:111
    je L5
    jg L17
    testl %eax,%eax    # x:0
    je L4
    jmp L14
    . . .
```

```
    . . .
L5:
    movl $1,%eax
    jmp L19
L6:
    movl $2,%eax
    jmp L19
L7:
    movl $3,%eax
    jmp L19
L8:
    movl $4,%eax
    jmp L19
    . . .
```

# Summarizing

- C Control
  - if-then-else
  - do-while
  - while, for
  - switch
- Assembler Control
  - Conditional jump
  - Conditional move
  - Indirect jump (via jump tables)
  - Compiler generates code sequence to implement more complex control
- Standard Techniques
  - Loops converted to do-while or jump-to-middle form
  - Large switch statements use jump tables
  - Sparse switch statements may use decision trees (if-elseif-elseif-else)

# Summary

## ■ Today

- Control: Condition codes
- Conditional branches & conditional moves
- Loops
- Switch statements

## ■ Next Time

- Stack
- Call / return
- Procedure call discipline