# StateFarm Distracted Driver Detection Model

Rania Haas Matthew Goldsberry Nhat Pham
University of Cincinnati
Cincinnati, OH, USA
{haasr3, goldsbme, phamn2}@mail.uc.edu

## Abstract

*Approached with the task of detecting distracted drivers, we studied image-based distracted driver detection models on the StateFarm Distracted Driver Detection dataset, viewing several images from the dashboard including: safe driving, texting, phone calls, and reaching behind the passenger seat. Distracted driving is a leading cause of road accidents, and automated in-cabin monitoring could enable timely driver alerts. We trained and fine tuned models from Kaggle's competition using [key choices: augmentation, transfer learning, loss], and we evaluated with a driver-disjoint 70-30 test split. Our best model achieves an accuracy of [X%]. Denote about errors These results suggest*

## 1. Introduction

This is the introduction.

## 2. Literary Analysis

To find a basis for creating a model, we first started with a literary analysis to find effective methods and shortcomings. Each participant read numberous articles and summarized the teams' results.

### 2.1. Distracted Driving Detection using CNNs

Four CNN models were used to training their[1] collected data using transfer learning and softmax regression: VGG-16 model, AlexNet, GoogleNet, and ResNet. The best performance came from the ResNet model, performing an accuracy of 92%, out performing the other models by up to 6%. The researchers concluded that most of the incorrect classifications from the models were due to the similarities in postures, such as drinking, hair and makeup, and texting on the phone with the left hand. One possible implementation to help reduce the number of misclassifications is to combine their overall approach with a face-based approach or to replace the final fully connected layers with classifiers such as SVM or HMM.

### 2.2. Distracted Driving Monitoring with Artificial Intelligence

The article[3], written by Hui Xiong and Zhiming Zhang (2026). The authors note in their overall abstract for the paper, that one of the leading causes of traffic accidents occur due to distracted driving. In the final experiment, the total F1 score used to measure performance of the model is represented by comparing the correct predictions to the actuality of the dangerous driving. In the five types of driving tested, normal, speeding, hard-breaking, distracted, and drowsy driving, all F1 scores exceed 90% with the exception of hard braking receiving an F1 score of 88.48%. The system has an overall high performance, especially with consideration to the abnormal driving behaviors. Xiong and Zhang were able to implement a system to test for distracted driving in the form of a behavioral monitoring system through the use of machine learning and computer vision techniques alongside artificial intelligence. The biggest short coming for their final model is more complex scenarios and overall road safety.

## 3. Limitations

What we could to do improve the model.

## 4. Conclusion

Final conclusions.

## References

[1] Yunsheng Ma, Runjia Du, Amr Abdelraouf, Kyungtae Han, Rohit Gupta, and Ziran Wang. Driver digital twin for online recognition of distracted driving behaviors. *IEEE TPAMI*, 9, 2024. Face and Gesture submission ID 324. Supplied as supplemental material `fg324.pdf`. 1

[2] Duy Tran, Ha Mahn Do, Weihua Sheng, He Bai, and Girish Chowdhary. Real-time detection of distracted driving based on deep learning. *IET*, 12, 2018.

[3] Hui Xiong and Zhiming Zhang. Design and implementation of a driving behavior monitoring system based on artificall

intelligence. *IJAASR*, 5, 2026. Supplied as supplemental material `tr.pdf`. 1