

Vector — Schéma de la base de données

12 tables · 3 domaines · PostgreSQL + pgvector

AUTH & CONVERSATION

AGENTS	
id	UUID PK
slug	string UQ
name	string
role	string
system_prompt	text
accent_color	string
created_at	timestamp

USERS	
id	UUID PK
email	string UQ
password_hash	string
full_name	string?
is_active	boolean
created_at	timestamp
updated_at	timestamp

CONVERSATIONS	
id	UUID PK
user_id	UUID FK
agent_id	UUID FK
title	string
created_at	timestamp
updated_at	timestamp

MESSAGES	
id	UUID PK
conversation_id	UUID FK
role	string
content	text
created_at	timestamp

DATA ANALYSIS (PIPELINE A)

DATASETS	
id	UUID PK
user_id	UUID FK
name	string
file_path	string
row_count	int?
quality_score	int?
status	string
created_at	timestamp

DASHBOARDS	
id	UUID PK
dataset_id	UUID FK
conversation_id	UUID? FK
title	string
type	string
html_content	text
json_source	jsonb

DATASET_COLUMNS	
id	UUID PK
dataset_id	UUID FK
name	string
dtype	string
unique_count	int?
null_count	int?
sample_values	jsonb

KPIs	
id	UUID PK
dataset_id	UUID FK
name	string
formula	text
unit	string?
target_value	float?
display_order	int

ANALYSES	
id	UUID PK
dataset_id	UUID FK
type	string
content	jsonb
created_at	timestamp

KPI_VALUES	
id	UUID PK
kpi_id	UUID FK
value	float
computed_at	timestamp

LÉGENDE

- PK** Primary Key (UUID)
- FK** Foreign Key
- UQ** Unique constraint
- ?** Nullable
- ★ Type vectoriel pgvector (1536 dim) avec index IVFFlat cosinus

RAG (PIPELINE B)

DOCUMENTS	
id	UUID PK
user_id	UUID FK
name	string
file_path	string
status	string
chunk_count	int
created_at	timestamp

CHUNKS	
id	UUID PK
document_id	UUID FK
chunk_index	int
content	text
token_count	int
embedding	vector(1536) ★