

spaCy

Features

NAME	DESCRIPTION
Tokenization	Segmenting text into words, punctuations marks etc.
Part-of-speech (POS) Tagging	Assigning word types to tokens, like verb or noun.
Dependency Parsing	Assigning syntactic dependency labels, describing the relations between individual tokens, like subject or object.
Lemmatization	Assigning the base forms of words. For example, the lemma of "was" is "be", and the lemma of "rats" is "rat".
Sentence Boundary Detection (SBD)	Finding and segmenting individual sentences.
Named Entity Recognition (NER)	Labelling named "real-world" objects, like persons, companies or locations.
Entity Linking (EL)	Disambiguating textual entities to unique identifiers in a Knowledge Base.
Similarity	Comparing words, text spans and documents and how similar they are to each other.
Text Classification	Assigning categories or labels to a whole document, or parts of a document.
Rule-based Matching	Finding sequences of tokens based on their texts and linguistic annotations, similar to regular expressions.
Training	Updating and improving a statistical model's predictions.
Serialization	Saving objects to files or byte strings.

Model (ex: en_core_web_sm)

- **Binary weights** for the part-of-speech tagger, dependency parser and named entity recognizer to predict those annotations in context.
- **Lexical entries** in the vocabulary, i.e. words and their context-independent attributes like the shape or spelling.
- **Data files** like lemmatization rules and lookup tables.
- **Word vectors**, i.e. multi-dimensional meaning representations of words that let you determine how similar they are to each other.
- **Configuration** options, like the language and processing pipeline settings, to put spaCy in the correct state when you load in the model.

POS tags

```
import spacy

nlp = spacy.load("en_core_web_sm")
doc = nlp("Apple is looking at buying U.K. startup for $1 billion")

for token in doc:
    print(token.text, token.lemma_, token.pos_, token.tag_, token.dep_,
          token.shape_, token.is_alpha, token.is_stop)
```

RUN

TEXT	LEMMA	POS	TAG	DEP	SHAPE	ALPHA	STOP
Apple	apple	PROPN	NNP	nsubj	Xxxxx	True	False
is	be	AUX	VBZ	aux	xx	True	True
looking	look	VERB	VBG	ROOT	xxxx	True	False
at	at	ADP	IN	prep	xx	True	True
buying	buy	VERB	VBG	pcomp	xxxx	True	False
U.K.	u.k.	PROPN	NNP	compound	X.X.	False	False
startup	startup	NOUN	NN	dobj	xxxx	True	False
for	for	ADP	IN	prep	xxx	True	True
\$	\$	SYM	\$	quantmod	\$	False	False
1	1	NUM	CD	compound	d	False	False
billion	billion	NUM	CD	pobj	xxxx	True	False

Named Entities (real-world objects)

Editable Code spaCy v2.3.0 · Python 3 · via Binder

```
import spacy

nlp = spacy.load("en_core_web_sm")
doc = nlp("Apple is looking at buying U.K. startup for $1 billion")

for ent in doc.ents:
    print(ent.text, ent.start_char, ent.end_char, ent.label_)
```

RUN

TEXT	START	END	LABEL	DESCRIPTION
Apple	0	5	ORG	Companies, agencies, institutions.
U.K.	27	31	GPE	Geopolitical entity, i.e. countries, cities, states.
\$1 billion	44	54	MONEY	Monetary values, including unit.