Question 63 (Extended Scenario)

03: Understand Data & Architecture

What is used by GitHub Copilot in the IDE to determine the prompt context?

✔ **A. The active file, cursor position, neighboring open tabs, and relevant project structure.**

B. Every single file contained within the local git repository history.

C. Strictly the exact line of code directly preceding the cursor.

D. Cloud search indices queried from public GitHub repositories.

Correct Answer: A

GitHub Copilot constructs prompt context by analyzing the active file contents, the exact cursor position (utilizing prefix and suffix context via Fill-In-the-Middle), content from neighboring open editor tabs, and relevant project structure heuristics to deliver targeted inline completions.

Option Breakdown

- **A. Active file, cursor position, neighboring tabs & project structure:** Correct. Balances local context breadth with token limits.
- **B. Every file in git repository history:** Incorrect. Loading an entire git history would exceed prompt token limits and include outdated code.
- **C. Strictly the exact preceding line:** Incorrect. Copilot leverages broader file context and neighboring tabs rather than just the single preceding line.
- **D. Public GitHub repository cloud search indices:** Incorrect. Real-time IDE completions rely on local workspace context, not live public repo searches.

💡 **GH-300 Exam Tip & Demo Scenario**

When recording your YouTube demo, show how closing unrelated open tabs instantly refines Copilot's context window, preventing outdated functions from polluting inline suggestions.