Question 34

GH-300: Enterprise Network & Security

If developers in an enterprise environment operate behind an HTTP proxy server with custom SSL inspection certificates, what configuration must be updated for GitHub Copilot in the IDE?

A. Change the default git remote URL to SSH.

✔ **B. Configure HTTP proxy settings and import custom root CA certificates into the editor's Copilot extension configuration.**

C. Disable TLS encryption across developer workstations.

D. Install local language models to bypass network calls entirely.

Correct Answer: B

Enterprise networks performing TLS/SSL inspection require configuring custom Certificate Authority (CA) certificates within the IDE settings (e.g., `http.proxyStrictSSL` and custom CA paths) so the Copilot extension can establish secure HTTPS connections to Copilot endpoints.

Option Breakdown

- **A. Change git remote to SSH:** Incorrect. SSH affects Git operations, not the HTTPS API communication used by Copilot.
- **B. Configure proxy & import custom CA certs:** Correct. Ensures Copilot HTTP requests pass through corporate proxies without SSL verification failures.
- **C. Disable TLS encryption:** Incorrect. Disabling security protocols violates compliance and is not supported by Copilot APIs.
- **D. Install local models:** Incorrect. Copilot relies on managed cloud services and does not support local offline model execution.

💡 **GH-300 Exam Tip**

Copilot traffic uses standard HTTPS port 443 to endpoints like `api.githubcopilot.com`. Ensure proxy settings and custom CA bundles are configured in the editor settings to prevent connection errors.