Question 46

06: Privacy & Content Exclusions

Which path pattern format is used by organization administrators to configure Content Exclusion rules in GitHub settings?

A. RegEx (Regular Expressions) string syntax only.

✔ **B. Standard glob pattern syntax (e.g., `**/secrets/*.env` or `config/keys.pem`).**

C. Absolute hard drive file system paths (e.g., `C:\Users\Admin\...`).

D. XML schema definitions.

Correct Answer: B

GitHub Copilot Content Exclusions utilize standard **fnmatch glob syntax** to target paths, directory trees, or specific file extensions across organization repositories.

Option Breakdown

- **A. RegEx syntax only:** Incorrect. Content Exclusion rules rely on glob patterns rather than full PCRE RegEx syntax.
- **B. Standard glob pattern syntax:** Correct. Uses repository-relative glob paths (e.g., `*.pem`, `secrets/**`).
- **C. Absolute local paths:** Incorrect. Absolute OS paths vary per user machine and cannot be used in repository policy settings.
- **D. XML schema definitions:** Incorrect. Policies are defined via plain text pattern lists in GitHub settings.

> 💡 **GH-300 Exam Tip**
> When files are excluded via glob patterns, Copilot inline suggestions are disabled inside those files, and their contents will not be sent as context for other completions.