Question 17

GH-300: CLI Configuration

GitHub Copilot in the Command Line Interface (CLI) can be used to configure which of the following settings? (Choose two.)

A. The default execution confirmation

✔ **B. Usage analytics**

✔ **C. The default editor**

D. GitHub CLI subcommands

Correct Answer: B and C

GitHub Copilot in the CLI enables users to configure core environment preferences, such as whether anonymous **usage analytics (telemetry)** are sent to GitHub and specifying **the default text editor** used for command editing or reviewing generated scripts.

Option Breakdown

- **A. The default execution confirmation:** Incorrect. While Copilot CLI prompts before executing commands, setting default confirmation modes is not a standard standalone CLI configuration option.
- **B. Usage analytics:** Correct. Users can explicitly opt in or out of telemetry collection via the CLI setup parameters.
- **C. The default editor:** Correct. Copilot CLI allows specifying the preferred editor (e.g., VS Code, Vim, Nano) for editing script proposals.
- **D. GitHub CLI subcommands:** Incorrect. Subcommands are defined by GitHub CLI (`gh`) extension architecture, not configured as user settings inside Copilot CLI.

💡 **GH-300 Exam Tip**
Remember that GitHub Copilot CLI operates as an extension to the GitHub CLI (`gh`). Focus on the distinction between CLI settings (telemetry, editor selection) versus general GitHub account/org policies (content exclusions, duplication detection).