Question 58 (Ordering / Drag-and-Drop)

03: Understand Data & Architecture

Arrange the five stages of the GitHub Copilot Chat processing lifecycle in the exact chronological sequence from prompt submission to IDE rendering.

1. User submits a natural-language prompt in Copilot Chat
2. Pre-processing gathers relevant workspace context and enriches the prompt
3. Secure HTTPS transmission to the Azure-hosted Large Language Model (LLM) for inference
4. Post-processing applies toxicity, security (CWE), and public code duplication filters
5. Filtered response is delivered and rendered inside the developer's IDE

Correct Sequence: 1 → 2 → 3 → 4 → 5

Every Copilot request follows a strict five-step pipeline. Context enrichment (pre-processing) always occurs before LLM inference, while safety, vulnerability, and duplication filters (post-processing) inspect the generated tokens before anything reaches the user's screen.

Stage Breakdown

- **Pre-processing:** Assembles active file snippets, open tabs, and `.github/copilot-instructions.md` rules into a structured prompt payload.
- **Inference:** The Azure-hosted LLM generates probabilistic completion tokens over an encrypted TLS channel.
- **Post-processing:** Evaluates output against harmful content rules, CWE patterns, and the ~150-character public code match filter.

> 💡 **GH-300 Exam Tip**
> In Pearson VUE drag-and-drop sequence questions, remember that **context gathering happens before inference** and **duplication/safety filtering happens after inference**.