“Popup gone but relearning not updating” – what to do

Short answer: do **not** put the popup back. What used to look like relearning was not relearning. Follow the steps below in order and stop where the document tells you to stop.

What was really happening before

With the old `innerSave()`, Apply wrote the **values typed on screen straight into the new configuration**. The threshold row changed on the spot, so it looked as though the relearn had run instantly. It had not – the configuration had simply been overwritten with your typed value. That is exactly the behaviour Benoit asked to remove.

Real relearning has never been instant. `HealthDao.createRelearnThresholdRequest` sets only these fields:

```
      RelearnThresholdRequest request = new RelearnThresholdRequest(UUID.randomUUID().toString());
      request.setStartDate(effectiveDate);
      request.setStartFlightDate(startFlightDate);
      request.setHistoryLearningTime(historyLearningTime);
      request.setDescription(comment);
      request.setLearnedValue(learnedThreshold.getValue());     <-- the OLD value, copied forward
      learnedThreshold.getRelearnRequests().add(request);
```

There is no `setHandled(true)`, no new learned value and no `setApplicableFlightDate(...)`. Those three are set later, by `LearnedThresholdAnalyzer.completeLearning()`, and that only runs **when a flight is downloaded**. On top of that we create the request with `historyLearningTime = 0`, which by Benoit's own definition means *learn on the following flight hours only*. Zero history plus no new flight equals nothing to learn from yet.

So the current behaviour is correct. What changed is only that the fake instant update is gone.

Step by step

Step 1 — run this query. Do nothing else until you have the result.

```
SELECT id, startdate, startflightdate, historylearningtime, handled, learnedvalue, description
FROM public.relearn_threshold_request
ORDER BY startdate DESC LIMIT 5;
```

Step 2 — look at the top row

What you see	Go to
`description` contains the TE reference of the deviation you just created	**Step 3** (expected case)
No new row at all	**Step 6**

Expected case – the row is there

Step 3 — confirm nothing is broken

You should see `handled = false` and `historylearningtime = 0`. That means the request is queued and cannot have a value yet, because it only learns from flight hours recorded *after* the request was raised. This is the correct state.

Step 4 — download or replay one flight for that aircraft

This is what makes `LearnedThresholdAnalyzer` run. Without it nothing will ever change, with or without the popup.

Step 5 — re-run the query from step 1

Pass: the same row now shows `handled = true`, a new `learnedvalue`, and a non-null `applicableflightdate`. Open the indicator graph – the threshold line has moved to the learned value.

That is the test procedure from now on. **Stop here.**

Other case – no new row

Step 6 — check the threshold is actually a learned one

Take the `indicator_configuration_id` from the deviation row you just created and run:

```
SELECT tc.id, tc.dtype, t.severity
FROM public.threshold_configuration tc
JOIN public.threshold t ON t.id = tc.threshold_id
WHERE tc.indicator_configuration_id = '<paste the ic id here>';
```

What you see	Meaning
`dtype = LearnedThresholdConfiguration`	A relearn was expected. Go to **step 7**
`dtype = FixedThresholdConfiguration` and your deviation did not set `threshold_type = 'LEARNED'`	No relearn is expected. This is correct, not a bug. **Stop here**

Step 7 — log what is being sent

In `HealthCommonBusiness`, first line of `launchRelearn(...)`, add:

```
      LOGGER.info("BCR-6605 launchRelearn ids={} reason={}", learnedThresholdIds, learningReason);
```

Rebuild, Apply again, read the server log.

Log shows	Cause	Next
`ids=[]`	`getLearnedThresholdIds(...)` resolved nothing – the id lookup, not the popup	Send me the log line and the `getLearnedThresholdIds` method as it stands now
`ids=[…]` with real ids	The client side is fine; the request is being rejected or dropped server side	Send me `HealthCommonService.createRelearnThresholdRequests`

Do not do these

Tempting fix	Why not
Put the popup / configuration creation back	It does not relearn anything. It overwrites the configuration with the typed value, which is the behaviour Benoit asked to remove, and it reintroduces the `ConcurrentAccessException` on Apply
Set `historyLearningTime` to something non-zero so it learns instantly	That changes the requirement. `0` means learning on following flight hours only – it is the specified value. Change it only if Benoit says so
Set `handled = true` or write `learnedvalue` by hand to make the UI move	It fakes the same thing the old code faked, and the next analyzer run will overwrite it

Reporting back

One line is enough: the step number you stopped at and what you saw. For example “step 5, handled = true, graph moved” or “step 7, ids=[] in the log”.