Practical No. 2

Objective: Write a program to implement Bubble Sort Algorithm.

Pseudo Code:

Code:

```
#include<iostream>
using namespace std;
int bubbleSort(int arr[],int n){
    for(int i=0;i<n-1;i++){
        for(int j=0;j<n-i-1;j++){
            if(arr[j]>arr[j+1]){
                int temp=arr[j];
                arr[j]=arr[j+1];
                arr[j+1]=temp;
            }
```

```
        }
    }
    return 0;
}
int main(){
    int arr[]={3,4,6,5,1};
    bubbleSort(arr,5);
    for(int i=0;i<5;i++){
        cout<<arr[i]<<" ";
    }
    return 0;
}
```

Output:



Practical No. 3

Objective: Write a Program to implement Insertion Sort Algorithm.

Pseudo Code:

Code:

```
#include<iostream>
using namespace std;
void InsertionSort(int arr[],int n){
    for(int j=1;j<n;j++){
        int temp=arr[j];
        int i=j-1;
        while(i>=0 && arr[i]>temp){
            arr[i+1]=arr[i];
            i=i-1;
        }
        arr[i+1]=temp;
```

```
    }
}
int main(){
    int arr[]={3,4,6,5,1};
    InsertionSort(arr,5);
    for(int i=0;i<5;i++){
        cout<<arr[i]<<" ";
    }

}
```

Output:

