# Rajalakshmi Engineering College

Name: RANNESH KHUMAR B R

Email: 240701422@rajalakshmi.edu.in

Roll no: 2116240701 Phone: 9042350670

Branch: REC

Department: I CSE FD

Batch: 2028

Degree: B.E - CSE



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

REC\_DS using C\_Week 4\_COD\_Question 5

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

#### 1. Problem Statement

You are tasked with implementing basic operations on a queue data structure using a linked list.

You need to write a program that performs the following operations on a queue:

Enqueue Operation: Implement a function that inserts an integer element at the rear end of the queue.Print Front and Rear: Implement a function that prints the front and rear elements of the queue. Dequeue Operation: Implement a function that removes the front element from the queue.

### Input Format

The first line of input consists of an integer N, representing the number of elements to be inserted into the queue.

The second line consists of N space-separated integers, representing the queue elements.

#### **Output Format**

The first line prints "Front: X, Rear: Y" where X is the front and Y is the rear elements of the queue.

The second line prints the message indicating that the dequeue operation (front element removed) is performed: "Performing Dequeue Operation:".

The last line prints "Front: M, Rear: N" where M is the front and N is the rear elements after the dequeue operation.

Refer to the sample output for the formatting specifications.

#### Sample Test Case

```
Input: 5
12 56 87 23 45
Output: Front: 12, Rear: 45
Performing Dequeue Operation:
Front: 56, Rear: 45
Answer
#include <stdio.h>
#include <stdlib.h>
struct Node {
  int data:
  struct Node* next:
};
struct Node* front = NULL;
struct Node* rear = NULL;
// You are using GCC
typedef struct Node node;
void enqueue(int d) {
 //Type your code here
```

```
node*nnode=(node*)malloc(sizeof(node));
nnode->data=d;
   nnode->next=NULL;
   if(rear==NULL){
     front=rear=nnode;
   }
   else{
     rear->next=nnode;
     rear=nnode;
   }
 }
 void printFrontRear() {
 //Type your code here
   printf("Front:%d, Rear:%d\n",front->data,rear->data);
 void dequeue() {
   //Type your code here
   node*temp=front;
   front=temp->next;
   free(temp);
 }
 int main() {
   int n, data;
   scanf("%d", &n);
for (int i = 0; i < n; i++) {
     scanf("%d", &data);
     enqueue(data);
   printFrontRear();
   printf("Performing Dequeue Operation:\n");
   dequeue();
   printFrontRear();
   return 0;
 }
                                                                    Marks: 10/10
 Status: Correct
```