

# Rajalakshmi Engineering College

Name: RANNESH KHUMAR B R  
Email: 240701422@rajalakshmi.edu.in  
Roll no: 2116240701  
Phone: 9042350670  
Branch: REC  
Department: I CSE FD  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_COD\_Question 2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Moniksha, a chess coach organizing a tournament, needs a program to manage participant IDs efficiently. The program maintains a doubly linked list of IDs and offers two functions: Append to add IDs as students register, and Print Maximum ID to identify the highest ID for administrative tasks.

This tool streamlines tournament organization, allowing Moniksha to focus on coaching her students effectively.

##### ***Input Format***

The first line consists of an integer  $n$ , representing the number of participant IDs to be added.

The second line consists of  $n$  space-separated integers representing the participant IDs.

### **Output Format**

The output displays a single integer, representing the maximum participant ID.

If the list is empty, the output prints "Empty list!".

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 3

163 137 155

Output: 163

### **Answer**

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
struct node{
    struct node*next;
    int id;
    struct node*prev;
};
typedef struct node Node;
void insert(Node**head,int id){
    Node*newnode=(Node*)malloc(sizeof(Node));
    newnode->id=id;
    newnode->next=NULL;
    if(*head==NULL){
        newnode->prev=NULL;
        *head=newnode;
        return;
    }
    Node*temp=*head;
    while(temp->next!=NULL){
        temp=temp->next;
    }
    temp->next=newnode;
    newnode->prev=temp;
}
```

```
void print(Node*head){
    if(head==NULL){
        printf("Empty list!");
        return;
    }
    int maxid=head->id;
    Node*temp=head;
    while(temp!=NULL){
        if(temp->id>maxid){
            maxid=temp->id;
        }
        temp=temp->next;
    }
    printf("%d\n",maxid);
}
```

```
void fl(Node*head){
    Node*temp;
    while(head!=NULL){
        temp=head;
        head=head->next;
        free(temp);
    }
}
```

```
int main(){
    Node*plist=NULL;
    int n,id;
    scanf("%d",&n);
    if(n==0){
        printf("Empty list!");
        return 0;
    }
    for(int i=0;i<n;i++){
        scanf("%d",&id);
        insert(&plist,id);}
    print(plist);
    fl(plist);
```

```
    return 0;
```

}

**Status :** Correct

**Marks :** 10/10