Rajalakshmi Engineering College

Name: RANNESH KHUMAR B R
Email: 240701422@rajalakshmi.edu.in
Roll no: 2116240701
Phone: 9042350670
Branch: REC
Department: I CSE FD
Batch: 2028
Degree: B.E - CSE

Scan to verify results

NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_MCQ_Updated

Attempt : 1
Total Mark : 20
Marks Obtained : 16

Section 1 : MCQ

1. What would be the result of folding 123456 into three parts and summing: (12 + 34 + 56)?

Answer

102

Status : Correct ***Marks : 1/1***

2. Which of the following best describes linear probing in hashing?

Answer

Resolving collisions by linearly searching for the next free slot

Status : Correct ***Marks : 1/1***

3. What does a deleted slot in linear probing typically contain?

Answer

A special "deleted" marker

Status : Correct ***Marks : 1/1***

4. What is the output of the mid-square method for a key k = 123 if the hash table size is 10 and you extract the middle two digits of k * k?

Answer

1

Status : Correct ***Marks : 1/1***

5. Which situation causes clustering in linear probing?

Answer

Sequential key insertion

Status : Wrong ***Marks : 0/1***

6. What is the primary disadvantage of linear probing?

Answer

Clustering

Status : Correct ***Marks : 1/1***

7. What is the initial position for a key k in a linear probing hash table?

Answer

k % table_size

Status : Correct ***Marks : 1/1***

8. Which of the following statements is TRUE regarding the folding method?

Answer

It divides the key into parts and adds them.

Status : Correct ***Marks : 1/1***

9. In the division method of hashing, the hash function is typically written as:

Answer

h(k) = k % m

Status : Correct ***Marks : 1/1***

10. Which of these hashing methods may result in more uniform distribution with small keys?

Answer

Division

Status : Wrong ***Marks : 0/1***

11. In the folding method, what is the primary reason for reversing alternate parts before addition?

Answer

To reduce the chance of collisions caused by similar digit patterns

Status : Correct ***Marks : 1/1***

12. In linear probing, if a collision occurs at index i, what is the next index checked?

Answer

(i + 1) % table_size

Status : Correct **Marks : 1/1**

13. In C, how do you calculate the mid-square hash index for a key k, assuming we extract two middle digits and the table size is 100?

Answer

((k * k) / 10) % 100

Status : Wrong **Marks : 0/1**

14. What is the worst-case time complexity for inserting an element in a hash table with linear probing?

Answer

O(n)

Status : Correct **Marks : 1/1**

15. Which of the following values of 'm' is recommended for the division method in hashing?

Answer

A prime number

Status : Correct **Marks : 1/1**

16. What happens if we do not use modular arithmetic in linear probing?

Answer

Index goes out of bounds

Status : Correct **Marks : 1/1**

17. Which folding method divides the key into equal parts, reverses some of them, and then adds all parts?

Answer

Folding boundary method

Status : Wrong ***Marks : 0/1***

18. In division method, if key = 125 and m = 13, what is the hash index?

Answer

8

Status : Correct ***Marks : 1/1***

19. Which data structure is primarily used in linear probing?

Answer

Array

Status : Correct ***Marks : 1/1***

20. Which C statement is correct for finding the next index in linear probing?

Answer

index = (index + 1) % size;

Status : Correct ***Marks : 1/1***