

Spawning of wavepackets in 1D non-adiabatic transitions

Raoul Bourquin

Dr. Vasile Grădinaru
Prof. Dr. Ralf Hiptmair

Seminar for Applied Mathematics, ETH Zurich
Spring semester 2011

Outline

Introduction

Schrödinger equation, Potential and Initial Values

Semiclassical wavepackets

Spawning

In the non-adiabatic setting

Mathematical problem description and details

Implementation

An Example

Future work

End

Time-dependent Schrödinger equation

$$i\varepsilon^2 \frac{\partial}{\partial t} |\psi\rangle = \underbrace{(T + V)}_H |\psi\rangle$$

where

$$T := -\frac{1}{2}\varepsilon^4 \frac{\partial^2}{\partial x^2} \quad V := V(x)$$

- ▶ Time evolution for a state $|\psi\rangle$
- ▶ Kinetic operator T and potential $V(x)$
- ▶ Semi-classical scaling $\varepsilon^2 \approx 10^{-2}, 10^{-3}, \dots$
- ▶ Recover classical mechanics for $\varepsilon \rightarrow 0$

Wavefunction

Representation of the wavefunction

- ▶ Separation of variables
- ▶ Basis set expansion
 - ▶ very successful idea → Roothaan equations in Hartree-Fock

$$\begin{aligned}\psi(x, t) &= \sum_k c_k(t) \phi_k(x) \\ &= \sum_k c_k(t) \phi_k[\Pi(t)](x)\end{aligned}$$

Parameters:

$$\Pi(t) := \{P(t), Q(t), p(t), q(t)\}$$

Expansion coefficients:

$$c(t) := (c_0(t), \dots, c_K(t))$$

Semiclassical wavepackets

Definition of the basis functions

- ▶ Basis functions: product of a Gaussian times a polynomial

$$\phi_0(x) := (\pi\varepsilon^2)^{-\frac{1}{4}} Q^{-\frac{1}{2}} \exp\left(\frac{i}{2\varepsilon^2} PQ^{-1}(x-q)^2 + \frac{i}{\varepsilon^2} p(x-q)\right)$$

- ▶ Parameters $P \in \mathbb{C}$, $Q \in \mathbb{C}$
- ▶ Position $q \in \mathbb{R}$ and momentum $p \in \mathbb{R}$
- ▶ Construct ϕ_k by applying the *raising operator* \mathcal{R}

$$\phi_k := \frac{1}{\sqrt{k!}} \mathcal{R}^k \phi_0$$

- ▶ $\{\phi_i\}_i$ complete basis of L^2 for fixed P , Q , p , q

Semiclassical wavepackets

Definition of a wavepacket

- ▶ General wavepacket as linear combination

$$\Phi(x) := e^{\frac{iS}{\varepsilon^2}} \sum_{k=0}^K c_k \phi_k(x)$$

- ▶ In theory $K = \infty$, practically $K \leq 512$
- ▶ Time propagation of wavepackets:
 - ▶ propagate parameters P, Q, p, q
 - ▶ propagate coefficients $\{c_i\}_i$
- ▶ *Wavepackets stay in this mathematical form*
- ▶ Explicit algorithm \rightarrow my Bachelor Thesis


Non-adiabatic potentials

- ▶ Potential $V(x)$ with *multiple* energy levels $\lambda_i(x)$
- ▶ Wavepackets can *jump* to other levels
- ▶ and *split up* over different levels
- ▶ Energy levels do never cross

Very simple example

$$V(x) = \begin{bmatrix} \frac{1}{2} \tanh(x) & \delta \\ \delta & -\frac{1}{2} \tanh(x) \end{bmatrix}$$

- ▶ $0 < \delta \in \mathbb{R}$



Non-adiabatic potentials

Technical details

- ▶ Potential $V(x)$ is a matrix
 - ▶ Matrix valued TDSE
 - ▶ Vector valued wavefunction
- ▶ Wavepackets of the form:

$$|\Psi\rangle = \begin{pmatrix} \Phi_0 \\ \vdots \\ \Phi_{N-1} \end{pmatrix}$$





- ▶ Usually homogeneous: same Π for all Φ_i
 - ▶ *really* a good idea?
 - ▶ no, not always \rightarrow *spawning*

Video of the time evolution without spawning

Spawning

Motivating example

Time 5.6



Spawning

In the non-adiabatic setting

- ▶ Goal: reduce basis size K
 - ▶ transformation to *better* basis
- ▶ Split up wavepackets: $|\Psi\rangle = |\Psi_0\rangle + |\Psi_1\rangle$
- ▶ Each $|\Psi_i\rangle$ has own set Π_i
 - ▶ Important if Π_0 and Π_1 differ too much
 - ▶ Allows smaller basis size for Ψ_0, Ψ_1
- ▶ Important:
 - ▶ Spawning may solve problems arising in *long-time* simulations
 - ▶ It does *not* help with difficulties at the avoided crossing

Spawning

In the non-adiabatic setting

- ▶ Split up wavepackets: $|\Psi\rangle \approx |\Psi_0\rangle + |\Psi_1\rangle = |\Psi'\rangle$
- ▶ Reason: part Φ_1 on lower level λ_1 travels faster
- ▶ Before split up by spawning:

▶

$$|\Psi\rangle = \begin{pmatrix} \Phi_0 \\ \Phi_1 \end{pmatrix}$$

- ▶ Single set Π for both Φ_i
 - ▶ Probably big basis necessary: K is large
- ▶ After split up by spawning:

▶

$$|\Psi'\rangle = \begin{pmatrix} \Phi'_0 \\ 0 \end{pmatrix} + \begin{pmatrix} 0 \\ \Phi'_1 \end{pmatrix}$$

- ▶ Each Φ'_i has own parameter set Π_i
- ▶ Hopefully each Ψ'_i needs only much smaller basis

Spawning

Mathematical problem description

Given a linear combination $\sum_{k=\alpha}^{\beta} c_k \phi_k [\Pi] (x)$ with $\alpha \geq 0$ and $\beta \leq K$ find a new, optimal basis of L^2 . More precisely, find a new set $\tilde{\Pi}$ of parameters. Then do a basis expansion in the new basis $\sum_{k=\alpha}^{\beta} \tilde{c}_k \phi_k [\tilde{\Pi}]$ resulting in new coefficients \tilde{c} .

Spawning

Parameter estimation in detail

- ▶ A fragment: $w := \sum_{k=\alpha}^{\beta} c_k \phi_k$
- ▶ Estimate optimal $\tilde{\Pi}$ for w via expectation values

$$\tilde{q} := \frac{\langle w | x | w \rangle}{\langle w | w \rangle} = \frac{\sqrt{2\varepsilon^2}}{\sum_{k=\alpha}^{\beta} \bar{c}_k c_k} \Re \left(Q \sum_{k=\alpha+1}^{\beta} \bar{c}_k c_{k-1} \sqrt{k} \right) + q$$

$$\tilde{p} := \frac{\langle w | -i\varepsilon^2 \frac{\partial}{\partial x} | w \rangle}{\langle w | w \rangle} = \frac{\sqrt{2\varepsilon^2}}{\sum_{k=\alpha}^{\beta} \bar{c}_k c_k} \Re \left(P \sum_{k=\alpha+1}^{\beta} \bar{c}_k c_{k-1} \sqrt{k} \right) + p$$

- ▶ Similar procedure for \tilde{Q} and \tilde{P}
- ▶ Non-adiabatic setting: $\Phi_1 \equiv w$ and $\alpha = 0, \beta = K$

Spawning

Change of basis

- ▶ Find the expansion coefficients \tilde{c}_k
- ▶ Different strategies possible
 - ▶ *Lumping*
 - ▶ *Basis projection*
 - ▶ ...
- ▶ Both have advantages and drawbacks
 - ▶ *Basis projection* is the cleaner solution

Spawning

Basis projection

- Project w to first μ new basis functions $\tilde{\phi}_k := \phi_k[\tilde{\mathbf{\Gamma}}]$

$$\tilde{c}_i := \frac{\langle w | \tilde{\phi}_i \rangle}{\langle w | w \rangle}$$

- Do these integrals with highly accurate quadrature

$$\tilde{c}_i = \varepsilon \cdot Q_0 \sum_{r=0}^{R-1} \overline{\sum_{k=\alpha}^{\beta} c_k \phi_k(\gamma_r) \cdot \tilde{\phi}_i(\gamma_r) \cdot \omega_r}.$$


- Finally assign the coefficients

$$\begin{aligned} \tilde{c} &:= (\tilde{c}_0 \quad \cdots \quad \tilde{c}_\mu \quad \tilde{c}_{\mu+1} = 0 \quad \cdots \quad \tilde{c}_{\eta-1} = 0) \\ (c_\alpha \quad \cdots \quad c_\beta) &:= 0. \end{aligned}$$

Spawning

Spawning criteria

- ▶ An oracle telling us if and when to spawn
 - ▶ Spawn too early is *very bad*
 - ▶ Spawn too late is of little risk



- ▶ Simple threshold based criterion
 - ▶ $\langle w, w \rangle \geq \tau$
 - ▶ asymptotic value $\approx \tau$
 - ▶ but a priori unknown!
- ▶ More advanced criteria possible







Implementation

- ▶ Implementation on top of WaveBlocks
 - ▶ My code framework from the Bachelor Thesis
 - ▶ Currently about 8k lines of python code (core only)
 - ▶ Highly modular and easily extendable
 - ▶ Object oriented python code using numpy for numerics
- ▶ Adding spawning algorithms was really easy
 - ▶ Only 4 new classes
 - ▶ Parameter estimation routines
 - ▶ Change of basis routines
 - ▶ Code that checks for spawning during time propagation
 - ▶ About 500 lines of new code (w/o data analysis and plotting)




An example

Estimated parameters



An example

Norms




An example

Video

Video of the time evolution with spawning

An example

Spawning error



- *Systematic* ways to reduce the spawning error

Current research

Refine spawning in the *non-adiabatic* case

- ▶ Open issues with parameter estimation
- ▶ Can we improve the change of basis?
- ▶ Compare spawn criteria and find best one
- ▶ Propagation algorithm in case the interaction of the spawned packets can not be neglected (hard!)
- ▶ Adaptive basis size (almost done)

Thanks for your attention

Questions?

More information on the topic

- ▶ The full thesis:

http://n.ethz.ch/~raoulb/research/term_thesis/main.pdf

- ▶ The WaveBlocks source code:

<http://waveblocks.origo.ethz.ch/>

svn <http://svn.origo.ethz.ch/waveblocks/>