

Logic and Set Theory

January 19, 2018

<i>CONTENTS</i>	2
-----------------	---

Contents

0 Miscellaneous	3
------------------------	----------

1 Propositional logic	4
------------------------------	----------

0 Miscellaneous

Some introductory speech

1 Propositional logic

Let P denote a set of *primitive proposition*, unless otherwise stated, $P = \{p_1, p_2, \dots\}$.

The *language* or *set of propositions* $L = L(P)$ is defined inductively by:

- 1) $p \in L \ \forall p \in P$;
- 2) $\perp \in L$, where \perp is read as 'false';
- 3) If $p, q \in L$, then $(p \implies q) \in L$. For example, $(p_1 \implies L)$, $((p_1 \implies p_2) \implies (p_1 \implies p_3))$.

Note that at this point, each proposition is only a finite string of symbols from the alphabet $(,), \implies, \perp, p_1, p_2, \dots$ and do not really mean anything (until we define so).

By *inductively define*, we mean more precisely that we set $L_1 = P \cup \{\perp\}$, and $L_{n+1} = L_n \cup \{(p \implies q) : p, q \in L_n\}$, and then put $L = L_1 \cup L_2 \cup \dots$.

Each proposition is built up *uniquely* from 1) and 2) using 3). For example, $((p_1 \implies p_2) \implies (p_1 \implies p_3))$ came from $(p_1 \implies p_2)$ and $(p_1 \implies p_3)$. We often omit outer brackets or use different brackets for clarity.

Now we can define some useful things:

- $\neg p$ (not p), as an abbreviation for $p \implies \perp$;
- $p \vee q$ (p or q), as an abbreviation for $(\neg p) \implies q$;
- $p \wedge q$ (p and q), as an abbreviation for $(p \implies (\neg q))$.