

Simple Mail Transfer

Last Updated: 16-09-2020

Email is emerging as one of the most v

ternet systems use SMTP as a method to transfer mail from one user to another. SMTP is a push protocol and is used to send the mail whereas POP (post office protocol) or IMAP (internet message access protocol) are used to retrieve those mails at the receiver's side.

SMTP Fundamentals

SMTP is an application layer protocol. The client who wants to send the mail opens a TCP connection to the SMTP server and then sends the mail across the connection. The SMTP server is always on listening mode. As soon as it listens for a TCP connection from any client, the SMTP process initiates a connection on that port (25). After successfully establishing the TCP connection the client process sends the mail instantly.

SMTP Protocol

The SMTP model is of two type :

1. End-to- end method
2. Store-and- forward method

The end to end model is used to communicate between different organizations whereas the store and forward method are used within an organization. A SMTP client who wants to send the mail will contact the destination's host SMTP directly in order to send the mail to the destination. The SMTP server will keep the mail to itself until it is successfully copied to the receiver's SMTP.

The client SMTP is the one which initiates the session let us call it as the client- SMTP and the server SMTP is the one which responds to the session request and let us call it as receiver-SMTP. The client- SMTP will start the session and the receiver-SMTP will respond to the request.

Sign in to geeksforgeeks.org with Google




Raph RALAIKOA
raph35ral@gmail.com

Continue as Raph



Model of SMTP system

In the SMTP model user deals with the user agent (UA) for example Microsoft Outlook, Netscape, Mozilla, etc. In order to exchange the mail using TCP, MTA is used. The users sending the mail do not have to deal with the MTA it is the responsibility of the system admin to set up the local MTA. The MTA maintains a small queue of mails so that it can schedule repeat delivery of mail in case the receiver is not available. The MTA delivers the mail to the mailboxes and the information can later be downloaded by the user agents.



Both the SMTP-client and SMTP-server should have 2 components:

1. User agent (UA)
2. Local MTA



SENDING EMAIL:

Mail is sent by a series of request and response messages between the client and a server. The message which is sent across consists of a header and the body. A null line is used to terminate the mail header. Everything which is after the null line is considered as the body of the message which is a sequence of ASCII characters. The message body contains the actual information read by the receipt.

RECEIVING EMAIL:

The user agent at the server-side checks the mailboxes at a particular time of intervals. If any information is received it informs the user about the mail. When the user tries to read the mail it displays a list of mails with a short description of each mail in the mailbox. By selecting any of the mail user can view its contents on the terminal.

Some SMTP Commands:

- HELO – Identifies the client to the server, fully qualified domain name, only sent once per session
- MAIL – Initiate a message transfer, fully qualified domain of originator
- RCPT – Follows MAIL, identifies an addressee, typically the fully qualified name of the addressee and for multiple addressees use one RCPT for each addressee
- DATA – send data line by line

This article is contributed by **Monika Singh**

Attention reader! Don't stop learning now. Get hold of all the important CS Theory concepts for SDE interviews with the [CS Theory Course](#) at a student-friendly price and become industry ready.

Recommended Posts:

[Difference between File Transfer Protocol \(FTP\) and Secure File Transfer Protocol \(SFTP\)](#)

[Multipurpose Internet Mail Extension \(MIME\) Protocol](#)

[File Transfer Protocol \(FTP\) in Application Layer](#)

[Principle Of Reliable Data Transfer Protocol](#)

[Network News Transfer Protocol \(NNTP\)](#)

[XMODEM File Transfer Protocol](#)

[Difference between SMTP and POP3](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#)

Got It !



Simple Network Management Protocol (SNMP)

Hot Standby Router Protocol (HSRP) and Virtual Router Redundancy Protocol (VRRP)

Difference between Stop and Wait protocol and Sliding Window protocol

Difference between Serial Line Internet Protocol (SLIP) and Point-to-Point Protocol (PPP)

Cisco Discovery Protocol (CDP) and Link Layer Discovery Protocol (LLDP) in Data Link Layer

Difference between Border Gateway Protocol (BGP) and Routing Information Protocol (RIP)

Difference between Spam and Phishing Mail

Privacy Enhanced Mail (PEM) and it's Working

Difference between E-mail marketing and Affiliate marketing

C program for file Transfer using UDP

Improved By : [VaibhavRai3](#), [iam_chandan17](#)

Article Tags : [Computer Networks](#)

Practice Tags : [Computer Networks](#)



19

2.6

☐ To-do ☐ Done

Based on **11** vote(s)

Improve Article

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.



📍 5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh – 201305

✉ feedback@geeksforgeeks.org

Company

About Us
Careers
Privacy Policy
Contact Us

Practice

Courses
Company-wise
Topic-wise
How to begin?

Learn

Algorithms
Data Structures
Languages
CS Subjects
Video Tutorials

Contribute

Write an Article
Write Interview Experience
Internships
Videos

@geeksforgeeks , Some rights reserved