

```

1 import scipy.io
2 import matplotlib.pyplot as plt
3 import numpy as np
4 from tqdm import tqdm
5 from sklearn.metrics import accuracy_score
6
7
8 class LogisticRegression:
9
10     def __init__(self, X_train, y_train, X_test, y_test) -> None:
11         self.X_train = X_train
12         self.y_train = y_train
13         self.X_test = X_test
14         self.y_test = y_test
15
16         self.X_train_original = self.X_train
17         self.X_test_original = self.X_test
18
19         self.X_train, self.X_test = self.normalize(self.X_train, self.X_test)
20
21         # If our set is already flat, we don't need the next line
22         # self.X_train, self.X_test = self.flatten_pixels(
23         #     self.X_train, self.X_test)
24
25         self.W, self.b = self.initialization(self.X_train)
26
27         self.trained = False
28
29     @staticmethod
30     def initialization(X):
31         W = np.random.randn(X.shape[1]) # np.random.randn(X.shape[1], 1)
32         b = np.random.randn(1)[0] # np.random.randn(1)[0]
33         return (W, b)
34
35     @staticmethod
36     def normalize(train_set, test_set):
37         return (train_set / train_set.max(), test_set / test_set.max())
38
39     @staticmethod
40     def flatten_pixels(train_set, test_set):
41         train_set = train_set.reshape(
42             train_set.shape[0], train_set.shape[1]*train_set.shape[2])
43         test_set = test_set.reshape(
44             test_set.shape[0], test_set.shape[1]*test_set.shape[2])
45         return (train_set, test_set)
46
47     @staticmethod
48     def model(X, W, b):
49         Z = X.dot(W) + b
50         A = 1 / (1 + np.exp(-Z))
51         return A
52
53     @staticmethod
54     def log_loss(A, y, epsilon=1e-15):
55         return 1 / len(y) * np.sum(-y * np.log(A + epsilon) - (1-y) * np.log(1 - A +
epsilon))
56
57     @staticmethod
58     def gradients(A, X, y):
59         dW = 1 / len(y) * np.dot(X.T, A - y)
60         db = 1 / len(y) * np.sum(A - y)
61         return (dW, db)
62
63     @staticmethod
64     def update(dW, db, W, b, learning_rate):
65         W = W - learning_rate * dW
66         b = b - learning_rate * db
67         return (W, b)
68
69     def train(self, learning_rate=1.2, n_iter=300):
70         if self.trained:
71             print("The model has been already trained.")
72             return
73
74         Loss = []
75         history = []
76
77         for i in tqdm(range(n_iter)):

```

```

78         A = self.model(self.X_train, self.W, self.b)
79         Loss.append(self.log_loss(A, self.y_train))
80         dW, db = self.gradients(A, self.X_train, self.y_train)
81         self.W, self.b = self.update(dW, db, self.W, self.b, learning_rate)
82         history.append([self.W, self.b, Loss[i]])
83
84     plt.plot(Loss)
85     plt.show()
86     y_pred = self.predict(self.X_train, self.W, self.b)
87     print("Accuracy score: ", accuracy_score(self.y_train, y_pred))
88
89     self.trained = True
90
91     def predict(self, X, W, b):
92         A = self.model(X, W, b)
93         return A >= 0.5
94
95     def show_train_set(self):
96         plt.figure(figsize=(16, 8))
97         for i in range(1, 15):
98             plt.subplot(4, 5, i)
99             plt.imshow(self.X_train_original[i], cmap='gray')
100            plt.title("chien" if self.y_train[i] == 1.0 else "chat")
101            plt.tight_layout()
102        plt.show()
103
104     def show_test_set(self):
105         y_predict = self.predict(self.X_train, self.W, self.b)
106         for i in range(1, 15):
107             plt.subplot(4, 5, i)
108             plt.imshow(self.X_train_original[i], cmap='gray')
109             plt.title("chien" if y_predict[i] == 1.0 else "chat")
110             plt.tight_layout()
111        plt.show()
112
113
114     def retrain_data():
115         mat = scipy.io.loadmat('mnist_all.mat')
116
117         x1 = mat.get('train1')
118         x2 = mat.get('train2')
119         X_train = np.concatenate((x1, x2), axis=0)
120
121         y1 = np.zeros(len(x1), dtype=int)
122         y2 = np.ones(len(x2), dtype=int)
123         y_train = np.concatenate((y1, y2), axis=0)
124
125         x1_test = mat.get('test1')
126         x2_test = mat.get('test2')
127         X_test = np.concatenate((x1_test, x2_test), axis=0)
128
129         y1_test = np.zeros(len(x1_test), dtype=int)
130         y2_test = np.ones(len(x1_test), dtype=int)
131         y_test = np.concatenate((y1_test, y2_test), axis=0)
132
133         return X_train, y_train, X_test, y_test
134
135
136     if __name__ == "__main__":
137
138         X_train, y_train, X_test, y_test = retrain_data()
139         myModel = LogisticRegression(X_train, y_train, X_test, y_test)
140         myModel.train()
141

```